

# SQL Injection

# Agenda

- *Code injection* vulnerability - untrusted input inserted into query or command
  - Attack string alters intended semantics of command
  - Ex: **SQL Injection**
    - unsanitized data used in query to back-end database
- SQL Injection Attack Scenarios
  - **First-order SQL Injection**
    - Type 1: compromises user data
    - Type 2: modifies critical data
  - **Second-order SQL Injection**
    - Two-phases attack (first store data, then exploit)


# SQL Injection Impact

- CardSystems, credit card payment processing ruined by SQL Injection attack in June 2005
  - 263,000 credit card #s stolen from its DB
  - #s stored unencrypted, 40 million exposed
- Heartland Payment Systems (2005-2007)
  - 130 million cards were hacked
  - [Hackers sentenced for SQL injections that cost \\$300 million](#)
- More examples:
  - [http://en.wikipedia.org/wiki/SQL\\_injection#Examples](http://en.wikipedia.org/wiki/SQL_injection#Examples)
  - <https://moneywise.com/a/worst-data-breaches-of-the-century>

# **SQL Injection Attack Scenarios**

# First-order SQL Injection example

- <https://www.hacksplaining.com/exercises/sql-injection#/start>



# First-order SQL Injection (1/6)

- Ex: Pizza Site Reviewing Orders
  - Form requesting month # to view orders for



- HTTP request:

[https://www.deliver-me-pizza.com/show\\_orders?month=10](https://www.deliver-me-pizza.com/show_orders?month=10)

# First-order SQL Injection (2/6)

- App constructs SQL query from parameter:

```
sql_query = "SELECT pizza, toppings, quantity, order_day " +  
            "FROM orders " +  
            "WHERE userid=" + session.getCurrentUserId() + " " +  
            "AND order_month=" + request.getParameter("month");
```

## Normal SQL Query

```
SELECT pizza, toppings, quantity, order_day  
FROM orders  
WHERE userid=4123  
AND order_month=10
```

- Type 1 Attack: inputs month='0 OR 1=1' !
- Goes to encoded URL: (space -> %20, = -> %3D)

[https://www.deliver-me-pizza.com/show\\_orders?month=0%20OR%201%3D1](https://www.deliver-me-pizza.com/show_orders?month=0%20OR%201%3D1)

# First-order SQL Injection (3/6)

**Malicious Query** `SELECT pizza, toppings, quantity, order_day  
FROM orders  
WHERE userid=4123 AND order_month=0 OR 1=1`

- WHERE condition is always true!
  - AND precedes OR
  - Type 1 Attack: Gains access to other users' private data!

**All User Data  
Compromised**



The screenshot shows a Mozilla Firefox browser window titled "Order History - Mozilla Firefox". The address bar and menu bar are visible. Below the menu bar, the text "Your Pizza Orders:" is displayed. A table with four columns: "Pizza", "Toppings", "Quantity", and "Order Day" is shown. The table contains eight rows of data, each representing a different pizza order. The data is as follows:

Pizza	Toppings	Quantity	Order Day
Diavola	Tomato, Mozarella, Pepperoni, ...	2	12
Napoli	Tomato, Mozarella, Anchovies, ...	1	17
Margherita	Tomato, Mozarella, Chicken, ...	3	5
Marinara	Oregano, Anchovies, Garlic, ...	1	24
Capricciosa	Mushrooms, Artichokes, Olives, ...	2	15
Veronese	Mushrooms, Prosciutto, Peas, ...	1	21
Godfather	Corleone Chicken, Mozarella, ...	5	13
...			



# First-order SQL Injection (4/6)


More damaging attack: attacker sets

`month='0 AND 1=0`

`UNION`

`SELECT cardholder, number, exp_month, exp_year`  
`FROM creditcards'`

- Attacker is able to
  - Combine 2 queries
  - 1<sup>st</sup> query: empty table (where fails)
  - 2<sup>nd</sup> query: credit card #s of all users



Pizza	Toppings	Quantity	Order Day
Neil Daswani	1234 1234 9999 1111	11	2007
Christoph Kern	1234 4321 3333 2222	4	2008
Anita Kesavan	2354 7777 1111 1234	3	2007
...			

# First-order SQL Injection (5/6)

- Even worse, attacker sets

```
month='0;  
DROP TABLE creditcards;
```

- Then DB executes
  - Type 2 Attack:  
Removes `creditcards`  
from schema!
  - Future orders fail: DoS!

```
SELECT pizza, toppings,  
quantity, order_day  
FROM orders  
WHERE userid=4123  
AND order_month=0;  
DROP TABLE creditcards;
```

- Problematic Statements:
  - Modifiers: `INSERT INTO admin_users VALUES ('hacker',...)`
  - Administrative: shut down DB, control OS...

# First-order SQL Injection (6/6)

- Injecting String Parameters: Topping Search

```
sql_query =  
    "SELECT pizza, toppings, quantity, order_day " +  
    "FROM orders " +  
    "WHERE userid=" + session.getCurrentUserId() + " " +  
    "AND topping LIKE '%" + request.getParameter("topping") + "%' ";
```

- Attack searches for:


**brzfg%'; DROP table creditcards; --**

- Query evaluates as:

- SELECT: empty table
- -- comments out end
- Credit card info dropped

```
SELECT pizza, toppings,  
quantity, order_day  
FROM orders  
WHERE userid=4123  
AND topping LIKE '%brzfg%';  
DROP table creditcards; --%
```

# Sanitize your Database Inputs



Source: <http://xkcd.com/327/>

# Second-Order SQL Injection (1/2)

- *Second-Order SQL Injection*: data stored in database is later used to conduct SQL injection
  - Common if string escaping is applied inconsistently
  - Ex: o'connor updates passwd to SkYn3t

```
new_passwd = request.getParameter("new_passwd");
uname = session.getUsername();
sql = "UPDATE USERS SET passwd='" + escape(new_passwd) +
      "' WHERE uname='" + uname + "'";
```

- uname not escaped, b/c originally escaped before entering into the DB, now inside our trust zone:

```
UPDATE USERS SET passwd='SkYn3t' WHERE uname='o'connor'
```

- Query fails b/c ' after o ends command prematurely

# Second-Order SQL Injection (2/2)

- Even Worse: What if user set  
uname=**admin' -- !?**

```
UPDATE USERS SET passwd='cracked' WHERE uname='admin' --'
```

- Attacker changes admin's password to cracked
  - Has full access to admin account
  - Username avoids collision with real admin
  - -- comments out trailing quote
- All parameters dangerous

# Solutions

# Solutions

- A. Blacklisting
- B. Whitelisting over Blacklisting
- C. Input Validation & Escaping
- D. Use Prepared Statements & Bind Variables



# A. Blacklisting

- Eliminating quotes enough (blacklist them)?

```
sql_query =  
"SELECT pizza, toppings, quantity, order_day " +  
"FROM orders " +  
"WHERE userid=" + session.getCurrentUserId() + " " +  
"AND topping LIKE  
'kill_quotes(request.getParamenter("topping")) + "%'";
```

- `kill_quotes (Java)` removes single quotes:

```
String kill_quotes(String str) {  
    StringBuffer result = new StringBuffer(str.length());  
    for (int i = 0; i < str.length(); i++) {  
        if (str.charAt(i) != '\')  
            result.append(str.charAt(i));  
    }  
    return result.toString();  
}
```

## A. Pitfalls of Blacklisting

- Filter quotes, semicolons, whitespace, and...?
  - Could always miss a dangerous character
  - Blacklisting not comprehensive solution
  - Ex: `kill_quotes()` can't prevent attacks against numeric parameters
- May conflict with functional requirements
  - Ex: How to store O'Brien in DB if quotes blacklisted?

## B. Whitelisting

- *Whitelisting* – only allow input within well-defined set of safe values
  - set implicitly defined through *regular expressions*
  - *RegExp* – pattern to match strings against
- Ex: `month` parameter: non-negative integer
  - **RegExp:** `^[0-9]*$` - 0 or more digits, safe subset
    - The `^`, `$` match beginning and end of string
    - `[0-9]` matches a digit,
    - `*` specifies 0 or more

## C. Input Validation and Escaping

- Could escape quotes instead of blacklisting
- **Ex: insert user** o'connor, password terminator

```
sql = "INSERT INTO USERS (uname,passwd) " +  
      "VALUES (" + escape(uname)+ "," +  
      escape(password) +")";
```

– `escape(o'connor) = o''connor`

```
INSERT INTO USERS (uname,passwd) VALUES ('o''connor','terminator');
```


- Like `kill_quotes`, only works for string inputs
- Numeric parameters could still be vulnerable

## D. Prepared Statements & Bind Variables

- Metachars (e.g. quotes) provide distinction between **data** & **control** in queries
  - most attacks: **data** interpreted as **control**
  - alters the semantics of a query
- **Bind Variables**: **?** placeholders guaranteed to be **data** (not **control**)
- *Prepared Statements* allow creation of static queries with **bind variables**
  - Preserves the structure of intended query
  - Parameters not involved in query parsing/compiling

# Java Prepared Statements

```
PreparedStatement ps =  
db.prepareStatement("SELECT pizza, toppings, quantity, order_day "  
                    + "FROM orders WHERE userid=? AND order_month=?");  
ps.setInt(1, session.getCurrentUserId());  
ps.setInt(2, Integer.parseInt(request.getParameter("month")));  
ResultSet res = ps.executeQuery();
```



**Bind Variable:  
Data Placeholder**

- Query parsed without parameters
- Bind variables are **typed**: input must be of expected type (e.g. int, string)