



Módulo 32





BackEnd Java



A decorative graphic on the left side of the slide. It features a large cyan hexagon in the center with the number '1' inside. Surrounding this central hexagon are several smaller hexagons of varying shades of blue and cyan. Some of these smaller hexagons contain white icons: a lightbulb, a thumbs-up, a smartphone, a magnifying glass, and a gear. There is also a network-like icon with a central node and radiating lines, and a speech bubble icon.

1

Configurando o projeto com hibernate



Configurando Hibernate

Entrar no site do [hibernate](https://hibernate.org/) e fazer o download do zip.

Descompactar e adicionar os jars da pasta lib/required no classpath da aplicação.

Igual imagem abaixo.



Configurando Hibernate

The screenshot displays the Eclipse IDE interface with the 'Properties for ExemploJPA' dialog box open. The 'Java Build Path' tab is selected, showing the 'Libraries' section. The 'Classpath' is configured with the following entries:

- Modulepath
 - JRE System Library [JavaSE-11]
- Classpath
 - postgresql-42.3.1.jar - /Users/rodrigo.pires/Downloads
 - hibernate-5.6.2
 - JUnit 4

The 'Favorites' list on the right includes:

- AirDrop
- Recentes
- Aplicativos
- Mesa
- Documentos
- Downloads
- dev
- iCloud
- iCloud Drive
- Localizações
- Authy Desktop...
- Etiquetas
- Vermelho

The 'Nome' list on the right shows the following JAR files:

- antlr-2.7.7.jar
- byte-buddy-1.11.20.jar
- classmate-1.5.1.jar
- FastInfoset-1.2.15.jar
- hibernate-commons-annotations-5.1.2.Final.jar
- hibernate-core-5.6.2.Final.jar
- istack-commons-runtime-3.0.7.jar
- jandex-2.2.3.Final.jar
- javax.activation-api-1.2.0.jar
- javax.persistence-api-2.2.jar
- jaxb-api-2.3.1.jar
- jaxb-runtime-2.3.1.jar
- jboss-logging-3.4.2.Final.jar
- jboss-transaction-api_1.2_spec-1.1.1.Final.jar
- stax-ex-1.8.jar
- txw2-2.3.1.jar



Configurando Hibernate

```
ExemploJPA [backend-java-ebac main]
├── src/main/java
│   ├── br.com.rpires.dao
│   │   ├── ClienteDAO.java
│   │   └── IClienteDAO.java
│   └── br.com.rpires.domain
│       └── Cliente.java
├── META-INF
│   └── persistence.xml
├── src/test/java
│   └── br.com.rpires
│       └── ClienteDAOTest.java
├── src/main/resources
├── src/test/resources
├── JRE System Library [JavaSE-11]
├── hibernate-5.6.2
├── Referenced Libraries
├── JUnit 4
├── build
└── src
```





Configurando Hibernate

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence version="2.2" xmlns="http://xmlns.jcp.org/xml/ns/persistence"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/persistence http://xmlns.jcp.org/xml/ns/persistence/p
  <persistence-unit name="ExemploJPA">

    <provider>org.hibernate.ejb.HibernatePersistence</provider>

    <class>br.com.rpires.domain.Cliente</class>

    <properties>
      <property name="javax.persistence.jdbc.driver" value="org.postgresql.Driver" /> <!-- DB Driver -->
      <property name="javax.persistence.jdbc.url" value="jdbc:postgresql://localhost:15432/vendas_or
      <property name="javax.persistence.jdbc.user" value="postgres" /> <!-- DB User -->
      <property name="javax.persistence.jdbc.password" value="admin" /> <!-- DB Password -->

      <property name="hibernate.dialect" value="org.hibernate.dialect.PostgreSQLDialect"/> <!-- DB D
      <property name="hibernate.hbm2ddl.auto" value="update" /> <!-- create / create-drop / update -->

      <property name="hibernate.show_sql" value="true" /> <!-- Show SQL in console -->
      <property name="hibernate.format_sql" value="true" /> <!-- Show SQL formatted -->
    </properties>

  </persistence-unit>
</persistence>
```





Referências

Exemplos disponíveis no meu github:

<https://github.com/digaomilleniun/backend-java-ebac>

Bibliotecas hibernate:

<https://sourceforge.net/projects/hibernate/>

