
Node 2110

Start State: UE is in 5GMM-IDLE mode with suspend indication.
Condition: Lower layers indicate that the RRC connection has been resumed.
Action: The UE transitions from 5GMM-IDLE mode with suspend indication to 5GMM-CONNECTED mode.
End State: UE is in 5GMM-CONNECTED mode.



Temporal Connection

Node 2055

Start State: UE is in 5GMM-CONNECTED mode.

Node 2093

Node 2724

Node 2062

...

...

Node 2073

Action: The UE moves to 5GMM-IDLE mode over 3GPP access and proceeds with the registration procedure for mobility and periodic registration as specified in subclause 5.5.1.3.2.

Causal Connection

Reference Guided Connection

Node 5263

Action: UE releases N1 NAS, enters IDLE, and starts registration.
End State: UE is in 5GMM-IDLE mode and has initiated the registration procedure with updated radio capability information.

...

Node 2037

Start State: UE has an active N1 NAS signalling connection and timer T3540 is running.
Condition: Receipt of a message for a network-initiated 5GMM common procedure.

Semantic Connection

Node 2107

Start State: UE is in an initial state where it is attempting to send a REGISTRATION REQUEST message.

Node ID: 2110 (Derived from Section 5.3.1.5):
Start State: UE is in 5GMM-IDLE mode with suspend indication.
Condition: Lower layers indicate that the RRC connection has been resumed.
Action: The UE transitions from 5GMM-IDLE mode with suspend indication to 5GMM-CONNECTED mode.
End State: UE is in 5GMM-CONNECTED mode.

Temporal Connection

Node (ID: 2055):
Start State: UE is in 5GMM-CONNECTED mode.

Node (ID: 2093)

Node (ID: 2724)

Node (ID: 2063)

Node (ID: 2073):
Action: The UE moves to 5GMM-IDLE mode over 3GPP access and proceeds with the registration procedure for mobility and periodic registration as specified in subclause 5.5.1.3.2.

Reference Guided Connection

Node ID: 5263 (Derived from Section 5.5.1.3.2)
Action: UE releases N1 NAS, enters IDLE, and starts registration.

End State: UE is in 5GMM-IDLE mode and has initiated the registration procedure with updated radio capability information.

Causal Connection

Node(ID: 2037):
Start State: UE has an active N1 NAS signalling connection and timer T3540 is running.
Condition: Receipt of a message for a network-initiated 5GMM common procedure.

Semantic Connection

Node(ID: 2107):
Start State: UE is in an initial state where it is attempting to send a REGISTRATION REQUEST message.