

Log In

Join

Back To Course Home

# Grokking Modern System Design Interview for Engineers & Managers

0% completed

## System Design Interviews

### Introduction

### Abstractions

### Non-functional System Characteristics

### Back-of-the-envelope Calculations

### Building Blocks

### Domain Name System

### Load Balancers

### Databases

**Key-value Store**

**Content Delivery Network (CDN)**

**Sequencer**

**Distributed Monitoring**

**Monitor Server-side Errors**

**Monitor Client-side Errors**

**Distributed Cache**

**Distributed Messaging Queue**

**Pub-sub**

**Rate Limiter**

**Blob Store**

**Distributed Search**

**Distributed Logging**

## **Distributed Task Scheduler**

## **Sharded Counters**

## **Concluding the Building Blocks Discussion**

## **Design YouTube**

## **Design Quora**

## **Design Google Maps**

## **Design a Proximity Service / Yelp**

## **Design Uber**

## **Design Twitter**

## **Design Newsfeed System**

## **Design Instagram**

## **Design a URL Shortening Service / TinyURL**

## **Design a Web Crawler**

# Design WhatsApp



## Design Typeahead Suggestion

## Design a Collaborative Document Editing Service / Google Docs

## Spectacular Failures

## Concluding Remarks

## Course Certificate

**Mark Course as Completed**

# High-level Design of WhatsApp

Get introduced to the high-level design of the WhatsApp system.

### We'll cover the following

- High-level design
- API design
  - Send message
  - Get message
  - Upload media or document file
  - Download a document or media file

## High-level design#


At an abstract level, the high-level design consists of a chat server responsible for communication between the sender and the receiver. When a user wants to send a message to another user, both connect to the chat server. Both users send their messages to the chat server. The chat server then sends the message to the other intended user and also stores the message in the database.

## The high-level design of WhatsApp messenger

The following steps describe the communication between both clients:

1. User A and user B create a communication channel with the chat server.
2. User A sends a message to the chat server.
3. Upon receiving the message, the chat server acknowledges back to user A.
4. The chat server sends the message to user B and stores the message in the database if the receiver's status is offline.
5. User B sends an acknowledgment to the chat server.
6. The chat server notifies user A that the message has been successfully delivered.
7. When user B reads the message, the application notifies the chat server.
8. The chat server notifies user A that user B has read the message.

The process is shown in the following illustrations:



## API design#

WhatsApp provides a vast amount of features to its users via different APIs. Some features are mentioned below:

- Send message
- Get message or receive message
- Upload a media file or document
- Download document or media file
- Send a location

- Send a contact
- Create a status

However, we’ll discuss essential APIs related to the first four features.

## Send message#

The `sendMessage` API is as follows:

```
sendMessage(sender_ID, reciever_ID, type, text=none, media_object=none, document=none)
```

This API is used to send a `text` message from a sender to a receiver by making a POST API call to the `/messages` API endpoint. Generally, the sender’s and receiver’s IDs are their phone numbers. The parameters used in this API call are described in the following table:

Parameter	Description
<code>sender_ID</code>	This is a unique identifier of the user who sends the message.
<code>reciever_ID</code>	This is a unique identifier of the user who receives the message.
<code>type</code>	The default message <code>type</code> is text. This represents whether the sender sends a media file or a document.
<code>text</code>	This feild contains the text that has to be sent as a message.
<code>media_object</code>	This parameter is defined based on the type parameter. It represents the media file to be sent.
<code>document</code>	This represents the document file to be sent.

## Get message#

The `getMessage` API is as follows:

```
getMessage(user_Id)
```

Using this API call, users can fetch all unread messages when they come online after being offline for some time.

Parameter	Description
user_Id	This is a unique identifier representing the user who has to fetch all unread messages.

## Upload media or document file#

The `uploadFile` API is as follows:

```
uploadFile(file_type, file)
```

We can upload media files via the `uploadFile` API by making a POST request to the `/v1/media` API endpoint. A successful response returns an ID that’s forwarded to the receiver. The maximum file size for media that can be uploaded is 16 MB, while the limit is 100 MB for a document.

Parameter	Description
file_type	This represents the type of file uploaded via the API call.
file	This contains the file being uploaded via the API call.

## Download a document or media file#

The `downloadFile` API is as follows:

```
downloadFile(user_id, file, file_id)
```



The parameters of this API call are explained in the following table:

Parameter	Description
<code>user_id</code>	This is a unique identifier of the user who will download a file.
<code>file</code>	This contains the file to be downloaded.
<code>file_id</code>	This is a unique identifier of a file. It's generated while uploading a file via <code>uploadFile()</code> API call. The <code>downloadFile()</code> API call downloads the media file through this identifier.

In the next lesson, we'll focus on the detailed design of the WhatsApp system.

Back

Requirements of WhatsApp's Design

Next

Detailed Design of WhatsApp

Mark as Completed

Report an Issue