

AKTIVKOHLEFILTER Ø100mm

Professional Series • Nachfüllbar • umkehrbare Flansche

◆ LIEFERUMFANG

 **1× Aktivkohlefilter** **1× Prefilter-Vlies (Baumwolle)** **1× Aufhängeseil-Set mit Karabinern**

Nachfüllkohle (GE-CAR-4) und Trichter sind nicht enthalten — bitte separat bereithalten. Flexschläuche und Schlauchschellen nicht enthalten.


◆ TECHNISCHE DATEN

Modell	GE-CF-01
Anschluss	Ø100 mm • 4"
Filtermaß	Ø100 × 305 mm
Aktivkohle	≈ 1,3–1,4 kg
Luftdurchsatz	357 m³/h • 210 CFM
Geruchsentfernung	bis zu 98 %
Kohle-Standzeit	1–2 Grow Cycles
Material	Pulverb. Stahl
Flansche	Alu • umkehrbar
Kompatibel	GE-DUF-01

◆ VOR DEM EINBAU

- ✓ Prefilter-Vlies über den Filter ziehen — schützt die Kohle vor Staub.
- ✓ Mit Seil-Set und Haken sicher aufhängen oder auf den Rohrventilator setzen.
- ✓ Lüftrichtung beachten (siehe unten).
- ✓ Nur trocken einsetzen — Kohle nicht nass werden lassen.

◆ SO HERUM EINBAUEN • LUFTRICHTUNG




Die Luft wird durch den Aktivkohlefilter angesaugt und über den Rohrventilator nach außen geführt — Gerüche werden gebunden, das Zelt bleibt im Unterdruck.

◆ PFLEGE & SICHERHEIT

1. Trocken halten und lagern. Kohle nicht waschen oder nass werden lassen.
2. **Nur für Abluft** von Growzelten/Innenräumen. Keine aggressiven Chemikalien filtern.
3. Prefilter-Vlies regelmäßig prüfen und bei Verschmutzung tauschen.
4. Sicher aufhängen — festen Sitz von Seil, Karabinern und Haken prüfen.
5. Nicht fallen lassen; verformtes Gehäuse mindert die Leistung.
6. Von Zündquellen und offener Flamme fernhalten. Kühl und trocken lagern.

1 · Standzeit verlängern *Flansche umkehren — kostet nichts*


Lässt der Geruchsschutz nach, tauschst du die beiden Flansche. Die Luft strömt dann andersherum durch den Filter — die noch frische Kohle kommt zum Einsatz und **die ganze Kohle wird genutzt**.



SCHRITT 1

Lösen


Filter flach hinlegen. Beide End-Flansche abschrauben.



SCHRITT 2

Seiten tauschen

Beide Flansche über Kreuz auf die andere Seite setzen.



SCHRITT 3

Festdrehen

Fest zudrehen. Stopfen prüfen, damit keine Kohle rausfällt.

2 · Kohle nachfüllen *wenn beide Seiten verbraucht sind*

Ist die Kohle nach 1–2 Grow Cycles durch, wechselst du nur die Kohle — nicht den ganzen Filter. Das spart Geld und Müll.



SCHRITT 1

Vorfilter ab


Prefilter-Vlies abnehmen und einen Flansch aufschrauben.



SCHRITT 2

Kohle einfüllen

Mit Trichter (nicht enthalten) frische Aktivkohle einfüllen, fest packen.



SCHRITT 3

Zuschrauben

Nicht über den Vorfilter füllen. Flansch wieder festschrauben.

SERVICE & GARANTIE

1 Jahr Herstellergarantie ab Lieferdatum. Die gesetzliche Gewährleistung von 2 Jahren bleibt unberührt. Kaufbeleg aufbewahren.

Kontakt: info@growexpert-shop.de

ENTSORGUNG & PFLICHTANGABEN



NICHT ÜBER HAUSMÜLL

Kohle kompostierbar · Metallgehäuse über Wertstoff · Made in China

Importeur: Need That · Bebelstraße 42 · 67549 Worms · Germany · WEEE-Reg.-Nr. DE27607569

CARBON FILTER Ø100mm

Professional Series · Refillable · Reversible flanges

◆ IN THE BOX

 **1× Carbon filter**

 **1× Pre-filter sleeve (cotton)**

 **1× Hanging rope set with clips**

Refill carbon (GE-CAR-4) and a funnel are not included — please prepare them beforehand. Ducting and clamps not included.


◆ SPECIFICATIONS

Model	GE-CF-01
Connection	Ø100 mm · 4"
Filter size	Ø100 × 305 mm
Activated carbon	≈ 1.3–1.4 kg
Airflow	357 m³/h · 210 CFM
Odour removal	up to 98 %
Carbon life	1–2 grow cycles
Material	Powder-coated steel
Flanges	Alu · reversible
Compatible	GE-DUF-01

◆ BEFORE USE

- ✓ Pull the cotton pre-filter over the filter to protect the carbon from dust.
- ✓ Suspend securely with the rope set and hooks, or mount it on the fan.
- ✓ Mind the airflow direction (see below).
- ✓ Use dry only — never let the carbon get wet.

◆ FITTING & AIRFLOW DIRECTION




Air is drawn through the carbon filter and pushed outside by the inline fan — odours are captured and the tent stays under negative pressure.

◆ CARE & SAFETY

1. Keep and store dry. Do not wash the carbon or let it get wet.
2. **Exhaust use only** for grow tents/indoor rooms. Do not filter aggressive chemicals.
3. Check the pre-filter sleeve regularly and replace when soiled.
4. Suspend securely — check rope, clips and hooks are firmly seated.
5. Do not drop; a deformed housing reduces performance.
6. Keep away from ignition sources and open flame. Store cool and dry.

1 · Extend the life *reverse the flanges — costs nothing*


When odour control drops, reverse the airflow direction: the still-fresh carbon comes into the stream and the **entire carbon bed** is used.



STEP 1

Unscrew


Lay the filter flat. Unscrew both end flanges.



STEP 2

Swap sides

Move both flanges to the opposite end, crosswise.



STEP 3

Tighten

Tighten firmly. Check the stopper so no carbon spills out.

2 · Refill the carbon *when both sides are spent*


After 1–2 grow cycles you replace only the carbon, not the whole filter — saving money and waste.



STEP 1

Remove sleeve

Take off the cotton pre-filter and unscrew one flange.



STEP 2

Pour carbon

Fill through a funnel (not included), pack evenly and firmly.



STEP 3

Screw shut

Do not fill past the pre-filter. Screw the flange back on.

SERVICE & WARRANTY

1-year manufacturer warranty from delivery. Statutory warranty rights remain unaffected. Please keep your receipt.
Contact: info@growexpert-shop.de

DISPOSAL & MANDATORY INFO

NOT HOUSEHOLD WASTE

Carbon compostable · metal housing via recycling ·
Made in China

Importer: Need That · Bebelstraße 42 · 67549 Worms
· Germany · WEEE reg. no. DE27607569