OreSat Block Diagram

Deployable Triband Turnstile Antenna Assembly

- **UHF** (436 MHz) Turnstile Elements
- **L Band** (1.3 GHz) Turnstile Elements
- **S Band** (2.4 GHz) Turnstile Elements
- Burn Wire Deploy Mechanism

Deployable Helical Antenna Assembly

- Burn Wire Deploy Mechanism
- S Band (2.4 GHz) 12 dBi 16 turn helical antenna

Critical Subsystem

C3 Card (Flight Computer)

- RH Watchdog
- 16 GB eMMC Flash Memory
- OreSat Power Domain (OPD) Controller
- 436 MHz TX/RX
- PA / LNA Front End
- AX5043 Transceiver
- LNA Front End
- Down Converter
- AX5043 Transceiver
- 1.27 GHz RX only
- SPI
- M4

Battery Card 1 (+Z) — M0 / OPD
(6.0, 7.2, 8.4) V @ 5.2 Ah
Fuel gauge, BPM, Temp, Heater Inhibit and Disconnect Switches

Battery Card 2 (-Z) — M0 / OPD
(6.0, 7.2, 8.4) V @ 5.2 Ah
Fuel gauge, BPM, Temp, Heater Inhibit and Disconnect Switches

Solar Modules
Alta Devices modules
CVD GaAs ~ 28% eff.
~ 1.1 W each
3.16 W max array output
1.81 W average (tumbling)
Boost SPS with true MPPT
V/I/P/T telemetry

- Solar Module 1 (+X+Z) — M0
- Solar Module 2 (+X-Z) — M0
- Solar Module 3 (+Y+Z) — M0
- Solar Module 4 (+Y-Z) — M0
- Solar Module 5 (-X+Z) — M0
- Solar Module 6 (-X-Z) — M0
- Solar Module 7 (-Y+Z) — M0
- Solar Module 8 (-Y-Z) — M0

CAN bus 1 (Critical) — VBUS (6.0,7.2,8.4)V + OPD — CAN bus 2 (Mission)

Backplane

- 40 pin 1.27 mm Card Connectors
  - VBUS power rail
  - OreSat Power Domain signals
  - CAN1 and CAN2 buses
- SMPM RF Connectors
  - UHF, L, and S band microstrips

OreSat Live

OreSat Live Card — A8 / OPD
16 GB eMMC Flash Memory
Image Processing and Encoding Algorithms

- Atheros AR9271 USB WiFi Adapter
- LNA and 31 dBm PA
- Antenna Switch
- Sony IMX219 8MP USB Camera
- 16 mm Lens

Cirrus Flux Camera

Cirrus Flux Camera Card — A8 / OPD
16 GB eMMC Flash Memory
Sensor and Filter Control Algorithms

- Princeton Short Wave Infrared (SWIR) Sensor
- piece of paper right now.
- 50 mm SWIR Lens
- Thermal Electric Cooler (TEC) + Thermal Radiator

Attitude Control System (ACS) Card

IMU + MAG — M0 / OPD
Bosch BMI088 6 DOF IMU
Memsic MMC5803 Magnetometers
(2x on +Z and 2x on -Z End Caps)

ACS Assembly 1 — L4 / OPD
+X+Y Reaction Wheel
Z Magnetorquer

ACS Assembly 2 — L4 / OPD
-X+Y Reaction Wheel
X Magnetorquer

ACS Assembly 3 — L4 / OPD
-X-Y Reaction Wheel
Y Magnetorquer

ACS Assembly 4 — L4 / OPD
+X-Y Reaction Wheel

Attitude Determination and Control System (ADCS)

1.575 GHz RX only

SDR GPS + ADCS Card — A8 / OPD
Maxim MAX2771-based SDR
16 GB eMMC Flash Memory
GPSTK and ADCS Control Algorithms

Star Tracker Card — A8 / OPD
On Semi AR0134CS Camera
16 GB eMMC Flash Memory
OpenStarTracker.org Algorithms

OreSat Block Diagram
Oregon's First satellite
www.oresat.org
V5.0 2020/04/21

M0 = ST STM32F046K6 48 MHz 32 bit ARM Cortex-M0 running ChibiOS
L4 = ST STM32L452RE 80 MHz 32 bit ARM Cortex-M4F running ChibiOS
M4 = ST STM32F446 168 MHz 32 bit ARM Cortex-M4F running ChibiOS
A8 = Octavo OSD335x-SM 1 GHz 32 bit ARM Cortex-A8 running Linux
OPD = OreSat Power Domain (power bus + I2C card power control)