CSE 344 System Programming

Week 10

Synchronizing with threads

- Mutexes
- Condition variables
- Classic problems and their solutions in terms of threads

Threads are a beautiful concept, they are:

- "lighter" than processes in terms of memory use
- faster in terms of creation and context switching
- **easier** to establish inter-thread communication as they share the process memory.

However, all this comes at a cost, and that cost is solving the associated synchronization problems. You have already seen (counting) semaphores. You can use Posix/IPC semaphores with threads as well to solve **some** of your synchronization problems.

Posix threads offer us two more synchronization tools that enable us to solve (theoretically) **any** synchronization problem: **mutexes** and **condition variables**.

When faced with a critical section (i.e. a block of code executed in parallel, posing a synchronization risk), there is **no way** of avoiding an eventual rescheduling by the kernel.

All we can (and should) do, is make sure no other thread/process accesses the critical section while there is already a thread/process inside it.

We achieved this with semaphores by surrounding critical sections with wait and post calls:

```
wait(s)
//critical section, common variable, common data structure, etc
post(s)
```

Threads employ **mutexes** (**mut**ual **ex**clusion) for the same purpose.

A mutex m can be in either of two states: **locked (owned)** or **unlocked (not owned)**. It can change states through lock() and unlock() calls.

Once a mutex m is locked/owned by a thread t1, all other threads trying to lock m will block, until t1 unlocks m.

```
Thread t1 Thread t2 lock(m) lock(m) v = pop() // critical section unlock(m) unlock(m)
```

Creating a mutex (**dynamically**, with eventually custom attributes)

or **statically** (with default attributes; convenient for global variables)

```
pthread_mutex_t mutex = PTHREAD_MUTEX_INITIALIZER;
```

Attention: calling pthread_mutex_init() on an already initialized mutex leads to undefined behavior!

Once you no longer need to use a mutex, call pthread_mutex_destroy()

It is not necessary to call pthread_mutex_destroy() on a mutex that was statically initialized using PTHREAD_MUTEX_INITIALIZER

!!! Make sure **it's not locked** when you call it !!!

```
#include <pthread.h>
int pthread_mutex_lock(pthread_mutex_t * m );
int pthread_mutex_unlock(pthread_mutex_t * m );

Both return 0 on success, or a positive error number on error
```

Assuming that m is a mutex, and t1, t2 are threads using it.

| What happens when -> | t1 calls lock | t1 calls unlock | t2 calls lock | t2 calls unlock |
|------------------------|--------------------------|---|---------------|-----------------------------------|
| While m is owned by t1 | depends on the type of m | m is unlocked | t2 is blocked | undefined/error depending on type |
| while m is not owned | t1 locks m | undefined/error depending on type | t2 locks m | undefined/error depending on type |

Rules (the exact behavior depends on the type of the mutex):

- A single thread may not lock the same mutex twice.
- A thread may not unlock a mutex that it doesn't currently own (i.e., that it did not lock).
- A thread may not unlock a mutex that is not currently locked.

Normal/Fast: default, no checks, deadlocks in case of double lock (waits for itself)

Recursive: keeps count of locks, and only unlocks when the count is zero

Errorcheck: slower, but returns errors on all 3 scenarios

Example on how to set the mutex type:

```
pthread mutex t mtx;
pthread mutexattr t mtxAttr;
int s, type;
s = pthread mutexattr init(&mtxAttr);
if (s != 0)
   errExitEN(s, "pthread mutexattr init");
s = pthread mutexattr settype(&mtxAttr, PTHREAD MUTEX ERRORCHECK);
if (s != 0)
    errExitEN(s, "pthread_mutexattr_settype");
s = pthread mutex init(mtx, &mtxAttr);
if (s != 0)
    errExitEN(s, "pthread mutex init");
s = pthread mutexattr destroy(&mtxAttr);
                                         /* No longer needed */
if (s != 0)
    errExitEN(s, "pthread mutexattr destroy");
```

Common errors with mutexes

Different orders of locks across threads.

```
Thread A

1. pthread_mutex_lock(mutex1);

2. pthread_mutex_lock(mutex2);

3. pthread_mutex_lock(mutex1);

4. pthread_mutex_lock(mutex1);

5. pthread_mutex_lock(mutex1);

6. pthread_mutex_lock(mutex1);

7. pthread_mutex_lock(mutex1);

8. pthread_mutex_lock(mutex1);

9. pthread_mutex_lock(mutex1);
```

- Relocking an already locked mutex
- Trying to unlock another thread's mutex

Tip: you can check safely whether a mutex is locked using pthread_mutex_trylock(); it returns zero if the lock is acquired or an immediate error otherwise.

Important: is a mutex **identical** to a binary semaphore?

No. Because conversely to semaphores, mutexes revolve around the core concept of ownership. Semaphores don't have an owner, they can be increased through "post()" by any thread/process. A mutex can be unlocked/released **only** by its owner.

Mutexes are excellent for controlling access to critical sections.

Semaphores are great for implementing shared counters.

In practice however we encounter far more complex situations; for those we have **condition variables**.

Examples of real-world synchronization problems:

- wait for t to acquire the value of 17
- wait for x+y > 13
- wait for some buffer to fill up to at least 85%... etc.

Common denominator of all problems: wait for a certain condition or logical predicate to be satisfied.

A condition variable c possesses three main methods:

- 1) cwait(c,?): blocks the thread (?: is a hidden parameter, *more on this soon*)
- 2) signal(c): awakens a thread blocked on c because it called cwait(c,?)
- 3) broadcast(c): awakens all threads blocked on c because they called cwait(c,?)

A condition variable **knows nothing** about the condition that it's waiting.

Example

```
T1, T2 and T3: threads, c: condition variable, x=y=0
T3 must not advance unless x+y > 13
```

```
T1 T2 T3 while(!(x + y > 13)) signal(c); signal(c); cwait(c,?);
```

With every call of signal(), T3 checks whether the condition is satisfied; if yes, it continues, otherwise it goes back to sleep.

| T3: test condition | FALSE | cwait and sleep again | x=0, y=0 |
|--------------------|--------|-----------------------|-----------|
| T1: $x+=5$ | signal | T3 awake and ready | x=5, y=0 |
| ••• | | | |
| T3: test condition | FALSE | cwait and sleep again | x=5, y=0 |
| T2: y+=7 | signal | T3 awake and ready | x=5, y=7 |
| T3: test condition | FALSE | cwait and sleep again | x=5, y=7 |
| T1: $x+=5$ | signal | T3 awake and ready | x=10, y=7 |
| T3: test condition | TRUE | exit loop | x=10, y=7 |

The while clause could be about any logical predicate, that's what enables condition variables to be used with any problem.

Issues

The variables involved in the condition are shared between T1, T2 and T3. Let's say the condition is satisfied, and T3 exits the while loop. How do we know the condition is still satisfied at that point? We don't!

All we know is that the condition was satisfied certainly for at least a brief moment in time. Some thread could have possibly changed them back to unwanted values.

Conclusion: condition variables are **never used alone**, but **always with a mutex**.

- 1) Signal and broadcast calls must be made always under an exclusive lock.
- 2) The condition must be tested under an exclusive lock.

Conclusion:

- 1) Signal and broadcast calls must be made always under an exclusive lock.
- 2) The condition must be tested under an exclusive lock.

```
T2
                                        <u>T3</u>
T1
                                        lock(m)
lock(m)
                    lock(m)
                                        while (!(x + y > 13)) {
x += 5;
                    y += 7;
signal(c);
                    signal(c);
                                            unlock (m)
unlock (m)
                    unlock (m)
                                            cwait(c,?);
                                            lock (m)
                                         }
                                        unlock (m)
```

Are we done?

No! What if T1 or T2 call signal while T3 is between unlock and cwait? The signal will be lost, and T3 will wait for the next signal which might never arrive.

```
T2
T1
                                      Т3
                   lock(m)
lock (m)
                                      lock(m)
                                      while(!(x + y > 13)){
x += 5;
                   y += 7;
signal(c);
                   signal(c);
                                          unlock (m)
                                          cwait(c,?);
unlock (m)
                   unlock (m)
                                          lock (m)
                                       }
                                      unlock (m)
```

The truth is you cannot solve this at user level. That is why cwait receives not one but two parameters: **the condition variable to operate on and a mutex**.

And thus we talk about a monitor = a lock and zero or more condition variables

```
cwait (c, m)
```

This way when a signal arrives (due to signal() or broadcast()) the mutex is first locked and then cwait returns (atomically).

AND

When calling cwait, the mutex is first unlocked (atomically).

In other words, all three statements are combined into one.

```
T3
lock(m)
while(!(x + y > 13)){
    unlock(m)
    cwait(c,?);
    lock(m)
}
...
unlock(m)
```

```
T3
lock(m)
while(!(x + y > 13)){
    cwait(c,m)
}
... // safe to proceed on x,y
unlock(m)
```

Example: the **bounded producer-consumer** problem.

int count=0: number of products, N upper limit, mutex m for storage Condition variables empty and full.

Producer

```
for(;;)
  lock(m)
  while(count == N)
    cwait(empty, m)
  produce_item()
  count++
  broadcast(full)
  unlock(m)
```

Consumer

```
for(;;)
  lock(m)
  while(count == 0)
     cwait(full, m)
  consume_item
  count--
  broadcast(empty)
  unlock(m)
```

Example: **synchronization barrier** with N threads.

Condition variable c, mutex m, arrived = 0

Example: readers-writers

Reader

```
wait until no writers
   access database
   check out -- wake up waiting writer
Writer
  wait until no readers or writers
  access database
  check out -- wake up waiting readers or writer
```

State variables

```
number of active readersAR=0number of active writersAW=0number of waiting readersWR=0number of waiting writersWW=0
```

Condition variable okToRead
Condition variable okToWrite
Lock m

```
Reader()
    lock (m);
    while ((AW + WW) > 0) { // if any writers, wait
      WR++; // waiting reader
      cwait (okToRead, m);
      WR--;
    }
    AR++; // active reader
    unlock (m);
    Access DB
    lock(m);
    AR--;
    if (AR == 0 \&\& WW > 0)
      signal(okToWrite, m);
    unlock (m);
```

```
Writer()
    lock(m);
    while ((AW + AR) > 0) { // if any readers or writers, wait
       WW++;
                                   // waiting writer
        cwait(okToWrite, m);
       ₩W--;
                               // active writer
    AW++;
    unlock (m);
    Access DB
    lock(m);
    AW--;
    if (WW > 0)
                               // give priority to other writers
        signal(okToWrite, m);
    else if (WR > 0)
       broadcast(okToRead, m);
    unlock (m);
```

The **dining philosophers**: 5 condition variables, one for every fork (resource). The status array stores every fork's status: free or inUse

```
lock (m)
while (status[i] == inUse \mid | status[(i+1) % 5] == inUse)
   cwait(c[i],m);
status[i]=status[(i+1) % 5]=inUse
unlock (m)
//eat
lock (m)
status[i]=status[(i+1) % 5]=free
signal(c[i],m)
signal(c[(i+1) % 5], m)
unlock (m)
```

Cigarette smokers: c condition variable, m mutex, s=0 semaphore

```
Agent
```

Smoker

Similarly to mutexes, condition variables can be allocated statically or dynamically.

Use NULL in place of attr for default parameters.

Do not re-initialize (with init) an already initialized cond. var. \rightarrow undefined! Copying a cond. variable \rightarrow undefined behavior. Work on the originals!

```
#include <pthread.h>
int pthread cond signal (pthread_cond_t * cond );
int pthread_cond_broadcast(pthread_cond_t * cond );
int pthread cond wait (pthread_cond_t * cond ,
                              pthread mutex t * mutex );
All return 0 on success, or a positive error number on
error
```

The thread to be awoken by pthread_cond_signal() is unpredictable.

Same as pthread_cond_wait, but it waits at most for abstime, after

which if it's still waiting it returns ETIMEDOUT

When an automatically or dynamically allocated condition variable is no longer required, then it should be destroyed using pthread_cond_destroy().

```
#include <pthread.h>
int pthread_cond_destroy(pthread_cond_t * cond );
Returns 0 on success, or a positive error number on error
```

It is not necessary to call pthread_cond_destroy() on a condition variable that was statically initialized using PTHREAD_COND_INITIALIZER.

Make sure there are no threads waiting for the condition variable before destroying it. You can use it again if you want to; just make sure you call pthread_cond_init() first.