

Package ‘micsPlusTableR’

September 8, 2026

Title MICS Plus Excel Tabulation and Review Application

Version 0.3.0

Description Runs interactive and scriptable workflows for preparing, tabulating, checking, reviewing, and exporting MICS Plus tables from an Excel tabulation plan, survey data files, and a survey-specific preparation script.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.2.0)

Imports bslib, DiagrammeR, dplyr, flextable, ggplot2, gt, haven, Hmisc, here, htmltools, htmlwidgets, janitor, jsonlite, knitr, labelled, later, officer, openxlsx2, purrr, reactable, readr, readxl, reshape2, rlang, RM.weights, shiny, shinyFiles, sjlabelled, srvyr, stringdist, stringr, survey, tibble, tidyr, tidyxl

Suggests testthat (>= 3.0.0), rmarkdown

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Config/build/clean-inst-doc FALSE

Contents

micsPlusTableR-package	2
as_sdmx_compatible	4
calc_cells	5
check_mics_table	6
col_group_perc_total_check	6
col_group_total_check	7
compare_mics_tables	7
condition-parsing	8
create_excel_workbooks	9
direction-tabulation	9
extract_var	10

filter_second	10
get_blank_cols	11
list_survey_files	11
mics_session	13
mics_table_name	13
normalize_condition_text	14
offline-workflow	14
pivot_mics_table	15
prepare_mics_data	15
read_mics_tabulation	16
read_previous_mics_table	16
row_group_perc_total_check	17
row_group_total_check	18
row_indent_group_perc_total_check	18
row_indent_group_total_check	19
run_app	20
survey_choices	20
tabulate_extra_table	21
tabulate_mics_table	22
validate_sdmx_compatible	22
write_mics_footnotes	23
write_mics_table	23

Index 25

micsPlusTableR-package

micsPlusTableR: MICS Plus Excel tabulation and review

Description

Prepare, tabulate, check, review, and export MICS Plus survey tables using an Excel tabulation plan. Work interactively with `run_app()` or use the scripting functions with an isolated `mics_session()`.

Inputs

Supply an Excel tabulation plan with an IDX worksheet and a worksheet for each table, household and household-member SPSS files, and a survey-specific R preparation script that reads `hh_path` and `hl_path` and creates data frames named `hh` and `hl`. A sibling `FIES-inputs` directory is optional.

User setup

Install R and an editor such as RStudio Desktop. Before installing this package or starting the app, create or open your own survey project. In RStudio, use File > New Project for a new or existing folder, or File > Open Project for an existing `.Rproj` file. Install the package with `remotes::install_github("barisr/micsPlusTableR")` after installing `remotes`, then restart R. The bundled `doc/user-guide.pdf` and `doc/user-guide.html` explain computer setup, project creation, installation, and file uploads for beginners. The app's User's Guide tab opens the guide after launch.

Positron, VS Code, Cursor, Jupyter with an R kernel, and R's own console can also run the package. Configure R support and start R in the survey folder. Check `getwd()` and `here::here()` or set

`output_dir` explicitly; use `launch.browser = TRUE` if needed. Remote sessions need browser routing and access to server files. Users do not need the maintainer's project.

Interactive workflow

Reopen the survey project on each visit; installation is normally needed only once per R library. Select inputs again for each app session. Start `run_app()`. In Download Files, load the list and download one, several, or all survey folders to the current project or a chosen location. This saves plans and preparation materials; household/member data must be obtained from <https://mics.unicef.org/surveys> with permission. In Data Preparation, select the survey and wave, provide the inputs, prepare the data, calculate tables, review checks, and export the results. The app creates micsPlusTableR-output in the project root by default. To select another location, pass the `output_dir` argument to `run_app()`.

Scripting workflow

The main steps are:

- `mics_session()` creates an isolated session.
- `prepare_mics_data()` runs the preparation script.
- `tabulate_mics_table()` calculates cell results.
- `check_mics_table()` checks consistency.
- `pivot_mics_table()` arranges results for review.
- `create_excel_workbooks()` creates output workbooks.
- `write_mics_table()` writes the results.
- `write_mics_footnotes()` writes table footnotes.
- `read_previous_mics_table()` reads an earlier output.
- `compare_mics_tables()` compares two outputs.

See [offline-workflow](#) for a complete scripting example.

Individual steps and testing

`tabulate_v()` and `tabulate_h()` calculate a loaded plan in a specific direction; `calc_cells()` tests cells against explicit input data. `tabulate_extra_table()` maps supplied values to the loaded plan. `row_condition_f()` parses row predicates. `col_condition_f()` parses column predicates. `normalize_condition_text()` normalizes Excel text. `extract_var()` identifies variables. `get_blank_cols()` supports worksheet cleanup. `filter_second()` supports comparison cleanup.

Run a single consistency check:

- `row_group_total_check()` checks row counts.
- `row_group_perc_total_check()` checks row percentages.
- `col_group_total_check()` checks column counts.
- `col_group_perc_total_check()` checks column percentages.
- `row_indent_group_total_check()` checks indented counts.
- `row_indent_group_perc_total_check()` checks indented percentages.

Each returns status, issue count, all comparisons, and failing comparisons. Stateful helpers take a session; see the getting-started vignette for examples.

Survey and wave configuration

Maintain inst/extdata/survey_choices.csv in the package source. It remains a plain, editable CSV on GitHub and is bundled automatically on installation. See [survey_choices](#) for its columns, validation rules, and update workflow.

Outputs and interpretation

Outputs include Excel workbooks and long-format observations. The app offers Excel, CSV, and RDS downloads of the full prepared long-format dataset. Use `as_sdmx_compatible()` to convert observations to the project’s SDMX-compatible contract. Use `validate_sdmx_compatible()` to check them. This contract does not by itself establish compliance with an external SDMX data structure. Table checks assess consistency; analysts remain responsible for preparation scripts, survey design, denominators, and interpretation of estimates.

Author(s)

Maintainer: MICS Plus Tabulation Team <micsplustabler@example.org>

See Also

[run_app\(\)](#), [survey_choices](#), [offline-workflow](#)

Examples

```
session <- mics_session()
session
system.file("extdata", "survey_choices.csv", package = "micsPlusTableR")
```

as_sdmx_compatible	<i>Add an SDMX-compatible observation profile to MICS cell results</i>
--------------------	--

Description

Converts either the package’s engine cell results or an already standardized MICS cell table into a 35-variable long-format contract adapted from the mics-translation project. The output omits the custom table_id, value, estimate, digits, and unw duplicates; use TABLE_ID, OBS_VALUE, DECIMALS, and denominator_n instead. Input fields are unchanged. Source coordinates remain in row_order and column_order; the redundant row_id, column_id, ROW_ID, and COLUMN_ID fields are omitted. The output also omits unweighted_n, which duplicates denominator_n for engine cells. For standardized input, the supplied denominator_n is retained. The optional input unit_measure override is applied to UNIT_MEASURE but is not included as a separate output field.

Usage

```
as_sdmx_compatible(cells, config, table_id = NULL, table_context = NULL)
```

Arguments

cells	A data frame with one row per table cell.
config	A list containing frequency, ref_area, survey_id, and time_period.
table_id	Table identifier. Required for raw engine cell results.
table_context	Optional parsed tabulation context used to recover multi-level column headers and suppression settings.

Value

A tibble with one row per observation and the 35 standardized fields.

calc_cells	<i>Calculate individual horizontal table cells</i>
------------	--

Description

Calculate individual horizontal table cells

Usage

```
calc_cells(df, tab_r, tab_c3, tab, weight_var, weighted = FALSE)
```

Arguments

df	Prepared data frame, after block filters and calculations.
tab_r	Row specification with row_index and row_lgc.
tab_c3	Column specification with col_index, col_condition, and col_var_name; optional col_logic preserves display labels.
tab	Cell specification with row_index, col_index, and stat_type.
weight_var	Weight-column name. May be NA for unweighted calculations.
weighted	FALSE for unweighted results, TRUE for weighted results, or "both" (legacy mode, returns the unweighted result only).

Details

Supports n/n1, n_unw/n_unw1, p/p1/mean, mean(variable), median(variable), p_sum(variable), and 100. Median and Mean -prefixed indicators are unweighted. p_sum always uses the supplied weight column. Missing statistic cells return NA. An empty denominator can produce NaN.

Value

A tibble with row/column indices, logic, statistic, and numeric value.

Examples

```
calc_cells(data.frame(total = c(1, 1)),
  data.frame(row_index = 9L, row_lgc = "TRUE"),
  data.frame(col_index = 3L, col_condition = "total == 1", col_var_name = "total_1"),
  data.frame(row_index = 9L, col_index = 3L, stat_type = "n_unw"),
  weight_var = NA_character_)
```

check_mics_table	<i>Run all applicable consistency checks</i>
------------------	--

Description

Run all applicable consistency checks

Usage

```
check_mics_table(session, table = NULL, tolerance = 1e-06)
```

Arguments

session	A tabulation session.
table	Cell results; defaults to the session's latest result.
tolerance	Maximum absolute difference treated as consistent.

Value

A list containing a summary data frame and detailed check tables.

col_group_perc_total_check	<i>Check that column-block percentages sum to 100</i>
----------------------------	---

Description

Check that column-block percentages sum to 100

Usage

```
col_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

col_group_total_check *Compare column-group counts with the overall total*

Description

Compare column-group counts with the overall total

Usage

```
col_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

compare_mics_tables *Compare two generated tables*

Description

Compare two generated tables

Usage

```
compare_mics_tables(
  previous,
  current,
  ignore_col_names = FALSE,
  show_diff_over = 0
)
```

Arguments

previous	Previous or approved table.
current	Current table.
ignore_col_names	Compare columns by position instead of name.
show_diff_over	Minimum absolute numeric difference to report.

Value

A data frame containing differing cells.

condition-parsing	<i>Parse row and column conditions from a plan</i>
-------------------	--

Description

Parse row and column conditions from a plan

Usage

```
row_condition_f(tab_r)
col_condition_f(tab_c)
```

Arguments

tab_r	Data frame containing row_index and row_lgc.
tab_c	Data frame containing col_index and col_lgc.

Details

Row parsing separates mutate calls from predicates; blank or NA row logic means TRUE. Column parsing uses the last meaningful line after excluding source, filter, calculation, separator, and weight lines. These helpers parse text; they do not evaluate it against survey data.

Value

A tibble containing the index, original condition, cleaned condition, and generated variable name. Row output also contains calculation.

create_excel_workbooks	<i>Create output workbooks from a tabulation plan</i>
------------------------	---

Description

Copies the tabulation plan to standard output names without overwriting an existing file. A numeric suffix is added after a filename collision.

Usage

```
create_excel_workbooks(  
  path_tab_excel,  
  output_dir,  
  country_code,  
  period,  
  wave,  
  target = c("both", "output", "formatted"),  
  time_tag = format(Sys.time(), "%Y%m%d%H%M%S")  
)
```

Arguments

- path_tab_excel Existing .xls or .xlsx tabulation plan.
- output_dir Directory where workbooks will be created.
- country_code Short country code used in filenames.
- period Survey period used in filenames.
- wave Wave label used in filenames.
- target One of "output", "formatted", or "both".
- time_tag Timestamp used in filenames.

Value

A list with output and formatted paths.

direction-tabulation	<i>Calculate a table with a specific direction</i>
----------------------	--

Description

These lower-level entry points use the currently loaded plan. Vertical tabulation filters by column and computes row indicators; horizontal tabulation processes column filter blocks and computes column indicators. The direction must match the loaded plan. Both save the returned result in session\$cell_results. Use [tabulate_mics_table\(\)](#) for automatic selection and the additional variable-explanation labels.

Usage

```
tabulate_v(session, skip_row_conditions = FALSE)
```

```
tabulate_h(session, skip_row_conditions = FALSE)
```

Arguments

session A session created by `mics_session()` with prepared data and a plan loaded by `read_mics_tabulation()`.

skip_row_conditions Logical; replace row predicates with TRUE during calculation while retaining their labels. Intended for extra-table testing.

Value

A long-format cell-results data frame.

<code>extract_var</code>	<i>Extract the leading variable from a condition</i>
--------------------------	--

Description

Extract the leading variable from a condition

Usage

```
extract_var(x)
```

Arguments

x One condition string.

Value

A character scalar naming the left-hand operand of a comparison, between, or membership expression; NA for unsupported or invalid syntax.

<code>filter_second</code>	<i>Remove rows with a missing second-column value</i>
----------------------------	---

Description

Remove rows with a missing second-column value

Usage

```
filter_second(.)
```

Arguments

. A data frame with at least two columns.

Value

The input data frame with rows containing NA in column two removed.

Examples

```
filter_second(data.frame(label = c("A", "B"), value = c(NA, 3)))
```

get_blank_cols	<i>Find blank worksheet header columns</i>
----------------	--

Description

Find blank worksheet header columns

Usage

```
get_blank_cols(tab)
```

Arguments

tab Wide data frame containing row_index and Excel columns named 1, 2, etc. Header rows 3 through 8 are inspected.

Value

Sorted integer column indices, excluding column 1. NA, empty text, and the string NA count as blank.

list_survey_files	<i>List or download survey tabulation plans and preparation files</i>
-------------------	---

Description

Discover or download tabulation plans, preparation scripts, and their supporting reference assets from the separate survey files repository. Household and household-member microdata are not distributed here; obtain them separately from the MICS Plus website with the required permission. The repository must be public. No GitHub account or token is needed for these plans and preparation files.

Usage

```
list_survey_files(repo = "barisr/micsPlusTableR-Files", ref = "main")

download_survey_files(
  surveys = NULL,
  files = NULL,
  dest_dir = "inputs",
  overwrite = FALSE,
  quiet = FALSE,
  repo = "barisr/micsPlusTableR-Files",
  ref = "main"
)
```

Arguments

repo	GitHub repository in owner/name form.
ref	Branch, tag, or commit to download. Defaults to "main".
surveys	Character vector of root survey folder names, such as "JAM_W1". NULL selects all surveys.
files	Character vector of exact repository-relative paths from <code>list_survey_files()</code> . NULL selects all files in the selected surveys.
dest_dir	Destination folder, relative to the current R working directory unless an absolute path is supplied. Defaults to "inputs".
overwrite	Replace existing files? Defaults to FALSE; any existing selected file stops the operation before downloading file contents.
quiet	Suppress file download progress and the completion message?

Details

Survey folders use a three-letter country code and wave, such as JAM_W1. Downloads include root-level Excel plans (.xls, .xlsx) and .R scripts or .RData reference assets inside prep-files-* subfolders. Other files, including SPSS microdata and hidden files, are excluded. Preparation subfolders are preserved. A single Git commit is resolved before listing or downloading, so changes to the branch during a download cannot mix remote versions. Newly published survey folders are discovered without a package update.

Downloads are staged and their sizes checked before destination files are written. A network failure leaves existing destination files unchanged. Files are downloaded in binary mode and are never executed. Selecting individual files may omit preparation helpers; select a whole survey folder for all its published materials. Microdata must still be obtained separately. Git LFS pointers are not supported.

Internet access is required. Unauthenticated GitHub API rate limits apply; if a request fails, check the connection and public repository/ref, or retry later. The browser ZIP link in the user's guide is an alternative.

Value

`list_survey_files()` returns a data frame with survey, path, size (bytes), and url columns, plus a commit attribute. `download_survey_files()` invisibly returns the selected rows with an additional local_path column and the same commit attribute.

Examples

```
## Not run:
available <- list_survey_files()
unique(available$survey)
download_survey_files("JAM_W1")
download_survey_files(c("JAM_W1", "MNG_W2"), dest_dir = "survey-inputs")
download_survey_files() # Plans and preparation files for all surveys
available$path # Copy exact paths to select individual files
download_survey_files(files = available$path[1])

## End(Not run)
```

mics_session	<i>Create a non-Shiny MICS Plus tabulation session</i>
--------------	--

Description

Create a non-Shiny MICS Plus tabulation session

Usage

```
mics_session(hh = NULL, hl = NULL)
```

Arguments

hh	Optional prepared household data frame.
hl	Optional prepared household-member data frame.

Value

A mutable, isolated tabulation session environment.

mics_table_name	<i>Get the current table title</i>
-----------------	------------------------------------

Description

Get the current table title

Usage

```
mics_table_name(session)
```

Arguments

session	A session with a tabulation sheet already read.
---------	---

Value

The table title as a character scalar.

```
normalize_condition_text
```

Normalize condition text copied from Excel

Description

Normalize condition text copied from Excel

Usage

```
normalize_condition_text(x)
```

Arguments

`x` Character vector of conditions.

Value

Trimmed text with smart quotes, nonbreaking spaces, and Unicode comparison/logical operators replaced by their R equivalents; NA is retained.

```
offline-workflow
```

Run MICS Plus tabulation workflows outside Shiny

Description

These functions provide the supported non-Shiny interface to the packaged tabulation engine. The explicit session keeps survey data, plan context, extra tables, and calculated results together without writing them into the user's global workspace.

Details

Prepare survey data in a new session, calculate a table from the Excel plan, check its consistency, and pivot it for review before writing results. The example requires analyst-supplied files. See the package overview for links to the function references and workbook export steps.

See Also

[micsPlusTableR-package](#)

Examples

```
## Not run:
session <- mics_session()
prepare_mics_data(
  session,
  "hh.sav",
  "hl.sav",
  prep_script = "survey-preparation/survey_prep.R",
  output_dir = "micsPlusTableR-output"
)
```

```

result <- tabulate_mics_table(session, "TabulationPlan.xlsx", "1.1")
checks <- check_mics_table(session, result)
preview <- pivot_mics_table(session, result, type = "header")

## End(Not run)

```

pivot_mics_table	<i>Pivot long-format cell results for review</i>
------------------	--

Description

Pivot long-format cell results for review

Usage

```

pivot_mics_table(
  session,
  table = NULL,
  formatted = FALSE,
  type = c("index", "header", "logic")
)

```

Arguments

session	A tabulation session.
table	Cell results; defaults to the session's latest result.
formatted	FALSE, TRUE, or "view" as supported by the engine.
type	One of "index", "header", or "logic".

Value

A wide review table.

prepare_mics_data	<i>Run a survey preparation script outside the Shiny application</i>
-------------------	--

Description

Run a survey preparation script outside the Shiny application

Usage

```

prepare_mics_data(session, hh_path, hl_path, prep_script, output_dir = NULL)

```

Arguments

session	A session created by <code>mics_session()</code> .
hh_path	Path to the household .sav file.
hl_path	Path to the household-member .sav file.
prep_script	Path to the trusted preparation .R script. A sibling FIES-inputs folder is detected automatically.
output_dir	Main output folder. If the script's folder contains FIES-inputs, FIES artifacts are written to FIES-outputs below this folder.

Value

The session, invisibly.

read_mics_tabulation	<i>Read one sheet from a MICS Plus tabulation plan</i>
----------------------	--

Description

Read one sheet from a MICS Plus tabulation plan

Usage

```
read_mics_tabulation(session, path_tab_excel, sheet)
```

Arguments

session	A session created by <code>mics_session()</code> .
path_tab_excel	Path to the Excel tabulation plan.
sheet	Sheet name or index.

Value

The parsed tabulation-plan context.

read_previous_mics_table	<i>Read a previously generated worksheet for comparison</i>
--------------------------	---

Description

Read a previously generated worksheet for comparison

Usage

```
read_previous_mics_table(path, sheet, skip = 3)
```

Arguments

path	Excel workbook path.
sheet	Sheet name or index.
skip	Number of header rows to skip.

Value

A cleaned table.

row_group_perc_total_check	<i>Check that row-group percentages sum to 100</i>
----------------------------	--

Description

Check that row-group percentages sum to 100

Usage

```
row_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_group_total_check *Compare row-group counts with the overall total*

Description

Compare row-group counts with the overall total

Usage

```
row_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_indent_group_perc_total_check
Compare indented child percentages with their parent row

Description

Compare indented child percentages with their parent row

Usage

```
row_indent_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_indent_group_total_check

Compare indented child counts with their parent row

Description

Compare indented child counts with their parent row

Usage

```
row_indent_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

run_app	<i>Run the micsPlusTableR Shiny application</i>
---------	---

Description

Starts the Shiny application bundled with micsPlusTableR. The Download Files tab saves survey plans and preparation files to the current project by default; its destination can be changed in the tab.

Usage

```
run_app(
  host = "127.0.0.1",
  port = getOption("shiny.port"),
  launch.browser = interactive(),
  output_dir = NULL,
  ...
)
```

Arguments

host	Host interface passed to shiny::runApp().
port	Port passed to shiny::runApp(); NULL selects a free port.
launch.browser	Whether to open the application in a browser.
output_dir	Default directory for generated Excel workbooks. When NULL, the app creates micsPlusTableR-output in the project root detected by here::here().
...	Additional arguments passed to shiny::runApp().

Value

Invisibly returns the value from shiny::runApp().

survey_choices	<i>Maintain survey and wave choices</i>
----------------	---

Description

The plain UTF-8 CSV file ‘inst/extdata/survey_choices.csv’ in the package source controls the application’s survey and wave selectors. Edit this source file directly before committing to GitHub or building the package.

Columns

Each row represents one available country, period, and wave combination. All four columns are read as character strings:

country Full country name, for example Jamaica.

country_code Exactly three uppercase letters, for example JAM.

period Survey period as text, for example 2023-24.

wave Wave label, for example Wave 1.

Keep the column names. The file must have at least one row, with no empty fields or duplicate country/period/wave combinations. All waves of the same country and period must use the same country code. Leading and trailing whitespace is removed. Row order determines selector order and defaults.

Editing and installation

Use a text editor or a spreadsheet editor that preserves the period and wave columns as text. Save as UTF-8 CSV. From the package root, run `source("run_dev.R")` to load and launch the development source. Stop and restart the app after saving changes.

The CSV requires no conversion to an R data object.

R installs 'inst/extdata' files into the package's 'extdata' directory. For installed packages, reinstall the updated source and restart the app. Direct edits to an installed copy are replaced by re-installation or upgrades. The selected code, full period, and wave also contribute to output filenames and long-format metadata.

See Also

[run_app](#), [micsPlusTableR-package](#)

Examples

```
path <- system.file("extdata", "survey_choices.csv", package = "micsPlusTableR")
choices <- read.csv(path, colClasses = "character", fileEncoding = "UTF-8-BOM")
choices
```

tabulate_extra_table	<i>Map a supplied extra table to the current plan</i>
----------------------	---

Description

Map a supplied extra table to the current plan

Usage

```
tabulate_extra_table(session, table)
```

Arguments

session	A prepared session with a loaded plan.
table	A data frame whose first column contains row labels and whose remaining columns contain values in plan order.

Details

Row logic is retained as metadata, not evaluated against survey data. Values are mapped by position and the engine applies suppression.

Value

Long-format results, also saved in `session$cell_results`.

<code>tabulate_mics_table</code>	<i>Tabulate a MICS Plus table outside the application</i>
----------------------------------	---

Description

Tabulate a MICS Plus table outside the application

Usage

```
tabulate_mics_table(session, path_tab_excel = NULL, sheet = NULL)
```

Arguments

<code>session</code>	A prepared tabulation session.
<code>path_tab_excel</code>	Optional tabulation-plan path. Supply with <code>sheet</code> to read a new table before tabulating.
<code>sheet</code>	Optional sheet name or index.

Value

A long-format data frame containing one row per calculated cell.

<code>validate_sdmx_compatible</code>	<i>Validate SDMX-compatible MICS long-format data</i>
---------------------------------------	---

Description

Checks the complete 35-variable contract and the unique observation key: `SURVEY_ID`, `TABLE_ID`, `row_order`, `column_order`, and `TIME_PERIOD`.

Usage

```
validate_sdmx_compatible(data)
```

Arguments

<code>data</code>	A data frame produced by as_sdmx_compatible() .
-------------------	---

Value

`data`, invisibly.

write_mics_footnotes *Add standard footnotes to a tabulation workbook*

Description

Add standard footnotes to a tabulation workbook

Usage

```
write_mics_footnotes(session, destination, sheet = NULL, table = NULL)
```

Arguments

session	A tabulation session.
destination	Existing destination workbook.
sheet	Sheet name or index; defaults to the current sheet.
table	Cell results; defaults to the latest result.

Value

The destination path, invisibly.

write_mics_table *Write cell results to a tabulation workbook*

Description

Write cell results to a tabulation workbook

Usage

```
write_mics_table(
  session,
  destination,
  sheet = NULL,
  table = NULL,
  formatted = FALSE,
  drop_n_unw = FALSE
)
```

Arguments

session	A tabulation session with a loaded plan.
destination	Existing destination workbook.
sheet	Sheet name or index; defaults to the current sheet.
table	Cell results; defaults to the latest result.
formatted	Whether to write formatted display values.
drop_n_unw	Whether to omit unweighted-count columns when formatting.

Value

The destination path, invisibly.

Index

- * **documentation**
 - survey_choices, 20
- * **package**
 - micsPlusTableR-package, 2
- as_sdmx_compatible, 4
- as_sdmx_compatible(), 4, 22
- calc_cells, 5
- calc_cells(), 3
- check_mics_table, 6
- check_mics_table(), 3, 6, 7, 17–19
- col_condition_f (condition-parsing), 8
- col_condition_f(), 3
- col_group_perc_total_check, 6
- col_group_perc_total_check(), 3
- col_group_total_check, 7
- col_group_total_check(), 3
- compare_mics_tables, 7
- compare_mics_tables(), 3
- condition-parsing, 8
- create_excel_workbooks, 9
- create_excel_workbooks(), 3
- direction-tabulation, 9
- download_survey_files
 - (list_survey_files), 11
- extract_var, 10
- extract_var(), 3
- filter_second, 10
- filter_second(), 3
- get_blank_cols, 11
- get_blank_cols(), 3
- list_survey_files, 11
- list_survey_files(), 12
- mics_session, 13
- mics_session(), 2, 3, 10, 16
- mics_table_name, 13
- micsPlusTableR
 - (micsPlusTableR-package), 2
 - micsPlusTableR-package, 2
 - normalize_condition_text, 14
 - normalize_condition_text(), 3
 - offline-workflow, 3, 4, 14
 - pivot_mics_table, 15
 - pivot_mics_table(), 3
 - prepare_mics_data, 15
 - prepare_mics_data(), 3
 - read_mics_tabulation, 16
 - read_mics_tabulation(), 10
 - read_previous_mics_table, 16
 - read_previous_mics_table(), 3
 - row_condition_f (condition-parsing), 8
 - row_condition_f(), 3
 - row_group_perc_total_check, 17
 - row_group_perc_total_check(), 3
 - row_group_total_check, 18
 - row_group_total_check(), 3
 - row_indent_group_perc_total_check, 18
 - row_indent_group_perc_total_check(), 3
 - row_indent_group_total_check, 19
 - row_indent_group_total_check(), 3
 - run_app, 20, 21
 - run_app(), 2–4
 - survey_choices, 4, 20
 - tabulate_extra_table, 21
 - tabulate_extra_table(), 3
 - tabulate_h (direction-tabulation), 9
 - tabulate_h(), 3
 - tabulate_mics_table, 22
 - tabulate_mics_table(), 3, 9
 - tabulate_v (direction-tabulation), 9
 - tabulate_v(), 3
 - validate_sdmx_compatible, 22
 - validate_sdmx_compatible(), 4
 - write_mics_footnotes, 23
 - write_mics_footnotes(), 3
 - write_mics_table, 23
 - write_mics_table(), 3