

Package ‘micsPlusTableR’

September 19, 2026

Title MICS Plus Excel Tabulation and Review Application

Version 0.3.1

Description Provides the MICS Plus Tabulation application for preparing, calculating, checking, exploring, and exporting survey tables from an Excel tabulation plan, survey data, and a survey-specific preparation script. The package is built primarily to support this browser-based application. Its documented R functions expose the supporting engine for reference, testing, and workflows run directly in R.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R (>= 4.2.0)

Imports bslib, dplyr, flextable, haven, here, htmltools, htmlwidgets, janitor, jsonlite, later, officer, openxlsx2, purrr, reactable, readr, readxl, rlang, shiny, shinyFiles, stringr, tibble, tidyr, tidyr, tidyr, ggplot2, Hmisc, labelled, memisc, reshape2, RM.weights, survey, srvyr

Suggests testthat (>= 3.0.0)

Config/micsPlusTableR/prep-packages ggplot2, Hmisc, labelled, memisc, reshape2, RM.weights, survey, srvyr

Config/testthat/edition 3

NeedsCompilation no

Config/build/clean-inst-doc FALSE

Config/roxygen2/version 8.1.0

Contents

micsPlusTableR-package	2
as_sdmx_compatible	6
calc_cells	7
check_mics_table	8
check_prep_dependencies	8
col_condition_f	9
col_group_perc_total_check	10
col_group_total_check	10
compare_mics_tables	11

create_excel_workbooks	11
download_survey_files	12
extract_var	14
filter_second	14
get_blank_cols	15
install_prep_dependencies	15
list_survey_files	16
mics_session	17
mics_table_name	18
normalize_condition_text	18
offline-workflow	19
package-dependencies	20
pivot_mics_table	21
prep-script-dependencies	22
prepare_mics_data	23
read_mics_tabulation	24
read_previous_mics_table	24
row_condition_f	25
row_group_perc_total_check	25
row_group_total_check	26
row_indent_group_perc_total_check	27
row_indent_group_total_check	27
run_app	28
statistic-precision	29
statistic-types	30
survey_choices	32
tabulate_extra_table	33
tabulate_h	33
tabulate_mics_table	34
tabulate_v	35
validate_sdmx_compatible	35
worksheet-conditions	36
write_mics_footnotes	37
write_mics_table	38

Index	39
--------------	-----------

micsPlusTableR-package

micsPlusTableR: MICS Plus Excel tabulation and review

Description

micsPlusTableR is the R package behind the MICS Plus Tabulation application. Its main purpose is to provide a browser-based interface for preparing survey data, calculating tables from a tabulation plan, checking results, exploring data, and saving outputs when needed. Start the application with `run_app()`. R performs the calculations; Shiny provides the interface running in the browser.

The app and the supporting functions

The package was created primarily to serve the application. Most other functions perform background tasks used by, or exposed from, its tabulation engine. Their help pages document how the system works and support testing, diagnosis, and workflows run entirely in R. App users do not need to call these functions individually or follow the function index as a workflow.

Use the bundled User's Guide for setup, tab-by-tab instructions, and understanding a tabulation plan. Use this reference manual for exact function arguments, return values, examples, and engine behavior.

Two routes to producing tables

Use supplied plans, preparation files, and matching survey data, or create and adapt a tabulation plan with a compatible preparation script and data. Both routes can use the application. Creating a plan does not require replacing the app with a scripted workflow. Results can be reviewed in the app without exporting; Excel workbooks and combined table-data downloads are available when files are needed.

Inputs

Supply an Excel tabulation plan with an IDX worksheet and a worksheet for each table, household and household-member SPSS files, and a survey-specific preparation folder containing one main R script that reads `hh_path` and `hl_path` and creates data frames named `hh` and `hl`. Include its supporting files; a `FIES-inputs` subfolder is needed when the selected script uses it.

User setup

Install R and an editor such as RStudio Desktop. Before installing this package or starting the app, create or open your own survey project. In RStudio, use `File > New Project` for a new or existing folder, or `File > Open Project` or double-click an existing `.Rproj` file. Install remotes only if it is not already available; once installed, it need not be installed again for ordinary use. Then install this package with `remotes::install_github("barisr/micsPlusTableR")` and restart the R session before launching the app. Restart R after package updates too. The bundled `doc/user-guide.pdf` and `doc/user-guide.html` explain computer setup, project creation, installation, and file uploads for beginners. The app's User's Guide tab opens the guide after launch.

Positron, VS Code, Cursor, Jupyter with an R kernel, and R's own console can also run the package. Configure R support and start R in the survey folder. Check `getwd()` and `here::here()` or set `output_dir` explicitly; use `launch.browser = TRUE` if needed. Remote sessions need browser routing and access to server files. Users do not need the maintainer's project.

Application tabs and outputs

Reopen the survey project on each visit and start `run_app()`. Select inputs again for each app session. The app opens on Data Preparation; its tabs are arranged in this order:

1. User's Guide: read the embedded instructions, open the full guide in a separate browser tab, or download the PDF.
2. Download Files: obtain plans and preparation materials for one, several, or all surveys. Readable names include Jamaica (2023–24) Wave 1. Downloads default to the current project. Household/member microdata are obtained separately from the [MICS surveys page](#) with permission.
3. Data Preparation: choose the country, period, and wave; select the data, plan, and complete preparation folder; click Set.

4. Tabulator: calculate one sheet and inspect its values. Header shows descriptive labels, Index shows worksheet positions, and Logic shows conditions. These views do not change the calculations.
5. Consistency Checks: compare counts and percentages across groups. Checks and their results remain visible in the app without console output. A check that does not apply is not a passing validation.
6. Write to Excel: create or select workbooks and write the current table. Keep the same destinations when adding more tables.
7. Multi-Sheet Tabulator: calculate and write selected sheets together. It creates required workbooks automatically for unset destinations and reuses destinations already created or selected in Write to Excel.
8. Data Exploration: investigate frequencies and cross-tabulations.
9. Data View: inspect selected variables in the prepared survey data.
10. Long Format Data: combine calculated table cells and download the complete result as Excel, CSV, or RDS, irrespective of preview filters.

Choose the tools needed for the task; using every tab or exporting is not required. Generated workbooks default to `micsPlusTableR-output` in the project root; `run_app()` accepts another `output_dir`. Previously saved workbook destinations are not restored after restarting the app: select them explicitly to continue writing to those files.

Understanding a tabulation plan

The User's Guide explains the worksheet layout, dataset name in B4:B7, filters, row/column conditions, and cell statistics, for readers as well as plan authors. [worksheet-conditions](#) explains output-oriented condition design, total aliases, and household-member bases. [statistic-types](#) documents each statistic's population, weighting, and supported direction. [statistic-precision](#) explains optional `d=` display settings. [tabulate_h\(\)](#) documents global and additional filters, including non-mean-to-mean boundaries and consecutive mean columns.

Internet access

Installing packages and downloading survey materials require internet. The app's workbook preview loads the SheetJS browser library externally; a browser may cache it, but availability after closing or clearing the browser is not guaranteed. Once packages and inputs are local, table calculations and Excel output do not require that library or an external download.

Scripting workflow

For work directly in R, use an isolated session and call the required steps. These interfaces also make the app's engine available for testing:

- `mics_session()` creates an isolated session.
- `prepare_mics_data()` runs the preparation script.
- `read_mics_tabulation()` reads a worksheet's instructions.
- `tabulate_mics_table()` calculates cell results.
- `check_mics_table()` checks consistency.
- `pivot_mics_table()` arranges results for review.
- `create_excel_workbooks()` creates output workbooks.
- `write_mics_table()` writes the results.

- `write_mics_footnotes()` writes table footnotes.
- `read_previous_mics_table()` reads an earlier output.
- `compare_mics_tables()` compares two outputs.

See [offline-workflow](#) for a complete scripting example.

Individual steps and testing

`tabulate_v()` and `tabulate_h()` calculate a loaded plan in a specific direction; `calc_cells()` tests cells against explicit input data. `tabulate_extra_table()` maps supplied values to the loaded plan. `row_condition_f()` parses row predicates. `col_condition_f()` parses column predicates. `normalize_condition_text()` normalizes Excel text. `extract_var()` identifies variables. `get_blank_cols()` supports worksheet cleanup. `filter_second()` supports comparison cleanup.

Run a single consistency check:

- `row_group_total_check()` checks row counts.
- `row_group_perc_total_check()` checks row percentages.
- `col_group_total_check()` checks column counts.
- `col_group_perc_total_check()` checks column percentages.
- `row_indent_group_total_check()` checks indented counts.
- `row_indent_group_perc_total_check()` checks indented percentages.

Each returns status, issue count, all comparisons, and failing comparisons. Stateful helpers take a session. See [offline-workflow](#) for individual-step examples. The `calc_cells()` help page includes a runnable weighted example.

Dependencies

[package-dependencies](#) explains required app/engine packages and development tools. [prep-script-dependencies](#) documents survey packages separately. Both dependency groups install with the package; no separate preparation setup is needed.

For diagnosis, use `check_prep_dependencies()`. For repairs or extra custom-script requirements, use `install_prep_dependencies()`.

Survey and wave configuration

Maintain `inst/extdata/survey_choices.csv` in the package source. It remains a plain, editable CSV on GitHub and is bundled automatically on installation. See [survey_choices](#) for its columns, validation rules, and update workflow.

Outputs and interpretation

Outputs include Excel workbooks and long-format observations. The app offers Excel, CSV, and RDS downloads of combined calculated table cells. These are aggregate table results, distinct from the survey records shown in Data View. Use `as_sdmx_compatible()` to convert observations to the project's SDMX-compatible contract. Use `validate_sdmx_compatible()` to check them. This contract does not by itself establish compliance with an external SDMX data structure. Table checks assess consistency; analysts remain responsible for preparation scripts, survey design, denominators, and interpretation of estimates.

Author(s)

Maintainer: MICS Plus Tabulation Team <micsplustabler@example.org>

Authors:

- MICS Plus Tabulation Team <micsplustabler@example.org>

See Also

[run_app\(\)](#), [statistic-types](#), [statistic-precision](#), [survey_choices](#), [offline-workflow](#)

Examples

```
session <- mics_session()
session
system.file("extdata", "survey_choices.csv", package = "micsPlusTableR")
```

as_sdmx_compatible	<i>Add an SDMX-compatible observation profile to MICS cell results</i>
--------------------	--

Description

Converts either the package's engine cell results or an already standardized MICS cell table into a 35-variable long-format contract adapted from the mics-translation project. The output omits the custom `table_id`, `value`, `estimate`, `digits`, and `unw` duplicates; use `TABLE_ID`, `OBS_VALUE`, `DECIMALS`, and `denominator_n` instead. Input fields are unchanged. Source coordinates remain in `row_order` and `column_order`; the redundant `row_id`, `column_id`, `ROW_ID`, and `COLUMN_ID` fields are omitted. The output also omits `unweighted_n`, which duplicates `denominator_n` for engine cells. For standardized input, the supplied `denominator_n` is retained. The optional input `unit_measure` override is applied to `UNIT_MEASURE` but is not included as a separate output field.

Usage

```
as_sdmx_compatible(cells, config, table_id = NULL, table_context = NULL)
```

Arguments

<code>cells</code>	A data frame with one row per table cell.
<code>config</code>	A list containing frequency, <code>ref_area</code> , <code>survey_id</code> , and <code>time_period</code> .
<code>table_id</code>	Table identifier. Required for raw engine cell results.
<code>table_context</code>	Optional parsed tabulation context used to recover multi-level column headers and suppression settings.

Value

A tibble with one row per observation and the 35 standardized fields.

calc_cells	<i>Calculate individual horizontal table cells</i>
------------	--

Description

Calculate individual horizontal table cells

Usage

```
calc_cells(df, tab_r, tab_c3, tab, weight_var, weighted = FALSE)
```

Arguments

df	Prepared data frame, after block filters and calculations.
tab_r	Row specification with row_index and row_lgc.
tab_c3	Column specification with col_index, col_condition, and col_var_name; optional col_logic preserves display labels.
tab	Cell specification with row_index, col_index, and stat_type.
weight_var	Weight-column name. Unweighted calculations may use NA. The p_sum statistic always needs a weight column.
weighted	FALSE for unweighted results, TRUE for weighted results, or "both" (legacy mode, returns the unweighted result only).

Details

This background helper is available for explicit cell tests and code-only work; app users normally use Tabulator. Supported statistics include counts, indicator percentages, numeric means, medians, and constant totals. See [statistic-types](#) for the complete horizontal forms and their populations. With n_unw or n_unw1, the column condition hhmembers instead sums HLnum for row-selected records with total == 1. This is a household member base from household records, not an ordinary record count. Worksheet aliases such as total1 == 1 and totalHL == 1 are converted by [read_mics_tabulation\(\)](#), not this helper; see [worksheet-conditions](#).

Bare mean is an indicator percentage; mean(variable) averages the named variable. Median and mean_unw forms are unweighted, as are legacy capitalized Mean indicators. The p_sum statistic divides the variable sum by the weight sum within both conditions, then multiplies by 100.

Missing statistic cells return NA. An empty denominator can produce NaN. Optional d= arguments are returned as display_digits metadata and never round the calculated value; see [statistic-precision](#).

Value

A tibble with row/column indices, logic, statistic, and numeric value.

Examples

```
calc_cells(data.frame(total = c(1, 1)),
  data.frame(row_index = 9L, row_lgc = "TRUE"),
  data.frame(col_index = 3L, col_condition = "total == 1", col_var_name = "total_1"),
  data.frame(row_index = 9L, col_index = 3L, stat_type = "n_unw"),
  weight_var = NA_character_)
```

```
# Weighted count of sex == 2: 5. Use weighted = FALSE for a count of 2.
calc_cells(
  df = data.frame(total = 1, sex = c(1, 2, 2), weight = c(1, 2, 3)),
  tab_r = data.frame(row_index = 9L, row_lgc = "TRUE"),
  tab_c3 = data.frame(col_index = 3L, col_condition = "sex == 2",
    col_var_name = "sex_2"),
  tab = data.frame(row_index = 9L, col_index = 3L, stat_type = "n"),
  weight_var = "weight", weighted = TRUE
)
```

check_mics_table

Run all applicable consistency checks

Description

Runs the six group-count and percentage checks used by the application. Direct R calls retain engine diagnostics; the app suppresses console output while showing check results in its interface. Non-applicable checks are not passing validations. Details retain internal column names such as `diff_value`; the app displays readable labels such as Difference.

Usage

```
check_mics_table(session, table = NULL, tolerance = 1e-06)
```

Arguments

<code>session</code>	A tabulation session.
<code>table</code>	Cell results; defaults to the session's latest result.
<code>tolerance</code>	Maximum absolute difference treated as consistent.

Value

A list containing a summary data frame and detailed check tables.

check_prep_dependencies

Check dependencies of a preparation script and its helpers

Description

Inspect preparation code without executing it, then check whether each required package can be loaded. App dependencies and survey-specific preparation dependencies install together and are documented separately in [prep-script-dependencies](#). This is a diagnostic tool; preparation checks dependencies automatically.

Usage

```
check_prep_dependencies(prepare_script, stop_on_missing = FALSE)
```

Arguments

`prep_script` Path to a preparation R script.

`stop_on_missing` Stop with an installation command if a required package is missing or cannot be loaded. Defaults to FALSE for inspection.

Details

Reads the script's literal `prep_dependencies` declaration, qualified calls, `library/require` calls with literal package names, and known legacy survey/FIES function calls. It also inspects all R files in the sibling FIES-inputs folder and recursively follows literal source paths. Dynamically computed package names and source paths require an explicit `prep_dependencies` declaration in the main script. This checks package availability, not numerical correctness or version compatibility of the survey code. It never executes preparation code.

Value

A data frame with `package`, `required_by` (script basenames), `available`, and `problem` (NA when loadable).

See Also

[install_prep_dependencies\(\)](#), [prepare_mics_data\(\)](#)

col_condition_f	<i>Parse column conditions from a plan</i>
-----------------	--

Description

Parse column conditions from a plan

Usage

```
col_condition_f(tab_c)
```

Arguments

`tab_c` Data frame containing `col_index` and `col_lgc`.

Details

Uses the last meaningful line after excluding source, filter, calculation, separator, and weight lines. Parses text without evaluating it against survey data. Worksheet total aliases are converted by [read_mics_tabulation\(\)](#) before this parser is called; this helper alone does not convert them.

Value

A tibble containing the column index, original condition, cleaned condition, and generated variable name.

See Also

[row_condition_f\(\)](#), [normalize_condition_text\(\)](#), [worksheet-conditions](#)

col_group_perc_total_check

Check that column-block percentages sum to 100

Description

Check that column-block percentages sum to 100

Usage

```
col_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

col_group_total_check *Compare column-group counts with the overall total*

Description

Compare column-group counts with the overall total

Usage

```
col_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use `check_mics_table()` to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

compare_mics_tables	<i>Compare two generated tables</i>
---------------------	-------------------------------------

Description

Compare two generated tables

Usage

```
compare_mics_tables(  
  previous,  
  current,  
  ignore_col_names = FALSE,  
  show_diff_over = 0  
)
```

Arguments

- previous Previous or approved table.
- current Current table.
- ignore_col_names Compare columns by position instead of name.
- show_diff_over Minimum absolute numeric difference to report.

Value

A data frame containing differing cells.

create_excel_workbooks	<i>Create output workbooks from a tabulation plan</i>
------------------------	---

Description

Copies the tabulation plan to standard output names without overwriting an existing file. A numeric suffix is added after a filename collision.

Usage

```
create_excel_workbooks(
  path_tab_excel,
  output_dir,
  country_code,
  period,
  wave,
  target = c("both", "output", "formatted"),
  time_tag = format(Sys.time(), "%Y%m%d%H%M%S")
)
```

Arguments

path_tab_excel	Existing .xls or .xlsx tabulation plan.
output_dir	Directory where workbooks will be created.
country_code	Short country code used in filenames.
period	Survey period used in filenames.
wave	Wave label used in filenames.
target	One of "output", "formatted", or "both".
time_tag	Timestamp used in filenames.

Details

Creates copies of the tabulation plan; it does not calculate or populate table results. In the app, Write to Excel calls it on request, and Multi-Sheet Tabulator calls it automatically for unset required destinations. In R workflows, call it before [write_mics_table](#) unless using an existing workbook. Unrequested entries in the returned list are NULL.

Value

A list with output and formatted paths.

download_survey_files *Download survey tabulation plans and preparation files*

Description

Save selected plans, preparation scripts, and supporting reference assets from the public survey files repository. Household and household-member microdata must be obtained separately with the required permission.

Usage

```
download_survey_files(
  surveys = NULL,
  files = NULL,
  dest_dir = "inputs",
  overwrite = FALSE,
  quiet = FALSE,
```

```

    repo = "barisr/micsPlusTableR-Files",
    ref = "main"
  )

```

Arguments

surveys	Character vector of root survey folder names, such as "Jamaica (2023-24) Wave 1". NULL selects all surveys. Legacy codes for the initial published surveys (for example, "JAM_W1") remain accepted.
files	Character vector of exact repository-relative paths from <code>list_survey_files()</code> . NULL selects all files in the selected surveys.
dest_dir	Destination folder, relative to the current R working directory unless an absolute path is supplied. Defaults to "inputs".
overwrite	Replace existing files? Defaults to FALSE; any existing selected file stops the operation before downloading file contents.
quiet	Suppress file download progress and the completion message?
repo	GitHub repository in owner/name form.
ref	Branch, tag, or commit to download. Defaults to "main".

Details

Survey folders use the country, survey period, and wave, such as Jamaica (2023-24) Wave 1. Legacy code-and-wave folders are also supported. Downloads include root-level tabulation plans (.xls, .xlsx) and .R scripts or .RData reference assets inside prep-files-* subfolders. Other files, including SPSS microdata and hidden files, are excluded. Preparation subfolders are preserved. A single Git commit is resolved before listing or downloading, so changes to the branch during a download cannot mix remote versions. Newly published survey folders are discovered without a package update.

Downloads are staged and their sizes checked before destination files are written. A network failure leaves existing destination files unchanged. Files are downloaded in binary mode and are never executed. Selecting individual files may omit preparation helpers; select a whole survey folder for all its published materials. Microdata must still be obtained separately. Git LFS pointers are not supported.

Internet access is required. Unauthenticated GitHub API rate limits apply; if a request fails, check the connection and public repository/ref, or retry later. The browser ZIP link in the user's guide is an alternative.

Value

Invisibly returns the selected file-list rows with survey, path, size, url, and local_path columns, plus the resolved commit attribute.

See Also

[list_survey_files\(\)](#)

Examples

```

## Not run:
download_survey_files("Jamaica (2023-24) Wave 1")
download_survey_files(c("Jamaica (2023-24) Wave 1",

```

```

                                "Mongolia (2025-26) Wave 2"), dest_dir = "survey-inputs")
download_survey_files() # All surveys
available <- list_survey_files()
download_survey_files(files = available$path[1])

## End(Not run)

```

extract_var	<i>Extract the leading variable from a condition</i>
-------------	--

Description

Extract the leading variable from a condition

Usage

```
extract_var(x)
```

Arguments

x One condition string.

Value

A character scalar naming the left-hand operand of a comparison, between, or membership expression; NA for unsupported or invalid syntax.

filter_second	<i>Remove rows with a missing second-column value</i>
---------------	---

Description

Remove rows with a missing second-column value

Usage

```
filter_second(.)
```

Arguments

. A data frame with at least two columns.

Value

The input data frame with rows containing NA in column two removed.

Examples

```
filter_second(data.frame(label = c("A", "B"), value = c(NA, 3)))
```

get_blank_cols	<i>Find blank worksheet header columns</i>
----------------	--

Description

Find blank worksheet header columns

Usage

```
get_blank_cols(tab)
```

Arguments

tab	Wide data frame containing row_index and Excel columns named 1, 2, etc. Header rows 3 through 8 are inspected.
-----	--

Value

Sorted integer column indices, excluding column 1. NA, empty text, and the string NA count as blank.

install_prep_dependencies	<i>Install missing preparation-script dependencies</i>
---------------------------	--

Description

Install missing preparation-script dependencies

Usage

```
install_prep_dependencies(
  prep_script,
  repos = "https://cloud.r-project.org",
  lib = .libPaths()[[1L]]
)
```

Arguments

prep_script	Path to a preparation R script.
repos	Package repository URL, defaulting to the CRAN cloud mirror.
lib	Installation library. Defaults to the first active library. It must be listed in .libPaths().

Details

Maintained survey dependencies install with `micsPlusTableR`. This function is only needed for re-pair or extra custom-script packages.

`check_prep_dependencies()` identifies missing or unloadable packages. Only those packages are installed. Transitive required dependencies are installed by R. Preparation scripts are never executed by this function.

Installation happens only when this function is explicitly called.

`prepare_mics_data()` reports missing packages without installing them.

Value

The dependency check data frame, invisibly, after installation.

See Also

`check_prep_dependencies()`, `prep-script-dependencies`

<code>list_survey_files</code>	<i>List survey tabulation plans and preparation files</i>
--------------------------------	---

Description

Discover or download tabulation plans, preparation scripts, and their supporting reference assets from the separate survey files repository. Household and household-member microdata are not distributed here; obtain them separately from the MICS Plus website with the required permission. The repository must be public. No GitHub account or token is needed for these plans and preparation files.

Usage

```
list_survey_files(repo = "bariscr/micsPlusTableR-Files", ref = "main")
```

Arguments

<code>repo</code>	GitHub repository in owner/name form.
<code>ref</code>	Branch, tag, or commit to download. Defaults to "main".

Details

Survey folders use the country, survey period, and wave, such as Jamaica (2023-24) Wave 1. Legacy code-and-wave folders are also supported. Downloads include root-level tabulation plans (.xls, .xlsx) and .R scripts or .RData reference assets inside prep-files-* subfolders. Other files, including SPSS microdata and hidden files, are excluded. Preparation subfolders are preserved. A single Git commit is resolved before listing or downloading, so changes to the branch during a download cannot mix remote versions. Newly published survey folders are discovered without a package update.

Downloads are staged and their sizes checked before destination files are written. A network failure leaves existing destination files unchanged. Files are downloaded in binary mode and are never executed. Selecting individual files may omit preparation helpers; select a whole survey folder for

all its published materials. Microdata must still be obtained separately. Git LFS pointers are not supported.

Internet access is required. Unauthenticated GitHub API rate limits apply; if a request fails, check the connection and public repository/ref, or retry later. The browser ZIP link in the user's guide is an alternative.

Value

`list_survey_files()` returns a data frame with `survey`, `path`, `size` (bytes), and `url` columns, plus a `commit` attribute.

See Also

[download_survey_files\(\)](#)

Examples

```
## Not run:
available <- list_survey_files()
unique(available$survey)
available$path

## End(Not run)
```

mics_session	Create an isolated MICS Plus tabulation session
--------------	---

Description

Holds prepared data, a loaded plan, engine functions, and results. The app creates its own session automatically. Use this function directly for code-only workflows, diagnosis, or tests; see [offline-workflow](#).

Usage

```
mics_session(hh = NULL, hl = NULL)
```

Arguments

hh	Optional prepared household data frame.
hl	Optional prepared household-member data frame.

Value

A mutable, isolated tabulation session environment.

mics_table_name	<i>Get the current table title</i>
-----------------	------------------------------------

Description

Get the current table title

Usage

```
mics_table_name(session)
```

Arguments

session	A session with a tabulation sheet already read.
---------	---

Value

The table title as a character scalar.

normalize_condition_text	<i>Normalize condition text copied from Excel</i>
--------------------------	---

Description

Normalize condition text copied from Excel

Usage

```
normalize_condition_text(x)
```

Arguments

x	Character vector of conditions.
---	---------------------------------

Value

Trimmed text with smart quotes, nonbreaking spaces, and Unicode comparison/logical operators replaced by their R equivalents; NA is retained.

offline-workflow

Run MICS Plus tabulation workflows outside Shiny

Description

The application is the main user interface. These supporting functions expose its packaged engine for reference, tests, and workflows run directly in R. They are not additional steps required when using the app. The explicit session keeps survey data, plan context, extra tables, and calculated results together without writing them into the user's global workspace.

Details

Here, outside Shiny means running without the interface, not a guarantee that every operation is offline. Installing packages or downloading survey files requires internet. With local packages and inputs, table calculations and workbook output can run offline.

Prepare survey data in a new session, calculate a table from the tabulation plan, check its consistency, and pivot it for review before writing results. The example requires analyst-supplied files. See the package overview for links to the function references and workbook export steps.

Inspect individual steps

Stateful helpers take a session as their first argument; use a separate session for each independent workflow. After preparing data, read the plan and inspect its row and column predicates before calling the direction-specific engine. `tabulate_mics_table()` selects the direction automatically and additionally attaches variable-explanation labels.

Use raw long-format numeric results for consistency checks, rather than pivoted or formatted tables. Each individual check returns status, issue_count, details (all comparisons), and issues (failing comparisons). A `not_applicable` result means the required total or distribution is absent; it is not a passing validation. `check_mics_table()` runs all six checks with a default tolerance of $1e-6$; individual helpers default to $1e-11$.

Calculation errors identify the worksheet, block or cell, and expression when available. A missing-variable message means an expression refers to a column absent from that block's prepared data. Correct the named input and rerun. Checks cannot validate the substantive choices in a preparation script or plan.

See Also

[micsPlusTableR-package](#) for the package overview.

[calc_cells](#) for a runnable weighted-count example.

[statistic-types](#) and [statistic-precision](#) for statistic reference.

[download_survey_files](#) for survey-material download examples.

Examples

```
## Not run:
session <- mics_session()
prepare_mics_data(
  session,
  "hh.sav",
  "hl.sav",
```

```

    prep_script = "survey-preparation/survey_prep.R",
    output_dir = "micsPlusTableR-output"
  )
  result <- tabulate_mics_table(session, "TabulationPlan.xlsx", "1.1")
  checks <- check_mics_table(session, result)
  preview <- pivot_mics_table(session, result, type = "header")
  # Export only when needed; this function requires an existing destination.
  workbooks <- create_excel_workbooks(
    "TabulationPlan.xlsx", "micsPlusTableR-output",
    country_code = "JAM", period = "2023-24", wave = "Wave 1"
  )
  write_mics_table(session, workbooks$output, sheet = "1.1", table = result)
  write_mics_footnotes(session, workbooks$output, sheet = "1.1", table = result)

# Alternatively, inspect and run individual steps after preparing the session.
plan <- read_mics_tabulation(session, "TabulationPlan.xlsx", "1.1")
row_rules <- row_condition_f(plan$tab_r)
column_rules <- col_condition_f(plan$tab_c)
result <- if (plan$tab_direction == "v") tabulate_v(session) else tabulate_h(session)
row_check <- row_group_total_check(session, result, diff = 1e-6)
row_check$status
row_check$issues

## End(Not run)

```

package-dependencies *Package runtime and development dependencies*

Description

Required Imports cover the app, tabulation engine, and maintained preparation scripts. They install together. Preparation-only packages are documented separately in [prep-script-dependencies](#).

Details

Runtime packages and their purposes:

- shiny, bslib, shinyFiles: application UI, server, and file selection.
- htmltools, htmlwidgets, reactable: HTML controls and table displays.
- flextable, officer: formatted table previews and borders.
- openxlsx2: Excel output workbooks and formatting.
- readxl, tidyxl: worksheet values, cell formats, and plan parsing.
- dplyr, tidyr, tibble: table transformation and cell results.
- purrr, rlang, stringr: iteration, expressions, and condition parsing.
- haven: display and clean labelled survey values in the app.
- janitor: remove empty columns from comparison workbooks.
- here: locate the user's project and default output folder.
- jsonlite: read the remote survey-file listing.
- readr: CSV downloads of long-format results.

- later: schedule application UI updates.

The development-only Suggests entry is testthat for tests. Developer tools such as roxygen2, pkgload, and remotes are installed separately as described in the README. Rebuilding the User’s Guide requires Quarto and XeLaTeX; its rendered HTML and PDF are bundled for users.

The maintainer command Rscript tools/check-dependencies.R inspects executable app and engine code, qualified references, and imported function calls. It rejects undeclared direct references and Imports with no detected usage in the app, engine, or preparation namespace loaders. It also checks that all documented preparation dependencies are required Imports. Both package and reference-manual builds run this audit.

See Also

[prep-script-dependencies](#), [micsPlusTableR-package](#)

pivot_mics_table	<i>Pivot long-format cell results for review</i>
------------------	--

Description

Pivot long-format cell results for review

Usage

```
pivot_mics_table(  
  session,  
  table = NULL,  
  formatted = FALSE,  
  type = c("index", "header", "logic")  
)
```

Arguments

session	A tabulation session.
table	Cell results; defaults to the session’s latest result.
formatted	FALSE uses raw numeric value; TRUE uses the engine’s value_f display strings; "view" uses preview strings in value_f_view.
type	"index" uses worksheet row/column positions, "header" uses descriptive labels, and "logic" uses row/column conditions. The choice changes labels, not calculated values.

Value

A wide review table.

```
prep-script-dependencies
```

Preparation script dependencies

Description

Survey preparation packages are tracked separately from the packages needed to launch the app and run the tabulation engine. Both groups are required Imports and install together with `mic-sPlusTableR`; no separate setup is needed.

Details

The maintained preparation scripts declare `prep_dependencies` near the top of the file.

`prepare_mics_data()` checks these packages and the detected helper dependencies before executing the script. The Shiny Data Preparation workflow uses the same check. Missing or unloadable packages produce an error naming the package, the script requiring it, and an installation command.

Use `check_prep_dependencies()` for diagnosis.

Use `install_prep_dependencies()` for repair or extra custom-script packages. Neither is a required step for normal installation or switching between maintained surveys.

Additional DESCRIPTION field: `Config/micsPlusTableR/prep-packages`.

Preparation-only packages in the maintained Jamaica workflows:

- `ggplot2`: FIES distribution and thermometer plots.
- `Hmisc`: weighted prevalence means in the FIES helpers.
- `memisc`: SPSS import retaining value labels for the FIES routines.
- `reshape2`: reshape FIES plotting data with `melt`.
- `RM.weights`: weighted Rasch model and food-insecurity calculations.
- `survey`: survey designs and design-based FIES estimates.
- `srvyr`: survey-design pipelines in the main preparation scripts.
- `labelled`: variable/value labels in Jamaica Wave 2 recodes.

All eight packages are installed by the normal package installation command. They are not imported into the app's namespace. Packages required by the selected script are made available in its private preparation environment; package functions already supplied by the core workflow retain precedence. Use explicit `package::function` calls if a script needs a conflicting name.

Shared dependencies are also declared by the scripts: Mongolia Waves 1 and 2 use `dplyr` and `haven`. Jamaica Waves 1 and 2 also use `here`, `tibble`, and `tidyr`; Wave 2 additionally uses `purrr`. These are already package Imports.

Keep declarations current when editing scripts or adding helpers. The checker scans the main script, all R files in its sibling `FIES-inputs` directory, and literal source paths. Declare packages used through dynamically constructed names or source paths explicitly. The checker does not execute preparation code and does not certify statistical results or package-version compatibility.

See Also

[prepare_mics_data\(\)](#), [package-dependencies](#)

Examples

```
## Not run:
prep_script <- "survey-preparation/survey_prep.R"
check_prep_dependencies(prepare_script)
# For repair or additional dependencies in a custom script only:
install_prep_dependencies(prepare_script)

## End(Not run)
```

prepare_mics_data	<i>Run a survey preparation script outside the Shiny application</i>
-------------------	--

Description

Run a survey preparation script outside the Shiny application

Usage

```
prepare_mics_data(session, hh_path, hl_path, prep_script, output_dir = NULL)
```

Arguments

session	A session created by mics_session() .
hh_path	Path to the household .sav file.
hl_path	Path to the household-member .sav file.
prep_script	Path to the trusted preparation .R script. A sibling FIES-inputs folder is detected automatically.
output_dir	Main output folder. If the script's folder contains FIES-inputs, FIES artifacts are written to FIES-outputs below this folder.

Details

Checks declared and detected preparation dependencies before running any preparation code. Maintained survey dependencies install with the package. [install_prep_dependencies\(\)](#) is available for repair or extra custom-script requirements. See [prep-script-dependencies](#) for the separate dependency list.

Value

The session, invisibly.

read_mics_tabulation	<i>Read one sheet from a MICS Plus tabulation plan</i>
----------------------	--

Description

Reads the source name in B4:B7, filters, weights, conditions, cell statistics, headers, and layout metadata into the session. Blank statistic cells are filled by the worksheet reader. Direction is horizontal when an `n_unw` instruction immediately precedes `IDX` or a `100/100.0` statistic is present; otherwise it is vertical. Optional `d=` does not change that decision. The reader converts recognized numbered total column aliases to `total == 1` and `totalHL` column aliases to `hhmembers`. See [worksheet-conditions](#), [statistic-types](#), [statistic-precision](#), and [tabulate_h\(\)](#).

Usage

```
read_mics_tabulation(session, path_tab_excel, sheet)
```

Arguments

<code>session</code>	A session created by mics_session() .
<code>path_tab_excel</code>	Path to the Excel tabulation plan.
<code>sheet</code>	Sheet name or index.

Value

The parsed tabulation-plan context.

read_previous_mics_table	<i>Read a previously generated worksheet for comparison</i>
--------------------------	---

Description

Read a previously generated worksheet for comparison

Usage

```
read_previous_mics_table(path, sheet, skip = 3)
```

Arguments

<code>path</code>	Excel workbook path.
<code>sheet</code>	Sheet name or index.
<code>skip</code>	Number of header rows to skip.

Value

A cleaned table.

`row_condition_f`*Parse row conditions from a plan*

Description

Parse row conditions from a plan

Usage

```
row_condition_f(tab_r)
```

Arguments

`tab_r` Data frame containing `row_index` and `row_lgc`.

Details

Separates mutate calls from predicates; blank or NA row logic means TRUE. Parses text without evaluating it against survey data.

Value

A tibble containing the row index, original condition, cleaned condition, generated variable name, and calculation.

See Also

[col_condition_f\(\)](#), [normalize_condition_text\(\)](#), [worksheet-conditions](#)

`row_group_perc_total_check`*Check that row-group percentages sum to 100*

Description

Check that row-group percentages sum to 100

Usage

```
row_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

<code>session</code>	A tabulation session. Indent checks also require the loaded plan's <code>indent_rows</code> metadata.
<code>cell_results</code>	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
<code>diff</code>	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use `check_mics_table()` to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_group_total_check	<i>Compare row-group counts with the overall total</i>
-----------------------	--

Description

Compare row-group counts with the overall total

Usage

```
row_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

- | | |
|--------------|--|
| session | A tabulation session. Indent checks also require the loaded plan's indent_rows metadata. |
| cell_results | Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata. |
| diff | Maximum absolute difference accepted as consistent. |

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use `check_mics_table()` to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_indent_group_perc_total_check

Compare indented child percentages with their parent row

Description

Compare indented child percentages with their parent row

Usage

```
row_indent_group_perc_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use [check_mics_table\(\)](#) to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

row_indent_group_total_check

Compare indented child counts with their parent row

Description

Compare indented child counts with their parent row

Usage

```
row_indent_group_total_check(session, cell_results = NULL, diff = 1e-11)
```

Arguments

session	A tabulation session. Indent checks also require the loaded plan's indent_rows metadata.
cell_results	Long-format numeric results, defaulting to the latest result in the session. Use the complete results with logic/group metadata.
diff	Maximum absolute difference accepted as consistent.

Details

Runs only this check and updates its corresponding session check state. A missing total or distribution produces not_applicable. Use `check_mics_table()` to run all six checks together.

Value

A list with status (pass, fail, or not_applicable), issue_count, details (all comparisons), and issues (failing comparisons).

run_app	<i>Run the micsPlusTableR Shiny application</i>
---------	---

Description

The main user entry point to micsPlusTableR. Opens the browser-based MICS Plus Tabulation app for preparing inputs, calculating and checking tables, exploring data, and saving results. Other package functions mainly expose its supporting engine for documentation, tests, and code-only workflows.

Usage

```
run_app(  
  host = "127.0.0.1",  
  port = getOption("shiny.port"),  
  launch.browser = interactive(),  
  output_dir = NULL,  
  ...  
)
```

Arguments

host	Host interface passed to shiny::runApp().
port	Port passed to shiny::runApp(); NULL selects a free port.
launch.browser	Whether to open the application in a browser.
output_dir	Default directory for generated Excel workbooks. When NULL, the app creates micsPlusTableR-output in the project root detected by here::here().
...	Additional arguments passed to shiny::runApp().

Details

The app opens on Data Preparation. User’s Guide provides embedded instructions, Open full guide, and Download PDF. Download Files saves plans and preparation materials to the current project by default.

Results can be inspected without exporting. Single-table Excel writing needs a created or selected workbook. Multi-Sheet Tabulator automatically creates required workbooks for unset destinations and reuses destinations already set in Write to Excel. The default output folder is below the survey project; output_dir selects another location. Existing destinations and uploaded inputs must be selected again after restarting the app.

Restart the R session after installing or updating the package before launching, so previously loaded functions are not retained in memory. The external SheetJS browser library is needed for the workbook preview; local calculations and Excel output do not depend on that download.

Value

Invisibly returns the value from `shiny::runApp()`.

See Also

[micsPlusTableR-package](#), [offline-workflow](#)

statistic-precision	<i>Worksheet display precision</i>
---------------------	------------------------------------

Description

Every supported worksheet statistic accepts an optional named `d` argument specifying the number of decimal places to display.

Details

Use `mean(HCS8, d=0)` for a whole-number expense mean, `mean(d=1)` for a mean indicator with one decimal place, `p(d=2)` for two percentage decimals, or `n(d=1)` for a count with one displayed decimal. Existing argument forms retain their arguments: `median(age, d=2)`, `mean_unw(age, d=0)`, `p_sum(x, d=2)`, and `p(100, d=2)`. A constant may use `100(d=2)`. The statistic must be supported in the table's direction; adding `d` does not change the calculation or its weighting.

`d` must be a literal non-negative whole number, supplied once. Zero means no decimal point. Omit `d` to keep the existing formatting for that statistic and output mode; means still default to one decimal place. Spaces around arguments are allowed. `d` means decimal places, not significant figures.

The Formatted and Suppressed Tabulator views honor explicit precision for visible numbers; Unformatted retains full numeric estimates. Excel applies number formats in both output workbooks, including multi-sheet runs. Parentheses retain the requested precision; (*) and - remain markers. Display rounding does not alter stored estimates, calculations, weights, denominators, suppression thresholds, or consistency checks.

Internally, `stat_type` contains the statistic without `d`; `display_digits` holds the explicit integer or NA when omitted. Worksheet filling carries the statistic and its precision together. Changing only `d` does not change mean filter boundaries or the identification of `n_unw` before `IDX`. Long-format output uses the override in `DECIMALS` and display strings while retaining full precision in `OBS_VALUE`.

See Also

[tabulate_h\(\)](#), [tabulate_v\(\)](#), [write_mics_table\(\)](#)

Description

A worksheet's `stat_type` specifies the calculation for a result cell. These instructions drive the application and the R tabulation engine. The User's Guide's Understand the tabulation plan reference introduces the worksheet layout, dataset, filters, conditions, and worked examples.

Cell scope and direction

Statistics are written below the condition row, from Excel column C onward. The worksheet reader fills blank statistic cells from preceding instructions; a blank is not necessarily a skipped cell or a zero. Direct `calc_cells()` calls instead return NA for missing statistic specifications.

Dataset and active filters first define the available records. In horizontal tables, the row condition selects the percentage base and the column condition defines its outcome. In vertical tables, the column condition selects the base and the row condition defines the outcome. Counts, numeric means, and medians use records satisfying both conditions. See [worksheet-conditions](#) for preparing predicates, numbered total aliases, and household-member bases.

A percentage denominator comes from the applicable population, not a nearby count cell. Weighted percentages are 100 times the sum of outcome weights divided by the sum of base weights. Normal application tabulation uses the plan's weight; the low-level `calc_cells()` helper also has an explicit weighted argument for tests and code-only calculations.

Counts and indicator percentages

- `n` Weighted count: sum of weights for qualifying records. Both directions.
- `n_unw` Unweighted count of qualifying records. Both directions. In horizontal tables, the special `hhmembers` column condition instead sums `HLnum` for qualifying household records with `total == 1`. The worksheet column alias `totalHL == 1` selects this behavior; it does not change the weight or apply to vertical tables.
- `p` Weighted percentage of the outcome within the base. Both directions.
- `p_unw` Unweighted percentage of the row outcome within the column base. Vertical tables only.
- `mean` Bare mean: the same weighted indicator-percentage calculation as `p`, on a 0-100 scale. It does not select a numeric variable. Both directions.
- `mean_unw` Unweighted indicator percentage, on a 0-100 scale. Both directions. Legacy capitalized Mean also calculates this unweighted indicator percentage; it is distinct from lowercase weighted mean.

Numeric summaries

- `mean(variable)` Weighted arithmetic mean of the named numeric variable among records satisfying both conditions. Both directions.
- `mean_unw(variable)` Unweighted arithmetic mean of that variable. Both directions.
- `median(variable)` Unweighted median, even when the plan specifies a weight. Both directions. `median_unw(variable)` is a vertical-only synonym.

`mean(newvar = expression)` Vertical tables only: create the named variable from the expression, then calculate its weighted mean for the applicable records. For example, `mean(expense = HCS8 / 1000)`.

Missing values of the summarized variable are omitted. Numeric codes for unknown or inapplicable responses are not automatically missing.

Totals and specialized forms

`100, 100.0` Constant 100, not an estimated percentage. Presence in a worksheet selects horizontal mode and can mark a distribution total. Zero-base and suppression rules can change the displayed value.

`p(100), p_unw(100)` Vertical tables: return 100 on the first calculated row, then calculate weighted or unweighted percentages on later rows.

`n_unw(100)` Vertical tables: return 100 on the first calculated row, then unweighted counts on later rows. Later counts are not percentages.

`n(100)` Recognized only on the first calculated vertical row, returning 100. Use `n` on later rows. Repeating `n(100)` is unsupported.

`p_sum(variable)` Horizontal tables only: for records satisfying both conditions, calculate 100 times `sum(variable)` divided by `sum(weight)`. The numerator is not multiplied by the weight; the prepared variable must be defined appropriately for this calculation.

`n1, n_unw1, p1` Calculation variants of `n`, `n_unw`, and `p` in both directions. Suffixes do not set decimal places.

`n2, n_unw2` Vertical-only count variants of `n` and `n_unw`.

The `(100)` forms are not supported by the horizontal calculator. They refer to the first calculated row, not any row whose label says Total. Prefer the ordinary count and percentage forms unless an existing plan needs a variant: identical calculations do not guarantee identical direction selection, suppression, count linkage, or consistency-check handling.

Missing conditions

Missing outcome conditions do not contribute to weighted percentage numerators, but their available weights remain in the base denominator. Horizontal unweighted indicator percentages treat missing outcomes as false; vertical unweighted indicator percentages omit missing indicators from their denominator. Define exclusions explicitly if unknown responses should be removed from the base.

Filters and display

Column B's filter remains global. A transition from a non-mean to a mean type stops an inherited additional horizontal filter unless a new explicit filter starts there. Consecutive bare, variable, and unweighted means keep the active filter; see [tabulate_h\(\)](#).

Every supported statistic accepts optional `d=` display precision without changing its calculation or direction support. For example, `mean(d=1)`, `mean(HCS8, d=0)`, and `p(100, d=2)`. See [statistic-precision](#).

See Also

[tabulate_mics_table\(\)](#), [statistic-precision](#)

Description

The plain UTF-8 CSV file ‘inst/extdata/survey_choices.csv’ in the package source controls the application’s survey and wave selectors. Edit this source file directly before committing to GitHub or building the package.

Columns

Each row represents one available country, period, and wave combination. All four columns are read as character strings:

country Full country name, for example Jamaica.

country_code Exactly three uppercase letters, for example JAM.

period Survey period as text, for example 2023–24.

wave Wave label, for example Wave 1.

Keep the column names. The file must have at least one row, with no empty fields or duplicate country/period/wave combinations. All waves of the same country and period must use the same country code. Leading and trailing whitespace is removed. Row order determines selector order and defaults.

Editing and installation

Use a text editor or a spreadsheet editor that preserves the period and wave columns as text. Save as UTF-8 CSV. From the package root, run `source("run_dev.R")` to load and launch the development source. Stop and restart the app after saving changes.

The CSV requires no conversion to an R data object.

R installs ‘inst/extdata’ files into the package’s ‘extdata’ directory. For installed packages, reinstall the updated source and restart the R session before launching the app. Direct edits to an installed copy are replaced by reinstallation or upgrades. The selected code, full period, and wave also contribute to output filenames and long-format metadata.

See Also

[run_app, micsPlusTableR-package](#)

Examples

```
path <- system.file("extdata", "survey_choices.csv", package = "micsPlusTableR")
choices <- read.csv(path, colClasses = "character", fileEncoding = "UTF-8-BOM")
choices
```

tabulate_extra_table	<i>Map a supplied extra table to the current plan</i>
----------------------	---

Description

Map a supplied extra table to the current plan

Usage

```
tabulate_extra_table(session, table)
```

Arguments

session	A prepared session with a loaded plan.
table	A data frame whose first column contains row labels and whose remaining columns contain values in plan order.

Details

Row logic is retained as metadata, not evaluated against survey data. Values are mapped by position and the engine applies suppression. The plan's optional `d=` argument controls display precision for supplied values too; see [statistic-precision](#).

Value

Long-format results, also saved in `session$cell_results`.

tabulate_h	<i>Calculate a horizontal table</i>
------------	-------------------------------------

Description

Process column filter blocks and calculate column indicators using the currently loaded horizontal plan. The direction must match the plan. Results are also saved in `session$cell_results`. Use [tabulate_mics_table\(\)](#) for automatic direction selection and additional variable-explanation labels.

Usage

```
tabulate_h(session, skip_row_conditions = FALSE)
```

Arguments

session	A session created by mics_session() with prepared data and a plan loaded by read_mics_tabulation() .
skip_row_conditions	Logical; replace row predicates with TRUE during calculation while retaining their labels. Intended for extra-table testing.

Details

The condition-row filter(...) in Excel column B applies globally. Each additional horizontal filter(...) starts at its own column and combines with B. For each row independently, it extends right until the next explicit filter or the first transition from a non-mean statistic to a mean statistic. That mean cell uses B alone unless it starts a new explicit filter. A stopped filter stays off until another explicit filter starts. Mean statistics include bare mean, mean(variable), their mean_unw variants, and the legacy Mean form. Switching between bare and variable means preserves an active filter, as does changing only d=. Changes among other statistics (including p, n, and n_unw), between mean variables, or from a mean to a non-mean do not stop inheritance. Worksheet statistic filling and trimming surrounding whitespace happen before scope is determined. Changes down rows do not stop a filter. Sources, calculation chains, weights, and column/row predicates retain their existing roles; filters run before calculations. Vertical tabulation keeps its separate primary-filter behavior; see [tabulate_v\(\)](#). See [statistic-types](#) for calculation rules. Display precision d= is independent of filter scope; see [statistic-precision](#).

Value

A long-format cell-results data frame.

See Also

[tabulate_v\(\)](#), [tabulate_mics_table\(\)](#)

tabulate_mics_table	<i>Tabulate a MICS Plus table outside the application</i>
---------------------	---

Description

Exposes the app’s calculation engine for code-only workflows and tests. Selects the loaded plan’s direction automatically or maps an available supplied extra table, saves results in the session, and attaches variable explanations. Use numeric long-format results for checks before pivoting. See [statistic-types](#) for calculations and [offline-workflow](#) for an example.

Usage

```
tabulate_mics_table(session, path_tab_excel = NULL, sheet = NULL)
```

Arguments

- session A prepared tabulation session.
- path_tab_excel Optional tabulation-plan path. Supply with sheet to read a new table before tabulating.
- sheet Optional sheet name or index.

Value

A long-format data frame containing one row per calculated cell.

tabulate_v	<i>Calculate a vertical table</i>
------------	-----------------------------------

Description

Filter prepared data by column and calculate row indicators using the currently loaded vertical plan. The direction must match the plan. Results are also saved in `session$cell_results`. Use [tabulate_mics_table\(\)](#) for automatic direction selection and additional variable-explanation labels.

Usage

```
tabulate_v(session, skip_row_conditions = FALSE)
```

Arguments

<code>session</code>	A session created by mics_session() with prepared data and a plan loaded by read_mics_tabulation() .
<code>skip_row_conditions</code>	Logical; replace row predicates with TRUE during calculation while retaining their labels. Intended for extra-table testing.

Details

Every supported statistic accepts an optional `d=` display argument; for example, `mean(x, d=0)`, `mean(d=1)`, or `p(d=2)`. Omitting it preserves existing formatting. See [statistic-types](#) for each calculation, population, weighting rule, and direction limit, and [statistic-precision](#) for display rules.

Value

A long-format cell-results data frame.

See Also

[tabulate_h\(\)](#), [tabulate_mics_table\(\)](#)

<code>validate_sdmx_compatible</code>	<i>Validate SDMX-compatible MICS long-format data</i>
---------------------------------------	---

Description

Checks the complete 35-variable contract and the unique observation key: `SURVEY_ID`, `TABLE_ID`, `row_order`, `column_order`, and `TIME_PERIOD`.

Usage

```
validate_sdmx_compatible(data)
```

Arguments

`data` A data frame produced by `as_sdmx_compatible()`.

Value

`data`, invisibly.

worksheet-conditions *Worksheet row and column conditions*

Description

Prepare conditions around the required output's unit, eligible population, comparison groups, and statistic. The User's Guide section Define row and column conditions for your output provides worked worksheet layouts.

Location and population

Row predicates are written in column B below the condition row. Column predicates are written from C onward on the condition row identified by the source instruction in B4:B7. Labels alone do not select records. Ordinary predicates use prepared variables, for example `area == 1`, `age >= 15 & age <= 49`, or `response %in% c(1, 2)`.

After dataset selection and filters, horizontal percentages use the row predicate as the base and the column predicate as the outcome. Vertical percentages use the column predicate as the base and the row predicate as the outcome. Counts and numeric summaries normally use both predicates. A count in a neighboring cell does not define a percentage's denominator. Missing-outcome handling is documented in [statistic-types](#).

The worksheet reader omits blank row-condition cells. The standalone `row_condition_f()` helper instead treats blank predicates as TRUE. Column instructions can fill from the preceding column. Write changed predicates explicitly. In a multiline column instruction, use a separator - - - after source/filter/weight instructions and put the complete predicate on the final logical line.

Total aliases in worksheet columns

Maintained preparation scripts set `total = 1` in household and member data. `total == 1` therefore selects the records remaining under the applicable filters and the other axis's predicate. The worksheet reader converts these exact column forms:

- `total1 == 1` through `total5 == 1` become `total == 1`.
- `totalHL == 1` and `totalHL1 == 1` through `totalHL4 == 1` become `hhmembers`.
- The legacy column form `all` becomes `total == 1`.

Numbered aliases accommodate repeated total/base columns in separate blocks. Their suffix does not select a subgroup, change weights, or set decimals; filters and source instructions define the block population. These names need not exist as prepared variables when used as recognized column aliases. Use the exact spelling and internal spacing shown above. Bare `total1`, additional suffixes, and compound expressions such as `total1 == 1 & area == 1` are not alias forms.

Conversion belongs to `read_mics_tabulation()`, not the predicate parsers or calculators. Aliases in row predicates or inside filters are not converted. Direct `calc_cells()` calls must use `total == 1` or the supported `hhmembers` condition explicitly.

Household-member bases

For a horizontal `n_unw` or `n_unw1` cell with column condition `hhmembers`, the calculator applies the row predicate and sums `if_else(total == 1, 1, 0, missing = 0) * HLnum`, with missing contributions removed. This counts people represented by household records. It requires prepared `total` and numeric, complete household-size `HLnum`. Two eligible household records with sizes 2 and 4 contribute 6 members; ordinary `total == 1` with `n_unw` contributes 2 household records.

Weighted member counts use ordinary `total == 1` with `n` and a suitable member-based weight, such as the approved household weight multiplied by `HLnum`. Member-based percentages use that weight with the desired outcome. `totalHL` and `hhmembers` do not create or select a weight. For sizes 2 and 4 and household weights 1 and 3, the weighted member count is 14, compared with 4 weighted households and 6 unweighted members.

The member-size special case does not apply to vertical calculations or other statistics. On one-record-per-member data, count qualifying records with ordinary predicates and `n_unw`; summing household sizes on every member record would overcount. Use member records for member-level subsets, such as children selected by age, rather than the full household-size sum.

Preparing repeated blocks

For a horizontal percentage reporting an outcome, use its predicate (for example `HCS7 == 1`) with `p`, followed by `total == 1` columns with `n` and `n_unw` for the base. To average a numeric amount only among records reporting it, place the eligibility/valid-value filter on the mean column, then `- - -` and `total1 == 1`. Use `mean(HCS8)` there and `n/n_unw` in following `total1 == 1` columns. The filter, not the numbered alias, creates the restricted population. See [tabulate_h\(\)](#) for filter scope. Select survey-specific variables, valid-value rules, and weights before adapting this pattern. A mean among positive reporters differs from a mean across all eligible records with correctly prepared zeros for non-reporters.

See Also

[read_mics_tabulation\(\)](#), [statistic-types](#), [calc_cells\(\)](#)

`write_mics_footnotes` *Add standard footnotes to a tabulation workbook*

Description

Add standard footnotes to a tabulation workbook

Usage

```
write_mics_footnotes(session, destination, sheet = NULL, table = NULL)
```

Arguments

<code>session</code>	A tabulation session.
<code>destination</code>	Existing destination workbook.
<code>sheet</code>	Sheet name or index; defaults to the current sheet.
<code>table</code>	Cell results; defaults to the latest result.

Value

The destination path, invisibly.

write_mics_table	<i>Write cell results to a tabulation workbook</i>
------------------	--

Description

Write cell results to a tabulation workbook

Usage

```
write_mics_table(  
  session,  
  destination,  
  sheet = NULL,  
  table = NULL,  
  formatted = FALSE,  
  drop_n_unw = FALSE  
)
```

Arguments

session	A tabulation session with a loaded plan.
destination	Existing destination workbook. Create it with create_excel_workbooks() or supply a previously created workbook.
sheet	Sheet name or index; defaults to the current sheet.
table	Cell results; defaults to the latest result.
formatted	Whether to write formatted display values.
drop_n_unw	Whether to omit unweighted-count columns when formatting.

Details

Writes to an existing workbook; this function does not create one. Automatic creation for unset destinations is part of the app’s Multi-Sheet Tabulator workflow. Rewriting a sheet replaces its previously written values. Optional worksheet d= arguments set Excel decimal places in both output formats. Numeric values retain their precision; suppression markers and parentheses retain their meaning. See [statistic-precision](#).

Value

The destination path, invisibly.

Index

- * **documentation**
 - survey_choices, 32
- * **package**
 - micsPlusTableR-package, 2
- as_sdmx_compatible, 6
- as_sdmx_compatible(), 5, 36
- calc_cells, 7, 19
- calc_cells(), 5, 30, 36, 37
- check_mics_table, 8
- check_mics_table(), 4, 10, 11, 26–28
- check_prep_dependencies, 8
- check_prep_dependencies(), 5, 16, 22
- col_condition_f, 9
- col_condition_f(), 5, 25
- col_group_perc_total_check, 10
- col_group_perc_total_check(), 5
- col_group_total_check, 10
- col_group_total_check(), 5
- compare_mics_tables, 11
- compare_mics_tables(), 5
- create_excel_workbooks, 11
- create_excel_workbooks(), 4, 38
- download_survey_files, 12, 19
- download_survey_files(), 17
- extract_var, 14
- extract_var(), 5
- filter_second, 14
- filter_second(), 5
- get_blank_cols, 15
- get_blank_cols(), 5
- install_prep_dependencies, 15
- install_prep_dependencies(), 5, 9, 22, 23
- list_survey_files, 16
- list_survey_files(), 13
- mics_session, 17
- mics_session(), 4, 23, 24, 33, 35
- mics_table_name, 18
- micsPlusTableR
 - (micsPlusTableR-package), 2
- micsPlusTableR-package, 2, 19, 21, 29
- normalize_condition_text, 18
- normalize_condition_text(), 5, 9, 25
- offline-workflow, 5, 6, 17, 19, 29, 34
- package-dependencies, 5, 20, 22
- pivot_mics_table, 21
- pivot_mics_table(), 4
- prep-script-dependencies, 5, 8, 16, 20, 21, 22, 23
- prepare_mics_data, 23
- prepare_mics_data(), 4, 9, 16, 22
- read_mics_tabulation, 24
- read_mics_tabulation(), 4, 7, 9, 33, 35–37
- read_previous_mics_table, 24
- read_previous_mics_table(), 5
- row_condition_f, 25
- row_condition_f(), 5, 9, 36
- row_group_perc_total_check, 25
- row_group_perc_total_check(), 5
- row_group_total_check, 26
- row_group_total_check(), 5
- row_indent_group_perc_total_check, 27
- row_indent_group_perc_total_check(), 5
- row_indent_group_total_check, 27
- row_indent_group_total_check(), 5
- run_app, 28, 32
- run_app(), 2–4, 6
- statistic-precision, 4, 6, 7, 19, 24, 29, 31, 33–35, 38
- statistic-types, 4, 6, 7, 19, 24, 30, 34–37
- survey_choices, 5, 6, 32
- tabulate_extra_table, 33
- tabulate_extra_table(), 5
- tabulate_h, 33
- tabulate_h(), 4, 5, 24, 29, 31, 35, 37
- tabulate_mics_table, 34

`tabulate_mics_table()`, [4](#), [31](#), [33–35](#)
`tabulate_v`, [35](#)
`tabulate_v()`, [5](#), [29](#), [34](#)

`validate_sdmx_compatible`, [35](#)
`validate_sdmx_compatible()`, [5](#)

`worksheet-conditions`, [4](#), [7](#), [9](#), [24](#), [25](#), [30](#), [36](#)
`write_mics_footnotes`, [37](#)
`write_mics_footnotes()`, [5](#)
`write_mics_table`, [12](#), [38](#)
`write_mics_table()`, [4](#), [29](#)