
INTERNET TABANLI PROGRAMLAMA- 13.ders

GRIDVIEW, DETAILSVIEW, ACCESSDATASOURCE NESNELERİ İLE BİLGİ GÖRÜNTÜLEME



Asp.Net kodları

```
<%@ Page Language="C#" AutoEventWireup="true" CodeFile="Default.aspx.cs"</pre>
Inherits="Sayfalar Default" %>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"</pre>
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
   <title>Untitled Page</title>
</head>
<body>
    <form id="Form1" runat="server">
     ENGLISH EXERCISE</h3>
    <!-- DETAILS VIEW KONTROL NESNESİ KULLANIMI-->
          <asp:GridView ID="qvIngilizce"</pre>
          DataSourceID="dsSorulariGetir"
         AutoGenerateColumns="False"
          runat="server"
          DataKeyNames="ID" >
            <HeaderStyle BackColor="Blue" ForeColor="White" />
            <Columns>
              <asp:BoundField DataField="ID"</pre>
                HeaderText="ID" SortExpression="ID" />
```

```
<asp:BoundField DataField="SoruMetni"</pre>
                HeaderText="SoruMetni" SortExpression="SoruMetni" />
              <asp:BoundField DataField="IngilizeeCumle"</pre>
                HeaderText="IngilizceCumle" SortExpression="IngilizceCumle" />
                <asp:BoundField DataField="A Sikki" HeaderText="A Sikki"</pre>
                    SortExpression="A Sikki" />
                <asp:BoundField DataField="B Sikki" HeaderText="B Sikki"</pre>
                    SortExpression="B Sikki" />
                <asp:BoundField DataField="C Sikki" HeaderText="C Sikki"</pre>
                    SortExpression="C Sikki" />
                <asp:BoundField DataField="E Sikki" HeaderText="E Sikki"</pre>
                    SortExpression="E Sikki" />
                <asp:BoundField DataField="D Sikki" HeaderText="D Sikki"</pre>
                    SortExpression="D Sikki" />
                <asp:CommandField ShowSelectButton="True" />
            </Columns>
          </asp:GridView>
        <mark><응</mark>--
          DETAYLARI GÖRÜNTÜLEME--%>
          <asp:DetailsView ID="dvDetaylar"</pre>
            DataSourceID="dsDetaylariGetir"
            AutoGenerateRows="false"
            AutoGenerateInsertButton="true"
            AutoGenerateEditButton="true"
            AutoGenerateDeleteButton="true"
            EmptyDataText="Kayıt Bulunamadı."
            DataKeyNames="ID"
            GridLines="Both"
            OnItemInserted="CustomerDetail_ItemInserted"
            OnItemInserting="CustomerDetail ItemInserting"
            OnItemUpdated="CustomerDetail_ItemUpdated"
            OnItemUpdating="CustomerDetail_ItemUpdating"
            OnItemDeleted="CustomerDetail ItemDeleted"
            runat="server">
            <HeaderStyle BackColor="Navy" ForeColor="White" />
            <RowStyle BackColor="White" />
            <AlternatingRowStyle BackColor="LightGray" />
            <EditRowStyle BackColor="LightCyan" />
            <Fields>
              <asp:BoundField DataField="ID" HeaderText="ID" ReadOnly="True" />
              <asp:BoundField DataField="SoruMetni" HeaderText="SoruMetni" />
              <asp:BoundField DataField="IngilizeeCumle"</pre>
HeaderText="IngilizceCumle" />
              <asp:BoundField DataField="A Sikki" HeaderText="A Sikki" />
              <asp:BoundField DataField="B Sikki" HeaderText="B Sikki" />
              <asp:BoundField DataField="C Sikki" HeaderText="C Sikki" />
              <asp:BoundField DataField="D Sikki" HeaderText="D Sikki" />
```

```
<asp:BoundField DataField="E Sikki" HeaderText="E Sikki" />
              <asp:BoundField DataField="DogruCevap" HeaderText="DogruCevap" />
              <asp:BoundField DataField="Resim" HeaderText="Resim" />
              <asp:BoundField DataField="IngilizeeCumleAnlami"</pre>
HeaderText="IngilizceCumleAnlami" />
              <asp:BoundField DataField="A SikkiAnlami" HeaderText="A SikkiAnlami"</pre>
/>
              <asp:BoundField DataField="B SikkiAnlami" HeaderText="B SikkiAnlami"</pre>
/>
              <asp:BoundField DataField="C SikkiAnlami" HeaderText="C SikkiAnlami"</pre>
              <asp:BoundField DataField="D SikkiAnlami" HeaderText="D SikkiAnlami"</pre>
              <asp:BoundField DataField="E SikkiAnlami" HeaderText="E SikkiAnlami"</pre>
              <asp:BoundField DataField="Aciklama" HeaderText="Aciklama" />
            </Fields>
          </asp:DetailsView>
        <!-- ANA TABLOYA BİLGİLERİ GETİRME -->
    <asp:AccessDataSource ID="dsSorulariGetir" runat="server"</pre>
        SelectCommand="SELECT [ID], [SoruMetni], [IngilizceCumle],
        [A Sikki], [B Sikki], [C Sikki], [E Sikki], [D Sikki]
        FROM [Ingilizce]"
        DataFile="~/App Data/VERITABANI.mdb">
    </asp:AccessDataSource>
           DETAY TABLOSUNA BİLGİLERİ GETİRME -->
    <asp:AccessDataSource ID="dsDetaylariGetir" runat="server"</pre>
      DataFile="~/App Data/VERITABANI.mdb"
      SelectCommand="SELECT * FROM [Ingilize] WHERE ([ID] = @ID)"
      DeleteCommand="DELETE FROM [Ingilize] WHERE [ID] = @ID"
      InsertCommand="INSERT INTO [Ingilize]
        ([Kategori],
        [SoruMetni],
        [IngilizceCumle],
        [A Sikki],
        [B Sikki],
        [C Sikki],
        [D Sikki],
        [E Sikki],
        [DogruCevap],
        [Resim],
        [IngilizceCumleAnlami],
        [A SikkiAnlami],
        [B SikkiAnlami],
        [C SikkiAnlami],
        [D SikkiAnlami],
        [E SikkiAnlami],
        [Aciklama])
```

```
VALUES
  ([@Kategori],
  [@SoruMetni],
  [@IngilizceCumle],
  [@A Sikki],
  [@B Sikki],
  [@C Sikki],
  [@D Sikki],
  [@E Sikki],
  [@DogruCevap],
  [@Resim],
  [@IngilizceCumleAnlami],
  [@A SikkiAnlami],
  [@B SikkiAnlami],
  [@C SikkiAnlami],
  [@D SikkiAnlami],
  [@E SikkiAnlami],
  [@Aciklama])"
UpdateCommand="UPDATE [Ingilizce] SET
  [Kategori] = @Kategori,
  [SoruMetni]=@SoruMetni,
  [IngilizceCumle] = @IngilizceCumle,
  [A Sikki]=@A Sikki,
  [B Sikki] = @B Sikki,
  [C Sikki] = @C Sikki,
  [D Sikki] = @D Sikki,
  [E Sikki] = @E Sikki,
  [DogruCevap] = @DogruCevap,
  [Resim] = @Resim,
  [IngilizceCumleAnlami] = @IngilizceCumleAnlami,
  [A SikkiAnlami]=@A SikkiAnlami,
  [B SikkiAnlami] = @B SikkiAnlami,
  [C_SikkiAnlami]=@C_SikkiAnlami,
  [D SikkiAnlami] = @D SikkiAnlami,
  [E SikkiAnlami]=@E SikkiAnlami,
  [Aciklama] = @Aciklama
  WHERE [ID] = @ID">
<SelectParameters>
  <asp:ControlParameter ControlID="gvIngilizce"</pre>
    Name="ID" PropertyName="SelectedValue"
    Type="Int32" />
</SelectParameters>
<DeleteParameters>
  <asp:Parameter Name="ID" Type="Int32" />
</DeleteParameters>
<UpdateParameters>
  <asp:Parameter Name="ID" Type="Int32" />
  <asp:Parameter Name="Kategori" Type="String" />
  <asp:Parameter Name="SoruMetni" Type="String" />
  <asp:Parameter Name="IngilizeeCumle" Type="String" />
  <asp:Parameter Name="A Sikki" Type="String" />
  <asp:Parameter Name="B Sikki" Type="String" />
  <asp:Parameter Name="C Sikki" Type="String" />
  <asp:Parameter Name="D_Sikki" Type="String" />
```

```
<asp:Parameter Name="E Sikki" Type="String" />
        <asp:Parameter Name="DogruCevap" Type="String" />
       <asp:Parameter Name="Resim" Type="String" />
       <asp:Parameter Name="IngilizeeCumleAnlami" Type="String" />
       <asp:Parameter Name="A SikkiAnlami" Type="String" />
       <asp:Parameter Name="B SikkiAnlami" Type="String" />
       <asp:Parameter Name="C SikkiAnlami" Type="String" />
       <asp:Parameter Name="D SikkiAnlami" Type="String" />
        <asp:Parameter Name="E SikkiAnlami" Type="String" />
        <asp:Parameter Name="Aciklama" Type="String" />
      </UpdateParameters>
      <InsertParameters>
        <asp:Parameter Name="Kategori" Type="String" />
       <asp:Parameter Name="SoruMetni" Type="String" />
       <asp:Parameter Name="IngilizeeCumle" Type="String" />
       <asp:Parameter Name="A Sikki" Type="String" />
       <asp:Parameter Name="B Sikki" Type="String" />
       <asp:Parameter Name="C Sikki" Type="String" />
       <asp:Parameter Name="D Sikki" Type="String" />
       <asp:Parameter Name="E Sikki" Type="String" />
       <asp:Parameter Name="DogruCevap" Type="String" />
       <asp:Parameter Name="Resim" Type="String" />
       <asp:Parameter Name="IngilizeCumleAnlami" Type="String" />
       <asp:Parameter Name="A SikkiAnlami" Type="String" />
       <asp:Parameter Name="B SikkiAnlami" Type="String" />
       <asp:Parameter Name="C SikkiAnlami" Type="String" />
       <asp:Parameter Name="D SikkiAnlami" Type="String" />
        <asp:Parameter Name="E SikkiAnlami" Type="String" />
        <asp:Parameter Name="Aciklama" Type="String" />
      </InsertParameters>
    </asp:AccessDataSource>
  </form>
</body>
</html>
```

C# kodları

```
using System;
using System.Collections;
using System.Configuration;
using System.Data;
using System.Linq;
using System.Web;
using System.Web.Security;
using System.Web.UI;
using System. Web. UI. Html Controls;
using System.Web.UI.WebControls;
using System.Web.UI.WebControls.WebParts;
using System.Xml.Ling;
public partial class Sayfalar Default : System. Web. UI. Page
    protected void Page Load(object sender, EventArgs e)
    {
    }
    public void CustomerDetail ItemInserted(object sender,
```

}

```
DetailsViewInsertedEventArgs e)
  {
      // Refresh the GridView control after a new record is inserted
      // in the DetailsView control.
      gvIngilizce.DataBind();
  }
  public void CustomerDetail ItemInserting(object sender,
    DetailsViewInsertEventArgs e)
      // Iterate though the values entered by the user and HTML encode
      // the values. This helps prevent malicious values from being
      // stored in the data source.
      for (int i = 0; i < e.Values.Count; i++)</pre>
      {
          if (e.Values[i] != null)
          {
              e.Values[i] = Server.HtmlEncode(e.Values[i].ToString());
          }
      }
  }
  public void CustomerDetail ItemUpdated(object sender,
    DetailsViewUpdatedEventArgs e)
      // Refresh the GridView control after a new record is updated
      // in the DetailsView control.
      gvIngilizce.DataBind();
  }
  public void CustomerDetail ItemUpdating(object sender,
    DetailsViewUpdateEventArgs e)
      // Iterate though the values entered by the user and HTML encode
      // the values. This helps prevent malicious values from being
      // stored in the data source.
      for (int i = 0; i < e.NewValues.Count; i++)</pre>
          if (e.NewValues[i] != null)
          {
              e.NewValues[i] = Server.HtmlEncode(e.NewValues[i].ToString());
          }
      }
  public void CustomerDetail ItemDeleted(object sender,
    DetailsViewDeletedEventArgs e)
      // Refresh the GridView control after a new record is updated
      // in the DetailsView control.
      gvIngilizce.DataBind();
  }
```