
ASO Atlas 2.0: a cost-based benchmark for antisense oligonucleotide preclinical screening

Anonymous Author(s)

Affiliation, Address

anon.email@example.org

Abstract

1 Preclinical drug development is a sequential, high-attrition process in which can-
2 didates must clear in vitro efficacy and dose-response screens before advancing
3 to costly in vivo toxicity studies, and failure at any late stage wastes the cost
4 of every preceding experiment. Despite growing interest in machine-learning-
5 guided drug design, no public benchmark is structured around the sequential
6 preclinical pipeline, linking the same candidates from in vitro efficacy through
7 in vivo toxicity with an evaluation framework that reflects stage-gated decision-
8 making. This gap has left the field without a realistic evaluation setting. Models
9 are trained and tested on isolated endpoints, with no framework for quantifying
10 whether predictive accuracy translates into practical savings in animals, time, or
11 cost. Here we introduce ASO Atlas 2.0, the first such multi-endpoint preclinical
12 dataset, built around antisense oligonucleotides (ASOs), short synthetic nucleic
13 acids that silence disease-related genes. ASO Atlas 2.0 comprises 174,459 in
14 vitro efficacy measurements, 99,821 dose-response curves, 4,341 hepatotoxicity
15 records, and 4,900 neurotoxicity records across 446 target genes, all extracted from
16 Ionis Pharmaceuticals patent filings using an agentic language-model workflow.
17 We propose a cost-based benchmarking framework that evaluates classifiers by
18 their ability to enrich the candidate pool at expensive in vivo stages, quantifying
19 savings in terms of the number of animals and dollars required to yield a devel-
20 opment candidate. ASO Atlas 2.0, the benchmarking framework, and all baseline
21 code are publicly available to accelerate computational ASO research.

22 1 Introduction

23 Antisense oligonucleotides (ASOs) that recruit RNase H to degrade target mRNA have emerged as
24 a clinically validated therapeutic modality, with several approved drugs targeting conditions from
25 spinal muscular atrophy to hereditary transthyretin amyloidosis. The 2'-MOE gapmer design —
26 flanking modified nucleotides surrounding a central DNA gap — has proven particularly successful
27 in the central nervous system, where intrathecal delivery achieves sustained target knockdown.

28 Despite this clinical success, the vast majority of genetically amenable conditions remain undevel-
29 oped. A key barrier is the cost of preclinical screening: identifying a single development candidate
30 typically requires synthesising and testing thousands of ASO sequences through a sequential pipeline
31 of in vitro efficacy assays, dose-response characterisation, and multi-species in vivo toxicity studies.
32 Each successive stage is more expensive and lower-throughput than the last, with in vivo studies in
33 rodents and primates dominating total programme costs.

34 Several computational approaches have demonstrated that oligonucleotide sequence features carry
35 predictive information about ASO properties. [1] showed that dinucleotide composition predicts
36 hepatotoxicity in locked nucleic acid (LNA) gapmers using random forest classifiers. [2] extended

this approach to neurotoxicity prediction using a logistic regression model based on five sequence features. More recently, [3] introduced OligoAI, a deep learning model trained on a proprietary database of 188,521 ASO sequences that achieves $3.14\times$ enrichment for in vitro efficacy prediction. However, these models were developed on proprietary datasets and there is no common benchmark for comparing their contributions across different pipeline stages.

A critical gap remains: there is no standardised public dataset linking ASO chemical structure to multiple preclinical endpoints, and no evaluation framework that translates model accuracy into practical screening cost savings. Without these, it is difficult to compare methods fairly or to quantify the real-world value of computational pre-screening.

In this work, we make three contributions:

1. **ASO Atlas 2.0** — the largest public multi-endpoint ASO preclinical dataset, extracted from USPTO patent filings and annotated with HELM chemical-structure strings. The dataset spans 446 target genes across four assay types.
2. A **cost-based benchmarking framework** that evaluates classifiers by their enrichment of the candidate pool at expensive pipeline stages, translating accuracy into dollar savings and animal reduction.
3. A **baseline benchmark** replicating the Hagedorn hepatotoxicity [1] and neurotoxicity [2] models on ASO Atlas 2.0 with proper GroupKFold cross-validation by target gene, establishing reference performance for future methods.

2 Results

2.1 ASO Atlas 2.0 Dataset




Figure 1: Overview of the ASO Atlas 2.0 extraction pipeline and resulting dataset. (A) Three-stage pipeline converting USPTO patent tables into structured preclinical ASO datasets with HELM annotations. (B) Distribution of measurements across target genes; each coloured segment represents a major gene, with remaining genes grouped as “Other”. (C) Flow of compounds through in vitro hit screening, dose-response characterisation, and in vivo toxicity assessment; box heights are proportional to measurement counts, flow widths to the fraction of shared compounds.

ASO Atlas 2.0 comprises four linked assay categories extracted from USPTO patent filings: 174,459 single-concentration in vitro inhibition measurements across 163,802 ASOs, 99,821 multi-dose response measurements across 16,834 ASOs, 4,341 hepatorenal toxicity records across 2,051 ASOs

with 7 biomarker channels, and 4,900 neurotoxicity records across 3,316 ASOs (Figure 1). All compounds are annotated with HELM chemical-structure strings enabling extraction of chemistry-aware features. Target gene identity was resolved for 97% of neurotoxicity records through compound-level cross-referencing and patent-level majority voting.

2.2 The Preclinical Screening Pipeline




Figure 2: The ASO preclinical screening pipeline. **(A)** Distribution of measurements at each pipeline stage with pass/fail thresholds (red dashed lines); grey shading marks the failing region. **(B)** Attrition funnel showing the number of ASO candidates entering each stage, per-stage pass rates, and cumulative costs. Box heights are proportional to log(ASO count).

The ASO preclinical pipeline consists of seven sequential stages: in vitro efficacy (inhibition >80%), in vitro potency (IC₅₀ <500 nM by electroporation), mouse liver toxicity (ALT <2×ULN), mouse neurotoxicity (bFOB ≤1), rat liver toxicity (ALT <2×ULN), rat neurotoxicity (mFOB ≤1), and monkey liver toxicity (Figure 2). Back-calculation from ASO Atlas 2.0 pass rates shows that producing a single development candidate requires screening approximately 568 initial ASOs at an estimated total cost of \$1.3M. The majority of this cost is concentrated at the in vivo stages, where per-ASO costs range from \$15,000 (mouse) to \$100,000 (monkey).

2.3 Toxicity Prediction




Figure 3: OligoAI-tox: Hagedorn’s dinucleotide RF trained on ASO Atlas 2.0 with GroupKFold cross-validation by target gene. **Top row:** Hepatotoxicity (mouse ALT, rat ALT). **Bottom row:** Neurotoxicity (mouse bFOB, rat mFOB). Each panel pair shows ROC curves and confusion matrices. For neurotoxicity, the dashed grey line shows the Hagedorn et al. 2022 baseline (5 fixed coefficients). Mouse ALT: accuracy = 0.702, AUC = 0.786. Mouse bFOB: accuracy = 0.777, AUC = 0.842.

We trained OligoAI-tox, Hagedorn’s dinucleotide random forest architecture applied to ASO Atlas 2.0, adapting it from LNA to DNA/MOE/cET chemistry (Figure 3). We trained four explicit models: mouse ALT, mouse bFOB, rat ALT, and rat mFOB, each evaluated with GroupKFold cross-validation (5 folds, grouped by target gene).

For hepatotoxicity, the mouse ALT model (128 dinucleotide features, 5,000 trees) achieved an accuracy of 0.702 with an AUC of 0.786 (sensitivity 0.803, specificity 0.644) on 2,701 compounds across 80 target gene groups. The rat ALT model achieved an AUC of 0.739 on 714 compounds.

For neurotoxicity, we compared OligoAI-tox against the Hagedorn et al. 2022 baseline (5 fixed coefficients from the original publication). On mouse bFOB scores (700 µg ICV; neurotoxic bFOB > 1 vs non-toxic bFOB ≤ 1), OligoAI-tox achieved an accuracy of 0.777 with an AUC of 0.842 on 2,696 compounds across 23 target gene groups, compared to an AUC of 0.785 for the Hagedorn et al. 2022 model. The rat mFOB model achieved an AUC of 0.787 on 1,779 compounds.

2.4 Cost Savings from Computational Pre-Screening




Figure 4: Cost savings from computational pre-screening. Stacked bar chart comparing total pipeline costs by stage across four scenarios: baseline (no screening), OligoAI only (in vitro efficacy), OligoAI-tox only (ALT + bFOB), and all models combined.

To quantify the practical value of computational pre-screening, we compared three enrichment scenarios against the baseline pipeline (Figure 4). OligoAI-tox (hepatotoxicity + neurotoxicity) enriches the candidate pool at the mouse ALT and mouse bFOB stages, reducing cost by 62% to \$0.49M. OligoAI, a recently published deep learning model for in vitro efficacy prediction [3], achieves a 3.14 × enrichment at the inhibition stage, reducing cost by 15% to \$1.09M. Combining all enrichment stages yields a 65.5% total reduction to \$0.44M — requiring only 44 initial ASOs instead of 568.

2.5 Cross-Species Concordance and Sequence Motifs




Figure 5: Selection bias, cross-assay and cross-biomarker correlations, base composition, and cross-species concordance. (A) Selection-bias KDEs showing biomarker distributions for compounds that do (blue) vs don't (grey) advance to the next pipeline stage. (B) Cross-assay Spearman ρ : pairwise correlations between per-compound metrics across pipeline stages (BH-corrected; n.s. = not significant). (C) Cross-biomarker Spearman ρ : correlations between mouse hepatotoxicity biomarkers (Bonferroni-corrected). (D) Nucleotide base × biomarker Spearman ρ : base composition vs toxicity biomarkers (BH-corrected). (E) Cross-species bFOB concordance: mouse bFOB vs rat mFOB score heatmap (integer-rounded); cell values are compound counts.

To assess whether mouse-based screening translates to rat outcomes, we compared per-compound mean biomarker values for compounds tested in both species (Figure 5). For hepatotoxicity biomarkers, Spearman correlations were modest but statistically significant: ALT ($\rho = 0.299$, $p < 10^{-10}$, $n = 449$), AST ($\rho = 0.272$, $p < 10^{-8}$, $n = 435$), and TBIL ($\rho = 0.244$, $p < 10^{-5}$, $n = 374$). Binary concordance rates (agreement on high vs low classification using species-specific ULN thresholds) were high: 0.762 for ALT, 0.959 for AST, and 0.964 for TBIL — though this largely reflects the dominance of concordant low-toxicity compounds.

Neurotoxicity showed stronger cross-species concordance. Mouse bFOB and rat mFOB scores (700 μg ICV vs 3,000 μg IT respectively) were well correlated ($\rho = 0.647$, $p \approx 0$, $n = 1,456$), with a binary concordance rate of 0.676 across 1456 classifiable compounds.

Within mouse, the hepatotoxicity biomarkers show a structured correlation pattern (Figure 5 C). ALT and AST are strongly correlated ($\rho = 0.92$), consistent with their shared hepatocellular origin, while TBIL is moderately correlated with both ($\rho \approx 0.4$). The renal markers BUN and CREA form a separate cluster ($\rho = 0.36$), largely independent of the liver enzymes. This structure suggests that ALT and AST carry largely redundant information for toxicity classification, while TBIL and renal biomarkers may offer complementary signal.

3 Discussion

We have introduced ASO Atlas 2.0, a public multi-endpoint ASO preclinical dataset, and a cost-based benchmarking framework for evaluating computational screening methods. OligoAI-tox — Hagedorn's dinucleotide random forest trained on ASO Atlas 2.0 — establishes baseline performance for future methods to improve upon.

OligoAI-tox achieves moderate classification accuracy on ASO Atlas 2.0, consistent with the original Hagedorn publications despite the shift from LNA to MOE/cET chemistry. The use of GroupKFold cross-validation by target gene provides a more realistic estimate of generalisation performance than random splits, since in practice new ASO programmes target novel genes not seen during model development.

146 The cross-species concordance analysis provides empirical support for mouse-based screening as a
147 proxy for rat outcomes, particularly for neurotoxicity where bFOB and mFOB scores are strongly
148 correlated between species. This supports the pipeline design assumption that mouse-stage enrich-
149 ment carries forward to later species.

150 Even modest enrichment at the expensive in vivo stages translates into meaningful cost savings, as
151 demonstrated by our cost-based framework. When combined with OligoAI’s in vitro enrichment [3],
152 the total cost reduction reaches 65.5%. This highlights the importance of evaluating models not just
153 by accuracy metrics but by their practical impact on screening economics, and suggests that stacking
154 complementary models across pipeline stages can yield compounding benefits.

155 Several limitations should be noted. First, OligoAI-tox uses only chemistry-derived sequence
156 features and does not incorporate target gene context, target site thermodynamics, or off-target
157 binding potential. Second, ASO Atlas 2.0 is derived from Ionis Pharmaceuticals patents and therefore
158 reflects the design space and chemical modifications used by a single organisation. Third, the binary
159 classification approach (high vs low toxicity) discards intermediate cases and may oversimplify the
160 dose-response relationship between sequence features and toxicity.

161 Future directions include: (i) deep learning models that operate directly on HELM strings rather than
162 hand-crafted features; (ii) multi-task approaches that jointly predict across endpoints; (iii) target-
163 aware models that incorporate gene-level information; and (iv) regression rather than classification
164 to capture the full spectrum of toxicity outcomes.

165 4 Methods

166 4.1 ASO Atlas 2.0 Extraction Pipeline

167 ASO Atlas 2.0 is a three-stage language-model-powered pipeline that converts unstructured tables
168 in USPTO patent XML files into flat, structured preclinical ASO datasets annotated with HELM
169 chemical-structure strings.

170 **Stage 1 — Table extraction.** USPTO patent XML documents filed after 2001 by ISIS Pharmaceu-
171 ticals (now Ionis Pharmaceuticals) were retrieved via the USPTO bulk-data API and split into
172 individual table files, each paired with the five paragraphs of prose immediately preceding the table.
173 Tables were deduplicated in two phases: exact MD5 hash matching, followed by pairwise sequence
174 similarity (Python SequenceMatcher, 90% threshold) with length-based pruning; connected compo-
175 nents were resolved by depth-first search to select a single canonical file per group, reducing 35,871
176 raw tables from 1,125 Ionis Pharmaceuticals patents to 8,435 canonical tables. For each canonical
177 table, GPT-5-mini generated a bespoke Python extraction function tailored to that table’s XML
178 layout. Generated scripts were executed in a sandboxed subprocess with a restricted import whitelist
179 (`json`, `re`, `xml.etree.ElementTree`, `math`) and a ten-second timeout. An agentic self-repair loop
180 allowed the model to observe execution output or errors and regenerate corrected code, for up to five
181 attempts per table.

182 **Stage 2 — HELM annotation.** For each canonical table the model received the surrounding patent
183 prose and a table preview, then generated a function that constructs Hierarchical Editing Language
184 for Macromolecules (HELM) strings nucleotide-by-nucleotide from the chemistry description. To
185 avoid hallucinated annotations, the function was required to return null when explicit modification
186 data could not be found in the patent text. All HELM strings were validated by a rule-based checker
187 that enforces correct sugar tokens (`[moe]`, `d`, `r`, `m`, `[cet]`, `[fR]`, `[lNa]`), canonical bases (`A`, `C`, `G`,
188 `T`, `U`, `[5meC]`), backbone tokens (`[sp]`, `[am]`, `.`), balanced bracket syntax, and terminal-nucleotide
189 constraints.

190 **Stage 3 — Schema-driven collation.** Each assay category was extracted in a separate pass by
191 supplying a schema dictionary that maps desired column names to natural-language descriptions.
192 GPT-5 generated a mapping function per table that translates table-specific field names to the target
193 schema, performs unit conversions, and unpivots multi-measurement rows into separate records.
194 The same sandboxed execution and self-repair loop as Stage 1 were applied. HELM annotations
195 were merged into each output record by compound identifier, following canonical-link chains across
196 duplicate tables. Four schemas were defined, one per assay category: (i) in vitro inhibition — percent

197 inhibition, cell line, dosage in nM, transfection method, treatment period, and target gene; (ii) dose
198 response — the same fields with dosage in the original unit (nM or μ M); (iii) hepatorenal toxicity
199 — seven serum biomarkers (ALB, ALT, AST, BUN, CREA, TBIL, protein/creatinine ratio), dosage,
200 species, strain, number of doses, dosing period, measurement source, and administration route; and
201 (iv) neurotoxicity — FOB score (bFOB or mFOB), dosage, species, strain, latency, administration
202 method, and score type.

203 4.2 Data Collection and Preprocessing

204 All preclinical ASO data were extracted from USPTO patent filings using the ASO Atlas 2.0 pipeline.
205 Raw tables were parsed into four assay categories: in vitro hit screening (single-concentration percent
206 inhibition), in vitro dose response (multi-dose percent inhibition), in vivo hepatorenal toxicity
207 (serum biomarkers), and in vivo neurological toxicity (functional observational battery scores). Each
208 category underwent a standardised cleaning pipeline described below.

209 Five HELM-level quality filters were applied uniformly across all four assay categories before
210 any assay-specific cleaning. Compounds whose HELM annotation contained uncertain sugar or
211 backbone tokens (indicated by ? placeholders in the HELM string) were removed, as were sequences
212 with ten or fewer nucleotides (likely extraction artefacts), uniformly modified compounds with
213 no DNA gap (steric-blocking ASOs outside the scope of gapmer-focused analysis), homopolymer
214 sequences comprising a single repeated nucleotide (extraction artefacts from poly-T or poly-A place-
215 holder annotations), and naked DNA oligonucleotides lacking any sugar modifications (unmodified
216 sequences where the extraction model could not identify the modification pattern).

217 **In vitro inhibition.** Inhibition values outside the range $[-1000\%, 100\%]$ were discarded as extraction
218 artefacts. Cell line names and species labels were standardised to canonical forms (e.g. “A-431” $\rightarrow$
219 “A431”, “cynomolgus” $\rightarrow$ “monkey”). Duplicate measurements — defined as identical compound
220 ID and inhibition value — were collapsed, retaining the most recent patent. This yielded 174,459
221 measurements across 163,802 ASOs.

222 **Dose response.** Dosages reported in μ M were converted to nM. The same inhibition range filter
223 and species standardisation were applied. Rows with non-positive dosages were removed. Cell line
224 names were harmonised using a lookup table of 150+ known aliases. Deduplication on compound,
225 dosage, and inhibition yielded 99,821 measurements across 16,834 ASOs.

226 **Hepatorenal toxicity.** Dosage strings were parsed into numeric values and units. Weekly dosing
227 rates (mg/kg/wk) were converted to per-dose equivalents (mg/kg) using the reported number of
228 doses and dosing period. Only subcutaneous and intraperitoneal administration routes with plasma
229 or urine measurement sources were retained. Extreme dosages ($> 10,000$ mg/kg) were excluded.
230 Biomarker values were range-filtered (ALT and AST: 10–50,000 IU/L; ALB: 1–100 g/dL). Rows
231 sharing the same compound, species, dosing regimen, and administration method were collapsed,
232 aggregating biomarker replicates into lists. Species and strain names were standardised. The final
233 dataset contained 4,341 collapsed records across 2,051 ASOs, with 7 biomarker channels (ALB,
234 ALT, AST, BUN, CREA, TBIL, protein/creatinine ratio).

235 **Neurological toxicity.** Tolerability score strings (bFOB for mice, mFOB for rats) were parsed into
236 numeric lists, retaining only values in the valid range $[0, 7]$.

237 ASO Atlas 2.0 contains two complementary tolerability scoring systems developed at Ionis Phar-
238 maceuticals. In each system, seven criteria are each scored 0 (met) or 1 (not met), and summed
239 into a tolerability score ranging from 0 (no signs) to 7 (all criteria failed). The *behavioural FOB*
240 (bFOB) assesses consciousness and motor responsiveness 3 h after intracerebroventricular (ICV)
241 delivery of 700 μ g in C57BL/6 mice: bright/alert/responsive, standing or hunched without stimuli,
242 any movement without stimuli, forward movement after lifting, any movement after lifting, response
243 to tail pinch, and regular breathing. The *motor FOB* (mFOB) assesses segmental motor function 3 h
244 after intrathecal (IT) delivery of 3,000 μ g in Sprague-Dawley rats: movement of the tail, posterior
245 posture, hind limbs, hind paws, forepaws, anterior posture, and head. In the processed dataset,
246 bFOB accounts for 2,928 mouse records and mFOB for 1,804 rat records. Species and strain names
247 were standardised (e.g. “C57/B16 mice” $\rightarrow$ “C57BL/6 mice”). Since the raw neurotoxicity data
248 lacked target gene annotations, compound-to-gene mappings were inferred in two steps: first by
249 direct lookup against the in vitro and dose response datasets, then by patent-level majority vote for

250 remaining compounds (assigning the most frequent target gene within each USPTO patent). This
251 resolved target gene identity for 97% of neurotoxicity records. Deduplication on HELM annotation,
252 species, administration method, score type, and dosage yielded 4,900 records across 3,316 ASOs.

253 **Gene symbol mapping.** Target RNA names from the patent text were mapped to canonical HGNC
254 gene symbols using the Ensembl REST API, supplemented by a manually curated dictionary of 300+
255 aliases (e.g. “Tau” $\rightarrow$ *MAPT*, “PKK” $\rightarrow$ *PRKDC*, “K-Ras” $\rightarrow$ *KRAS*). After merging synonyms, the
256 combined dataset spans 446 unique target genes and 280,027 total measurements.

257 4.3 Hagedorn Hepatotoxicity Model (2013)

258 We replicated the [1] approach for predicting ASO hepatotoxicity from sequence composition. The
259 original method uses random forest classifiers trained on dinucleotide features of LNA gapmers to
260 classify compounds as high or low hepatotoxicity based on serum ALT levels.

261 **Feature extraction.** Four feature sets of increasing complexity were evaluated: (i) a baseline
262 model with 5 features (presence of chemical modification, MOE/cET/DNA nucleotide counts, and
263 sequence length); (ii) a counts model with 15 features (sugar-base combination counts plus phos-
264 phorothioate linkage count); (iii) the Hagedorn dinucleotide model with 288 features (all pairwise
265 dinucleotide transitions across 12 nucleotide types and 2 linkage types); and (iv) a position-specific
266 model with 480 features (nucleotide identity at each position from both ends). Dosing covariates
267 (mg/kg, number of doses, dosing period, administration route) were included as additional features.

268 **Label assignment.** Species-specific upper limits of normal (ULN) were taken from published
269 reference intervals as the mean of male and female 97.5th percentiles: 75 IU/L for C57BL/6J mice
270 [4], 39 IU/L for Sprague-Dawley rats [5], and 103 IU/L for adult cynomolgus macaques [6]. The
271 pipeline pass threshold was set at $2 \times \text{ULN}$ (150 IU/L mouse, 78 IU/L rat, 206 IU/L monkey). For
272 classifier training, compounds with mean ALT $\geq 2 \times \text{ULN}$ were labelled “high” toxicity; those with
273 ALT $< 2 \times \text{ULN}$ were labelled “low”.

274 **Model training.** Random forest classifiers (1000 trees, max 8 features per split, balanced class
275 weights) were trained with GroupKFold cross-validation (5 folds, grouped by target gene). This
276 prevents information leakage from compounds targeting the same gene appearing in both training
277 and test sets.

278 4.4 Hagedorn Neurotoxicity Model (2022)

279 We replicated the [2] approach for predicting ASO neurotoxicity from sequence features, evaluated
280 on mouse bFOB scores from ICV administration at 700 μg .

281 **Linear model.** The original 5-feature logistic regression model uses: G nucleotide count, A
282 nucleotide count, G-free stretch from the 3' end, G-free stretch from the 5' end, and total sequence
283 length. Balanced class weights were applied.

284 **RF models.** The same four random forest feature sets used for hepatotoxicity were also evaluated for
285 neurotoxicity, without dosing covariates (all neurotoxicity data used the same ICV 700 μg protocol).

286 **Label assignment.** Compounds with mean bFOB > 1 were labelled “neurotoxic”; those with mean
287 bFOB ≤ 1 were labelled “non-toxic”.

288 4.5 Cross-Validation Procedure

289 All models were evaluated using GroupKFold cross-validation with 5 folds, where groups were
290 defined by target gene. This ensures that all compounds targeting the same gene appear exclusively
291 in either the training or test set within each fold, preventing inflated performance estimates from
292 gene-level information leakage. Group assignment prioritised direct target gene annotations, supple-
293 mented by compound-level cross-referencing to the in vitro dataset and USPTO patent ID as a
294 fallback proxy.

295 4.6 Cost-Based Evaluation Framework

To translate classification accuracy into practical value, we developed a cost-based evaluation framework. For each pipeline stage, per-ASO costs were estimated from industry benchmarks: \$500 (in vitro efficacy), \$2,000 (dose-response), \$15,000 (mouse hepatotoxicity), \$20,000 (mouse neurotoxicity), \$25,000 (rat hepatotoxicity), \$30,000 (rat neurotoxicity), and \$100,000 (monkey hepatotoxicity).

The **enrichment factor** at a given stage is defined as the ratio of the pass rate among classifier-selected compounds to the base pass rate: $EF = \frac{P(\text{pass} | \text{selected})}{P(\text{pass})}$, where “selected” denotes the top 25% compounds with lowest predicted toxicity risk (lowest P(high)). An enrichment factor greater than one indicates that the classifier concentrates passing compounds among its predictions.

Pipeline costs are back-calculated by determining the number of initial ASOs needed to yield one development candidate, given the pass rates at each stage. With classifier pre-screening, the effective pass rates at enriched stages increase by the enrichment factor, reducing the required number of initial candidates and the associated costs at all downstream stages.

5 Code Availability

References

- [1] P. H. Hagedorn *et al.*, “Hepatotoxic Potential of Therapeutic Oligonucleotides Can Be Predicted from Their Sequence and Modification Pattern,” *Nucleic Acid Therapeutics*, vol. 23, no. 5, pp. 302–310, Oct. 2013, doi: 10.1089/nat.2013.0436.
- [2] P. H. Hagedorn *et al.*, “Acute Neurotoxicity of Antisense Oligonucleotides After Intracerebroventricular Injection Into Mouse Brain Can Be Predicted from Sequence Features,” *Nucleic Acid Therapeutics*, vol. 32, no. 3, pp. 151–162, June 2022, doi: 10.1089/nat.2021.0071.
- [3] B. Hill *et al.*, “Accurately modelling RNase H-mediated antisense oligonucleotide efficacy.” Accessed: Feb. 27, 2026. [Online]. Available: <https://www.biorxiv.org/content/10.1101/2025.10.29.685292v1>
- [4] G. P. Otto *et al.*, “Clinical Chemistry Reference Intervals for C57BL/6J, C57BL/6N, and C3HeB/FeJ Mice (*Mus musculus*),” *Journal of the American Association for Laboratory Animal Science: JAALAS*, vol. 55, no. 4, pp. 375–386, 2016.
- [5] Q. He *et al.*, “Sex-specific reference intervals of hematologic and biochemical analytes in Sprague-Dawley rats using the nonparametric rank percentile method,” *PloS One*, vol. 12, no. 12, p. e189837, 2017, doi: 10.1371/journal.pone.0189837.
- [6] J. Bakker *et al.*, “Reference Intervals and Percentiles for Hematologic and Serum Biochemical Values in Captive Bred Rhesus (*Macaca mulatta*) and Cynomolgus Macaques (*Macaca fascicularis*),” *Animals: an open access journal from MDPI*, vol. 13, no. 3, p. 445, Jan. 2023, doi: 10.3390/ani13030445.

A Supplementary Figures





Figure 6: Clinical benchmark: ION582 (Zilganersen) in context of ASO Atlas 2.0 distributions. Grey bars show all targets; blue bars highlight *UBE3A-ATS*-targeting ASOs; the red arrow marks ION582. (A) IC₅₀ distribution under gymnosis/free-uptake conditions. (B) Mouse bFOB score distribution (ICV, 700 µg, 3 h post-dose). (C) Rat mFOB score distribution (IT, 3,000 µg, 3 h post-dose).



334 Figure 7: Cross-species hepatotoxicity concordance. Mean ALT per compound in mouse vs rat (log-
335 log), with Spearman correlation shown.