Package 'glebe.datasets'

July 23, 2020

vary 25, 2020
Title Create demo datasets for instructional use
Version 0.5
Author Joel Barnes <j@barnzilla.ca>[aut, cre], Michelle Guerrero <mguerrero@cheo.on.ca>[aut]</mguerrero@cheo.on.ca></j@barnzilla.ca>
Maintainer Joel Barnes <j@barnzilla.ca></j@barnzilla.ca>
Description This package contains tools to create demo datasets for instructional use (e.g., in undergraduate statistics classes).
License GPL-3
<pre>URL https://github.com/barnzilla/glebe</pre>
BugReports https://github.com/barnzilla/glebe/issues
Depends R (>= 2.10)
VignetteBuilder knitr
Encoding UTF-8
Language en
LazyData true
Roxygen list(markdown = TRUE)
RoxygenNote 7.1.0
Imports haven, scales, simstudy, writexl
Suggests klippy, knitr
R topics documented:
export_dataset
Index

export_dataset

Export a dataset.

Description

This function allows users to export a dataset to Excel or SPSS.

Usage

```
export_dataset(
    x,
    path = paste0(getwd(), "/", deparse(substitute(x))),
    type = "xlsx"
)
```

Arguments

x A data frame.

path The path to the location on the user's local computer where the data frame should

be stored. This parameter is set to the working directory #' by default.

type A character element representing the type of export to perform (options: "xlsx"

or "spss"). This parameter is set to "xlsx" by default.

Value

Returns none.

```
get_correlation_coefficient
```

Randomly create a correlation coefficient.

Description

This function randomly creates a correlation coefficient.

Usage

```
get_correlation_coefficient(size, direction = "p", seed_number = 1)
```

Arguments

size A character element (options: "w" for weak, "s" for small, "m" for moderate or

"l" for large).

direction A character element (options: "p" for positive or "n" for negative) This para-

mater is set to "p" by default.

seed_number A numeric (integer) element that allows a randomly generated effect size to be

reproduced. This parameter is set to 1 by default.

Value

Returns a numeric element between -0.70 and 0.70.

get_dataset 3

 $get_dataset$

Create a demo dataset

Description

This function creates a demo dataset.

Usage

```
get_dataset(n = 1000)
```

Arguments

n

A numberic (integer) element representing the number of participants (rows) in the dataset. This parameter is set to 1000 by default.

Value

Returns a data frame.

Index

```
export_dataset, 2
get_correlation_coefficient, 2
get_dataset, 3
```