

CS105/CS360/SE360

[Fundamentals of]Artificial Intelligence

Group project for An optimal samples selection System

It is known that the amount of data generated has been increasing tremendously in the last few years due to the ease of accessing to the internet, cheap or inexpensive mass storage devices, the ease of transferring data through internet, communication lines and digital data are used in all walks of life. Nowadays, these big data have been used for data mining, knowledge discovery, machine learning, statistical learning, statistical analysis and experiments. In order to extract or discover useful data, information or knowledge from these big data, one of methods we usually adopted is samples selection.

In this group project, you are expected to extract a subset of samples from these big data. In order to extract this subset of data (samples), we have to make sure that the subset of samples extracted or selected should be as fair and unbiased as possible and also as optimal as possible. In the following we propose one method.

Assuming that there are m samples ($45 \leq m \leq 54$), any n ($7 \leq n \leq 25$) samples out of these m samples are selected. There are ${}_m C_n$ groups of n samples. From one of these groups of n samples, we randomly select e.g., $k=6$ ($4 \leq k \leq 7$) samples to form some groups. So there will be ${}_n C_k$ groups of $k=6$ samples selected. Among these groups of $k=6$ samples, we would like to optimize them by selecting ONLY some of them. The conditions that need to be fulfilled are listed as follows:

1. There are at least ONE group of k samples, in which s ($3 \leq s \leq 7$) samples have been selected from the j (where $s \leq j \leq k$) samples, i.e., when $j=4$, we have $s=3$ or 4 ; when $j=5$, we have $s=3, 4$ or 5 ; when $j=6$, we have $s=3, 4, 5$ or 6 ; and when $j=7$, we have $s=3, 4, 5, 6$ or 7 .

E.g. 1, when $m=45$, $n=7$ (assume we have chosen 7 samples, A, B, C, D, E, F, G and $k=6$, $j=5$, $s=5$, we could obtain the following minimum 6 groups of $k=6$ samples, which guarantee at least ONE group of $k=6$ samples has $s=5$ samples groups from ALL $j=5$ samples groups of $n=7$ samples, (i.e., ${}_n C_j = {}_7 C_5$ and ${}_j C_s = {}_5 C_5$).

- | | | |
|-----------------------|-----------------------|-----------------------|
| 1. A, B, C, D, E, G | 2. A, B, C, D, F, G | 3. A, B, C, E, F, G |
| 4. A, B, D, E, F, G | 5. A, C, D, E, F, G | 6. B, C, D, E, F, G |

E.g. 2, when $m=45$, $n=8$ (assume we have chosen 8 samples, A, B, C, D, E, F, G, H and $k=6$, $j=4$, $s=4$, we could obtain the following minimum 7 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has $s=4$ samples groups from ALL $j=4$ samples groups of $n=8$ samples, (i.e., ${}_n C_j = {}_8 C_4$ and ${}_j C_s = {}_4 C_4$).

- | | | | |
|-----------------------|-----------------------|-----------------------|-----------------------|
| 1. A, B, C, D, G, H | 2. A, B, C, E, G, H | 3. A, B, C, F, G, H | |
| 4. A, B, D, E, F, G | 5. A, C, D, E, F, H | 6. B, C, D, E, F, H | 7. C, D, E, F, G, H |

E.g. 3, when $m=45$, $n=9$ (assume we have chosen 9 samples, $A, B, C, D, E, F, G, H, I$ and $k=6$, $j=4$, $s=4$, we could obtain the following minimum 12 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has $s=4$ samples groups from ALL $j=4$ samples groups of $n=9$ samples, (i.e., ${}_n C_j = {}_9 C_4$ and ${}_j C_s = {}_4 C_4$).

- | | | | |
|-----------------------|------------------------|------------------------|------------------------|
| 1. A, B, C, D, E, I | 2. A, B, C, E, G, H | 3. A, B, C, F, H, I | 4. A, B, D, E, F, G |
| 5. A, B, D, G, H, I | 6. A, C, D, E, F, H | 7. A, C, D, F, G, I | 8. A, E, F, G, H, I |
| 9. B, C, D, F, G, H | 10. B, C, E, F, G, I | 11. B, D, E, F, H, I | 12. C, D, E, G, H, I |

E.g.4, when $m=45$, $n=8$ (assume we have chosen 8 samples, A, B, C, D, E, F, G, H and $k=6$, $j=6$, $s=5$, we could obtain the following minimum 4 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has ONE $s=5$ samples group from ALL $j=6$ samples groups of $n=8$ samples, (i.e., ${}_n C_j = {}_8 C_6$ and ${}_j C_s = {}_6 C_5$).

- | | | | |
|-----------------------|-----------------------|-----------------------|-----------------------|
| 1. A, B, C, E, G, H | 2. A, B, D, F, G, H | 3. A, C, D, E, F, H | 4. B, C, D, E, F, G |
|-----------------------|-----------------------|-----------------------|-----------------------|

E.g. 5, when $m=45$, $n=9$ (assume we have chosen 9 samples, A,B,C,D,E,F,G,H,I and $k=6$, $j=5$, $s=4$, we could obtain the following minimum 3 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has ONE $s=4$ samples group from ALL $j=5$ samples groups of $n=9$ samples, (i.e., ${}_nC_{j=9}C_5$ and ${}_sC_4$).

1. A,B,D,F,G,H
2. A,C,E,G,H,I
3. B,C,D,E,F,I

E.g. 6, when $m=45$, $n=10$ (assume we have chosen 10 samples, A,B,C,D,E,F,G,H,I,J and $k=6$, $j=6$, $s=4$, we could obtain the following minimum 3 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has ONE $s=4$ samples group from ALL $j=6$ samples groups of $n=10$ samples, (i.e., ${}_{10}C_6$ and ${}_6C_4$).

1. A,B,E,G,I,J
2. A,C,E,G,H,J
3. B,C,D,F,H,I

E.g. 7, when $m=45$, $n=12$ (assume we have chosen 12 samples, A,B,C,D,E,F,G,H,I,J,K,L and $k=6$, $j=6$, $s=4$, we could obtain the following minimum 6 groups of $k=6$ samples, which guarantees at least ONE group of $k=6$ samples has ONE $s=4$ samples group from ALL $j=6$ samples groups of $n=12$ samples. (i.e., ${}_nC_{j=12}C_6$ and ${}_jC_{s=6}C_4$).

1. A,B,D,G,K,L
2. A,C,D,H,J,L
3. A,D,E,F,I,L
4. B,C,G,H,J,K
5. B,E,F,G,I,K
6. C,E,F,H,I,J

2. A user friendly interface should be provided. A system title is given as, e.g., “An Optimal Samples Selection System”.
3. The user needs to input the values for parameters m , n , k , j and s . They are all positive integers. See Screens below.
4. The system randomly selects n out of m numbers or a user inputs n numbers, and displays these n numbers on screen.
5. Output groups of $k=6$ samples (results) to a DB file, e.g., 40-9-6-4-4- x - y for $m=40$, $n=9$, $k=6$, $j=s=4$ for the x^{th} run.
6. Provide a way to **EXECUTE and DELETE, etc.** the obtained groups of k samples (results) onto the screen from a DB file, e.g., 45-9-6-4-4- x - y . These groups of $k=6$ samples are selected from the list. Please see the screens below.
7. Students are required to form groups yourselves. Each group should have 3 students. You are advised to include in your group at least ONE student who knows how to do programming in any programming languages.
8. Use numeral values, e.g., positive INTEGERS, 01,02,03,.....,54 instead of big capital letters A,B,C,D,E,F.....,Z for the m and n numbers.
9. Submit to me names of your group members next week. Group numbers will be provided to you later for presentation.
10. A presentation and demonstration is a **MUST** in weeks **14** and/or **15**.
11. Each group is required to have a **15 minutes** presentation which includes the brief introduction, description of method(s) adopted/used, what have been achieved in this project, and a demonstration of your system is a **MUST** in the presentation.
12. A clear, succinct, easy to understand **detailed** user manual/guide on how to **INSTALL and EXECUTE** your DEVELOPED system **step by step** and a *project report* must be submitted. The *PROJECT REPORT* must include **method(s)/methodology (supported by diagram(s), etc.), features you have developed/used, contributions such as good running time, optimal/near optimal results, etc., and problems such as long time to get results, results not good enough, etc. of your system, results of sample runs**, etc. should be submitted in **hardcopy**.
13. You are required to submit a **USB** which contains your developed system, all your source files (codes), free/share ware, database files, DB files of $k=6$ samples (sample runs outputs/results), and the **REPORT** mentioned in point 12.
14. Bonuses will be given to group(s) that allow users to select as many different parameters as possible for m , n , k , j and s , good method(s) adopted, could generate **optimal/ near optimal solutions**. Furthermore, bonuses will be given to the developed system(s) that could be executed in a **short time** and **run on mobile phones**.
15. All teams must submit their projects in a **USB** and **hardcopy** of the **REPORTs (User Manual and Project Report)** in **Week 15**. Group number, names, student numbers of your group members should be listed in your **REPORT**.

S₁

An Optimal Samples Selection System

please input the following parameters

M 45 ≤ M ≤ 54N 7 ≤ N ≤ 25K 4 ≤ K ≤ 7J 5 ≤ J ≤ KS 3 ≤ S ≤ 7

○ Random N ○ Input N

store DB

execute

Delete

Values Input

1st #	5
2nd #	12
3rd #	24

Results

54	
55	
59	
45-9-6-5-5-1-59	

Print

NEXT

User input n

25

S₂

An Optimal Sample Selection System

Data Base Resources

Display

Delete

○ 45-9-6-5-5-1-59.txt

○ 45-10-6-4-9-1.txt

○ 40-10-6-5-4-1.txt

○

○

○

○

○

○

○

○

58	
59	
45-9-6-5-5-1-59	

PREVIOUS

RE-FILTER

PRINT

S3

An optimal Samples Selection System

Please select the filter methods

- Define positions and numbers
- Define positions and range of numbers
- Select positions as fixed numbers

Previous

Next

S4

An Optimal Samples Selection System

Define positions and numbers

Please input 3 positions

- Please input the corresponding numbers
1st position 2nd position 3rd position

- Please input the numbers not to be included in the corresponding positions

1st position 2nd position 3rd position

please name ~~the~~ a file to create

▲

▼

Display

execute

Previous

Print

NEXT

S5 An optimal samples Selection System.

Define positions and range of numbers

Please input 3 positions

o Please input the range of numbers for

1st position - 2nd position - 3rd position -

o Please input range of numbers not to be included for

1st position - 2nd position - 3rd position -

please name a file to create

Display

execute

previous

Print

Next

S6

An optimal samples selection System

Select positions as fixed numbers

Please select 3 positions

1st position 2nd position 3rd position

please ^{enter} the sum of these 3 numbers in positions

please name a file to create

Display

execute

previous

Print

Next