
[23-2] UST Seminar

Exploring Uncertainty-aware Class-wise Thresholds for Recognition Model's Uncertainty Detection

UST-ETRI School Hwang Jihyun
(aribae@etri.re.kr)

Table of contents


1. Recap of previous study
2. Introduction
3. Methodology
4. Results
5. Conclusion

Recap of previous study

Recap of previous study

Setting different thresholds per class for uncertainty measurements


Proposed Architecture:



Recap of previous study

Results:

- Verify that different classes have different confidence distributions
- Different thresholds show improved classification performance



Comparison of confidence distributions by class

threshold	recall(avg)	precision(avg)
0.90	0.175	1
0.80	0.550	0.969
0.70	0.675	0.888
Q1	0.875	0.571
mean	0.700	0.671
median	0.700	0.675


Misclassification Classification Test Results

Introduction

Introduction

Estimating uncertainty in zero-shot image classification using the vision-language model, **CLIP**.

Proposed Architecture:



Introduction



[Open AI's CLIP]

Versatility:

- CLIP is a model for understanding the relationship between images and text, which can be used for a variety of tasks. This model processes **images and text together**
- CLIP can **perform multiple tasks in a single model**, including image classification, text classification, image search, text search, and image creation.

Zero-shot learning:

- CLIP was not explicitly learned for all class labels during training. Instead, it was learned using many image-text pairs with text descriptions.
- This makes CLIP robust to **make predictions about new classes**, and is effective in transfer learning about new tasks or datasets.

Introduction

[Open AI's CLIP]




Figure 1. Summary of our approach. While standard image models jointly train an image feature extractor and a linear classifier to predict some label, CLIP jointly trains an image encoder and a text encoder to predict the correct pairings of a batch of (image, text) training examples. At test time the learned text encoder synthesizes a zero-shot linear classifier by embedding the names or descriptions of the target dataset's classes.

Methodology

Methodology



[Two datasets used]

CIFAR-10:

- Consists of 60,000 32x32 colour images in 10 classes, with 6000 images per class.
- 50000 training images and 10000 test images

Food 101:

- Consists of 101,000 images in 101 food categories.

Methodology

[Split datasets]

Calibration dataset:

- Determine thresholds from entropy values extracted from Calibration dataset

Test dataset:

- Evaluate the performance of determined thresholds.
- Verify that misclassified samples can be screened through uncertainty thresholds

	Class-wise thresholds test				OOD dataset test			
Dataset	CIFAR-10		Food 101		CIFAR-10		Food 101	
Data split	Calibration	test	Calibration	test	Calibration	test	Calibration	test
# of classes	10	10	101	101	8	2	80	21
# of images	50,000	10,000	80,800	20,200	50,000	10,000	80,800	20,200



[Calculate Thresholds using cosine similarity]

Calculate image and text embedding:

- Calculate E_{img} , the image embedding for the input image img , and $E_{text}(j)$, the text embedding for each prompt j .

Calculate and Normalize Cosine Similarity:

- Calculate cosine similarity s_j between image embedding E_{img} and each text embedding $E_{text}(j)$
- The calculated cosine similarity s_j is normalized by dividing by 2 to obtain the final similarity score sim_j

$$s_j = \frac{E_{img} \cdot E_{text}(j)}{\|E_{img}\| \times \|E_{text}(j)\|}$$
$$sim_j = \frac{s_j + 1}{2} \quad for \ j = 1, 2, \dots, K$$



[Calculate Thresholds using cosine similarity]

Select and classify prompts with the highest similarity:

- Compare the normalized similarity sim_j for each prompt to select the prompt with the highest similarity
- Classifies the image into the class corresponding to the selected prompt

Estimating the uncertainty of classification:

- Calculate the entropy(H) of the similarity distribution between the input image and the prompt
- As entropy increases, so does the uncertainty of classification

$$H(img) = - \sum_{j=1}^K sim_j \log sim_j$$



[Find thresholds by using grid-search method]

Grid search method:

- One of the many classical methods for optimization
- Select the best parameter combination by systematically analyzing all possible parameter combinations



[Find thresholds by using grid-search method]

Set thresholds to minimize samples in the following two cases at the same time:

- Classified as certain even though the CLIP's prediction is wrong
- Classified as uncertain even though the CLIP's prediction is right

(a) Entropy List Preparation

1: `class_number = n`

2: `entropy_list = [e1, e2, e3, ..., ek]`

(b) Sampling of true positive and false positive

3: `TP = {ei | class(ei) = n ∧ predict(ei) = n}`

4: `FP = {ei | class(ei) ≠ n ∧ predict(ei) = n}`

Threshold setting algorithm used

(c) Find the optimal threshold value.

5: `min_count = ∞`

6: `threshold = None`

7: `for e in entropy_list:`

8: `TP' = {ei ∈ TP | ei > e}`

9: `FP' = {ei ∈ FP | ei < e}`

10: `count = card(TP') + card(FP')`

11: `if count < min_count:`

12: `min_count = count`

13: `threshold = e`



[Set three threshold criteria]

Class-Wise Thresholds:

- Use grid search to find the optimal threshold by considering the uncertainty of each class's sample

Average of Class-Wise Thresholds (Mean of Class-Wise Thresholds):

- The average of thresholds obtained for each class

Single Threshold by Grid Search on Entire Dataset (Grid Search Single Threshold):

- A single threshold obtained by applying grid search to the predictive results of the CLIP model for the entire dataset.

Results

Results

[Misclassification detection results]

- Class-wise entropy thresholding method shows higher performance as a result of synthesizing the entire set of results.

		Dataset	
		CIFAR10	Food101
1	# of images	10000	20200
2	# of correct predictions	7926	12434
3	# of incorrect predictions	2074	7766
4	Accuracy(%)	79.206	61.554

CLIP model accuracy

Results

[Misclassification detection results]

- Class-wise entropy thresholding method shows higher performance as a result of synthesizing the entire set of results.

		Dataset	
		CIFAR10	Food101
1	Class-wise Thresholds	0.779	0.845
2	Mean of class-wise thresholds single threshold	0.456	0.367
3	Grid search single threshold	0.529	0.576

Uncertainty detection performance

Results



[Misclassification detection results]

- Out-of-Distribution (OOD): The model represents an untrained data area and is used to assess predictive uncertainty for a given model.
- The results of OOD also confirmed that class-wise entropy thresholds showed the highest performance

		Dataset	
		CIFAR10	Food101
1	Class-wise Thresholds	0.933	0.894
2	Mean of class-wise thresholds single threshold	0.689	0.475
3	Grid search single threshold	0.779	0.751

Uncertainty detection performance In OOD dataset

Results



image class: cat
prediction: cat
entropy: 0.1193235
threshold: 0.8461579



image class: bird
prediction: ship
entropy: 0.8560749
threshold: 0.2974607

Uncertainty detection image sample

Conclusion

Conclusion



Transfer Learning:

- Easy to measure classification performance without additional learning

Necessity for fine tuning:

- Performance was not good on the Fine-Grained classification dataset
- No matter what model we use, we will need to learn about the domain data want to use

Thank you