

Social Networks & Recommendation Systems

VII. Probabilistic aspects of the complex networks.

Grzegorz Siudem

Warsaw University of Technology



**European
Funds**
Knowledge Education Development

**Warsaw University
of Technology**

European Union
European Social Fund



MSc program in Data Science has been developed
as a part of task 10 of the project
„NERW PW. Science - Education - Development - Cooperation”
co-funded by European Union from European Social Fund.

Before classes

Reminder

From SNARS_5:

- Properties of the ER graphs.

From SNARS_6:

- Mean-field approach to the BA model.

From other courses:

- generating functions approach in the combinatorics.

To think about:

- What do you think, which of the graphs: Erdős-Rényi or Barabasi-Albert is more vulnerable for intentional attacks and random failures? Why?

Lecture

Impressions after the derivations for the BA model?

Impressions after the derivations for the BA model?

Pros

- IT WORKS!

Impressions after the derivations for the BA model?

Pros

- IT WORKS!
- relatively simple (right?),

Impressions after the derivations for the BA model?

Pros

- IT WORKS!
- relatively simple (right?),
- short and based on the very basic tools.

Impressions after the derivations for the BA model?

Pros

- IT WORKS!
- relatively simple (right?),
- short and based on the very basic tools.

Cons

- unreal assumptions,

Impressions after the derivations for the BA model?

Pros

- IT WORKS!
- relatively simple (right?),
- short and based on the very basic tools.

Cons

- unreal assumptions,
- unverifiable approximations,

Impressions after the derivations for the BA model?

Pros

- IT WORKS!
- relatively simple (right?),
- short and based on the very basic tools.

Cons

- unreal assumptions,
- unverifiable approximations,
- lack of the mathematical precision.

Impressions after the derivations for the BA model?

Pros


- IT WORKS!
- relatively simple (right?),
- short and based on the very basic tools.

Cons

- unreal assumptions,
- unverifiable approximations,
- lack of the mathematical precision.

Conclusion:

I strongly recommend reading Durrett to those who are dissatisfied!



<https://services.math.duke.edu/~rtd/RGD/RGD.html>

Let's have a look to chapter 4.1.

Master equation

The equation describing the changes in the probability distribution over time

$$\frac{d\mathcal{P}_i}{dt} = \sum_j \mathcal{P}_j T_{j \rightarrow i} - \sum_j \mathcal{P}_j T_{i \rightarrow j},$$

which in the discrete version takes the following form

$$\mathcal{P}_i(t+1) - \mathcal{P}_i(t) = \sum_j \mathcal{P}_j(t) T_{j \rightarrow i} - \sum_j \mathcal{P}_j(t) T_{i \rightarrow j},$$

and this is what we will focus on.

Master equation for BA networks

We will follow

- chapter 4.1 in Durrett's book,
- S.N. Dorogovstev, J.F.F. Mendes i A.N Samukhin, *Structure of growing networks with preferential linking*, Phys. Rev. Letters. **85**, 4633–4636 (2000).

Master equation for BA networks

We will follow

- chapter 4.1 in Durrett's book,
- S.N. Dorogovstev, J.F.F. Mendes i A.N Samukhin, *Structure of growing networks with preferential linking*, Phys. Rev. Letters. **85**, 4633–4636 (2000).

Master equation takes the form:

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Master equation for BA networks

We will follow

- chapter 4.1 in Durrett's book,
- S.N. Dorogovstev, J.F.F. Mendes i A.N Samukhin, *Structure of growing networks with preferential linking*, Phys. Rev. Letters. **85**, 4633–4636 (2000).

Master equation takes the form:

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Question:

Can you justify the components of this equation?

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Interpretation:

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Interpretation:

- $\frac{m(k-1)}{2mt} N_{k-1}(t)$ the number of vertices that has just promoted to the k -th level.

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Interpretation:

- $\frac{m(k-1)}{2mt} N_{k-1}(t)$ the number of vertices that has just promoted to the k -th level.
- $\frac{mk}{2mt} N_k(t)$ the number of vertices that has just promoted to the $k+1$ -st level.

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Interpretation:

- $\frac{m(k-1)}{2mt} N_{k-1}(t)$ the number of vertices that has just promoted to the k -th level.
- $\frac{mk}{2mt} N_k(t)$ the number of vertices that has just promoted to the $k+1$ -st level.
- δ_{km} newly added vertex.

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{m(k-1)}{2mt} N_{k-1}(t) - \frac{mk}{2mt} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

Interpretation:

- $\frac{m(k-1)}{2mt} N_{k-1}(t)$ the number of vertices that has just promoted to the k -th level.
- $\frac{mk}{2mt} N_k(t)$ the number of vertices that has just promoted to the $k+1$ -st level.
- δ_{km} newly added vertex.

Question:

Is this solution mathematically exact?

Inaccuracies in the master equation approach:

- adding an edge does not change preferences (synchronous dynamics, mean-field theory reminiscence),

Inaccuracies in the master equation approach:

- adding an edge does not change preferences (synchronous dynamics, mean-field theory reminiscence),
- we allow for multiple connections.

Inaccuracies in the master equation approach:

- adding an edge does not change preferences (synchronous dynamics, mean-field theory reminiscence),
- we allow for multiple connections.

However, this approach works perfectly!

Why?

Master equation for BA networks

Inaccuracies in the master equation approach:

- adding an edge does not change preferences (synchronous dynamics, mean-field theory reminiscence),
- we allow for multiple connections.

However, this approach works perfectly!

Why?

Precision vs. simplicity of the method?

i.e. mathematicians vs. physicists...

Master equation for BA networks

$$N_k(t+1) - N_k(t) = \frac{k-1}{2t} N_{k-1}(t) - \frac{k}{2t} N_k(t) + \delta_{km}$$
$$N_{m-1}(t) = 0.$$

How to solve it?

goto Project;

Master equation for BA networks – solution

$$N_k(t+1) - N_k(t) = \frac{k-1}{2t} N_{k-1}(t) - \frac{k}{2t} N_k(t) + \delta_{km}.$$
$$N_{m-1}(t) = 0.$$

Solution:

$$\mathcal{P}(k) = \frac{2m(m+1)}{k(k+1)(k+2)}$$

Master equation for BA networks – solution

$$N_k(t+1) - N_k(t) = \frac{k-1}{2t} N_{k-1}(t) - \frac{k}{2t} N_k(t) + \delta_{km}.$$
$$N_{m-1}(t) = 0.$$

Solution:


$$\mathcal{P}(k) = \frac{2m(m+1)}{k(k+1)(k+2)}$$

Question:

Argue that for $k \gg 1$ above results agrees with mean-field approach.

Percolation – ER graphs

Let us now return to the ER graphs



What is happening in the middle? We will follow sec. 4.3.2 in Fronczak and Fronczak book.

Percolation – ER graphs

What is percolation?




wikipedia

SNARS Mathematical model of liquid leakage through porous material.

Percolation – ER graphs

How does this relate to graphs?




We ask when the graf is percolated

i.e. when percolation cluster's size is equal to $N^* \propto N$.

Percolation – ER graphs

How does this relate to graphs?



We ask when the graf is percolated

i.e. when percolation claster's size is equal to $N^* \propto N$.

Attention!

We will approach in the physicist way. For more detailed approaches (sic!) see chapter 2 in Durrett's book.

Percolation – ER graphs

Let us introduce distribution $Q(k)$

$Q(k)$ is the distribution of the degrees on the ends on the randomly selected edge.

Percolation – ER graphs

Let us introduce distribution $\mathcal{Q}(k)$

$\mathcal{Q}(k)$ is the distribution of the degrees on the ends on the randomly selected edge.

During project we will justify that $\mathcal{Q}(k) \propto k\mathcal{P}(k)$, thus

$$\mathcal{Q}(k) = \frac{k}{\langle k \rangle} \mathcal{P}(k).$$

Percolation – ER graphs

Let us introduce distribution $\mathcal{Q}(k)$

$\mathcal{Q}(k)$ is the distribution of the degrees on the ends on the randomly selected edge.

During project we will justify that $\mathcal{Q}(k) \propto k\mathcal{P}(k)$, thus

$$\mathcal{Q}(k) = \frac{k}{\langle k \rangle} \mathcal{P}(k).$$

During Project we will prove that percolation threshold can be defined as

$$\sum_k k \mathcal{Q}(k) \geq 2,$$

which is equivalent to $\langle k \rangle_{nn} = \frac{\langle k^2 \rangle}{\langle k \rangle} = 2$.


Percolation threshold for ER graphs

For ER graphs we obtain

$$\langle k \rangle = 1,$$

which means

$$p_c = \frac{1}{N}.$$



Thank you for your attention!



**European
Funds**
Knowledge Education Development

**Warsaw University
of Technology**

European Union
European Social Fund



MSc program in Data Science has been developed
as a part of task 10 of the project
„NERW PW. Science - Education - Development - Cooperation”
co-funded by European Union from European Social Fund.