

# TW3720TU: Object Oriented Scientific Programming with C++ (11/14/17)

Matthias Möller  
Numerical Analysis

# Overview

- Last lecture we started with polymorphism, that is, inheritance of one class from another class
  - Implement common functionality in base class (possibly realised as abstract class that cannot even be instantiated)
  - Derive specialised class(es) from the base class that
    - Implement the missing functionality (pure virtual functions)
    - Override generic functionality by specialised variants (virtual functions)
    - Reuse all other functionality from the base class

# Overview, cont'd

- Today, a more careful view on polymorphism
  - *Static* polymorphism: static binding/method overloading
  - *Dynamic* polymorphism: dynamic binding/method overriding
- C++11/14/17? auto functionality
- Template meta programming
  - A powerful variant of static polymorphism

# Quiz: Guess what happens

- ```
struct Base {  
    virtual void hello() = 0;  
};
```
- ```
struct Derived : public Base {  
    void hallo()  
    {  
        std::cout << "Hallo\n";  
    }  
};
```

# Quiz: Guess what happens

- ```
struct Base {  
    virtual void hello() = 0;  
};
```
- ```
struct Derived : public Base {  
    void hello()  
    {  
        std::cout << "Hallo\n";  
    }  
};
```

# Quiz: Guess what happens

- ```
struct Base {  
    virtual void hello() {  
        std::cout << "Hello\n";  
    }  
};
```
- ```
struct Derived : public Base {  
    void hello()  
    {  
        std::cout << "Hallo\n";  
    }  
};
```

# Quiz: Guess what happens

- ```
struct Base {  
    virtual void hello() {  
        std::cout << "Hello\n";  
    }  
};
```
- ```
struct Derived : public Base {  
    void hallo()  
    {  
        std::cout << "Hallo\n";  
    }  
};
```

# The override keyword

- C++11 introduces the **override** keyword to explicitly state that a function from the base class shall be overridden

```
struct Base {  
    virtual void hello() { std::cout << "Hello\n"; }  
};  
struct Derived : public Base {  
    void hello() override { std::cout << "Hallo\n"; }  
};
```

- If the function to be overridden does not exist in the base class an error is thrown by the compiler



# The override keyword, cont'd

- Overriding function must **exactly match** the signature of the function from the base class

```
struct Base {  
    virtual void hello() const { std::cout << "Hello\n"; }  
};  
struct Derived : public Base {  
    void hello() const override { std::cout << "Hallo\n"; }  
};
```

# The final keyword

- C++11 introduces the **final** keyword to explicitly state that a function from the base class **must not** be overridden

```
struct Base {  
    virtual void hello() final { std::cout << "Hello\n"; }  
};
```

- If a derived class tries to override the function **hello** an error is thrown by the compiler

# The override and final keywords

- The **override** and **final** keywords are often used together

```
struct Base {  
    // Pure virtual function must be overridden in derived class  
    virtual void hello() = 0;  
};  
struct Derived : public Base {  
    // Override pure virtual function and make it final  
    virtual void hello() override final  
    { std::cout << "Hello\n"; }  
};  
struct Derived2 : public Derived {  
    // Must not try to override function hello  
};
```

# Task: Calculator

- Write a class (or for demonstrating purposes a hierarchy of classes) that provide(s) a member function to calculate the **sum of two and three integer values**, respectively
  - Use *static* polymorphism: method overloading
  - Use *dynamic* polymorphism: method overriding

# Static polymorphism

- **Method overloading** (at compile time)

```
struct Calc {  
    int sum(int a, int b) { return a+b; }  
    int sum(int a, int b, int c) { return sum(sum(a,b),c); }  
};
```

- Class `Calc` has two member functions with **identical names** but **different interface**; it is decided **at compile time** which of the two functions should be called

```
std::cout << C.sum(1,2) << std::endl;  
std::cout << C.sum(1,2,3) << std::endl;
```

# Static polymorphism, cont'd

- **Method overloading** (not working!)

```
struct Calc {  
    int sum(int a, int b) { return a+b; }  
    void sum(int a, int b) { std::cout<< a+b <<std::endl; }  
};
```

- Difference must be in the **interface of arguments passed** to functions since the compiler cannot distinguish between two functions if they only differ in the **return type**

# Static polymorphism, cont'd

- **Method overloading:** decision about which method to call is made at compile time; hence the compiler can decide to inline code to improve performance (no overhead due to function calls/copy of data to and from the stack!)

```
std::cout << C.sum(1,2)    << std::endl;  
std::cout << C.sum(1,2,3) << std::endl;
```

becomes

```
std::cout << (1+2)          << std::endl;  
std::cout << ((1+2)+3)      << std::endl;
```

# Static polymorphism, cont'd

- **Method overloading:** since static polymorphism takes place at compile time, the `inline` specifier can be used to explicitly 'suggest' to the compiler to inline the function

```
struct Calc {  
    inline int sum(int a, int b)  
        { return a+b; }  
    inline void sum(int a, int b)  
        { std::cout<< a+b <<std::endl; }  
};
```



# Dynamic polymorphism

- **Method overriding:** re-implement a function inherited from base class with new function body (same interface!)

```
struct BaseCalc {  
    virtual int sum2(int a, int b) { return a+b; }  
    int sum3(int a, int b, int c)  
        { return sum2(sum2(a,b),c); }  
};  
  
struct DerivedCalc : public BaseCalc {  
    int sum2(int a, int b) override { return a+b; }  
};
```

# Dynamic polymorphism, cont'd

- DerivedCalc D;  
std::cout << D.sum2(1,2) << std::endl;  
-> DerivedCalc::sum2(a,b)  
-> 3  
std::cout << D.sum3(1,2,3) << std::endl;  
-> BaseCalc::sum3(a,b,c)  
-> DerivedCalc::sum2(a,b)  
-> DerivedCalc::sum2(a,b)  
-> 6

# Dynamic polymorphism, cont'd

- **Method overriding:** a common pitfall is to forget the `virtual` specifier to indicate that the `sum2` function from the base class might be overridden in a derived class

```
struct BaseCalc {  
    int sum2(int a, int b) { return a+b; }  
    int sum3(int a, int b, int c)  
        { return sum2(sum2(a,b),c); }  
};  
struct DerivedCalc : public BaseCalc {  
    int sum2(int a, int b) { return a+b; }  
};
```

# Dynamic polymorphism, cont'd

- These bugs are hard to find (they often remain unrecognised) and can be prevented by using the `override` keyword in C++11

```
DerivedCalc D;
```

```
std::cout << D.sum2(1,2) << std::endl;
```

```
-> DerivedCalc::sum2(a,b)
```

```
-> 3
```

```
std::cout << D.sum3(1,2,3) << std::endl;
```

```
-> BaseCalc::sum3(a,b,c)
```

```
-> BaseCalc::sum2(a,b)
```

```
-> BaseCalc::sum2(a,b)
```

```
-> 6
```

# Dynamic polymorphism, cont'd

- **Method overriding:** decision about which virtual method to call is made at run time; hence inlining is not possible
- Common design pattern
  - Specify **expected minimal functionality** of a group of classes in abstract base class via **pure virtual member functions**
  - Implement generic common functionality of a group of classes abstract base class via **virtual member functions**
  - Implement expected functionality of a particular class by **overriding the pure virtual member function**

# Example: inner product space

- In linear algebra, an inner product space is a vector space  $V$  that is equipped with a special mapping (inner product)

$$\langle \cdot, \cdot \rangle : V \times V \rightarrow \mathbb{R} \text{ or } \mathbb{C}$$

- Inner product spaces have a naturally induced norm

$$\|x\| = \sqrt{\langle x, x \rangle}$$

# Example: inner product space, cont'd

- Class `InnerProductSpaceBase` declares inner product as pure virtual and implements the naturally induced norm

```
struct InnerProductBase
{
    pure virtual double inner_product(... x,... y) = 0;
    double norm(x) { return inner_product(x,x); }
};
```

- Derived `InnerProductSpace` class implements inner product

```
struct InnerProductSpace : public InnerProductSpaceBase
{
    double inner_product(... x, ... y) = { return x*y; }
};
```

# Task: Calculator2

- Extend the calculator class so that it can handle numbers of integer, float and double type at the same time
  - Prevent manual code duplication
  - Prevent explicit type casting
  - Make use of auto-functionality (C++11/14/17?)
  - Make use of template meta programming



# Vanilla implementation in C++

- ```
struct Calc2 {  
    int sum(int a, int b)  
        { return a+b; }  
    int sum(int a, int b, int c)  
        { return sum(sum(a,b),c); }  
};  
  
int main() {  
    Calc2 C;  
    std::cout << C.sum(1,2)    << std::endl;  
    std::cout << C.sum(1,2,3) << std::endl;  
}
```

# Automatic return type deduction (C++11)

- Explicit definition of the function return type

```
int sum(int a, int b)
{ return a+b; }
```

- Automatic function return type (since C++11)

```
auto sum(int a, int b) -> decltype(a+b)
{ return a+b; }
```

- Using `decltype`, the return type of the sum function is determined automatically as the type of `operator+(a,b)`

# Automatic return type deduction, cont'd

- **decltype** specifier (C++11) queries the type of an expression

```
struct Calc2 {  
    auto sum(int a, int b)           -> decltype(a+b)  
        { return a+b; }  
    auto sum(int a, int b, int c)    -> decltype(sum(sum(a,b),c))  
        { return sum(sum(a,b),c); }  
};
```

```
int main() {  
    Calc2 C;  
    std::cout << C.sum(1,2) << std::endl;  
    std::cout << C.sum(1,2,3) << std::endl;  
}
```

# Automatic type deduction (C++14)

- C++14 deduces the type of parameters automatically

```
auto sum(int a, int b)           // no -> decltype(a+b)
{ return a+b; }
```

```
auto sum(int a, int b, int c) // no -> decltype(a+b+c)
{ return sum(sum(a,b),c); }
```

- Remark: Feature helps to improve readability and prevents deduction errors (due to forgotten/inconsistent deduction rule by the programmer) but it does not solve the problem to pass arguments of different type to the same function

# Generic functions (C++17)

- C++17 standard will support generic functions

```
auto sum(auto a, auto b)
    { return a+b; }
auto sum(auto a, auto b, auto c)
    { return sum(sum(a,b),c); }
```

- Remark: code compiles with GNU g++ 5.x and better

# Function templates

- Until C++17, template meta programming is the standard technique to deal with arbitrary function parameters
- **Function templates:** allow you to implement so-called parameterised functions for generic parameter types

```
template<typename R, typename A, typename B>  
R sum(A a, B b)  
{  
    return a+b;  
}
```

# Function templates

- Types must be specified explicitly when function is called

```
int    s1 = sum<int, int, int>(1, 2);  
double s2 = sum<double, double, int>(1.2, 2);  
double s3 = sum<double, float, double>(1.4, 2.2);
```

- This can be slightly simplified using the auto specifier

```
auto s1 = sum<int, int, int>(1, 2);  
auto s2 = sum<double, double, int>(1.2, 2);  
auto s3 = sum<double, float, double>(1.4, 2.2);
```

# Function templates, cont'd

- C++11: automatic return type deduction

```
template<typename A, typename B>  
auto sum(A a, B b) -> decltype(a+b)  
    { return a+b; }
```

- C++14: automatic type deduction

```
template<typename A, typename B>  
auto sum(A a, B b)  
    { return a+b; }
```

- Usage

```
auto s1 = sum<int, int>(1, 2);
```



# Function templates, cont'd

- How to convert this function into a templated function

```
int sum(int a, int b, int c)
{
    return sum(sum(a,b), c);
}
```

# Function templates, cont'd

- Use explicit return type parameter (ugly!)

```
template<typename R, typename A, typename B, typename C>  
auto sum(A a, B b, C c)  
{  
    return sum<R,C>(sum<A,B>(a,b), c);  
}
```

- Guess what this function call will return

```
auto s1 = sum<int,double,double,double>(1.1,2.2,3.3)
```

# Function templates, cont'd

- Use a smart combination of templates and auto

```
template<typename A, typename B>  
auto sum(A a, B b) -> decltype(a+b) // omit in C++14  
{  
    return a+b;
```

```
template<typename A, typename B, typename C>  
auto sum(A a, B b, C c)  
{  
    return sum<decltype(sum<A,B>(a,b)),C>  
        (sum<A,B>(a,b), c);  
}
```

# Function templates, cont'd

- Now, we can call sum functions as follows

```
auto s1 = sum<int, int>(1, 2);  
auto s2 = sum<double, int>(1.2, 2);  
auto s3 = sum<float, double>(1.4, 2.2);
```

- Since the compiler needs to duplicate code and substitute A,B,C for each combination of templated types both the compile time and the size of the executable will increase
- Template meta programming is simplest of the code resides in header files only; later we will see how to use template meta-programming together with pre-compiled libraries

# Task: generic Vector class

- Write Vector class that can store real values (float/double) and complex values and supports the following operations:
  - Addition of two vectors of same length (possibly different type)
  - Multiplication of a vector with a scalar (possible different type)
  - Dot product of a vector with another one (possibly different type)

# Vector class prototype

- Implementation of Vector-of-**double** class

```
class Vector {  
private:  
    double* data;  
    int n;  
public:  
    Vector()          : n(0), data(nullptr)      {}  
    Vector(int n)     : n(n), data(new double[n]) {}  
    ~Vector()         { n=0; delete[] data; }  
    ...  
}
```

# Vector class prototype, cont'd

```
Vector& operator+=(const Vector& other) {  
    for (auto i=0; i<n; i++)  
        data[i] += other.data[i];  
    return *this; }  
Vector& operator*=(double scalar) {  
    for (auto i=0; i<n; i++)  
        data[i] *= scalar;  
    return *this; }  
double dot(const Vector& other) const {  
    double d=0;  
    for (auto i=0; i<n; i++)  
        d += data[i]*other.data[i];  
    return d; }  
};
```

# Brainstorming

- Function templates alone will not help since the type of a class attribute needs to be templated -> **class templates**
- Some member functions can be implemented generically, e.g., addition of two vectors and multiplication of a vector with a scalar value since they are the same for all types
- Some member functions must be implemented in different manners for real and complex values -> **specialisation**

$$x \cdot y = \sum_{i=1}^n x_i y_i, \quad x, y \in \mathbb{R}, \quad x \cdot y = \sum_{i=1}^n x_i \bar{y}_i \quad x, y \in \mathbb{C}$$



# Class template

- Implementation of Vector-of-anything class

```
template<typename T>
class Vector {
private:
    T* data;
    int n;
public:
    Vector()          : n(0), data(nullptr) {}
    Vector(int n)     : n(n), data(new T[n]) {}
    ~Vector()         { n=0; delete[] data; }
    ...
};
```

# Class template, cont'd

- Template parameter must be explicitly specified

```
Vector<int>    x(10); // Vector-of-int with length 10
Vector<double> y;     // Empty Vector-of-double
Vector<float>  z(5);  // Vector-of-float with length 5
```

- Remark: if you want to pass a Vector-of-**anything** to a function in the templated class Vector you have to write

```
Vector<T>  v
Vector<T>& v
```

instead of

```
Vector  v
Vector& v
```

# Class template, cont'd

```
template <typename T>
class Vector {
public:
    ...
    Vector<T>& operator+=(const Vector<T>& other)
    {
        (for auto i=0; i<n; i++)
            data[i] += other.data[i];
        return *this;
    }
    ...
};
```

# Class template, cont'd

```
template <typename T>
class Vector {
public:
    ...
    Vector<T>& operator*=(T scalar)
    {
        (for auto i=0; i<n; i++)
            data[i] *= scalar;
        return *this;
    }
    ...
};
```

# Class template, cont'd

```
template <typename T>
class Vector {
public:
    ...
    T dot(const Vector<T>& other) const
    {
        T d=0;
        for (auto i=0; i<n; i++)
            d += data[i]*other.data[i];
        return d;
    }
    ...
};
```

# Class template, cont'd

- With the single class template parameter **T** we can do

```
Vector<int> x1(5), x2(5);
```

```
x1 += x2;
```

```
x1 *= (int)2;
```

```
int x1 = x1.dot(x2);
```

- How about?

```
Vector<int> x2(5);
```

```
x2 *= (double)1.2;
```

# Intermezzo

- Class templates and function templates can be combined

```
template<typename T>
class Vector {
    ...
    template<typename S>
    Vector<T>& multiply<S scalar>
    {
        (auto i=0; i<n; i++)
            data[i] *= S;
        return *this;
    }
};
```

# Intermezzo, cont'd

- At first glance, this seems to be more flexible

```
Vector<double> x1(5);  
x1.multiply<int>(5);
```

- But be really careful since strange things can happen

```
Vector<int> x1(5);  
x1.multiply<double>(5.5);
```

- Rule of thumb: before using extensive templating like this think about all(!) implications; it can help to think if the planned functionality has a meaningful mathematical counterpart, e.g., dot product of  $x \in \mathbb{R}$ ,  $y \in \mathbb{C}$



# Specialisation

- The dot product needs special treatment since

```
T dot(const Vector<T>& other) const
{
    T d=0;
    for (auto i=0; i<n; i++)
        d += data[i]*other.data[i];
    return d;
}
```

- Lacks the complex conjugate of other and yields the wrong return type in case of complex-valued vectors
- Remedy: implement a specialised variant for this case

# Specialisation, cont'd

- Generic dot product implemented in Vector class

```
#include <complex>
template<typename T>
class Vector { ...
    T dot(const Vector<T>& other) const {...}
};
```

- This function is used whenever no specialised implementation for a concrete type is available

# Specialisation, cont'd

- Specialised dot product for Vectors-of-complex-float

```
template<>
std::complex<float> Vector< std::complex<float> >::
    dot(const Vector< std::complex<float> >& other) const
{
    std::complex<float> d=0;
    // special treatment of dot product
    for (auto i=0; i<n; i++)
        d += data[i]*std::conj(other.data[i]);
    return d;
}
```

# Specialisation, cont'd

- Current implementation yields

```
Vector<float> x1(5), x2(5);  
auto x1.dot(x2); // calls generic implementation
```

```
Vector<std::complex<float> > y1(5), y2(5);  
auto y1.dot(y2); // calls specialised implementation
```

```
Vector<std::complex<double> > z1(5), z2(5);  
auto z1.dot(z2); // calls generic implementation
```

```
auto x1.dot(y1); // does not compile(!)
```

# Outlook on next session

- C++ allows you to **partially specialise** class templates  
Note that this code will not compile (we will see why!)

```
template<typename S>
std::complex<S> Vector<std::complex<S> >::
    dot(const Vector<std::complex<S> > other) const {
    std::complex<S> d=0;
    for (auto i=0; i<n; i++)
        d += data[i]*std::conj(other.data[i]);
    return d;
}
```

- Welcome to where the magic begins!