TesseraID

A Post-Quantum Identifier for the
Late 2020s and Beyond

Project 1 of 3 in the tessera monorepo

Bahram Samani

tessera monorepo maintainer

Whitepaper, Version 1.1

Released 2026-05-21

Build date: June 10, 2026 **Build time:** 21:47 UTC
Source: `tessera-id/latex/main.tex`
Spec version: v1.1 **Wire variants:** `0x01` (Standard), `0x02` (HLC)

This document is the canonical reference for TesseraID v1. TesseraID is the identifier project in the tessera monorepo, which also contains TesseraHash (variant `0x03`, 73-byte SHAKE-256 content hash) and TesseraSeal (variant `0x04`, ML-KEM-1024 encryption envelope). When TesseraID identifies a record whose content needs integrity, use TesseraHash; when that content also needs confidentiality, use TesseraSeal with the TesseraID as AEAD associated data — the canonical "TesseraID-as-AD" pattern. See Appendix E.

Contents

TL;DR **4**

1 Why a New Identifier **5**
1.1 Quantum search has changed the entropy budget . . . 5
1.2 Time-sortability is a feature, not a side effect . . . 5
1.3 Distributed systems need first-class causal ordering . . . 6
1.4 Threat model and what TesseraID is not . . . 6
1.5 The cost: bytes . . . 7

2 TesseraID Specification **7**
2.1 Wire format . . . 7
2.2 Standard variant generation (variant `0x01`) . . . 8
2.3 Optional defensive helper: `validate_min_timestamp` . . . 9
2.4 CSPRNG requirements . . . 9
2.5 HLC variant generation (variant `0x02`) . . . 9
2.6 Text encodings . . . 11
2.7 TesseraHash — sibling content-identifier format (variant `0x03`) . . . 12

3 Why Each Choice **14**
3.1 Why 256 random bits? . . . 14
3.2 Why a 48-bit millisecond timestamp? . . . 14
3.3 Why a single-byte variant byte rather than two formats? . . . 14
3.4 Why HLC as a co-equal variant, not an optional extension? . . . 15
3.5 Why both Base64URL and Crockford Base32? . . . 15

4 When to Use What **16**
4.1 When TesseraID is the right format . . . 16
4.2 Choosing between Standard and HLC . . . 16
4.3 When to reach for something else . . . 17
4.4 Hybrid deployments . . . 18

5 How to Implement **18**
5.1 The CSPRNG is the bottleneck . . . 18
5.2 Clock clamping . . . 19
5.3 Counter exhaustion . . . 19
5.4 Thread safety . . . 19
5.5 Encoding implementation . . . 20
5.6 Decoder validation . . . 20

6 Security Analysis **20**
6.1 Threat model . . . 20
6.2 Quantum-relevant attacks . . . 21
6.3 Birthday-bound math at scale . . . 21
6.4 Side channels . . . 22

6.5 Random source quality 22

7 Distributed Systems **22**
7.1 Clock skew under the Standard variant 23
7.2 HLC: causal ordering across nodes 23
7.3 When HLC and Standard TesseraIDs mix 23
7.4 Coordination and uniqueness 24
7.5 Clock skew detection and alarming 24
7.6 Snapshots and consistent cuts 24
7.7 Cross-region replication 24

8 Comparison with Existing Formats **25**
8.1 vs UUIDv4 (Leach et al., 2005) 25
8.2 vs UUIDv7 (Davis et al., 2024) — the closest competitor, in detail 25
8.3 vs ULID (Feerasta et al., 2016) 27
8.4 vs KSUID (Segment, Inc., 2017) 28
8.5 vs Snowflake (Twitter Engineering, 2010) 28
8.6 vs TSID (Mihalcea, 2020) 28
8.7 vs NanoID (Sitnik, 2017) 29
8.8 Summary table 29

9 Reference Implementations and Benchmarks **29**
9.1 Implementation summaries 30
9.2 Cross-implementation benchmark results 32
9.3 Observations 32

10 Migration Guide **33**
10.1 The five phases 33
10.2 Pitfalls 34
10.3 Cross-region replication during migration 34
10.4 Legacy systems with no clean migration path 34

11 AI Infrastructure and Million-Node Regime **34**
11.1 The shape of the regime 34
11.2 UUIDv7's collision math at 10^{12} identifiers 35
11.3 UUIDv7's intra-millisecond ordering at heterogeneous scale 35
11.4 The HLC variant for cross-region causality 36
11.5 Storage cost at this scale 36
11.6 CPU cost at this scale 37
11.7 Compliance and audit at long horizons 37
11.8 Long-horizon archival 37
11.9 Summary 37

12 Future Work **38**

A Test Vectors **39**

B Quick Reference Card **40**

C Example TesseraIDs (Same Millisecond) **40**

D Glossary of Terms **41**

E The tessera Monorepo Context **42**

F Author and Document Provenance **43**

TL;DR

TesseraID is a 41-byte, lexicographically-sortable identifier designed to be useful for the next thirty years of distributed systems. It pairs a 48-bit millisecond timestamp with 256 bits of cryptographically-strong randomness — the smallest random field that retains 128 bits of effective security under Grover's quantum search algorithm (Grover, 1996). A version byte and a 16-bit per-millisecond counter sit between them. Two variants of the format share the same wire layout: **Standard** (variant `0x01`) for centralized generation against a wall clock, and **Hybrid Logical Clock** (variant `0x02`) for distributed systems where causal ordering across nodes matters (Kulkarni et al., 2014).

TesseraID encodes to **55 characters** of canonical Base64URL (Josefsson, 2006) or **66 characters** of human-typable Crockford Base32 (Crockford, 2002). Both encodings round-trip to identical 41-byte binary values, and binary sort and Crockford ASCII sort both reflect generation time. (Canonical Base64URL preserves byte order only when compared as bytes — its alphabet ordering does not match ASCII codepoint order, so consumers that need a textual column to sort by time should use Crockford or sort the underlying bytes.) The 55-character Base64URL form fits comfortably in URL paths, JSON, headers, and database primary-key columns; the Crockford form is meant for human transcription, log lines, CLI tools, and any column where lexicographic text sort must reflect generation time.

The format generates at **millions of IDs per second per thread** in the native reference implementations; the bottleneck across every implementation is the OS CSPRNG, not TesseraID's own logic. Current measured per-language rates, the measurement environment, and the procedure are maintained in `tessera-id/benchmarks/` (see `methodology.md`); this document deliberately embeds no point-in-time throughput numbers. Time-sortedness across consecutive IDs is 100% by construction, matching ULID (Feerasta et al., 2016) and beating UUIDv4 (Leach et al., 2005), UUIDv7 (Davis et al., 2024), and KSUID (Segment, Inc., 2017).

This document is the canonical reference for TesseraID v1: the wire format, the rationale for every numeric choice, when to use each variant, how to implement generators correctly, the security model, the distributed-systems model, detailed comparisons against UUIDv4, UUIDv7, ULID, KSUID, and Snowflake, and **eight reference implementations** (Python, Go, Rust, TypeScript, C, C++, Java, and a CPython extension) with per-language benchmark harnesses whose captured outputs live in `tessera-id/benchmarks/`.

The million-node regime

At the scales now emerging in frontier-AI training clusters and globally-distributed inference fleets, TesseraID is the only published format whose collision math, coordination model, causal-ordering semantics, and post-quantum margins all hold simultaneously. UUIDv4 fails on collision math (the 122-bit random field is undersized for trillions of identifiers per training run). UUIDv7 fails on intra-millisecond sort guarantees (RFC 9562 §6.2 permits implementations that randomize within a ms) and on causal ordering across geographically-distributed nodes. ULID and KSUID fail on entropy. Snowflake (Twitter Engineering, 2010) fails on coordination requirements. Part 11 makes this case in detail.

1 Why a New Identifier

Every identifier format reflects the constraints and assumptions of the moment it was designed. The decisions baked into UUIDv4 (Leach et al., 2005) in 2005 — 128 bits total, 122 bits of entropy, no time component, no ordering — made sense when distributed databases were rare, quantum computers were a footnote, and "unique" meant "unique in this rack." Twenty years later, the constraints have shifted enough that even the carefully-chosen successors to UUIDv4 (UUIDv7 (Davis et al., 2024), ULID (Feerasta et al., 2016), KSUID (Segment, Inc., 2017)) leave gaps. TesseraID is an attempt to fill the remaining gaps in a single, coherent format — not by adding features, but by making slightly different choices on three numbers: the size of the random field, the granularity of the timestamp, and the semantics of the version byte.

1.1 Quantum search has changed the entropy budget

Grover's algorithm (Grover, 1996) gives a quantum computer a quadratic speedup over classical search: finding a single matching value among 2^n candidates takes approximately $2^{n/2}$ quantum operations. For an identifier whose security model rests on the difficulty of guessing a specific value (a *targeted second preimage*), that means an n-bit random field gives only $n/2$ bits of effective post-quantum security. UUIDv4's 122 bits give 61. UUIDv7's 74 give 37. ULID's 80 give 40. KSUID's 128 give 64. TesseraID's 256 give 128 — the level NIST has designated as adequate for symmetric primitives through 2030 and beyond (Barker, 2020), and the level ML-DSA-44 (NIST, 2024b) and ML-KEM-512 (NIST, 2024a) are calibrated to. Choosing less for a new identifier means accepting that the identifier becomes the weakest cryptographic component of any system that combines it with AES-128 (NIST, 2023a) or stronger. Part 6 works through the math (Grover, BHT (Brassard et al., 1998), the classical and quantum birthday bounds) in detail.

1.2 Time-sortability is a feature, not a side effect

Random identifiers like UUIDv4 are catastrophic for B-tree indexes. Each new insert lands at a random point in the tree, causing scattered page writes, poor cache behavior, and eventually fragmentation that degrades read performance. The fix is well-understood: prefix the identifier with a timestamp so consecutive inserts land near each other. ULID, KSUID, and UUIDv7 all do this. TesseraID does too.

But there's a subtlety. ULID and KSUID expose lexicographic byte ordering as a first-class property: sorting their bytes (or, in ULID's case, their Crockford-encoded strings) yields time-ordering. UUIDv7's RFC permits implementations that randomize within a millisecond in ways that break this property; the spec only guarantees ordering *between* milliseconds, not *within* them. TesseraID guarantees both. Within a single millisecond, a per-generator counter makes consecutive IDs strictly increasing; across milliseconds, the timestamp dominates. The result is 100% time-sortedness across consecutive IDs from a single generator (binary order, and ASCII order in the Crockford encoding), measured against 10,000 consecutive IDs in the benchmark suite and against 100,000 unique IDs in the uniqueness test.

1.3 Distributed systems need first-class causal ordering

The Standard variant uses a wall-clock timestamp. That works fine when a single machine is producing IDs — the local clock is the source of truth and consumers that care about ordering get what they expect. It works less well when many machines are producing IDs and clocks disagree by tens of milliseconds.

The HLC variant solves this. A Hybrid Logical Clock (Kulkarni et al., 2014) combines physical time with a logical counter. An HLC reading is always at least the maximum of the local wall clock and any HLC value the node has observed from a peer; the counter increments whenever logical time fails to advance. The result is a clock that stays close to physical time, always moves forward, and preserves causal ordering across nodes that exchange HLC values in their messages.

TesseraID's HLC variant exposes that machinery as a first-class identifier shape. The wire format is identical to the Standard variant; the only difference is the variant byte (`0x02` instead of `0x01`) and the semantic interpretation of the timestamp (logical, not physical, with a 60-second drift bound). A consumer that doesn't care about variant semantics can sort TesseraIDs as opaque bytes and get correct ordering across both variants in the same stream.

1.4 Threat model and what TesseraID is not

The single sentence: **TesseraID is an identifier, not a cryptographic hash, not a MAC, and not a content fingerprint.** The post-quantum security claim is narrow, and conflating it with hash-function properties leads to misuse. Three points make the boundary explicit, with the math in §6 as the backing.

Targeted second-preimage is the right threat. An attacker who knows a specific target TesseraID and wants to produce a different generator output equal to it must brute-force the 256-bit random tail. Under Grover (Grover, 1996) that costs $\Theta(2^{128})$ quantum operations (see §6 lines for the exact bound). This is the *only* security claim TesseraID makes for its random field, and it is the one that matters for identifier use cases such as opaque references, audit-log row keys, and capability tokens.

Collision resistance is a statistical, not cryptographic, property. Two TesseraIDs colliding (any two, not a specific one) is the BHT (Brassard et al., 1998) regime: $\Theta(2^{n/3}) = 2^{85}$ for $n = 256$. §6 works through both bounds together. For UUIDv7 the equivalent number is 2^{25}; for ULID, 2^{27}; for KSUID, 2^{43}. TesseraID's 2^{85} is large enough that a deployment producing 10^9 IDs/s would run for 10^{18} years before the expected collision count reached 1. But it is not the second-preimage number, and it is not what the headline claim is about.

Do not use TesseraID where you would use a hash. TesseraID is not a SHA-2, SHA-3, BLAKE3, or KMAC substitute. The random tail has no relation to any input the generator has seen; TesseraID cannot be used to fingerprint content, prove possession of a preimage, derive a key, or authenticate a message. The 128-bit number applies only to the brute-force-the-random-tail game, not to any of the cryptographic-hash games.

If a system needs second-preimage resistance against an adversary who controls the input, use a hash function. If it needs message authentication, use a MAC. If it needs an identifier whose post-quantum brute-force cost is at parity with AES-128 (NIST, 2023a), TesseraID is the right tool.

The bound is the bound; treating it as a stronger one is a footgun.

1.5 The cost: bytes


TesseraID's distinguishing properties are the 256-bit random field — the only format with comfortable post-quantum margins — and the dual-variant design that makes the same wire format usable for both centralized and distributed generation. The cost is byte-count: at 41 bytes binary or 55 characters Base64URL, TesseraID is roughly 2.5× the size of UUIDv4. Part 8 works through the format-by-format tradeoffs; Part 4 maps them onto specific use cases.

2 TesseraID Specification

This part is the normative reference. Implementations that conform to this specification produce and consume identifiers with the byte layout, semantics, and encoding rules described below. Where this document uses RFC 2119 keywords (MUST, SHOULD, MAY), they carry the standard meanings.

2.1 Wire format

A TesseraID is exactly 41 bytes (328 bits), structured as four contiguous fields:



Field semantics:

Timestamp (offsets 0–5). Big-endian unsigned 48-bit integer, milliseconds since the Unix epoch (1970-01-01T00:00:00Z). The 48-bit field provides 2^{48} ms ≈ 8,919 years of forward range, sufficient through the year 10889.

Variant (offset 6). Single byte.

- `0x01` = Standard (wall-clock).
- `0x02` = HLC (Hybrid Logical Clock).
- `0x03` = TesseraHash (sibling content-identifier format, §2.7). Allocated 2026 from the reserved-future range; TesseraID decoders MUST reject `0x03` (a 0x03 buffer is not a TesseraID).
- `0x00` and `0xFF` are **permanently reserved**: they MUST be rejected by conformant decoders and MUST NOT be assigned in any future revision of this specification. These two values are reserved defensively so that TesseraID buffers cannot be confused with zero-filled or all-ones uninitialized memory.
- `0x04` = TesseraSeal (sibling encryption-envelope format; allocated 2026 from the reserved-future range). TesseraID decoders MUST reject `0x04` with an unknown-variant error: a

`0x04` buffer is a TesseraSeal envelope, not a TesseraID.

- `0x05`–`0xFE` are reserved for future variants. Conformant decoders MUST reject them with an unknown-variant error until they are assigned by a future revision of this specification.

Counter (offsets 7–8). Big-endian unsigned 16-bit integer. For Standard, the counter is incremented within a single millisecond by a small random step (1–16); for HLC, it is the HLC logical counter.

Random tail (offsets 9–40). 32 bytes from a cryptographically-strong random source. The full 256 bits provide 2^{128} effective post-quantum security against second-preimage attacks.

2.2 Standard variant generation (variant `0x01`)

The Standard generation algorithm assumes a wall-clock time source that returns milliseconds since the Unix epoch. It maintains two pieces of per-generator state: `last_ts` (initially 0) and `counter` (initially 0).

```
procedure new_standard():
    rnd[0..32]  <-  csprng()            # 33 bytes total
    ts          <-  now_ms()
    if ts < last_ts:                    # clamp on regression
        ts  <-  last_ts
    if ts == last_ts:                   # same ms as previous ID
        step    <-  1 + (rnd[0] & 0x0F)     # random step in [1, 16]
        next    <-  counter + step
        if next > 0xFFFF:               # counter exhausted, spin
            while now_ms() <= last_ts: pass
            ts       <-  now_ms()
            counter  <-  rnd[0]         # reseed at small value
        else:
            counter  <-  next
    else:                               # new ms
        counter  <-  rnd[0]             # randomized initial offset
    last_ts <-  ts
    return  be48(ts) || 0x01 || be16(counter) || rnd[1..32]
```

Listing 1: Standard TesseraID generation

The random step (rather than a fixed +1 increment) is a deliberate choice. It provides modest unlinkability of consecutive IDs from a single generator while preserving strict monotonicity (the step is always at least 1, so consecutive IDs always increase).

Non-normative remark on the exhaustion spin: the spin condition `while now_ms() <= last_ts` is deliberately `<=`, not `==`. After a clock regression, `last_ts` may sit ahead of the wall clock; spinning until `now_ms()` strictly exceeds `last_ts` guarantees the post-spin timestamp is strictly greater than every previously emitted timestamp, preserving strict monotonicity even when the regression spans the exhaustion event. An implementation that spins only while `now_ms() == last_ts` exits the loop immediately during a regression and can emit an identifier that sorts before its predecessor.

2.3 Optional defensive helper: `validate_min_timestamp`

Implementations SHOULD expose a non-normative helper that returns true iff a decoded TesseraID's timestamp is at or after a project epoch `MIN_TIMESTAMP_MS`. The reference value is `1,700,000,000,000` ms (≈ 2023-11-14), chosen as the earliest plausible timestamp any TesseraID-aware deployment will ever emit.

This helper is **not part of the wire contract**. Standard decoders MUST continue to accept all timestamps in $[0, 2^{48} - 1]$ as required by the field semantics in §1. The helper exists for callers who want to cheaply reject obvious mis-parses — a 41-byte buffer that decodes to timestamp 0 has either come from zeroed memory, a wrong-offset read, or a buggy producer. Rejecting such inputs at boundary entry points is a defense-in-depth measure, not a conformance requirement.

2.4 CSPRNG requirements

The 256-bit random tail is the only field carrying the post-quantum security claim. Conformant implementations MUST therefore use an operating-system-provided cryptographically-strong pseudorandom number generator. The following normative rules apply:

Source. Generators MUST draw the random tail from one of: `getrandom(2)` on Linux 3.17+, `arc4random_buf` or `getentropy(3)` on the BSDs and macOS, `BCryptGenRandom` on Windows, the language-level wrappers around these (`os.urandom`, `crypto/rand.Read`, `getrandom::fill`, `crypto.getRandomValues`, `SecureRandom`), or — as a last-resort portable fallback — `/dev/urandom`. Generators MUST NOT use a non-cryptographic userspace PRNG (Mersenne Twister, Xoshiro, `rand`, etc.) under any circumstance.

Failure. If the CSPRNG returns an error or refuses to produce 32 bytes, the generator MUST surface the error to the caller and MUST NOT emit a TesseraID. There is no fallback path.

Partial reads. Partial reads (an underlying `read()` or `getrandom()` returning fewer than 32 bytes) MUST be retried until either 32 bytes are obtained or an unrecoverable error is returned.

Independence. Each TesseraID's random tail MUST be drawn independently. A generator MAY combine the 32-byte tail with a small additional read (1–2 bytes) used for the counter step in the same syscall as an optimization; this is unrelated to the cryptographic claim and does not weaken it because the OS CSPRNG output is uniform.

A test vector cannot directly verify entropy quality, but conformance reviewers SHOULD spot-check each implementation's call site against this list. The current implementations call: `os.urandom` (Python), `getrandom`/`getentropy` (C/C++), `crypto/rand.Read` (Go), `getrandom::fill` (Rust), `crypto.getRandomValues`/`randomFillSync` (TypeScript), `SecureRandom` (Java), and the underlying C reference (CPython extension).

2.5 HLC variant generation (variant `0x02`)

The HLC generator maintains `l` (logical time, ms-grained) and `c` (logical counter). On every generation, it consults both the local physical clock and any peer HLC observation.

The contract uses two thresholds, distinct in purpose:

Hard outer bound $\Delta_{\max} = 60{,}000$ ms (normative). Conformant generators MUST reject ob-

servations whose logical time exceeds the local physical clock by more than $\Delta_{\max}$. The comparison is *strict*: an observation MUST be rejected iff $l_{msg} - pt > 60{,}000$ ms — an observation exactly 60,000 ms ahead MUST be accepted, and one 60,001 ms ahead MUST be rejected. A rejected observation MUST leave the generator's (l, c) state unchanged. These boundary semantics are pinned by the `hlc_drift` conformance vectors (TESS-00009). Implementations MUST expose this constant under the name `HLC_MAX_DRIFT_MS` (or the language's idiomatic equivalent). $\Delta_{\max}$ is part of the wire contract: a 60-second peer-ahead-of-local observation that one implementation accepts and another rejects is an interoperability bug.

Local tightening override (optional). $\Delta_{\max} = 60{,}000$ ms is the normative *maximum* and the default. Implementations MAY expose a per-generator override that only *tightens* the bound: a configured override MUST satisfy $1 \text{ ms} \leq \Delta < 60{,}000$ ms. Configuring a bound larger than $\Delta_{\max}$ MUST surface an error and produce no output (relaxing the bound defeats the monotonicity guarantee). Where the override API uses an integer field, the value 0 selects the normative default — matching the C reference's `max_drift_ms` semantics (TID-00020). Implementations that expose no override are conformant.

Soft alarm threshold Δ_{alarm} (configurable, default 1,000 ms). Implementations SHOULD emit a log, metric, or alarm when an observation exceeds Δ_{alarm}, even if it is still below $\Delta_{\max}$. The default of 1 second captures the operational reality that well-disciplined hosts (NTP, chrony, AWS Time Sync, GCP) maintain sub-100 ms drift; a peer 1 s ahead almost certainly indicates a clock-discipline or NTP-outage problem that an operator should know about, even though the wire format still accepts it. Δ_{alarm} is NOT part of the wire contract.

The rationale for $\Delta_{\max} = 60$ s: large enough to absorb a brief NTP outage, container time injection, or VM live-migration without breaking valid traffic; small enough that a maliciously advanced peer cannot stamp identifiers a year into the future. The HLC literature (Kulkarni et al. 2014, §3) explicitly leaves the bound to operators; the CockroachDB and kronos operational practice in production is approximately 500 ms to 1 s. We pick 60 s for the hard bound because the wire-format invariant should tolerate the worst plausible operational event without changing, and we pick 1 s as the default alarm because that's where well-run systems already live.

```
procedure new_hlc(observe = none):
    rnd[0..31] <- csprng()              # 32 bytes
    pt         <- now_ms()              # physical time
    l_old, c_old <- l, c
    if observe is not none:
        l_msg, c_msg <- observe
        if (l_msg > pt) and ((l_msg - pt) > MAX_DRIFT_MS):
            error  HLC_drift_exceeded
        l_new <- max(l_old, l_msg, pt)
        case:
            l_new == l_old == l_msg:  c_new <- max(c_old, c_msg) + 1
            l_new == l_old:           c_new <- c_old + 1
            l_new == l_msg:           c_new <- c_msg + 1
            default:                  c_new <- 0
    else:
        l_new <- max(l_old, pt)
        c_new <- (c_old + 1) when l_new == l_old, else 0
    if c_new > 0xFFFF: l_new += 1; c_new <- 0
    l, c <- l_new, c_new
```

```
20      return  be48(l_new) || 0x02 || be16(c_new) || rnd
```

Listing 2: HLC TesseraID generation (with optional peer observation)

2.6 Text encodings

TesseraID defines two text encodings. Both round-trip cleanly to the same 41-byte binary form and neither uses padding. They differ in their behavior under string sort: Crockford Base32 (Crockford, 2002) is ASCII-sort-preserving (sorting the strings as text gives generation-time order), while canonical Base64URL is sort-preserving only when its bytes are compared, not when its text is compared as ASCII. The reason is that the RFC 4648 §5 alphabet (Josefsson, 2006) (`A-Z`, `a-z`, `0-9`, `-`, `_`) maps alphabet values 0..63 to ASCII codepoints that are not monotonic — `A-Z` (65..90), `a-z` (97..122), `0-9` (48..57), `-` (45), `_` (95) interleave, so a string-level ASCII sort produces an order different from the underlying byte order. Crockford's alphabet (`0-9` then `A-Z` minus `I/L/O/U`) is monotonic in ASCII and so its strings sort identically to their decoded bytes. Choose accordingly: machine-to-machine paths use Base64URL and sort the bytes (or simply preserve insertion order); human-facing or text-sorted columns use Crockford.

2.6.1 Canonical: Base64URL (55 characters)

RFC 4648 Section 5 ("Base 64 Encoding with URL and Filename Safe Alphabet"), no padding. Encoding 41 bytes produces $\lceil 41 \cdot 8/6 \rceil = 55$ characters; the final character carries 4 bits of value plus 2 bits of zero padding. The alphabet is `A-Z`, `a-z`, `0-9`, `-`, `_`. Decoders MUST reject inputs whose final character carries non-zero padding bits.

2.6.2 Human-typable: Crockford Base32 (66 characters)

Crockford's alphabet (`0123456789ABCDEFGHJKMNPQRSTVWXYZ`) and its case-insensitive decoding (with the I/L→1 and O→0 confusables canonicalized) make this encoding suitable for human transcription. Encoding 41 bytes produces $\lceil 41 \cdot 8/5 \rceil = 66$ characters; the final character carries 3 bits of value plus 2 bits of zero padding.

The Crockford form is intended for use cases where humans handle the identifier directly: pasted into chat messages, read aloud over phones, written on paper, or appearing in CLI tools where mixed-case is hostile. The Base64URL form is intended for everything else.

2.6.3 Decode-time variant validation (both encodings)

Both text decoders — the 55-character Base64URL decoder and the 66-character Crockford Base32 decoder — MUST validate the variant byte of the decoded 41-byte value and MUST reject any value other than `0x01` or `0x02` with the unknown-variant error *at decode time*. Variant validation is part of decode, not a separate post-decode step: a conformant text decoder never returns a 41-byte buffer whose variant byte it does not own.

Non-normative remark: combined with the padding-bit guards above, decode-time variant validation makes each text decoder a bijection onto the set of valid TesseraIDs — every accepted string maps to exactly one valid TesseraID, and every valid TesseraID maps to exactly one accepted canonical string.

2.7 TesseraHash — sibling content-identifier format (variant `0x03`)

TesseraHash is a **sibling format** to TesseraID, sharing TesseraID's 9-byte header layout but extending the wire size and replacing the random tail with a deterministic content digest. TesseraHash is *additive*: it does not change TesseraID, and the two formats are guaranteed to not cross-decode.

This subsection is a non-normative summary for TesseraID implementers. The normative source for the TesseraHash wire format, its encodings, and its security claims is the TesseraHash whitepaper (LaTeX sources under `tessera-hash/latex/`); where this summary and that paper disagree, the TesseraHash paper wins. The only normative statement TesseraID makes about TesseraHash is the cross-format rejection contract in §2.1 and below.

2.7.1 Wire layout (73 bytes)

```
0        6       7        9                                                 73
+-------+------+-------+-------------------------------------------------+
|  TS    | 0x03 |  CTR  |              SHAKE256(content, 64B)             |
| 48 b   |  8 b | 16 b  |                       512 b                     |
+-------+------+-------+-------------------------------------------------+
```

Timestamp (offsets 0–5). Big-endian unsigned 48-bit ms since Unix epoch. Provenance metadata: *when* this identifier was assigned. NOT a security claim.

Variant (offset 6). Fixed at `0x03`, allocated from TesseraID's reserved-future range (§2.1).

Counter (offsets 7–8). Big-endian unsigned 16-bit. Same-ms disambiguator within a generator.

Tail (offsets 9–72). 64 bytes (512 bits) of `SHAKE256(content)` (National Institute of Standards and Technology, 2015), output truncated to 64 bytes. The tail is *deterministic from the content alone*: two callers that TesseraHash the same content produce the same tail, regardless of generator or timestamp.

2.7.2 Security claim

The 512-bit tail gives:

- Second-preimage resistance of $\min(2^d, 2^{256})$ per FIPS 202 (National Institute of Standards and Technology, 2015) — 2^{256} classical at $d = 512$ output bits (the SHAKE-256 capacity cap, not the output width, is the binding term). The generic quantum (Grover (Grover, 1996)) bound on the same search is also 2^{256}, so the figure holds post-quantum.
- 2^{256} classical collision resistance (birthday).
- 2^{170} post-quantum collision resistance (BHT (Brassard et al., 1998)). This is the surface that matters for content addressing across multi-decade archival horizons.

What TesseraHash is NOT: not a hash function (use SHAKE-256 directly), not a MAC (use KMAC256), not a signature (use ML-DSA / SLH-DSA). TesseraHash is a content identifier with provenance metadata; the timestamp carries no security claim. See §1.4 for the framing TesseraID established; the same boundary applies, sharpened: the second-preimage figure for TesseraHash is the brute-force-the-content-via-SHAKE game, which is what every content-addressed format gets.

2.7.3 Cross-format non-overlap

TesseraID and TesseraHash MUST NOT cross-decode:

- TesseraID is exactly 41 bytes with variant `0x01` or `0x02`. Conformant TesseraID decoders reject 73-byte buffers (length error) and reject the `0x03` variant byte (unknown-variant error, codified by the §2.1 reservation).
- TesseraHash is exactly 73 bytes with variant `0x03`. Conformant TesseraHash decoders reject 41-byte buffers (length error) and reject any variant other than `0x03`.

An application that may receive either format dispatches at the application boundary:

```
if len(buf) == 73 and buf[6] == 0x03:  TesseraHash.decode(buf)
elif len(buf) == 41 and buf[6] in {0x01, 0x02}:  TesseraID.decode(buf)
else: error
```

2.7.4 Encodings

TesseraHash uses the same Base64URL and Crockford Base32 alphabets as TesseraID, sized for the larger payload:

- **Base64URL: 98 characters.** $\lceil 73 \cdot 8/6 \rceil = 98$. 584 input bits fill 97 full characters plus 2 bits, so the final character carries 2 bits of value plus 4 bits of zero padding (it is always one of `A`, `Q`, `g`, `w`). Decoders MUST reject inputs whose final character carries non-zero padding bits.
- **Crockford Base32: 117 characters.** $\lceil 73 \cdot 8/5 \rceil = 117$. 584 bits of input produce 585 output bits with 1 zero pad bit at the bottom of the final character. Case-insensitive decoding with the same I/L→1 and O→0 confusables as TesseraID.

2.7.5 Verify

A conformant TesseraHash implementation MUST expose a `verify(raw, content)` predicate that returns true iff `raw` is a 73-byte TesseraHash with variant `0x03` *and* its tail equals `SHAKE256(content)` truncated to 64 bytes. The tail comparison MUST be constant-time on the 64-byte input to avoid timing oracles. Malformed buffers return false rather than raising.

2.7.6 Generator semantics

The TesseraHash generator maintains `last_ts` and `counter`. On every call:

1. Compute `tail = SHAKE256(content, 64)`.
2. Read the wall clock; clamp on regression (as for TesseraID Standard).
3. If the new timestamp equals `last_ts`, increment the counter (spin to next ms on overflow).
4. Otherwise reset the counter to 0.

Consecutive calls from a single generator produce strictly monotonic identifiers (binary order, and ASCII order under Crockford). Two callers that TesseraHash the same content at different times produce identifiers that differ only in `(ts, counter)` and share the 64-byte tail.

3 Why Each Choice

This part walks through every numeric and structural choice in the TesseraID specification and explains why the choice was made. The intent is to make the reasoning transparent enough that a reader can disagree on first principles rather than wondering whether a number came out of a hat.

3.1 Why 256 random bits?

The 256-bit random tail is the largest single design choice in TesseraID. It is the reason TesseraID is 41 bytes rather than 16, 20, or 24. The alternative — 128 random bits, fitting comfortably inside a 24-byte identifier — gives 64-bit post-quantum security against birthday-bound collisions, which is plenty for almost every classical use case but uncomfortable as a long-term margin in the regime where quantum search is a credible threat. The 256-bit choice is calibrated to give 128 bits of effective post-quantum security against a targeted second-preimage attack, matching the level NIST has designated as adequate for symmetric primitives through 2030 and beyond. Part 6 carries the full Grover/BHT/birthday-bound derivation.

The cost is sixteen extra bytes per identifier — the same level the cryptographic community has converged on for symmetric primitives like AES-256 (NIST, 2023a) and SHA-256-based (NIST, 2015) hashes. In an era where average HTTP responses are kilobytes and average database row sizes are hundreds of bytes, sixteen bytes is unremarkable.

3.2 Why a 48-bit millisecond timestamp?

Forty-eight bits of milliseconds gives roughly 8,919 years of forward range. We chose this over 32 bits (which gives 49 days from epoch and would have wrapped already) and 64 bits (which gives 584 million years and would be wasteful). Forty-eight bits is the same width Snowflake (Twitter Engineering, 2010) uses for its timestamp, the same width UUIDv7 (Davis et al., 2024) uses, and the same width ULID (Feerasta et al., 2016) uses. The cross-format consistency is convenient.

Millisecond granularity is a compromise. Microseconds (or nanoseconds) would let two consecutive IDs from a single generator fall into different timestamp buckets without needing a counter, but cross-machine clock skew is typically larger than a microsecond, so the apparent gain is illusory. Seconds would mean every server in a cluster could collide with every other server every second, and the counter would have to be much larger to recover order. Milliseconds split the difference: per-millisecond collisions across nodes are common but recoverable from the random tail; per-millisecond collisions within a single node are eliminated by the counter.

If you genuinely need finer ordering across nodes — closer to single-microsecond — the right tool is the HLC variant, which captures causal ordering through message exchange rather than relying on synchronized clocks. The Standard variant accepts that wall-clock granularity below a millisecond is a fiction and stops there.

3.3 Why a single-byte variant byte rather than two formats?

Two design choices were considered for the relationship between Standard and HLC TesseraIDs: separate identifier formats with separate names, or a single format with a discriminator byte. The variant-byte approach won on three grounds.

Wire-format compatibility. Both variants are 41 bytes, both encode and decode identically, and both are lexicographically sortable. A consumer that has no opinion about whether an identifier was generated against a wall clock or an HLC can treat all TesseraIDs as opaque sortable bytes; only consumers that care about the timestamp's semantics need to read the variant byte. This minimizes the surface area producers and consumers must agree on.

Storage compatibility. A single column type (`CHAR(55)`, `BYTEA(41)`, or whatever) holds both variants. Mixing variants in the same table is permitted and the rows still sort correctly across variants — though we caution users against doing this in practice (see Part 7 for why mixing HLC and Standard TesseraIDs in the same ordered stream introduces some subtle gotchas).

Future evolution. The variant byte gives us a 254-value space for additional generation strategies without changing the wire format. A future signed variant (Part 12) would be a straightforward `0x03`, with the identifier itself unchanged in length and shape.

The cost is one byte per identifier — a price we are happy to pay for the option value of future evolution and the immediate value of letting Standard and HLC coexist in a single deployable format.

3.4 Why HLC as a co-equal variant, not an optional extension?

Hybrid Logical Clocks (Kulkarni et al., 2014) are not a new idea, but they are conspicuously absent from existing identifier formats. ULID, KSUID, and UUIDv7 all use wall-clock timestamps with no logical-clock layer. A few production systems (CockroachDB (Cockroach Labs), MongoDB cluster time, FoundationDB) have built HLCs internally but not exposed them in their identifier formats.

TesseraID elevates HLC to a co-equal variant rather than an extension because we believe distributed-systems use cases are common enough — and HLC's semantic value clear enough — that the format should make HLC a first-class option. The Standard variant remains the default for the 95% of cases where wall-clock semantics are what users actually want; the HLC variant is there for the 5% where causal ordering across nodes is a real requirement.

A subtle but important property of this design: a system can start with Standard TesseraIDs and upgrade individual generators or services to HLC without rewriting consumers. The wire format is unchanged, the encoding is unchanged, and lexicographic ordering still works. Consumers that want to take advantage of HLC's causal ordering can read the variant byte; consumers that don't can ignore it.

3.5 Why both Base64URL and Crockford Base32?

Crockford Base32 exists for two related use cases. The first is human transcription. The Base64URL alphabet contains characters that are visually ambiguous in many fonts (lowercase `l` vs uppercase `I`, lowercase `o` vs digit `0`) and is case-sensitive. A user who reads a TesseraID from a sticker, a paper printout, or a printed receipt and types it back in is significantly more error-prone with Base64URL than with Crockford Base32. Crockford's alphabet drops the ambiguous letters entirely and treats case as insignificant; the I/L/O/0 confusables are explicitly canonicalized by the decoder.

The second use case is text-level lexicographic sort. Crockford's alphabet (`0-9` then `A-Z` minus `I/L/O/U`) is monotonic in ASCII, so sorting Crockford strings as text yields the same order as

sorting their decoded bytes. The Base64URL alphabet does not have that property, so a database column whose contents are sorted as text rather than as bytes will not produce time-ordered results from canonical Base64URL strings.

The cost of Crockford is 11 extra characters per identifier (66 vs 55), which we consider acceptable for the use cases that need either property.

Implementations SHOULD support both. Systems that never expose identifiers to humans MAY choose to skip the Crockford encoder; systems that do expose identifiers to humans SHOULD prefer Crockford for those interfaces while continuing to use Base64URL for machine-to-machine transport.

4 When to Use What

This part is the practical decision guide. We work through the question "should I use TesseraID, and if so, which variant?" in three layers: when TesseraID is the right format at all, when to choose Standard vs HLC, and when to reach for something else.

4.1 When TesseraID is the right format

Use TesseraID when one or more of the following apply:

- **Long horizon.** The identifier may need to remain unforgeable for ten years or longer, in a world where cryptographically-relevant quantum computers may exist by 2045–2050. This includes audit logs, financial records, training-corpus records, archival keys, and compliance artifacts.
- **Distributed-systems semantics.** Multiple nodes generate identifiers and the order of events across nodes matters for correctness. This is the HLC variant's home turf.
- **Heterogeneous implementations.** A deployment spans multiple languages or frameworks, and you need a guarantee that all of them produce sortable identifiers regardless of library choice. UUIDv7's optional intra-millisecond ordering breaks this; TesseraID's mandatory counter does not.
- **Large scale.** Identifier streams reach 10^9 IDs/sec or beyond, where birthday-bound math on 80- or 128-bit fields starts to matter even classically.

Don't use TesseraID when bytes are at an absolute premium. The 41-byte size is the cost of post-quantum margins; if your use case fits comfortably inside 16 or 20 bytes (because identifier counts are modest, security horizons are short, and storage cost dominates) then UUIDv7 or ULID is fine.

4.2 Choosing between Standard and HLC

Choose Standard when you have a single source of truth for time, or many sources whose clocks you trust to within a millisecond or two, and you don't need to reconstruct causal order across nodes from the identifier itself. The vast majority of single-database, single-tenant systems fall here. So do most multi-tenant SaaS applications: each tenant's events are conceptually independent, so cross-node ordering doesn't matter.

Choose HLC when you have a real causality requirement. Specifically: your system has multiple nodes that exchange messages, the order in which one node's events were observed by another node matters for correctness, and you are willing to plumb HLC observation through your message-passing layer (every message carries the sender's HLC, every receiver observes that HLC before generating its next ID). If any of these is missing, you don't get HLC's value, and you pay HLC's costs (mutex contention, drift bounds, harder debugging) for nothing.

Concrete examples where HLC earns its keep:

- **Distributed event logs** that span multiple regions and must be merged into a globally-sortable stream after the fact. The HLC ensures that events causally-ordered by message exchange end up in the right relative position even if their wall clocks disagreed at generation time.
- **CRDTs and version vectors.** HLC is the standard tool for ordering concurrent updates in a way that preserves causality. CRDTs that use HLC as their version vector get correct merge semantics for free.
- **Distributed snapshots.** Algorithms like Chandy–Lamport (Chandy and Lamport, 1985) need a way to determine which events happened before a snapshot cut; HLC provides exactly that.
- **Multi-region replication.** If a row is written in region A, replicated to region B, and modified in region B, the HLC variant of the new identifier in B reflects the causal dependency on A's write even if B's wall clock was behind.

In all of these cases, the HLC variant's causal-ordering property comes from a discipline the application must follow: every message must carry the sender's HLC observation, and every receiver must observe that HLC before generating its next ID. The format provides the substrate; the application provides the discipline.

4.3 When to reach for something else

Part 8 works through each of these in feature-level detail; the one-line verdicts:

- **UUIDv4** for throwaway operational IDs where you need broad library compatibility and don't care about ordering or post-quantum margins.
- **UUIDv7** for time-ordered UUIDs where being in RFC 9562 outweighs the 37-bit post-quantum margin, and where you control all generators (so they all use Method 3 of RFC 9562 §6.2 rather than the optional non-monotonic Method 2).
- **ULID** for 16-byte time-ordered identifiers with a community spec, broad ecosystem support, and a tolerable 40-bit post-quantum margin.
- **KSUID** for a 20-byte identifier with the largest possible random tail when second-granularity ordering is good enough.
- **Snowflake** when bytes are at an absolute premium, you can run a coordination service for unique machine IDs, and you accept that uniqueness depends on machine-ID assignment correctness rather than cryptographic randomness.

- **BIGSERIAL or auto-increment integers** when the data lives in exactly one database, you don't care about portability, and you want the smallest, fastest possible primary key.
- **A signed token format like PASETO (PASETO Working Group, 2018) or JWT (Jones et al., 2015)** when you need the identifier to be unforgeable by anyone but the issuer. TesseraID is not a signed token; anyone with a CSPRNG can produce a TesseraID that looks valid. TesseraIDs can be valuable as the *payload* inside such a signed token — the token authenticates, the TesseraID provides time-ordering and uniqueness.

4.4 Hybrid deployments

In practice, large systems often use multiple identifier formats simultaneously. A reasonable layering:

- **TesseraID** for archival, audit, and identifier-of-record use cases where post-quantum margins matter and ten-year defensibility is required.
- **UUIDv7** or **ULID** for operational identifiers (request IDs, span IDs, trace IDs) where 16 bytes is preferable and the identifier's lifetime is measured in seconds to days.
- **Snowflake** or **BIGSERIAL** for purely intra-database keys where the system controls all generators.

The formats coexist fine. TesseraID's encoded forms (Base64URL or Crockford) are visually distinct from UUIDs (no hyphens, no fixed length match) so distinguishing identifier types in mixed logs is straightforward.

5 How to Implement

This part walks through the practical decisions a generator implementation must make. The reference implementations in Part 9 embody these decisions; this section explains why each choice was made so a porter can confidently produce a conformant implementation in any language.

5.1 The CSPRNG is the bottleneck

Across every reference implementation, the dominant cost is the call into the operating system's cryptographically-strong PRNG. On Linux this is `getrandom(2)`; on macOS and the BSDs, `arc4random_buf(3)` or equivalent; on Windows, `BCryptGenRandom` or `RtlGenRandom`. The typical cost of one call — regardless of how few or how many bytes you fetch — is a few hundred nanoseconds, dominated by the syscall overhead and the kernel-side entropy mixing.

Two practical consequences:

Fetch in bulk. A naive implementation calls the CSPRNG twice per generation: once for the counter step byte and once for the 32-byte random tail. The reference implementations fetch all 33 bytes in a single call (`rnd[0]` for the counter step, `rnd[1..32]` for the tail), saving one syscall per generation. This is a measurable win.

Don't call the CSPRNG from a hot loop. If you need to generate many TesseraIDs in succession (e.g., backfilling a large table), batch the CSPRNG calls. The reference Python "fast" variant pre-fills a buffer and serves IDs out of it. The Rust and Go implementations don't bother

because their syscall overhead is already low.

5.2 Clock clamping

If the wall clock moves backward (NTP (Mills et al., 2010) correction, leap second, system clock adjustment), we use the last-known timestamp instead. This preserves local monotonicity at the cost of generating IDs whose timestamps are slightly ahead of the actual wall clock for as long as the regression lasts. This is the right tradeoff: a non-monotonic ID stream breaks B-tree indexes, replication ordering, and human intuition; a brief future-skew of a few hundred milliseconds is invisible to virtually all consumers.

A more sophisticated implementation could use a monotonic clock to detect regressions and recompute timestamps based on the monotonic offset. The reference implementations don't do this because the simple "clamp to last_ts" approach is correct, simple, and never visible in practice except during clock-correction events.

5.3 Counter exhaustion

The 16-bit counter holds 65,536 values. With a random step in $[1, 16]$, the average counter value after N generations within a millisecond is $N \cdot 8.5$. This means the counter exhausts at approximately 7,700 generations per millisecond per generator, i.e., about 7.7 million IDs per second per generator from a single thread.

In practice, no single-threaded generator hits this rate. The CSPRNG syscall caps single-threaded throughput well below 7M ops/sec in every environment measured to date (current per-language figures live in the `benchmarks/` directory). The exhaustion case is therefore largely theoretical for single-threaded use.

When it does happen — typically because the system clock is frozen or moving backward and the generator is being driven hard — the implementation spins in a tight loop waiting for `now_ms()` to advance, then reseeds the counter from `rnd[0]`. The spin is bounded because clocks are guaranteed to advance eventually; in practice the spin lasts at most one millisecond.

5.4 Thread safety

The Standard generator is lock-free per-instance: it maintains private `last_ts` and `counter` state and is safe to call from a single thread. For multi-threaded use, the reference implementations adopt one of two strategies:

- **One generator per thread** (Go's preferred approach): cheap, no contention, and the per-thread state is small enough that even thousands of threads fit comfortably in memory.
- **One global generator behind a mutex** (Python and TypeScript's default): simpler API at the cost of contention. The contention is usually tolerable because the critical section is microseconds.

The HLC generator must serialize access in all cases because the HLC algorithm reads-then-writes the `(l, c)` state. The reference C++ implementation guards the HLC state with a `std::mutex`; the Python implementation uses a `threading.Lock`; the Go implementation uses a `sync.Mutex`. The contention cost is similar to the Standard global-generator approach.

5.5 Encoding implementation

The Base64URL encoding is straightforward: standard 6-bits-per-char packing with the URL-safe alphabet, no padding. The trailing two bytes (offsets 39–40) become three characters carrying 16 bits of value plus 2 bits of zero padding, and decoders MUST verify that the padding bits are zero.

The Crockford Base32 encoding is similar but uses 5-bits-per-char packing and the Crockford alphabet (`0-9` then `A-Z` minus `I/L/O/U`). The decoder MUST be case-insensitive and MUST canonicalize the I/L/O/0 confusables: `I` and `L` (both cases) decode to value 1; `O` (both cases) decodes to value 0. The trailing byte (offset 40) becomes two characters carrying 8 bits of value plus 2 bits of zero padding.

Both encodings are pure functions of the input bytes; no random state, no time. They can be implemented in roughly 50 lines of code per direction in any modern language.

5.6 Decoder validation

A conformant decoder MUST:

- Reject inputs whose length is wrong (55 chars for Base64URL, 66 for Crockford, 41 bytes for raw binary).
- Reject inputs containing characters outside the alphabet.
- Reject inputs whose final character carries non-zero padding bits.
- For binary inputs, validate that the variant byte is `0x01` or `0x02`; reject other values.

A conformant decoder SHOULD also expose the variant byte, timestamp, and counter as accessors so that consumers can inspect the structured fields without re-parsing the entire identifier.

6 Security Analysis

This part lays out the threat model TesseraID is designed against, the cryptographic primitives that back it, and the attacks it does *not* defend against.

6.1 Threat model

TesseraID is designed to provide three security properties:

1. **Uniqueness.** The probability that two independently-generated TesseraIDs collide is vanishingly small under both classical and quantum adversaries.
2. **Unguessability.** An attacker who has seen many TesseraIDs cannot guess a TesseraID that has not yet been generated, or a TesseraID generated by a different system, with non-negligible probability.
3. **Tamper-evidence under outer authentication.** When a TesseraID is wrapped in a signed envelope (e.g., a JWT (Jones et al., 2015) or PASETO (PASETO Working Group, 2018) token), modifying the TesseraID invalidates the signature. TesseraID itself does not provide authentication; that is the envelope's job.

TesseraID is *not* designed to provide:

- **Authentication of the producer.** Anyone with a CSPRNG can forge a valid-looking TesseraID. Use a signed envelope (PASETO, JWT, custom MAC) if you need to verify the producer.
- **Integrity of the identifier itself.** TesseraID has no checksum, MAC, or hash. A bit-flipped TesseraID may decode to another valid TesseraID. If integrity matters, the TesseraID belongs inside a signed or HMAC'd (Krawczyk et al., 1997) container that protects it. In the tessera monorepo, two siblings address this gap natively: TesseraHash (variant `0x03`, 73-byte SHAKE-256-based content hash) provides a tamper-evident binding from the TesseraID to its referenced content, and TesseraSeal (variant `0x04`, ML-KEM-1024 encryption envelope) authenticates the TesseraID via its AEAD AD path when the TesseraID is passed as `associated_data` (the canonical "TesseraID-as-AD" pattern; see Appendix E).
- **Confidentiality of the identifier or its timestamp.** The 48-bit timestamp is plaintext. An attacker who sees a TesseraID learns approximately when it was generated. TesseraID has no built-in encryption. If timestamp confidentiality matters, wrap the entire identifier in TesseraSeal (or any AEAD); the TesseraID is then carried as the envelope's authenticated AD, not as cleartext.

6.2 Quantum-relevant attacks

6.2.1 Grover's algorithm (Grover, 1996)

Grover's algorithm searches an unstructured space of N elements in $O(\sqrt{N})$ operations. For an n-bit random field, this means finding a single specific value (a targeted second preimage) costs $2^{n/2}$ quantum operations instead of 2^n classical operations. For TesseraID's 256-bit random field, that's 2^{128} — astronomically out of reach for any plausible quantum computer.

6.2.2 Brassard–Høyer–Tapp (Brassard et al., 1998)

BHT extends Grover to find collisions: any two values in the space that share an output. For an n-bit space, BHT finds a collision in $O(2^{n/3})$ operations. For TesseraID's 256-bit field, that's 2^{85} — large but not as comfortable as the 128-bit second-preimage bound. The relevant point is that for *identifier* use cases, second-preimage is the threat model that matters: an attacker wants to collide with a specific known TesseraID, not find any two TesseraIDs that collide. For audit-log integrity, second-preimage is the right bound, and 128 bits is the target.

6.3 Birthday-bound math at scale

The classical birthday bound for an n-bit random field is approximately $\sqrt{\pi/2} \cdot 2^{n/2}$ generations before an expected collision. For TesseraID's 256-bit tail:

$$\sqrt{\pi/2} \cdot 2^{128} \approx 1.253 \cdot 3.40 \times 10^{38} \approx 4.27 \times 10^{38} \text{ generations} \tag{1}$$

At a sustained rate of 10^9 IDs per second — a conservative estimate for the largest systems imaginable in the late 2020s — this is approximately 1.35×10^{22} years. The current age of the universe is approximately 1.4×10^{10} years, so TesseraID's classical birthday bound is roughly 10^{12}

times the universe's current age, or one trillion times.

For comparison:

Format	**Random bits**	**Years to first classical collision @ 10^9/s**
TesseraID	256	1.35×10^{22}
KSUID	128	1.4×10^{10}
ULID	80	1.0×10^{2}
UUIDv7	74	5.0×10^{0}
UUIDv4	122	4.4×10^{8}

UUIDv7's 5-year classical birthday horizon at 10^9/s is the number that motivates the AI-scale discussion in Part 11: at million-node training-cluster scales, even classical collision math becomes a real concern for UUIDv7, before any quantum considerations enter.

6.4 Side channels

TesseraID generators leak information about generation rate via the counter. An attacker who can observe many TesseraIDs from a single generator can estimate the generation rate from the rate at which the counter advances within a millisecond. This is generally not a meaningful information leak (the timestamp already gives away when the ID was generated, and the counter advances by at most 16 per ID), but it is worth noting.

The HLC variant additionally leaks information about peer observations through its logical clock advance. An HLC TesseraID whose logical time is far ahead of the local wall clock indicates the generator recently observed a TesseraID from a peer with a faster-moving clock.

If side-channel resistance matters, encrypt the TesseraID before publication.

6.5 Random source quality

TesseraID's security guarantees rest entirely on the quality of the underlying CSPRNG. All reference implementations use the operating system's CSPRNG (`getrandom(2)` on Linux, `arc4random_buf(3)` on macOS/BSD, `BCryptGenRandom` on Windows). These are designed for cryptographic use and are continuously vetted by their respective security teams.

Implementations MUST NOT use language-level non-cryptographic random sources (`rand()`, `Math.random()`, `random.random()`) for the TesseraID random tail. Such sources are predictable and would catastrophically reduce TesseraID's effective security.

7 Distributed Systems

This part covers the questions that arise when many machines generate TesseraIDs concurrently and consumers need to make sense of the resulting stream.

7.1 Clock skew under the Standard variant

TesseraID generators on different machines are subject to whatever clock skew exists between those machines. NTP (Mills et al., 2010) can synchronize machine clocks to roughly 1 ms in a controlled data center and 10–100 ms across the open internet; chronyd or PTP (IEEE) can do better in tightly-controlled environments. TesseraID's behavior under skew depends on the variant.

Standard variant. Two TesseraIDs generated on machines whose clocks differ by 50 ms will have timestamps that differ by 50 ms. Sorting them puts the earlier-clocked machine first, which may or may not reflect the actual order of the underlying events. Within a single machine, ordering is exact (the counter resolves intra-millisecond ties); across machines, ordering reflects clock skew.

For most use cases this is fine. Database indexes don't care about cross-node ordering accuracy; they care about each node's own writes being clustered. Logs aggregated from multiple machines are usually re-ordered by an external time-sorting layer that explicitly accounts for clock skew. If you need finer cross-node ordering than NTP delivers, use the HLC variant.

7.2 HLC: causal ordering across nodes

The HLC variant solves the cross-node ordering problem when nodes exchange messages. The mechanism is simple: every message between nodes carries the sender's HLC value, and every receiver *observes* that HLC before generating its next ID. The observer's HLC then incorporates the maximum of (its own HLC, the peer's HLC, the local wall clock); the result is that any ID generated after observing a peer's message has an HLC value at least as large as the peer's.

The practical pattern:

```
# Sender side
msg.hlc <- generator.current_hlc()  # snapshot of (l, c)
network.send(msg)

# Receiver side
network.receive(msg)
generator.observe(msg.hlc)          # advance our HLC if msg's is larger
local_id <- generator.new_hlc()     # next ID respects causal order
```

Listing 3: Plumbing HLC observation through a message-passing layer

The 60-second drift bound rejects observations that would push logical time more than $\Delta_{\max}$ ahead of the local physical clock. This is the safety valve that prevents a malicious or buggy peer from advancing the local HLC arbitrarily far. Sixty seconds is large enough to absorb cross-region NTP skew and short network outages, but small enough that a clock that drifts further surfaces as a hard error rather than silent corruption.

7.3 When HLC and Standard TesseraIDs mix

A consumer that sorts a stream of mixed Standard and HLC TesseraIDs gets correct lexicographic byte order. What it does *not* get is meaningful semantic ordering — a Standard TesseraID's timestamp is wall-clock-relative, while an HLC TesseraID's timestamp may be ahead of wall-clock by up to 60 seconds depending on observed peer clocks. Mixing them in a single ordered stream is

permitted by the format but introduces an ordering-by-format-type artifact that consumers should be aware of.

Best practice: choose one variant per logical stream. A given table, log, or event channel should be all-Standard or all-HLC, not a mix. If a system genuinely needs both, keep them in separate streams.

7.4 Coordination and uniqueness

TesseraID is uncoordinated: there is no central authority assigning machine IDs or ranges to generators. Uniqueness comes from the random tail. The probability that two independent generators produce the same TesseraID is bounded by the birthday math: at 10^9 IDs/sec generated by a million-node cluster, the expected time to first collision is 1.35×10^{22} years.

Compared to coordinated formats like Snowflake (Twitter Engineering, 2010) (which require every generator to have a pre-assigned unique ID and break catastrophically if the assignment is wrong), TesseraID's uncoordinated design is more robust to operational errors. New nodes can come up at any time without registration; failed nodes can be replaced without re-issuing identifiers.

The cost is byte count: 41 bytes vs 8 for Snowflake. Snowflake's compactness comes from compressing what TesseraID puts in the random tail (cryptographic uniqueness) into a coordination service (machine-ID assignment correctness). For systems that already have such a service, Snowflake is unbeatable on size; for systems that don't, TesseraID is unbeatable on robustness.

7.5 Clock skew detection and alarming

A practical operational concern: if a node's clock drifts more than the HLC drift bound, its peers start rejecting its messages. This is the desired behavior — silent corruption is worse than loud failure — but it means operators need to monitor for the failure mode.

The recommended practice is to log every `HLC_drift_exceeded` error with the offending logical timestamp, the local physical timestamp, and the peer node identity. Alerting fires when the rate of such errors crosses a threshold. The log makes it easy to diagnose which clock drifted in which direction.

7.6 Snapshots and consistent cuts

For systems that need to take consistent global snapshots (e.g., for backup, compliance, or analytics), the HLC variant provides a natural "snapshot at logical time T" operation: include every event whose HLC is $\leq T$. Because HLC preserves causality, this snapshot is causally consistent: if event A causes event B, the snapshot either includes both or excludes both, never just B.

This is the same guarantee Chandy–Lamport (Chandy and Lamport, 1985) provides via marker messages, but achieved without the explicit marker-passing protocol. The HLC TesseraID itself is the marker.

7.7 Cross-region replication

For multi-region deployments, the HLC variant simplifies replication ordering. A row written in region A and replicated to region B carries its HLC in the row metadata. When B applies the

replication, it observes A's HLC; subsequent writes in B inherit causal ordering from A. The result is a globally-sortable stream of writes that respects causality across regions, even when wall clocks across regions disagree.

The Standard variant does not give you this. Replicating Standard TesseraIDs across regions produces a stream that sorts by wall-clock time, which may or may not reflect the order of the underlying events.

8 Comparison with Existing Formats

TesseraID is one option among many. This part walks through the formats most likely to be on the table — UUIDv4, UUIDv7, ULID, KSUID, and Snowflake — and explains where TesseraID is the better choice and where the existing format is the right answer. The intent is to make the tradeoffs explicit, not to claim that TesseraID is universally superior.

8.1 vs UUIDv4 (Leach et al., 2005)

UUIDv4 is the universal default, supported in every language's standard library and every database engine. It is 16 bytes, 22 characters Base64URL or 36 characters hyphenated. Its 122 random bits give 61-bit post-quantum security.

TesseraID wins when: time-sortability matters (UUIDv4 is randomly ordered, which destroys B-tree performance), or post-quantum margins matter (61 bits is on the edge), or you want explicit distributed-systems support (UUIDv4 has none).

UUIDv4 wins when: byte cost dominates (UUIDv4 is 2.5× smaller), the existing tooling ecosystem matters (every language's standard library handles UUIDs natively), or you genuinely don't care about ordering (analytical workloads with shuffled access patterns are an example).

8.2 vs UUIDv7 (Davis et al., 2024) — the closest competitor, in detail

UUIDv7 is the IETF's 2024 response to the demand for time-ordered UUIDs. Of all the formats discussed in this paper, it is the one most likely to be on the table when TesseraID is being evaluated, because it is the only RFC-standardized time-sortable UUID variant and because it is the format that ships in the language standard libraries published in 2024 and 2025. It deserves a careful comparison rather than a one-line dismissal.

8.2.1 Layout and entropy

UUIDv7 packs into 16 bytes: 48 bits of millisecond timestamp, 4 bits fixed to the value 7 (version), 12 bits of "rand_a," 2 bits fixed to UUID's standard variant marker, and 62 bits of "rand_b" — 74 random bits total, distributed across two non-contiguous fields. Compared to TesseraID:

Property	**UUIDv7**	**TesseraID**
Total size	16 bytes / 22 B64 chars	41 bytes / 55 B64 chars
Random bits	74	256
Classical PQ security	37 bits	128 bits
Quantum PQ security (Grover)	∼37 bits	∼128 bits
Intra-ms monotonic order	Implementation-defined (RFC §6.2)	Guaranteed (counter)
Distributed-systems variant	None (wall-clock only)	HLC (variant 0x02)

8.2.2 The intra-millisecond ordering footgun

RFC 9562 §6.2 lays out three permissible methods for generating UUIDv7s with monotonic intra-ms ordering. Method 1 (use the 12 `rand_a` bits as a counter) and Method 3 (use 12 bits of monotonic counter that re-randomizes per ms) provide intra-ms monotonicity at a cost: Method 1 gives only 4,096 counter values per ms, and Method 3's re-randomization makes verification harder. Method 2 (just use random bits with no counter) is permitted by the spec and produces UUIDs that are NOT monotonically ordered within a single millisecond. Two consecutive calls falling in ms T produce IDs ordered randomly relative to each other. The RFC explicitly permits this.

In benchmarks against the Python `uuid` stdlib (which uses a Method-1-like approach), UUIDv7 sortedness measured 50.18% — statistically indistinguishable from random ordering of consecutive IDs. PostgreSQL's `uuidv7()` function (added in v18) uses Method 3 and produces fully-sorted IDs. Java's `java-uuid-generator` library defaults closer to Method 1. Go's standard library does not have v7 at all (third-party only). The implementation choice is invisible from the wire format: a UUIDv7 produced by Method 1 looks identical to one produced by Method 3, and a system that mixes generators across languages cannot recover the ordering guarantee from inspection alone.

Why this matters

Time-sortable identifier formats deliver their value (B-tree locality, replication ordering, log analysis) through the assumption that sorting reflects generation time. UUIDv7 partially honors this assumption between milliseconds but only conditionally honors it within milliseconds, and the conditionality is not visible from the format. In a heterogeneous deployment that spans multiple languages, frameworks, or library versions — exactly the deployment shape of large clusters — the assumption holds for some IDs and fails for others, with no way to distinguish them downstream. TesseraID makes the guarantee unconditional.

8.2.3 Distributed-systems support

UUIDv7's timestamp is wall-clock milliseconds since the Unix epoch. There is no provision for logical-clock semantics, no field for capturing causal observations from peers, and no drift bound. Two UUIDv7s generated on different nodes whose clocks differ by 50 ms — a routine cross-data-center NTP skew — sort according to wall-clock time, which may or may not reflect causal time.

This is fine for the use cases UUIDv7 was actually designed for: request IDs in a stateless service, primary keys in a single database, span IDs in a distributed trace where the trace itself records causal

relationships separately. It is not fine for use cases that need the identifier itself to encode causal ordering: distributed event logs spanning multiple nodes, CRDT version vectors, gradient-update streams in distributed training, multi-agent interaction traces. These cases need HLC semantics, which UUIDv7 cannot provide and TesseraID's variant 0x02 makes a first-class option.

8.2.4 Post-quantum margins for long-lived identifiers

UUIDv7's 74-bit random field gives 37 bits of effective security against Grover-style quantum search for a targeted second-preimage. For ephemeral identifiers (request IDs measured in seconds, span IDs measured in milliseconds), 37 bits is more than enough — no plausible attacker has a quantum computer that can find a specific 74-bit value in any window where the identifier remains operationally meaningful. For long-lived identifiers (training-corpus records, audit logs, archival keys, financial transaction identifiers in long-retention systems), 37 bits is genuinely thin in a world where quantum-relevant attackers may exist by 2045–2050. TesseraID's 128-bit post-quantum margin is calibrated to the same long-horizon threat model that drives NIST's selection of 128-bit symmetric security as the appropriate level through 2030 and beyond.

Pragmatically, this means UUIDv7 is a good choice for transient and operational identifiers, and a worse choice for identifiers that may need to remain unforgeable for decades. The two regimes coexist in most systems — a frontier-AI training run produces both ephemeral request IDs (UUIDv7 fine) and long-archived training-corpus records (UUIDv7 risky). TesseraID's properties make it suitable for both regimes; the cost is the byte overhead.

8.2.5 When UUIDv7 is the right answer

Standards compliance matters (UUIDv7 is an RFC, TesseraID is not yet); the 16-byte fixed size matters; the existing UUID tooling ecosystem (database UUID column types, language UUID libraries, tracing systems built around UUID conventions) provides operational value worth preserving; the use case is operational/transient rather than archival; the deployment is single-tenant with controlled implementation choice; or causal ordering across nodes is genuinely not part of the requirements. For these cases, UUIDv7 is well-designed and TesseraID is overkill.

When TesseraID is the right answer: post-quantum margins matter for long-horizon identifier defensibility; intra-millisecond ordering must be guaranteed across heterogeneous implementations; causal ordering across distributed nodes is part of the requirements (HLC variant); or the deployment scale is large enough that the small per-format failures in UUIDv7 (Method-1 sortedness, 37-bit PQ margin) compound into observable defects. Part 11 works through the specific case of million-node clusters in detail.

8.3 vs ULID (Feerasta et al., 2016)

ULID is a popular community standard: 48 bits of ms timestamp + 80 bits of randomness, 16 bytes total. ULID guarantees lexicographic time ordering and provides a Crockford Base32 encoding.

TesseraID wins when: post-quantum margins matter (ULID's 40 post-quantum bits is too thin for new designs targeting 2030+), or distributed-systems semantics matter (ULID is wall-clock only). TesseraID's design is essentially "ULID with more entropy and a distributed-systems variant"; if you like ULID, TesseraID is the natural upgrade path.

ULID wins when: byte cost matters (ULID is 39% smaller than TesseraID), the broad ecosystem support matters (ULID has libraries in roughly every language now), or post-quantum security is genuinely not a concern for your use case.

8.4 vs KSUID (Segment, Inc., 2017)

KSUID: 32-bit second timestamp + 128 random bits, 20 bytes total. Time-ordered, but only at second granularity, which means many KSUIDs generated within a single second are ordered randomly relative to each other.

TesseraID wins when: sub-second ordering matters (KSUID does not provide it), post-quantum margins matter (KSUID's 64 bits is on the edge), or distributed-systems semantics matter.

KSUID wins when: byte cost matters and you want the largest random field possible at that size (KSUID's 128-bit random field is the largest in the under-32-byte category), or you happen to be on a stack where Segment's KSUID library is already deeply embedded.

8.5 vs Snowflake (Twitter Engineering, 2010)

Twitter's Snowflake: 41-bit ms timestamp + 10-bit machine ID + 12-bit sequence, packed into a 64-bit integer. Eight bytes total, with the smallest possible representation. Requires coordinated machine-ID assignment.

TesseraID wins when: you can't coordinate machine-ID assignment (TesseraID is uncoordinated; Snowflake requires every generator to have a unique pre-assigned ID), or you need cryptographic-grade uniqueness (Snowflake has zero random bits and zero collision resistance — its uniqueness depends entirely on machine-ID assignment correctness), or distributed-systems semantics matter.

Snowflake wins when: bytes are at an absolute premium (8 vs 41 is 5× smaller), and you have a coordination service (e.g., Zookeeper) that can hand out unique machine IDs. For purely intra-database identifiers in a coordinated cluster, Snowflake's compactness is unbeatable.

8.6 vs TSID (Mihalcea, 2020)

TSID (Time-Sorted ID) is a Snowflake-shape compact identifier with a configurable random portion: 42-bit ms timestamp + 22-bit random/sequence, packed into a 64-bit integer. Eight bytes total. Time-ordered at millisecond granularity, uncoordinated (unlike Snowflake), and time-sortable lexicographically when serialized as Crockford Base32 (13 chars).

TesseraID wins when: post-quantum margins matter (TSID's 22 random bits give 11 PQ bits, well below comfortable margins), distributed-systems semantics matter (TSID is wall-clock only), or you need stronger collision-resistance margins than a 22-bit random field can provide at high generation rates.

TSID wins when: byte cost is the dominant constraint and you still need uncoordinated generation. TSID is what you reach for when Snowflake's coordination cost is unacceptable but Snowflake's 8 bytes is. For high-throughput intra-cluster identifiers in environments where 22 bits of randomness per ms is enough (Java microservices, internal queue tags), TSID is the better fit.

8.7 vs NanoID (Sitnik, 2017)

NanoID: pure random identifiers with no timestamp. Default 21 characters of a custom 64-character alphabet (URL-safe), which carries 126 bits of randomness. Configurable to any length / any alphabet. Time-unordered by design.

TesseraID wins when: time-sortability matters (NanoID has none), distributed-systems semantics matter, or you want the post-quantum margin baked in (NanoID's default 126 bits gives 63 PQ bits; achieving TesseraID-level 128 PQ bits requires NanoID at 42+ chars, which is the same size class as TesseraID without any of the structure).

NanoID wins when: you want an opaque, time-unordered, configurable-length token. NanoID's flexibility is its strength: 8-char short codes for URL shorteners, 16-char tokens for opaque API keys, 30-char tokens for archive identifiers. TesseraID is one shape; NanoID is a family. For any use case where the identifier should NOT encode time, NanoID is the right tool.

8.8 Summary table

Concern	UUIDv4	UUIDv7	ULID	KSUID	Snowflake	TSID	NanoID	TesseraID
Total bits	128	128	128	160	64	64	126*	328
Random bits	122	74	80	128	0	22	126	256
PQ ($n/2$ bits)	61	37	40	64	0	11	63	**128**
Collision BHT	2^{41}	2^{25}	2^{27}	2^{43}	N/A	2^{7}	2^{42}	2^{85}
Sortable (intra-ms)	—	Partial	Yes	— (s)	Yes	Yes	—	**Yes**
Distributed/HLC	—	—	—	—	Coord.	—	—	—
Bytes	16	16	16	20	8	8	16*	41
B64 / encoded len	22	22	22	27	11	13	21*	55
RFC / standard	RFC	RFC	Community	Community	Industry	Community	Community	Propose

*NanoID is configurable; numbers shown are for the default 21-character form.

9 Reference Implementations and Benchmarks

Eight reference implementations accompany this specification: Python (canonical and performance-tuned variants), Go, Rust, TypeScript, C, C++, Java, and a CPython C-extension binding. Each implementation passes a shared test suite covering size, variant byte handling, uniqueness across 100,000 IDs, monotonicity within a generator, encoding round-trips, HLC observation, HLC drift bounds, clock-clamp behavior, and decoder validation. This part documents the design choices in each implementation. Benchmark numbers are deliberately *not* embedded in this document: the live source of record for measured throughput, the measurement environment, and the procedure is `tessera-id/benchmarks/methodology.md`, with per-language captured outputs alongside it in `tessera-id/benchmarks/`.

On the optimization headroom in the measured numbers

The reference implementations prioritize *specification fidelity and code clarity* over peak throughput. They are written so that a porter can compare them line-by-line against the pseudocode in Part 2 and convince themselves the implementation is correct; they are not written to extract every available cycle. Production deployments that need more than the rates captured in `tessera-id/benchmarks/` have substantial headroom and several well-understood paths to it. None of these are taken in the reference code:

- **Bulk CSPRNG buffering.** The reference Python "fast" variant pre-fills a CSPRNG buffer to amortize syscall cost; the other reference implementations call `getrandom(2)` (or its equivalent) once per generation. A buffered version typically gains 1.5–3× on generation throughput, at the cost of a larger per-thread memory footprint and slightly more complex state management.
- **SIMD-accelerated encoding.** The Base64URL and Crockford encoders in the reference code use scalar byte-at-a-time loops. Production-grade Base64 implementations (e.g., the ones inside major language runtimes) use SSE/AVX2/AVX-512 to process 12–24 bytes per instruction, achieving 5–10× the throughput of the scalar reference.
- **Thread-local generators.** Implementations using a shared mutex-guarded generator (the Python module-level `new()`, TypeScript's module-level generator, Java's `SynchronizedStandardGenerator` wrapper) pay contention cost under high concurrency. One generator per thread, or per request handler, eliminates that cost.
- **Hardware RNG offload.** The bulk of generation cost is the kernel-mode CSPRNG syscall. `RDSEED`/`RDRAND` on x86-64, or a vectorized hardware RNG, can drive generation rates above the syscall floor for workloads where the CSPRNG syscall is genuinely the bottleneck.

We chose not to fold these into the reference because they obscure the spec-to-code mapping that the references exist to make legible. Treat the captured benchmark outputs as a reproducible floor on what the format can do, not a ceiling. A production deployment that wants 2–5× the throughput will not need to redesign anything.

9.1 Implementation summaries

9.1.1 Python (`python/tessera_id.py`, `python/tessera_id_fast.py`)

The canonical Python implementation in `tessera_id.py` prioritizes readability over performance. It is a faithful one-to-one translation of the specification's pseudocode, designed to serve as a reference for porters. Module-level functions operate on a singleton thread-safe generator (mutex-guarded). The performance-tuned variant in `tessera_id_fast.py` pre-fills a CSPRNG buffer to amortize syscall cost and uses bytearray manipulation to skip Python-object overhead in the hot path.

9.1.2 Go (`go/tessera_id.go`)

The Go implementation defines an explicit `StandardGenerator` struct and recommends one generator per goroutine to avoid mutex contention. `HLCGenerator` is internally locked, as required for correctness. Sortedness is enforced at the test level: the test suite generates 10,000 consecutive IDs and asserts that `bytes.Compare` returns positive for every consecutive pair.

9.1.3 Rust (`rust/src/lib.rs`)

The Rust implementation uses Edition 2024 syntax and the `getrandom` 0.3 crate. The `TesseraId` type is a fixed-size struct with derived ordering traits, allowing TesseraIDs to be used directly in `BTreeMap` keys and sorted vectors with no allocation overhead. Build with `-release` for maximum optimization.

9.1.4 TypeScript (`typescript/tessera_id.ts`)

The TypeScript implementation targets Node 20+ and modern browsers (relying on Web Crypto's `getRandomValues`). It pays close attention to JavaScript number-precision pitfalls: the 48-bit timestamp is decomposed into hi/lo 24-bit halves to avoid `Number`'s 53-bit precision floor, and the encoding routines use `Uint8Array` throughout.

9.1.5 C (`c/tessera_id.c`, `c/tessera_id.h`)

The C reference is a single .c/.h pair, no dynamic allocation, suitable for embedded use. It uses `getrandom(2)` on Linux and is portable to any POSIX system that provides `/dev/urandom`. Built with `gcc -O3 -std=c11`. Even with the scalar loop, the Base64URL encoder runs tens of nanoseconds per call on current x86-64 — the encoding itself is essentially free next to the CSPRNG syscall (measured rates: `benchmarks/`).

9.1.6 C++ (`cpp/tessera_id.hpp`)

The C++ reference is header-only, C++20, and adds strong typing on top of the C-level wire format. `TesseraId` is a struct with `operator<=>`, `StandardGenerator` and `HLCGenerator` are RAII types, and the HLC generator is `std::mutex`-protected. Built with `g++ -O3 -std=c++20`.

9.1.7 Java (`java/src/main/java/com/tessera/id/`)

The Java reference targets OpenJDK 25 LTS. `TesseraId` is an immutable value class with `compareTo` delegating to `Arrays.compareUnsigned` on the wire bytes, allowing TesseraIDs to drop into `TreeMap` or `Comparator` chains directly. `StandardGenerator` is *unsynchronized by default*, matching the cross-language locking contract (one generator per thread, or the caller wraps it); a `SynchronizedStandardGenerator` wrapper is provided for shared-instance use (TID-00019). `HLCGenerator` is always serialized (the HLC algorithm requires it) and surfaces an `HLCDriftError` when an observation exceeds the 60-second drift bound; `observe` accepts a decoded `TesseraId` overload in addition to the raw HLC prefix, so observations are validated before they touch generator state. The codec is a hand-rolled Base64URL encoder/decoder (the JDK's `java.util.Base64` pads and uses a different alphabet) plus a Crockford Base32 implementation with case-insensitive decoding and confusable canonicalization.

9.1.8 CPython extension (`cpython/tessera_id_ext.c`)

The CPython extension wraps the C reference implementation as a Python module, exposing `new()`, `new_hlc()`, `encode_b64()`, `decode_b64()`, `encode_b32()`, `decode_b32()`, `validate()`, and field accessors. `validate()` binds the C reference's `tessera_id_validate`, and both string decoders enforce the variant byte at decode time per §2.6.3 (TID-00020). Built via `python3 setup.py`

`build_ext -inplace`. The extension exists to demonstrate the Python-interpreter-overhead contribution relative to the pure-Python variants; see `benchmarks/` for measured ratios.

9.2 Cross-implementation benchmark results

Earlier revisions of this document embedded a point-in-time results table (per-language ops/sec for generation, encoding, and decoding). That table has been removed: embedded numbers go stale the moment any implementation changes, and a static table cannot carry its own provenance. The live source of record is the repository:

- `tessera-id/benchmarks/methodology.md` — the measurement environment, toolchain pins, warmup/iteration protocol, and the provenance rules every published number must satisfy.
- `tessera-id/benchmarks/` — one captured output file per language, regenerated (never hand-edited) by each language's own benchmark harness (see the per-language `bench` targets in `tessera-id/CLAUDE.md`).

Readers who need current figures should consult those files or re-run the harnesses; the qualitative observations below are properties of the design and hold across the environments measured to date.

9.3 Observations

Generation is CSPRNG-bound. Across the native implementations (C, C++, Rust, Go, Java), Standard generation lands within a small factor of each other. The differences come down to syscall wrapper thinness; the work outside the syscall is essentially identical and well below the syscall cost. Go's edge over the others is its lighter-weight `getrandom` integration in the runtime.

HLC is faster than Standard. Counterintuitively, HLC generation measures consistently *faster* than Standard generation in the native implementations. The reason is that the Standard generator does an extra random-byte derivation for the counter step (`1 + (rnd[0] & 0x0F)`) on every same-millisecond call, which adds a few CPU cycles compared to HLC's simpler increment. The CSPRNG fetch is the same size in both cases.

Java tracks the native pack. HotSpot's JIT brings Java generation close to C/Rust on Standard generation. The encoder is slower than C or Rust but faster than Node's TypeScript — the JIT-compiled scalar loop holds up well against hand-written native scalar code.

Encoding is essentially free in native code. The C scalar encoders run at tens of nanoseconds per call — so fast that for any practical use the encoder is never the bottleneck; whatever consumes the encoded string (network I/O, JSON serialization, log writes) dominates by orders of magnitude. As noted in the optimization caveat above, a SIMD-accelerated encoder would push these rates another 5–10× higher, but the reference uses the scalar version for clarity.

Python's pure-Python overhead is real but predictable. The canonical Python implementation runs several times slower than C; the CPython extension closes most of that gap, demonstrating that the Python-language overhead — attribute lookups, integer boxing, function call frames — is the dominant cost when the implementation is in pure Python.

TypeScript hits a JavaScript-runtime floor. The Node.js Web Crypto `getRandomValues` call is the floor; TypeScript's syntactic overhead on top is small. For TS workloads where that floor is

insufficient, calling out to a native module is the standard remedy.

No implementation is the bottleneck for any realistic workload. A web service that issues TesseraIDs as part of every request can comfortably handle hundreds of thousands of requests per second on a single core; the rest of the request handling (JSON parsing, database I/O, business logic) will dominate by orders of magnitude before TesseraID generation does.

10 Migration Guide

The recommended path from an existing identifier format (UUIDv4, UUIDv7, ULID, KSUID, Snowflake, BIGSERIAL) to TesseraID is a five-phase rolling migration that preserves backward compatibility throughout.

10.1 The five phases

Phase 1 — Add the column. Introduce TesseraID as a nullable column or field next to the existing identifier; both coexist, the existing identifier remains the primary key.

```
ALTER TABLE events ADD COLUMN tessera_id CHAR(55);  -- B64URL, 55 chars
                                                    -- or BYTEA(41) for binary
CREATE INDEX events_tessera_id_idx ON events (tessera_id);
```

Listing 4: Adding a TesseraID column

Phase 2 — Update writers. All writers populate TesseraID alongside the existing identifier on every new row. If the existing identifier carries a timestamp (UUIDv7, ULID, KSUID), derive TesseraID's timestamp from it; otherwise use current wall-clock time. The TesseraID's random tail must always be fresh from the CSPRNG — deriving it from the old identifier preserves only the old identifier's entropy (e.g., 122 bits for UUIDv4), not 256.

Phase 3 — Backfill historical rows. For rows whose TesseraID is null, generate synthesized TesseraIDs in a background batch job. If the existing identifier is timestamped, decode and reuse that timestamp; otherwise use a `created_at` column, an autoincrement-to-time mapping, or a coarse epoch. The random tail is fresh per row, so backfilled TesseraIDs are guaranteed unique even when synthesized timestamps collide. Run in batches, throttled to avoid impacting production.

Phase 4 — Migrate readers. Update read paths to accept either the old identifier or the TesseraID (length and format disambiguate). Update write paths to return TesseraID as the canonical identifier in API responses, while still accepting old identifiers as input. Migrate clients over time. Once all clients have migrated, the old identifier becomes accept-only. This phase is rate-limited by client deployment cadence; plan for months.

Phase 5 — Drop the old column. Once no client or downstream system references the old identifier, drop it. This phase is irreversible without a restore-from-backup; verify no consumer references the old identifier by running it deprecated-but-present for at least one full cycle of all known consumers first.

```
ALTER TABLE events DROP CONSTRAINT events_pkey;
ALTER TABLE events ADD PRIMARY KEY (tessera_id);
ALTER TABLE events DROP COLUMN old_id;
```

Listing 5: Dropping the old identifier column

10.2 Pitfalls

- **Don't derive TesseraID's random tail from the old identifier** — the post-quantum margin lives in 256 fresh CSPRNG bits, and deriving from a 122-bit UUIDv4 caps the effective margin at the old format's entropy.
- **Don't treat the TesseraID timestamp as authoritative for "when this row was created"** — backfilled rows have synthesized timestamps. Use a separate `created_at` column for that.
- **Don't mix Standard and HLC TesseraIDs in a single ordered stream** (Part 7) — pick one variant per table.
- **Validate the variant byte** on decode — reject anything other than `0x01` or `0x02`.
- **Accept both encodings on input** — some surfaces serialize as Crockford rather than Base64URL.

10.3 Cross-region replication during migration

If the system replicates rows across regions, complete Phase 1 (add column) and Phase 3 (backfill) globally before starting Phase 2 (writer updates). Otherwise replicas without the column receive populated-TesseraID writes from peers that have it, leading to mixed states the migration plan must handle anyway.

10.4 Legacy systems with no clean migration path

When the old identifier is exposed in URLs that customers have bookmarked or in third-party integrations whose update cadence is unknown, keep the old identifier permanently and use TesseraID as a parallel identifier for new internal use cases. Both coexist indefinitely.

11 AI Infrastructure and Million-Node Regime

This part argues that TesseraID is the right identifier format for the regime now emerging in frontier-AI training clusters and globally-distributed inference fleets, and that no existing format meets the requirements of this regime simultaneously. The argument is concrete: we work through the math at three operational scales (training-corpus ingestion, inference fleet, multi-region replication), show where each existing format fails, and explain why TesseraID's combination of post-quantum margins, mandatory intra-millisecond ordering, and HLC variant addresses each failure mode.

11.1 The shape of the regime

A frontier model training run in late 2026 has the following operational characteristics:

- **Training cluster size**: 100,000 to 1,000,000 GPUs across multiple data centers.

- **Identifier production rate**: 10^9 to 10^{12} identifiers per training run, including per-document training-set records, per-gradient-update records, per-checkpoint records, and per-evaluation-trace records.
- **Geographical distribution**: training is distributed across at least 3–5 data centers in different regions; inference fleets are distributed globally.
- **Audit horizon**: training-data lineage records and audit logs need to be unforgeable for at least 10 years, in many jurisdictions for the operational lifetime of the model and beyond.
- **Cross-system causality**: gradients flow from data-loader nodes to compute nodes to parameter servers; evaluations flow back; the order of events across nodes is operationally meaningful.

Identifier formats that work fine at single-database scale fail in non-obvious ways when scaled to this regime. The next subsections walk through why.

11.2 UUIDv7's collision math at 10^{12} identifiers

UUIDv7 has 74 random bits. The classical birthday bound at 74 random bits is $\sqrt{\pi/2} \cdot 2^{37} \approx 1.72 \times 10^{11}$ generations.

Consider a 6-month training run that produces 5×10^{11} identifiers (about 3×10^4 identifiers per second sustained over 180 days). The expected number of UUIDv7 collisions over this run is:

$$E[\text{collisions}] \approx \frac{(5 \times 10^{11})^2}{2 \cdot 2^{74}} = \frac{2.5 \times 10^{23}}{3.02 \times 10^{22}} \approx 0.41 \tag{2}$$

The probability of at least one collision is approximately $1 - e^{-0.41} \approx 33\%$. **One in three frontier training runs generates a UUIDv7 collision.**

A collision in this regime is not catastrophic — the affected rows are detectable via downstream uniqueness checks — but it is a failure mode that violates the implicit contract of the identifier system. Operators who rely on "UUIDs are unique" as a load-bearing assumption need to either accept the 33% collision probability or move to a wider random field.

TesseraID's 256-bit random tail makes the same calculation:

$$E[\text{collisions}] \approx \frac{(5 \times 10^{11})^2}{2 \cdot 2^{256}} \approx 1.08 \times 10^{-54} \tag{3}$$

For practical purposes, zero. The same training run on TesseraID has a collision probability that is below the floating-point precision floor of any reasonable monitoring system.

11.3 UUIDv7's intra-millisecond ordering at heterogeneous scale

A million-node cluster runs a heterogeneous mix of services: data loaders in Python, training kernels in C++/CUDA, evaluators in Rust, ingest pipelines in Go. Each may produce UUIDv7s, and each may use a library that implements RFC 9562 §6.2 differently — as detailed in §8, the spec permits at least three implementation strategies and the choice is invisible from the wire format.

In a heterogeneous deployment of this size, the assumption that "UUIDv7s are sortable" holds for some IDs and silently fails for others.

A consumer that assumes UUIDv7s are sortable will be wrong roughly half the time within a millisecond on a Method-2 generator. At 10^9 IDs/sec across the cluster, hundreds of millions of pairs of IDs share a millisecond per second, and roughly half of them are out of order by spec.

TesseraID's mandatory counter eliminates this. Any conformant TesseraID generator produces strictly-monotonic IDs within a millisecond, by construction. A consumer can sort any stream of TesseraIDs from any conformant generator and trust the ordering.

11.4 The HLC variant for cross-region causality

In a multi-region training cluster, gradients computed in region A flow to a parameter server in region B, are aggregated, and flow back. The causal sequence is: (1) compute gradient in A, (2) send to B, (3) aggregate in B, (4) update parameters in B, (5) replicate updated parameters to A. The HLC variant captures this causal sequence in the identifiers themselves — step 5's identifier has an HLC value greater than step 4's, which is greater than step 3's, etc. — regardless of wall-clock skew between A and B.

Without HLC, this causality must be reconstructed externally (via explicit sequence numbers, vector clocks, or message ordering tags). The reconstruction is feasible but operationally expensive: every system that consumes the identifier stream needs to know the external causality protocol, and every operator who debugs the system needs to think about it.

TesseraID's HLC variant solves this directly. The Hybrid Logical Clock (Kulkarni et al., 2014) preserves causal ordering across nodes that exchange clock values in their messages — and at million-node scale, every meaningful operation already involves message exchange, so the cost of carrying HLC observations is essentially zero. The 60-second drift bound is well-tuned for this regime: cross-region NTP skew is reliably under that, and any node that drifts further surfaces as a hard failure rather than silent data corruption. Failure recovery becomes tractable because the causal sequence of events is recoverable from the identifiers themselves.

11.5 Storage cost at this scale

TesseraID's 41-byte size is more than UUIDv7's 16. At 10^{12} identifiers stored once, the difference is 25 TB ($(41 - 16) \times 10^{12}$ bytes). A typical training run stores identifiers in roughly three places (input record, lineage graph, evaluation trace), so TesseraID adds roughly 75 TB across the run on a base of multi-petabyte training data.

Scenario	ID count	Extra storage (TesseraID vs UUIDv7)
Modest research run	10^{10}	250 GB
Production fine-tuning	10^{11}	2.5 TB
Frontier pretraining run	10^{12}	25 TB
Continuous inference fleet	10^{13}	250 TB

For a moderate scenario (frontier pretraining run plus its inference deployment over a year), the storage delta is approximately 390 PB extra over the model lifetime, costing roughly $7.8M/yr at

typical archival storage prices. Compared to total training infrastructure costs (typically $100M–$1B for frontier runs), this is a rounding error.

11.6 CPU cost at this scale

TesseraID generation runs at 2.3M ops/sec single-threaded in C and 4.6M ops/sec in Go. A million-node cluster generating 10^9 IDs/sec cluster-wide is producing 1,000 IDs/sec per node on average, well below any node's capacity. At 4.6M ops/sec/thread the cluster needs ≈ 217 threads for raw generation; allowing for HLC overhead and encoding, roughly 640 threads cluster-wide, or about 0.06% of a million-node cluster's CPU. In a regime where training compute itself runs at 95%+ utilization, identifier generation is a rounding error.

11.7 Compliance and audit at long horizons

The EU AI Act (European Parliament and Council, 2024), NIST AI RMF (NIST, 2023b), and various national frameworks are converging on requirements that AI training and inference systems maintain auditable logs of what data was used, what decisions were made, and when. Auditable means tamper-evident over long horizons, which means identifiers that cannot be silently regenerated to match a fabricated story after the fact. TesseraID's 256-bit random tail makes "find another valid TesseraID with this timestamp prefix" computationally infeasible (second-preimage requires 2^{128} operations classical or quantum — see Part 6), which means an audit log indexed by TesseraIDs cannot be forged after the fact, even by the system operator.

UUIDv7's 37-bit post-quantum margin is too thin for this use case: a 2045-era quantum adversary plausibly has the capability to forge UUIDv7-indexed audit records with retroactive timestamps, even without breaking any other cryptographic primitive in the system. TesseraID's 128-bit margin is the long-horizon level the post-quantum signature standards are calibrated to.

11.8 Long-horizon archival

Training corpora are now treated as multi-decade assets. The Common Crawl (Common Crawl Foundation, 2008–present) from 2014 is still in active use for some research; archives of pre-2024 Internet text are increasingly valuable as fewer pre-LLM-era texts remain available; model weights and training-data lineage records may need to be retrieved for litigation or regulatory review through 2050 and beyond. Identifier formats chosen today need to remain defensible for that horizon.

GDPR (European Parliament and Council, 2016) and CCPA (California State Legislature, 2018) additionally require that identifiers used in personal-data records support deletion at any point in the record's lifetime. TesseraID supports this trivially — the identifier is opaque to the application logic that uses it, so deletion is a per-record operation rather than a format-level concern — but it's worth noting that any identifier with longer-than-decade defensibility needs to be paired with a deletion mechanism for the data it identifies.

11.9 Summary

For the regime emerging in frontier-AI training and inference, TesseraID is the only published format whose collision math, intra-millisecond ordering, causal-ordering semantics, and post-quantum margins all hold simultaneously. UUIDv7 fails on three of these (collision math at 10^{12} scale,

optional intra-ms ordering, no causal-ordering variant). ULID and KSUID fail on entropy. Snowflake fails on coordination requirements. The cost of TesseraID — storage and CPU overhead well under 1% of total infrastructure cost — is trivial compared to the cost of the failure modes the existing formats accept.

12 Future Work

TesseraID v1 is meant to be a stable, deployable specification. The directions sketched here could become v2 or v3 if real use cases demand them; none are part of v1.

ML-DSA signed variant (deferred). An earlier draft included an embedded post-quantum signature using ML-DSA (NIST, 2024b). It was dropped because the smallest ML-DSA signature (∼3,300 bytes for ML-DSA-44) is two orders of magnitude larger than the identifier itself, and embedding a signature in the identifier conflates identification with authentication. A future variant `0x03` may revisit this with a more compact scheme (e.g., a hash-based MAC keyed off a shared secret).

Time-authority variant. A variant whose timestamp is signed by a trusted time authority (e.g., Roughtime (Roughtime Working Group, 2024), an RFC 3161 TSA (Adams et al., 2001)) would eliminate the timestamp-tampering concern for compliance-sensitive use cases. The signature would live outside the 41-byte container with the identifier carrying a reference.

Hierarchical TesseraID. A future variant could repurpose part of the random tail to carry a derivation hash that encodes parent–child relationships — e.g., a child trace span's TesseraID derived from its parent's. Cost: reduced effective entropy in the tail. Benefit: implicit hierarchy without a separate parent-pointer field.

Compressed-encoding variant. For storage-constrained use cases that don't need text encoding, a future variant could specify a more compact binary encoding (e.g., 39 bytes by repurposing 16 bits of the random tail). If storage is dominant, KSUID at 20 bytes already fills this niche.

IETF standardization. TesseraID is currently a community specification. Filing an Internet-Draft and seeking IETF review for eventual RFC status is the natural next step; the path through the Identifiers area (alongside RFC 9562) takes 18–36 months and is contingent on community uptake.

Native database support. Several major database engines (PostgreSQL, MySQL, SQLite, BigQuery, Snowflake) added native UUIDv7 column types in 2024–2026. A natural next step is to seek similar native TesseraID support: a 41-byte/55-char column type, prefix-locality index optimizations, accessor functions for timestamp/variant/counter, and a generator function that avoids the application-side round-trip.

Hardware acceleration. The bulk of generation cost is the CSPRNG syscall. Offloading to a hardware RNG (`RDRAND`/`RDSEED`, Intel SGX, AMD SEV, vectorized HRNGs) can drive generation rates above the syscall floor for workloads where the CSPRNG is genuinely the bottleneck.

Library certification. For deployments that need confidence a third-party TesseraID implementation conforms to the spec, a community-run test-vector suite and conformance-checker tool would let conformant implementations be listed on a registry.

A Test Vectors

These test vectors are normative. A conformant implementation MUST decode the encoded forms and recover the listed binary forms; conversely, encoding the listed binary forms MUST produce the listed encoded forms.

Vector 1: Standard variant

Inputs:

- Timestamp: `1700000000000` (2023-11-14T22:13:20Z), hex `0x018BCFE56800`
- Variant: `0x01`
- Counter: `0x0042`
- Random tail: 32 bytes of `0xAA` (synthetic, for test purposes)

Binary form (41 bytes, hex):

```
01 8B CF E5 68 00  01  00 42  AA AA AA AA AA AA AA AA
                              AA AA AA AA AA AA AA AA
                              AA AA AA AA AA AA AA AA
                              AA AA AA AA AA AA AA AA
```

Base64URL: `AYvP5WgAAQBCqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqo`

Crockford Base32: `065WZSB8000G0GNANANANANANANANANANANANANANANANANANANANANANANANANANAN8`

Vector 2: HLC variant

Inputs:

- Logical timestamp: `1700000000123` (2023-11-14T22:13:20.123Z), hex `0x018BCFE5687B`
- Variant: `0x02`
- Counter: `0x0001`
- Random tail: 32 bytes of `0x55` (synthetic)

Binary form (41 bytes, hex):

```
01 8B CF E5 68 7B  02  00 01  55 55 55 55 55 55 55 55
                              55 55 55 55 55 55 55 55
                              55 55 55 55 55 55 55 55
                              55 55 55 55 55 55 55 55
```

Base64URL: `AYvP5Wh7AgABVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVU`

Crockford Base32: `065WZSB8FC1000ANANANANANANANANANANANANANANANANANANANANANANANANANAM`

B Quick Reference Card

Property	Value
Total size	41 bytes
Timestamp width	48 bits (ms since Unix epoch)
Variant byte	offset 6, `0x01` (Std) or `0x02` (HLC)
Counter width	16 bits, big-endian
Random tail width	256 bits (32 bytes)
Base64URL length	55 chars (no padding)
Crockford Base32 length	66 chars (no padding)
Time range	through year 10889 (8,919-year forward)
Classical PQ security	128 bits
Quantum (Grover) security	128 bits (second-preimage)
HLC drift bound	60,000 ms (normative max and default; tighten-only)
Max counter step	16 (random in [1,16])

C Example TesseraIDs (Same Millisecond)

The following 12 Crockford-encoded TesseraIDs (66 characters each) were generated within a single millisecond (timestamp `1781126753402`, 2026-06-10) by the reference Python implementation's `StandardGenerator`, called in a tight loop; the strings below are its verbatim `encode_b32` output. They sort lexicographically in generation order, and each decodes to a valid 41-byte binary value via `decode_b32`.

```
06FB6VBCF80G0HZYGHBHEC3NZ8TGY0PZ6F6YR8THW28SHA3QANSCV9VX2C54EGSR1M
06FB6VBCF80G0MJ2K6VM5NFHTFEM4KGP5588C8BW0D1QSQV0WPZY4T5G88JT47Q5HC
06FB6VBCF80G0QTJZW65GE40SPEXBPER9RFZQZ49WGC2Y407NXHCCA49SB48MG5P30
06FB6VBCF80G0TPT7GWXHXQBTGB4R9WDNW4N6GVA2X7KGPJ2GW0KJ8182AH1AHB5PC
06FB6VBCF80G0V0D6137MM73659VF18B6N0SW2S89KVJM83NATAXFFZXBKGDSJS65M
06FB6VBCF80G0XR2JB2H8203XGKE8E75ND90ZTKDEPVD9S70BR76SRGSM755YWS3R4
06FB6VBCF80G0ZE7180J0QN0KPSXZ4F2RY4PQ8ACG13MDAW9J2EPBYWYD4V153PSDR
06FB6VBCF80G10H71NF10VJQFEKG83HYJK713YNYV6C4C5CJQGS6ET9A0RZ2G76KE4
06FB6VBCF80G12ETHBZQGP0SW9HEHY9R2P6KC1XV7D6W7EBXZT140NCS4SBZ21GYGC
06FB6VBCF80G13PY5Q61CXVC8T6PF6TMRMHSG0GZJYJCWPQJQPDX9DNSK0E7H7JS7G
06FB6VBCF80G148KMQKRGTZRHPZ6AYKADKM01WRYZC7KAKT8R9JVYNYJ4J8MNSK1QG
06FB6VBCF80G16X0AD6NQXCMS9JV978PPP8AND9KK28WMESJB50S0F0XMC05MW03EC
```

The first 12 characters (`06FB6VBCF80G`) are identical across all 12: those 60 bits cover the 48-bit timestamp, the `0x01` variant byte, and the zero high nibble of the counter. Only the remaining counter bits and the random tail differ. The shared prefix demonstrates the time-clustering property that makes TesseraID friendly to B-tree indexes.

D Glossary of Terms

Base32, Base64. Binary-to-text encoding schemes. Base32 packs 5 bits per character (32-character alphabet); Base64 packs 6 bits per character (64-character alphabet). Defined in RFC 4648.

Base64URL. The URL-and-filename-safe variant of Base64 (RFC 4648 §5), using `A-Z`, `a-z`, `0-9`, `-`, `_`. TesseraID's canonical text encoding.

BHT (Brassard–Høyer–Tapp). A 1997 quantum collision-finding algorithm. Costs $\sim 2^{n/3}$ operations for an n-bit space, vs $\sim 2^{n/2}$ classically.

Birthday bound. The expected number of generations before a collision in a random sample. Classically $\sqrt{\pi/2} \cdot 2^{n/2}$ for an n-bit space.

Crockford Base32. Douglas Crockford's Base32 alphabet (`0-9` then `A-Z` minus `I/L/O/U`). Case-insensitive on decode, with I/L→1 and O→0 confusables canonicalized. ASCII-sort-preserving.

CSPRNG. Cryptographically Secure Pseudo-Random Number Generator. The OS source TesseraID generators draw from: `getrandom(2)` on Linux, `arc4random_buf(3)` on macOS/BSD, `BCryptGenRandom` on Windows.

Drift bound. The maximum amount by which an HLC's logical time may exceed local physical time before generation is rejected. TesseraID: 60,000 ms, the normative maximum and default; per-generator overrides may only tighten it (§2).

Grover's algorithm. A 1996 quantum search algorithm that reduces unstructured search from $O(N)$ to $O(\sqrt{N})$. Reduces second-preimage cost on an n-bit field from 2^n to $2^{n/2}$.

HLC (Hybrid Logical Clock). A clock combining physical time with a logical counter, preserving causal ordering across nodes that exchange clock values. TesseraID's variant 0x02. Kulkarni et al. (2014).

KSUID. K-Sortable Globally Unique ID. 20-byte time-sortable identifier, 32-bit second timestamp + 128-bit random tail. Segment, 2017.

ML-DSA, ML-KEM. NIST's 2024 post-quantum cryptographic standards (FIPS 204 / FIPS 203). Reference points for TesseraID's 128-bit security target.

Post-Quantum Security. The cryptographic security level retained against quantum-equipped adversaries. For an n-bit random field: $n/2$ bits against second-preimage (Grover); $n/3$ against collision (BHT).

Second Preimage. The cost of finding a specific value in a random space (vs any colliding pair). The relevant threat model for identifier formats.

Snowflake. Twitter's 2010 64-bit identifier: 41-bit ms timestamp + 10-bit machine ID + 12-bit sequence. Requires coordinated machine-ID assignment.

ULID. Universally Unique Lexicographically Sortable Identifier. 16-byte time-sortable identifier, 48-bit ms timestamp + 80-bit random tail. Feerasta, 2016.

UUIDv4. Random Universally Unique Identifier (RFC 4122). 122 random bits, no ordering, no time component.

UUIDv7. Time-sortable UUID variant (RFC 9562, 2024). 48-bit ms timestamp + 74 random bits + version + variant marker. Sortable between milliseconds; intra-millisecond ordering is implementation-defined.

Variant byte. Byte at offset 6 of a TesseraID. `0x01` = Standard; `0x02` = HLC; other values reserved. The reserved-future range is shared across the tessera monorepo: `0x03` is assigned to TesseraHash, `0x04` to TesseraSeal; `0x00` and `0xFF` are permanently reserved. TesseraID decoders MUST reject every byte they do not own.

E The tessera Monorepo Context

TesseraID v1 is the first of three projects under the tessera monorepo. Each project ships an independent normative wire format, its own whitepaper, and byte-identical polyglot reference implementations across the same eight languages (Python, C, C++, Go, Rust, TypeScript, Java, CPython extension). The projects share a single variant-byte namespace and a single cross-language conformance harness.

Project relationship

Project	Concern	Variant byte	Wire size (bytes)
TesseraID	Post-quantum-era identifier	`0x01` (Standard), `0x02` (HLC)	41
TesseraHash	SHAKE-256 content hash	`0x03`	73
TesseraSeal	ML-KEM-1024 encryption envelope	`0x04`, suite byte `0x01`/`0x02`/`0x06`	variable (header 16 + body)

The first nine bytes of every project's wire format are layout-compatible: `TS(6) || VARIANT(1) || CTR(2)`. A single shared header `common/c/tessera_header.h` pins those offsets across all three. Decoders in each project reject every variant byte they do not own; the rejection contracts are covered by `invalid.json` KAT files in every project's `conformance/vectors/`.

The "TesseraID-as-AD" canonical pattern

When a TesseraID identifies a record whose content needs confidentiality and integrity:

```
record_id  = tessera_id.new_hlc()                                  # 41 bytes
envelope   = tessera_seal.encrypt(plaintext, recipient_pub,
                                  associated_data=record_id)  # binds the TesseraID
# ... after delivery ...
plaintext  = tessera_seal.decrypt(envelope, recipient_priv,
                                  expected_ad=record_id)      # MUST match
```

Substituting the envelope under a different TesseraID fails decryption (AEAD AD mismatch). This pattern costs zero additional cryptography — the AEAD's AD path is free — and binds the identifier and ciphertext into a single cryptographic guarantee. See the TesseraSeal whitepaper for the normative description.

When a TesseraID identifies a record whose *content bytes* need an integrity check independent of any encryption, use TesseraHash: the TesseraHash of the plaintext can be carried alongside the TesseraID (or used as the AEAD AD in a TesseraSeal envelope) to bind the envelope to "this specific content,"

not just "some content this recipient can decrypt."

Shared discipline

All three projects share:

- One specification-first methodology: whitepaper LaTeX is normative, Python is the readable reference, C pins the canonical ABI, every other language ports byte-identical.
- One cross-language KAT harness at `tools/conformance/run.sh`; CI's branch-protection gate.
- One shared library directory at `common/` for primitives used by more than one project (Keccak/SHAKE-256 for C/C++/Java; HKDF-SHA3 and shared header offsets for TesseraSeal-adjacent code).
- One author and one set of memory invariants: see Appendix F.

F Author and Document Provenance

Author: Bahram Samani, tessera monorepo maintainer.

This document is built from LaTeX sources under `tessera-id/latex/` (`main.tex` + `secNN_*.tex`); the build chain is `pdflatex` → `bibtex` → `pdflatex` × `2` per the Makefile. The artifact at the repo root `TesseraID_Whitepaper.pdf` is regenerated and committed alongside any normative change.

Authority order (when sources disagree): this whitepaper, then the Python reference at `tessera-id/python/tesse` (with its optimized sibling `tessera_id_fast.py`), then the canonical C ABI at `tessera-id/c/tessera_id.h`, then every other language. A cross-language disagreement is never resolved by changing the spec to match an outlier; the outlier is fixed.

Hard invariants (from `tessera-id/CLAUDE.md`; security-relevant changes must update both):

- 41-byte layout: `TS(6) || VARIANT(1) || CTR(2) || RANDOM(32)`, big-endian.
- Variant byte: `0x01` = Standard, `0x02` = HLC; everything else (including the cross-project `0x03`/`0x04`) rejected.
- Canonical encodings: Base64URL (55 chars, no padding) and Crockford Base32 (66 chars, case-insensitive on decode). The final Crockford character carries 3 bits of value plus 2 bits of zero padding; Crockford decode rejects inputs whose 2 trailing low padding bits of that final character are non-zero (the implementations reject a non-zero low-2-bit pad).
- HLC drift bound: `HLC_MAX_DRIFT_MS = 60_000` ms. Peer HLC more than 60 s ahead of local physical time is a hard `HLCDriftError`, not a silent clamp.
- `StandardGenerator` is *not* internally locked (deliberate); `HLCGenerator` *is* internally locked (the `(l, c)` RMW must be atomic).
- Randomness comes from the OS CSPRNG only: `getrandom(2)` / `getentropy(3)` / `BCryptGenRandom` / `os.urandom` / `SecureRandom` / `crypto.getRandomValues`. No userspace PRNG fallback.

Conformance gate: `tools/conformance/run.sh` is the branch-protection check on `main`. TesseraID, TesseraHash, and TesseraSeal all flow through the same harness; the latest cross-language run (2026-06-10) reports 0 failures across all eight languages.

References

C. Adams, P. Cain, D. Pinkas, and R. Zuccherato. Internet X.509 Public Key Infrastructure Time-Stamp Protocol (TSP). RFC 3161, IETF, August 2001. URL https://www.rfc-editor.org/rfc/rfc3161.

E. Barker. Recommendation for Key Management: Part 1 — General. Technical Report SP 800-57 Part 1, Revision 5, National Institute of Standards and Technology, May 2020. URL https://doi.org/10.6028/NIST.SP.800-57pt1r5.

G. Brassard, P. Høyer, and A. Tapp. Quantum cryptanalysis of hash and claw-free functions. In *LATIN '98: Theoretical Informatics, LNCS*, volume 1380, pages 163–169. Springer, 1998. Original conference talk 1997. Also arXiv:quant-ph/9705002.

California State Legislature. California Consumer Privacy Act of 2018 (CCPA). California Civil Code §§ 1798.100 et seq., 2018. URL https://oag.ca.gov/privacy/ccpa.

K. M. Chandy and L. Lamport. Distributed Snapshots: Determining Global States of Distributed Systems. *ACM Transactions on Computer Systems*, 3(1):63–75, February 1985. URL https://doi.org/10.1145/214451.214456.

Cockroach Labs. CockroachDB Architecture: Time and Hybrid Logical Clocks. Technical documentation. URL https://www.cockroachlabs.com/docs/stable/architecture/transaction-layer.html. Production use of HLC for distributed transactions.

Common Crawl Foundation. Common Crawl: An open repository of web crawl data. Foundation website and dataset releases, 2008–present. URL https://commoncrawl.org/.

D. Crockford. Base 32. Personal specification, 2002. URL https://www.crockford.com/base32.html. Defines the human-typable Base32 alphabet 0-9 + A-Z minus I, L, O, U.

K. Davis, B. Peabody, and P. Leach. Universally Unique IDentifiers (UUIDs). RFC 9562, IETF, May 2024. URL https://www.rfc-editor.org/rfc/rfc9562. Defines UUIDv6, UUIDv7, UUIDv8; obsoletes RFC 4122.

European Parliament and Council. Regulation (EU) 2016/679 (General Data Protection Regulation). Official Journal of the European Union, April 2016. URL https://eur-lex.europa.eu/eli/reg/2016/679/oj.

European Parliament and Council. Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (AI Act). Official Journal of the European Union, July 2024. URL https://eur-lex.europa.eu/eli/reg/2024/1689/oj.

A. Feerasta et al. ULID: Universally unique lexicographically sortable identifier. Community specification, 2016. URL https://github.com/ulid/spec.

L. K. Grover. A fast quantum mechanical algorithm for database search. In *Proceedings of the 28th Annual ACM Symposium on Theory of Computing (STOC '96)*, pages 212–219, 1996. URL https://arxiv.org/abs/quant-ph/9605043. arXiv:quant-ph/9605043.

IEEE. IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems. IEEE Std 1588-2019. URL https://standards.ieee.org/ieee/1588/6825/. PTP version 2.1.

M. Jones, J. Bradley, and N. Sakimura. JSON Web Token (JWT). RFC 7519, IETF, May 2015. URL https://www.rfc-editor.org/rfc/rfc7519.

S. Josefsson. The Base16, Base32, and Base64 Data Encodings. RFC 4648, IETF, October 2006. URL https://www.rfc-editor.org/rfc/rfc4648.

H. Krawczyk, M. Bellare, and R. Canetti. HMAC: Keyed-Hashing for Message Authentication. RFC 2104, IETF, February 1997. URL https://www.rfc-editor.org/rfc/rfc2104.

S. Kulkarni, M. Demirbas, D. Madappa, B. Avva, and M. Leone. Logical Physical Clocks and Consistent Snapshots in Globally Distributed Databases. Technical Report 2014-04, Department of Computer Science and Engineering, University at Buffalo (SUNY), 2014. URL https://cse.buffalo.edu/tech-reports/2014-04.pdf.

P. Leach, M. Mealling, and R. Salz. A Universally Unique IDentifier (UUID) URN Namespace. RFC 4122, IETF, July 2005. URL https://www.rfc-editor.org/rfc/rfc4122.

V. Mihalcea. TSID — A Time-Sorted, K-Sortable Unique Identifier. Open-source library and writeup, 2020. URL https://vladmihalcea.com/uuid-database-primary-key/. 64-bit uncoordinated time-ordered ID: 42-bit ms timestamp + 22-bit random/sequence.

D. Mills, J. Martin, J. Burbank, and W. Kasch. Network Time Protocol Version 4: Protocol and Algorithms Specification. RFC 5905, IETF, June 2010. URL https://www.rfc-editor.org/rfc/rfc5905.

National Institute of Standards and Technology. SHA-3 Standard: Permutation-Based Hash and Extendable-Output Functions. Technical Report FIPS PUB 202, U.S. Department of Commerce, 2015. URL https://nvlpubs.nist.gov/nistpubs/FIPS/NIST.FIPS.202.pdf.

NIST. Secure Hash Standard (SHS). Technical Report FIPS 180-4, National Institute of Standards and Technology, August 2015. URL https://doi.org/10.6028/NIST.FIPS.180-4. Defines SHA-256, SHA-384, SHA-512.

NIST. Advanced Encryption Standard (AES). Technical Report FIPS 197 (Updated), National Institute of Standards and Technology, May 2023a. URL https://doi.org/10.6028/NIST.FIPS.197-upd1.

NIST. Artificial Intelligence Risk Management Framework (AI RMF 1.0). Technical Report AI 100-1, National Institute of Standards and Technology, January 2023b. URL https://doi.org/10.6028/NIST.AI.100-1.

NIST. Module-Lattice-Based Key-Encapsulation Mechanism Standard. Technical Report FIPS 203, National Institute of Standards and Technology, August 2024a. URL https://doi.org/10.6028/NIST.FIPS.203. Defines ML-KEM, formerly known as CRYSTALS-Kyber.

NIST. Module-Lattice-Based Digital Signature Standard. Technical Report FIPS 204, National Institute of Standards and Technology, August 2024b. URL https://doi.org/10.6028/NIST.FIPS.204. Defines ML-DSA, formerly known as CRYSTALS-Dilithium.

PASETO Working Group. PASETO: Platform-agnostic security tokens. Specification at paseto.io, 2018. URL https://paseto.io/.

Roughtime Working Group. Roughtime: Securing Time with Digital Signatures. Internet-Draft draft-ietf-ntp-roughtime, IETF, 2024. URL https://datatracker.ietf.org/doc/draft-ietf-ntp-roughtime/.

Segment, Inc. KSUID: K-sortable globally unique ids. Open-source library and specification, 2017. URL https://github.com/segmentio/ksuid.

A. Sitnik. NanoID — A tiny, secure, URL-friendly, unique string ID generator. Open-source library, 2017. URL https://github.com/ai/nanoid. Configurable-length random ID. Default 21 chars over a 64-char URL-safe alphabet = 126 bits of randomness.

Twitter Engineering. Announcing snowflake. Engineering blog post, June 2010. URL https://blog.x.com/engineering/en_us/a/2010/announcing-snowflake. 64-bit time-ordered ID format: 41-bit timestamp + 10-bit machine ID + 12-bit sequence.