

Database Management Systems (CSN-351)

SQL (Contd. 3)

BTech 3rd Year (CS) + Minor + Audit

Instructor: **Ranita Biswas**
Department of Computer Science and Engineering
Indian Institute of Technology Roorkee
Roorkee, Uttarakhand - 247 667, India



Test for the Absence of Duplicate Tuples

course(course_id, title, dept_name, credits)

section(course_id, sec_id, semester, year, building, room_number, time_slot_id)

- Find all courses that were offered exactly once in 2009.

Test for the Absence of Duplicate Tuples

course(course_id, title, dept_name, credits)

section(course_id, sec_id, semester, year, building, room_number, time_slot_id)

- Find all courses that were offered exactly once in 2009.

```
select T.course_id
from course as T
where unique (select R.course_id
               from section as R
               where T.course_id = R.course_id and
                  R.year = 2009);
```

Test for the Presence of Duplicate Tuples

course(course_id, title, dept_name, credits)

section(course_id, sec_id, semester, year, building, room_number, time_slot_id)

- Find all courses that were offered at least twice in 2009.

Test for the Presence of Duplicate Tuples

course(course_id, title, dept_name, credits)

section(course_id, sec_id, semester, year, building, room_number, time_slot_id)

- Find all courses that were offered at least twice in 2009.

```
select T.course_id
from course as T
where not unique (select R.course_id
                  from section as R
                  where T.course_id = R.course_id and
                        R.year = 2009);
```

Subqueries in the From Clause

instructor(ID, name, dept_name, salary)

- Find the average instructors' salaries of those departments where the average salary is greater than 42,000.

Subqueries in the From Clause

instructor(ID, name, dept_name, salary)

- Find the average instructors' salaries of those departments where the average salary is greater than 42,000.

```
select dept_name, avg_salary
from (select dept_name, avg (salary) as avg_salary
      from instructor
      group by dept_name)
where avg_salary > 42000;
```

Subqueries in the From Clause

instructor(ID, name, dept_name, salary)

- Find the average instructors' salaries of those departments where the average salary is greater than 42,000.

```
select dept_name, avg_salary
from (select dept_name, avg (salary) as avg_salary
      from instructor
      group by dept_name)
where avg_salary > 42000;
```

```
select dept_name, avg_salary
from (select dept_name, avg (salary)
      from instructor
      group by dept_name)
      as dept_avg (dept_name, avg_salary)
where avg_salary > 42000;
```


Subqueries in the From Clause (contd.)

instructor(ID, name, dept_name, salary)

- Find the maximum across all departments of the total salary at each department.

Subqueries in the From Clause (contd.)

instructor(ID, name, dept_name, salary)

- Find the maximum across all departments of the total salary at each department.

```
select max(tot_salary)  
from (select dept_name, sum(salary)  
      from instructor  
      group by dept_name) as dept_total (dept_name, tot_salary);
```

The lateral Clause

instructor(ID, name, dept_name, salary)

- Find the names of each instructor, along with their salary and the average salary in their department.

The lateral Clause

instructor(ID, name, dept_name, salary)

- Find the names of each instructor, along with their salary and the average salary in their department.

```
select name, salary, avg_salary
from instructor I1, lateral (select avg(salary) as avg_salary
                             from instructor I2
                             where I2.dept_name= I1.dept_name);
```

The **with** Clause

department(dept_name, building, budget)

- Find the departments with the maximum budget.

The **with** Clause

department(dept_name, building, budget)

- Find the departments with the maximum budget.

```
with max_budget (value) as  
    (select max(budget)  
     from department)  
select budget  
from department, max_budget  
where department.budget = max_budget.value;
```

The **with** Clause (contd.)

instructor(ID, name, dept_name, salary)

- Find all departments where the total salary is greater than the average of the total salary at all departments.

The **with** Clause (contd.)

instructor(ID, name, dept_name, salary)

- Find all departments where the total salary is greater than the average of the total salary at all departments.

```
with dept_total (dept_name, value) as
    (select dept_name, sum(salary)
     from instructor
     group by dept_name),
dept_total_avg(value) as
    (select avg(value)
     from dept_total)
select dept_name
from dept_total, dept_total_avg
where dept_total.value >= dept_total_avg.value;
```


Scalar Subqueries

instructor(ID, name, dept_name, salary)

department(dept_name, building, budget)

- List all departments along with the number of instructors in each department.

Scalar Subqueries

instructor(ID, name, dept_name, salary)

department(dept_name, building, budget)

- List all departments along with the number of instructors in each department.

```
select dept_name,  
      (select count(*)  
       from instructor  
       where department.dept_name = instructor.dept_name)  
      as num_instructors  
from department;
```

Deletion

delete from r
where P ;

Deletion

delete from r
where P ;

- Delete all tuples from the *instructor* relation.

Deletion

delete from r
where P ;

- Delete all tuples from the *instructor* relation.

delete from *instructor*;

Deletion

delete from r
where P ;

- Delete all tuples from the *instructor* relation.

delete from *instructor*;

- Delete all tuples in the *instructor* relation pertaining to instructors in the Finance department.

Deletion

delete from r
where P ;

- Delete all tuples from the *instructor* relation.

delete from *instructor*;

- Delete all tuples in the *instructor* relation pertaining to instructors in the Finance department.

delete from *instructor*
where *dept_name* = 'Finance';

Deletion (contd.)

- Delete all instructors with a salary between 13,000 and 15,000.

Deletion (contd.)

- Delete all instructors with a salary between 13,000 and 15,000.

```
delete from instructor  
where salary between 13000 and 15000;
```

Deletion (contd.)

- Delete all instructors with a salary between 13,000 and 15,000.

```
delete from instructor  
where salary between 13000 and 15000;
```

- Delete all tuples in the *instructor* relation for those instructors associated with a department located in the Watson building.

Deletion (contd.)

- Delete all instructors with a salary between 13,000 and 15,000.

```
delete from instructor  
where salary between 13000 and 15000;
```

- Delete all tuples in the *instructor* relation for those instructors associated with a department located in the Watson building.

```
delete from instructor  
where dept_name in (select dept_name  
                        from department  
                        where building = 'Watson');
```

Deletion (contd.)

- Delete the records of all instructors with salary below the average at the university.

Deletion (contd.)

- Delete the records of all instructors with salary below the average at the university.

```
delete from instructor  
where salary < (select avg (salary)  
                from instructor);
```

Insertion

```
insert into course  
values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

Insertion

```
insert into course  
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

```
insert into course (course_id, title, dept_name, credits)  
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

```
insert into course (title, course_id, credits, dept_name)  
  values ('Database Systems', 'CS-437', 4, 'Comp. Sci.');
```

Insertion (contd.)

- Make each student in the Music department who has earned more than 144 credit hours, an instructor in the Music department, with a salary of 18,000.

Insertion (contd.)

- Make each student in the Music department who has earned more than 144 credit hours, an instructor in the Music department, with a salary of 18,000.

```
insert into instructor  
  select ID, name, dept_name, 18000  
  from student  
  where dept_name = 'Music' and tot_cred > 144;
```

Insertion (contd.)

```
insert into student  
  select *  
  from student;
```

Insertion (contd.)

```
insert into student  
  select *  
  from student;
```

```
insert into student  
  values ('3003', 'Green', 'Finance', null);
```

Updates

- Increase salaries of all instructors by 5 percent.

Updates

- Increase salaries of all instructors by 5 percent.

```
update instructor  
set salary = salary * 1.05;
```

Updates

- Increase salaries of all instructors by 5 percent.

```
update instructor  
set salary = salary * 1.05;
```

- Increase salaries of all instructors whose salary is less than 70,000 by 5 percent.

Updates

- Increase salaries of all instructors by 5 percent.

```
update instructor  
set salary = salary * 1.05;
```

- Increase salaries of all instructors whose salary is less than 70,000 by 5 percent.

```
update instructor  
set salary = salary * 1.05  
where salary < 70000;
```

Updates (contd.)

- Give a 5 percent salary raise to instructors whose salary is less than average.

Updates (contd.)

- Give a 5 percent salary raise to instructors whose salary is less than average.

```
update instructor  
set salary = salary * 1.05  
where salary < (select avg (salary)  
                    from instructor);
```

Updates (contd.)

- Give a 5 percent salary raise to instructors whose salary is less than average.

```
update instructor  
set salary = salary * 1.05  
where salary < (select avg (salary)  
                from instructor);
```

- All instructors with salary over 100,000 receive a 3 percent raise, whereas all others receive a 5 percent raise.

Updates (contd.)

- Give a 5 percent salary raise to instructors whose salary is less than average.

```
update instructor  
set salary = salary * 1.05  
where salary < (select avg (salary)  
                        from instructor);
```

- All instructors with salary over 100,000 receive a 3 percent raise, whereas all others receive a 5 percent raise.

```
update instructor  
set salary = salary * 1.03  
where salary > 100000;
```

```
update instructor  
set salary = salary * 1.05  
where salary <= 100000;
```

Updates (contd.)

```
update instructor  
set salary = case  
           when salary <= 100000 then salary * 1.05  
           else salary * 1.03  
end
```

Updates (contd.)

```
update instructor
set salary = case
    when salary <= 100000 then salary * 1.05
    else salary * 1.03
end

case
    when pred1 then result1
    when pred2 then result2
    ...
    when predn then resultn
    else result0
end
```

Updates (contd.)

- Set the *tot_cred* attribute of each *student* tuple to the sum of the credits of courses successfully completed by the student.

Updates (contd.)

- Set the *tot_cred* attribute of each *student* tuple to the sum of the credits of courses successfully completed by the student.

```
update student S  
set tot_cred = (  
    select sum(credits)  
    from takes natural join course  
    where S.ID= takes.ID and  
        takes.grade <> 'F' and  
        takes.grade is not null);
```

Updates (contd.)

- Set the *tot_cred* attribute of each *student* tuple to the sum of the credits of courses successfully completed by the student.

```
update student S  
set tot_cred = (  
    select sum(credits)  
    from takes natural join course  
    where S.ID= takes.ID and  
        takes.grade <> 'F' and  
        takes.grade is not null);
```

```
select case  
    when sum(credits) is not null then sum(credits)  
    else 0  
end
```