

# Database Management Systems (CSN-351)

## Concurrency Control

**BTech 3rd Year (CS) + Minor + Audit**

Instructor: **Ranita Biswas**  
Department of Computer Science and Engineering  
Indian Institute of Technology Roorkee  
Roorkee, Uttarakhand - 247 667, India



# Lock-Based Protocols

**Shared Lock:** If a transaction  $T_i$  has obtained a shared-mode lock (denoted by  $S$ ) on item  $Q$ , then  $T_i$  can read, but cannot write,  $Q$ .

# Lock-Based Protocols

**Shared Lock:** If a transaction  $T_i$  has obtained a shared-mode lock (denoted by  $S$ ) on item  $Q$ , then  $T_i$  can read, but cannot write,  $Q$ .

**Exclusive Lock:** If a transaction  $T_i$  has obtained an exclusive-mode lock (denoted by  $X$ ) on item  $Q$ , then  $T_i$  can both read and write  $Q$ .

# Lock-compatibility Matrix

	S	X
S	true	false
X	false	false

# Transactions with Locks

$T_1$ : lock-X( $B$ );  
  read( $B$ );  
   $B := B - 50$ ;  
  write( $B$ );  
  unlock( $B$ );  
  lock-X( $A$ );  
  read( $A$ );  
   $A := A + 50$ ;  
  write( $A$ );  
  unlock( $A$ ).

$T_2$ : lock-S( $A$ );  
  read( $A$ );  
  unlock( $A$ );  
  lock-S( $B$ );  
  read( $B$ );  
  unlock( $B$ );  
  display( $A + B$ ).

# Schedule 1

$T_1$	$T_2$	concurrency-control manager
lock-X( $B$ )		grant-X( $B, T_1$ )
read( $B$ )		
$B := B - 50$		
write( $B$ )		
unlock( $B$ )		
	lock-S( $A$ )	
	read( $A$ )	grant-S( $A, T_2$ )
	unlock( $A$ )	
	lock-S( $B$ )	
		grant-S( $B, T_2$ )
	read( $B$ )	
	unlock( $B$ )	
	display( $A + B$ )	
lock-X( $A$ )		grant-X( $A, T_1$ )
read( $A$ )		
$A := A - 50$		
write( $A$ )		
unlock( $A$ )		

# Transactions with Delayed Locks

$T_3$ : lock-X( $B$ );  
read( $B$ );  
 $B := B - 50$ ;  
write( $B$ );  
lock-X( $A$ );  
read( $A$ );  
 $A := A + 50$ ;  
write( $A$ );  
unlock( $B$ );  
unlock( $A$ ).

$T_4$ : lock-S( $A$ );  
read( $A$ );  
lock-S( $B$ );  
read( $B$ );  
display( $A + B$ );  
unlock( $A$ );  
unlock( $B$ ).

# Schedule 2

$T_3$	$T_4$
lock-X( $B$ ) read( $B$ ) $B := B - 50$ write( $B$ )	
lock-X( $A$ )	lock-S( $A$ ) read( $A$ ) lock-S( $B$ )



# Problems

## Deadlock

# Problems

Deadlock

Starvation

# Granting of Locks

- There is no other transaction holding a lock on  $Q$  in a mode that conflicts with  $M$ .

# Granting of Locks

- There is no other transaction holding a lock on  $Q$  in a mode that conflicts with  $M$ .
- There is no other transaction that is waiting for a lock on  $Q$  and that made its lock request before  $T_i$ .

# Two-Phase Locking Protocol

- **Growing phase:** A transaction may obtain locks, but may not release any lock.

# Two-Phase Locking Protocol

- **Growing phase:** A transaction may obtain locks, but may not release any lock.
- **Shrinking phase:** A transaction may release locks, but may not obtain any new locks.

# Partial Schedule under 2-Phase Locking

$T_5$	$T_6$	$T_7$
lock-X( $A$ ) read( $A$ ) lock-S( $B$ ) read( $B$ ) write( $A$ ) unlock( $A$ )	lock-X( $A$ ) read( $A$ ) write( $A$ ) unlock( $A$ )	lock-S( $A$ ) read( $A$ )

# Transactions

$T_8$ : read( $a_1$ );  
read( $a_2$ );

...

read( $a_n$ );  
write( $a_1$ ).

$T_9$ : read( $a_1$ );  
read( $a_2$ );  
display( $a_1 + a_2$ ).



# Incomplete Schedule with a Lock Conversion

$T_8$	$T_9$
lock-S( $a_1$ )	lock-S( $a_1$ )
lock-S( $a_2$ )	lock-S( $a_2$ )
lock-S( $a_3$ )	
lock-S( $a_4$ )	
	unlock( $a_1$ )
	unlock( $a_2$ )
lock-S( $a_n$ )	
upgrade( $a_1$ )	

# Question 1

Consider the following two phase locking protocol. Suppose a transaction  $T$  accesses (for read or write operations), a certain set of objects  $\{O_1, \dots, O_k\}$ . This is done in the following manner:

Step 1:  $T$  acquires exclusive locks to  $O_1, \dots, O_k$  in increasing order of their addresses.

Step 2: The required operations are performed.

Step 3. All locks are released.

This protocol will

- guarantee serializability and deadlock-freedom
- guarantee neither serializability nor deadlock-freedom
- guarantee serializability but not deadlock-freedom
- guarantee deadlock-freedom but not serializability

# Locking Protocols

**Two-phase locking** → Serializable schedules

# Locking Protocols

**Two-phase locking** → Serializable schedules

**Strict two-phase locking** → Cascadeless schedules

# Locking Protocols

**Two-phase locking** → Serializable schedules

**Strict two-phase locking** → Cascadeless schedules

**Rigorous two-phase locking** → Strict schedules

# Timestamp-Based Protocols

**Transaction timestamps:** With each transaction  $T_i$  in the system, we associate a unique fixed timestamp, denoted by  $TS(T_i)$ .

# Timestamp-Based Protocols

**Transaction timestamps:** With each transaction  $T_i$  in the system, we associate a unique fixed timestamp, denoted by  $TS(T_i)$ .

**Data item timestamps**  $\rightarrow$  with each data item  $Q$  two timestamp values are associated.

- **W-timestamp**( $Q$ ) denotes the largest timestamp of any transaction that executed *write*( $Q$ ) successfully.
- **R-timestamp**( $Q$ ) denotes the largest timestamp of any transaction that executed *read*( $Q$ ) successfully.

# Timestamp-Ordering Protocol

$T_i$  issues *read*( $Q$ )



# Timestamp-Ordering Protocol

$T_i$  issues *read*( $Q$ )

(a) If  $TS(T_i) < \text{W-timestamp}(Q)$ :

(b) If  $TS(T_i) \geq \text{W-timestamp}(Q)$ :

# Timestamp-Ordering Protocol

$T_i$  issues *read*( $Q$ )

(a) If  $TS(T_i) < \text{W-timestamp}(Q)$ :

(b) If  $TS(T_i) \geq \text{W-timestamp}(Q)$ :

$T_i$  issues *write*( $Q$ )

# Timestamp-Ordering Protocol

$T_i$  issues *read*( $Q$ )

(a) If  $TS(T_i) < \text{W-timestamp}(Q)$ :

(b) If  $TS(T_i) \geq \text{W-timestamp}(Q)$ :

$T_i$  issues *write*( $Q$ )

(a) If  $TS(T_i) < \text{R-timestamp}(Q)$ :

(b) If  $TS(T_i) < \text{W-timestamp}(Q)$ :

(c) Else:

# Example Schedule

$T_{25}$	$T_{26}$
read( $B$ )	read( $B$ ) $B := B - 50$ write( $B$ )
read( $A$ )	read( $A$ )
display( $A + B$ )	$A := A + 50$ write( $A$ ) display( $A + B$ )

# Thomas' Write Rule

$T_{27}$	$T_{28}$
read(Q)	write(Q)
write(Q)	

# Thomas' Write Rule

$T_{27}$	$T_{28}$
read(Q)	write(Q)
write(Q)	

Generates **View Serializability**, not conflict serializability.

# View Equivalence

Schedules  $S$  and  $S'$  are said to be *view equivalent* if

- For each data item  $Q$ , if transaction  $T_i$  reads the initial value of  $Q$  in schedule  $S$ , then transaction  $T_i$  must, in schedule  $S'$ , also read the initial value of  $Q$ .

# View Equivalence

Schedules  $S$  and  $S'$  are said to be *view equivalent* if

- For each data item  $Q$ , if transaction  $T_i$  reads the initial value of  $Q$  in schedule  $S$ , then transaction  $T_i$  must, in schedule  $S'$ , also read the initial value of  $Q$ .
- For each data item  $Q$ , if transaction  $T_i$  executes  $read(Q)$  in schedule  $S$ , and if that value was produced by a  $write(Q)$  operation executed by transaction  $T_j$ , then the  $read(Q)$  operation of transaction  $T_i$  must, in schedule  $S'$ , also read the value of  $Q$  that was produced by the same  $write(Q)$  operation of transaction  $T_j$ .



# View Equivalence

Schedules  $S$  and  $S'$  are said to be *view equivalent* if

- For each data item  $Q$ , if transaction  $T_i$  reads the initial value of  $Q$  in schedule  $S$ , then transaction  $T_i$  must, in schedule  $S'$ , also read the initial value of  $Q$ .
- For each data item  $Q$ , if transaction  $T_i$  executes  $read(Q)$  in schedule  $S$ , and if that value was produced by a  $write(Q)$  operation executed by transaction  $T_j$ , then the  $read(Q)$  operation of transaction  $T_i$  must, in schedule  $S'$ , also read the value of  $Q$  that was produced by the same  $write(Q)$  operation of transaction  $T_j$ .
- For each data item  $Q$ , the transaction (if any) that performs the final  $write(Q)$  operation in schedule  $S$  must perform the final  $write(Q)$  operation in schedule  $S'$ .

# View Serializability

A schedule  $S$  is *view serializable* if it is view equivalent to a serial schedule.

# View Serializability

A schedule  $S$  is *view serializable* if it is view equivalent to a serial schedule.

$T_{27}$	$T_{28}$	$T_{29}$
read (Q)	write (Q)	write (Q)
write (Q)		

# View Serializability

A schedule  $S$  is *view serializable* if it is view equivalent to a serial schedule.

$T_{27}$	$T_{28}$	$T_{29}$
read ( $Q$ )	write ( $Q$ )	write ( $Q$ )
write ( $Q$ )		

**Blind writes** appear in any view-serializable schedule that is not conflict serializable.

# Snapshot Isolation

Guarantees that all reads made in a transaction will see a consistent snapshot of the database

# Snapshot Isolation

Guarantees that all reads made in a transaction will see a consistent snapshot of the database

The transaction itself will successfully commit only if no updates it has made conflict with any concurrent updates made since that snapshot.

# Snapshot Isolation

Guarantees that all reads made in a transaction will see a consistent snapshot of the database

The transaction itself will successfully commit only if no updates it has made conflict with any concurrent updates made since that snapshot.

Used by SQL Anywhere, InterBase, Firebird, Oracle, PostgreSQL, MongoDB and Microsoft SQL Server (2005 and later).