

Guides / Customizing Clerk / Build your own UI / Authentication

Build a custom forgot password flow

 Copy as markdown

 Open in ChatGPT



Warning

This guide is for users who want to build a custom flow . To use a *prebuilt* UI, use the [Account Portal pages](#) or [prebuilt components](#).



Important

This guide applies to the following Clerk SDKs:

- `@clerk/react` v6 or higher
- `@clerk/nextjs` v7 or higher
- `@clerk/expo` v3 or higher
- `@clerk/react-router` v3 or higher
- `@clerk/tanstack-react-start` v0.26.0 or higher

If you're using an older version of one of these SDKs, or are using the legacy API, refer to the [legacy API documentation](#).

It's common for a sign-in flow to include a flow for users that forgot their password.

In Clerk, the forgot password flow requires that either **Email** or **Phone** is enabled, as the password reset code can only be delivered to one of these identifiers.



1. Users can have an email address or phone number, or both. The user enters their email address or phone number and asks for a password reset code.
2. Clerk sends an email or SMS to the user, containing a code.
3. The user enters the code and a new password.
4. Clerk verifies the code, and if successful, updates the user's password and signs them in.
5. If `signOutOfOtherSessions` is `true`, the user is signed out of all other authenticated sessions.

This guide demonstrates how to build a custom user interface for a forgot password flow that you can add to your existing sign-in flow. This guide covers the following scenarios:

- The user has an email address as an identifier
- The user has a phone number as an identifier

 Tip

To allow users to update their password **after they've already signed in**, see the [custom flow for updating a user's password](#).

Email address

`src/components/forgot-password.tsx`



```
1 'use client'
2 import React from 'react'
3 import { useSignIn } from '@clerk/nextjs'
4 import { useRouter } from 'next/navigation'
5 -
```

↓ Expand code

src/components/forgot-password.tsx



```
1 'use client'
2 import React from 'react'
3 import { useSignIn } from '@clerk/nextjs'
4 import { useRouter } from 'next/navigation'
5 -
```

[↓ Expand code](#)

Handle compromised passwords

If you have enabled [rejection of compromised passwords](#) also on sign-in, then it is possible for the sign-in attempt to be rejected with the `form_password_pwned` error code.

In this case, you can prompt the user to reset their password using the exact same logic detailed in the previous section.

What did you think of this content?

[It was helpful](#)[It was not helpful](#)[I have feedback](#)

Last updated on Jul 28, 2026

[Edit on GitHub ↗](#)



Product

Authentication

B2B Authentication

Billing

CLI

Agents

SDKs

React

Next.js

Expo

View all

Resources

Documentation

Changelog

Glossary

Feature requests

Startups

Students

LLM Leaderboard

Company

About

Careers

Blog

Contact

Brand assets

Legal

Terms and conditions

Privacy policy

Website terms of use

Legal Resources

Do not sell/share my info

Cookie manager