

Machine-Level Programming: Control

Today

- **Control: Condition codes**
- Conditional branches
- Loops
- Switch Statements

Processor State (x86-64, Partial)

■ Information about currently executing program

- Temporary data
(`%rax`, ...)
- Location of runtime stack
(`%rsp`)
- Location of current code control point
(`%rip`, ...)
- Status of recent tests
(`CF`, `ZF`, `SF`, `OF`)

Current stack top

Registers

<code>%rax</code>	<code>%r8</code>
<code>%rbx</code>	<code>%r9</code>
<code>%rcx</code>	<code>%r10</code>
<code>%rdx</code>	<code>%r11</code>
<code>%rsi</code>	<code>%r12</code>
<code>%rdi</code>	<code>%r13</code>
<code>%rsp</code>	<code>%r14</code>
<code>%rbp</code>	<code>%r15</code>

`%rip`

Instruction pointer

<code>CF</code>	<code>ZF</code>	<code>SF</code>	<code>OF</code>
-----------------	-----------------	-----------------	-----------------

Condition codes

Condition Codes (Implicit Setting)

■ Single bit registers

- CF Carry Flag (for unsigned) SF Sign Flag (for signed)
- ZF Zero Flag OF Overflow Flag (for signed)

■ Implicitly set (think of it as side effect) by arithmetic operations

Example: `addq Src, Dest` \leftrightarrow `t = a+b`

carry flag **CF set** if carry out from most significant bit (unsigned overflow)

zero flag **ZF set** if `t == 0`

sign flag **SF set** if `t < 0` (as signed)

overflow flag **OF set** if two's-complement (signed) overflow
`(a > 0 && b > 0 && t < 0) || (a < 0 && b < 0 && t >= 0)`

■ Not set by `leaq` instruction

Condition Codes (Explicit Setting: Compare)

■ Explicit Setting by Compare Instruction

- `cmpq Src2, Src1`
- `cmpq b, a` like computing `a-b` without setting destination
→ contents of a and b are not changed
- **CF set** if carry out from most significant bit (used for unsigned comparisons)
- **ZF set** if `a == b`
- **SF set** if `(a-b) < 0` (as signed)
- **OF set** if two's-complement (signed) overflow
`(a>0 && b<0 && (a-b)<0) || (a<0 && b>0 && (a-b)>0)`

Condition Codes (Explicit Setting: Test)

■ Explicit Setting by Test instruction

- `testq Src2, Src1`
 - `testq b, a` like computing *a & b* ^{bitwise} without setting destination
- Sets condition codes based on value of Src1 & Src2
- Useful to have one of the operands be a mask
- **ZF set** when `a & b == 0`
- **SF set** when `a & b < 0`

Reading Condition Codes

■ SetX Instructions

- Set low-order byte of destination to 0 or 1 based on combinations of condition codes
- Does not alter remaining 7 bytes

SetX	Condition	Description
sete	ZF	Equal / Zero
setne ^{not equal}	$\sim ZF$	Not Equal / Not Zero
sets	SF	Negative
setns	$\sim SF$	Nonnegative
setg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
setge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
setl	$(SF \wedge OF)$	Less (Signed)
setle	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
seta	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
setb	CF	Below (unsigned)

x86-64 Integer Registers

<code>%rax</code>	<code>%al</code>
<code>%rbx</code>	<code>%bl</code>
<code>%rcx</code>	<code>%cl</code>
<code>%rdx</code>	<code>%dl</code>
<code>%rsi</code>	<code>%sil</code>
<code>%rdi</code>	<code>%dil</code>
<code>%rsp</code>	<code>%spl</code>
<code>%rbp</code>	<code>%bpl</code>

<code>%r8</code>	<code>%r8b</code>
<code>%r9</code>	<code>%r9b</code>
<code>%r10</code>	<code>%r10b</code>
<code>%r11</code>	<code>%r11b</code>
<code>%r12</code>	<code>%r12b</code>
<code>%r13</code>	<code>%r13b</code>
<code>%r14</code>	<code>%r14b</code>
<code>%r15</code>	<code>%r15b</code>

- Can reference low-order byte

Reading Condition Codes (Cont.)

■ SetX Instructions:

- Set single byte based on combination of condition codes

■ One of addressable byte registers

- Does not alter remaining bytes
- Typically use `movzbl` to finish job
 - 32-bit instructions also set upper 32 bits to 0

```
int gt (long x, long y)
{
    return x > y;
}
```

Register	Use(s)
<code>%rdi</code>	Argument x
<code>%rsi</code>	Argument y
<code>%rax</code>	Return value


```
cmpq    %rsi, %rdi    # Compare x:y → x-y
setg     %al          # Set when > setg
movzbl   %al, %eax    # Zero rest of %rax
ret
```

$\sim (SF \wedge OF) \ \& \ \sim ZF$

Greater (Signed)

Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements



Jumping

■ jX Instructions

- Jump to different part of code depending on condition codes

jX	Condition	Description
jmp	1	Unconditional
j e	ZF	Equal / Zero
j ne	$\sim ZF$	Not Equal / Not Zero
j s	SF	Negative
j ns	$\sim SF$	Nonnegative
j g	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
j ge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
j l	$(SF \wedge OF)$	Less (Signed)
j le	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
j a	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
j b	CF	Below (unsigned)

Conditional Branch Example (Old Style)

■ Generation

```
inek> gcc -Og -S -fno-if-conversion control.c
```

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

L4

if le
jump
L4

absdiff:

```
cmpq    %rsi, %rdi    # x:y
jle     .L4           → an address in the main memory
movq    %rdi, %rax
subq    %rsi, %rax
ret

.L4:      # x <= y
movq    %rsi, %rax
subq    %rdi, %rax
ret
```

```
cmpq    %rsi, %rdi
jle     .L4
movq    %rdi, %rax
subq    %rsi, %rax
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Expressing with Goto Code

- C allows `goto` statement
- Jump to position designated by label

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j
(long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

*how compiler
understands*

General Conditional Expression Translation (Using Branches)

C Code

```
val = Test ? Then_Expr : Else_Expr;
```

```
val = x > y ? x - y : y - x;
```

Goto Version

```
ntest = !Test;  
if (ntest) goto Else;  
val = Then_Expr;  
goto Done;  
Else:  
    val = Else_Expr;  
Done:  
    . . .
```

- Create separate code regions for then & else expressions
- Execute appropriate one

Using Conditional Moves

■ Conditional Move Instructions

- Instruction supports:
if (Test) Dest \leftarrow Src
- Supported in post-1995 x86 processors
- GCC tries to use them
 - But, only when known to be safe

■ Why?

- Branches are very disruptive to instruction flow through pipelines
- Conditional moves do not require control transfer

C Code

```
val = Test  
    ? Then_Expr  
    : Else_Expr;
```

Goto Version

```
result = Then_Expr;  
eval = Else_Expr;  
nt = !Test;  
if (nt) result = eval;  
return result;
```

Conditional Move Example

```

long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}

```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

absdiff:

```

    movq    %rdi, %rax    # x
    subq    %rsi, %rax    # result = x-y
    movq    %rsi, %rdx
    subq    %rdi, %rdx    # eval = y-x
    cmpq    %rsi, %rdi    # x:y
    cmovle  %rdx, %rax    # if <=, result = eval
    ret

```


Exercise

`cmpq b, a` like computing $a-b$ without setting dest

■ **CF set** if carry/borrow out from most significant bit
(used for unsigned comparisons)

■ **ZF set** if $a == b$

■ **SF set** if $(a-b) < 0$ (asigned)

■ **OF set** if two's-complement (signed) overflow

Test	Condition	Description
<code>sete</code>	SF	Equal / Zero
<code>setne</code>	$\sim SF$	Not Equal / Not Zero
<code>setb</code>	SF	Negative
<code>setnb</code>	$\sim SF$	Nonnegative
<code>setg</code>	$\sim (SF \wedge OF) \wedge \sim SF$	Greater (Signed)
<code>setge</code>	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
<code>setl</code>	$(SF \wedge OF)$	Less (Signed)
<code>setle</code>	$(SF \wedge OF) \vee SF$	Less or Equal (Signed)
<code>seta</code>	$\sim CF \wedge \sim SF$	Above (unsigned)
<code>setb</code>	CF	Below (unsigned)

0-1

```

xorq    %rax, %rax
subq    $1, %rax
cmpq    $2, %rax
setl    %al
movzblq %al, %eax
    
```

%rax	SF	CF	OF	ZF
0000000000000000	0	0	0	1
1111111111111111	1	0	0	0
1111111111111111	1	1	0	0
1111111111111111	1	0	0	0
0000000000000001	1	0	0	0

Note: `setl` and `movzblq` do not modify condition codes

Handwritten binary subtraction:

```

  11111111
- 11111111
-----
  00000000
    
```

Handwritten binary subtraction:

```

  1111
- 1110
-----
  11101
    
```

Handwritten text: $x - y < 0$

Handwritten text: 0 1 1

Bad Cases for Conditional Move

Expensive Computations

```
val = Test(x) ? Hard1(x) : Hard2(x) ;
```

- Both values get computed
- Only makes sense when computations are very simple

Risky Computations

```
val = p ? *p : 0 ;
```

- Both values get computed
- May have undesirable effects

Computations with side effects

```
val = x > 0 ? x*=7 : x+=3 ;
```

- Both values get computed
- Must be side-effect free

Today

■ Control: Condition codes

■ Conditional branches

■ Loops

■ Switch Statements

leaq 0x8(%rax), %rbx

effective
address
of mem

leaq stores it
here

⇒ leaq does not set
condition codes

cmpq %rbx, %rax ⇒ %rax - %rbx

condition
code

xorq %rax, %rax %rax does not
change ⇒ ZF SF OF

ZF

SF

OF

1



0

0

sete %rdx

condition is
zero flag
= 1

⇒ set lower
byte to 1



condition codes → implicitly set by
ARITHMETIC Instructions

cmovele %rdx, %rax → move rdx to rax
if less than or equal (some instruction already
set condition codes)

“Do-While” Loop Example

C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
    loop:
        result += x & 0x1;
        x >>= 1;
        if(x) goto loop;
    return result;
}
```

- Count number of 1's in argument *x* (“popcount”)
- Use conditional branch to either continue looping or to exit loop

“Do-While” Loop Compilation

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

```
        movl    $0, %eax    # result = 0
.L2:                                # loop:
        movq    %rdi, %rdx
        andl    $1, %edx    # t = x & 0x1
        addq    %rdx, %rax  # result += t
        shrq    %rdi        # x >>= 1
        jne     .L2         # if (x) goto loop
        rep; ret
```

General “Do-While” Translation

C Code

```
do  
    Body  
while (Test) ;
```

Goto Version

```
loop:  
    Body  
    if (Test)  
        goto loop
```

■ **Body:** {
 Statement₁;
 Statement₂;
 ...
 Statement_n;
}

General “While” Translation #1

- “Jump-to-middle” translation
- Used with `-Og`

While version

```
while (Test)  
    Body
```



Goto Version

```
    goto test;  
loop:  
    Body  
test:  
    if (Test)  
        goto loop;  
done:
```

While Loop Example #1

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```


- Compare to do-while version of function
- Initial goto starts loop at test

General “While” Translation #2

While version

```
while (Test)  
    Body
```

- “Do-while” conversion
- Used with `-O1`



Do-While Version

```
if (!Test)  
    goto done;  
do  
    Body  
    while (Test) ;  
done:
```



Goto Version

```
if (!Test)  
    goto done;  
loop:  
    Body  
    if (Test)  
        goto loop;  
done:
```

While Loop Example #2

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Do-While Version

```
long pcount_goto_dw
(unsigned long x) {
    long result = 0;
    if (!x) goto done;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
done:
    return result;
}
```

- Compare to do-while version of function
- Initial conditional guards entrance to loop

“For” Loop Form

General Form

```
for (Init; Test; Update )
    Body
```

```
#define WSIZE 8*sizeof(int)
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{
    unsigned bit =
        (x >> i) & 0x1;
    result += bit;
}
```

“For” Loop → While Loop

For Version

```
for (Init; Test; Update )  
    Body
```



While Version

```
Init ;  
while (Test ) {  
    Body  
    Update ;  
}
```

For-While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{
    unsigned bit =
        (x >> i) & 0x1;
    result += bit;
}
```

```
long pcount_for_while
(unsigned long x)
{
    size_t i;
    long result = 0;
    i = 0;
    while (i < WSIZE)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
        i++;
    }
    return result;
}
```

“For” Loop Do-While Conversion

C Code

Goto Version

```
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

- Initial test can be optimized away

```
long pcount_for_goto_dw
(unsigned long x) {
    size_t i;
    long result = 0;
    i = 0; Init
    if (! (i < WSIZE)) !Test
    goto done;
loop:
    {
        unsigned bit =
            (x >> i) & 0x1; Body
        result += bit;
    }
    i++; Update
    if (i < WSIZE) Test
        goto loop;
done:
    return result;
}
```

Today

- Control: Condition codes
- Conditional branches
- Loops
- **Switch Statements**

```
long switch_eg
(long x, long y, long z)
{
    long w = 1;
    switch(x) {
    case 1:
        w = y*z;
        break;
    case 2:
        w = y/z;
        /* Fall Through */
    case 3:
        w += z;
        break;
    case 5:
    case 6:
        w -= z;
        break;
    default:
        w = 2;
    }
    return w;
}
```

Switch Statement Example

- Multiple case labels
 - Here: 5 & 6
- Fall through cases
 - Here: 2
- Missing cases
 - Here: 4

Jump Table Structure

Switch Form


```
switch(x) {
  case val_0:
    Block 0
  case val_1:
    Block 1
    . . .
  case val_n-1:
    Block n-1
}
```

Translation (Extended C)

```
goto *JTab[x];
```

let's say x=2

Jump Table



Jump Targets

Targ0:

Code Block
0

Targ1:

Code Block
1

Targ2:

Code Block
2

•
•
•

Targn-1:

Code Block
n-1


Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

.rodata → read only data

Setup:

```
switch_eg:
    movq    %rdx, %rcx
    cmpq    $6, %rdi    # x:6
    ja      .L8
    jmp     *.L4(, %rdi, 8)
```



What range of values
takes default?

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Note that **w** not
initialized here

Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Jump table

.section	.rodata	
.align 8		
.L4:		
.quad	.L8	# x = 0
.quad	.L3	# x = 1
.quad	.L5	# x = 2
.quad	.L9	# x = 3
.quad	.L8	# x = 4
.quad	.L7	# x = 5
.quad	.L7	# x = 6

Setup:

```
switch_eg:
    movq    %rdx, %rcx
    cmpq    $6, %rdi      # x:6
    ja      .L8            # Use default
    jmp     *.L4(,%rdi,8)  # goto *JTab[x]
```

Indirect
jump



Assembly Setup Explanation

■ Table Structure

- Each target requires 8 bytes
- Base address at `.L4`

■ Jumping

- **Direct:** `jmp .L8`
- Jump target is denoted by label `.L8`
- **Indirect:** `jmp *.L4(,%rdi,8)`
- Start of jump table: `.L4`
- Must scale by factor of 8 (addresses are 8 bytes)
- Fetch target from effective Address `.L4 + x*8`
 - Only for $0 \leq x \leq 6$

Jump table

```
.section      .rodata
    .align 8
.L4:
    .quad     .L8    # x = 0
    .quad     .L3    # x = 1
    .quad     .L5    # x = 2
    .quad     .L9    # x = 3
    .quad     .L8    # x = 4
    .quad     .L7    # x = 5
    .quad     .L7    # x = 6
```

Jump Table

Jump table

```
.section    .rodata
.align 8
.L4:
.quad      .L8    # x = 0
.quad      .L3    # x = 1
.quad      .L5    # x = 2
.quad      .L9    # x = 3
.quad      .L8    # x = 4
.quad      .L7    # x = 5
.quad      .L7    # x = 6
```

```
switch(x) {
case 1:      // .L3
    w = y*z;
    break;
case 2:      // .L5
    w = y/z;
    /* Fall Through */
case 3:      // .L9
    w += z;
    break;
case 5:
case 6:      // .L7
    w -= z;
    break;
default:    // .L8
    w = 2;
}
```

Code Blocks (x == 1)

```
switch(x) {
case 1:      // .L3
    w = y*z;
    break;
    . . .
}
```

```
.L3:
    movq    %rsi, %rax    # y
    imulq   %rdx, %rax    # y*z
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Handling Fall-Through

```
long w = 1;  
    . . .  
switch(x) {  
    . . .  
case 2:   
    w = y/z;  
    /* Fall Through */  
case 3:  
    w += z;  
    break;  
    . . .  
}
```

case 2:
 w = y/z;
 goto merge;

case 3:
 w = 1;
merge:
 w += z;

Code Blocks (x == 2, x == 3)

```

long w = 1;
. . .
switch(x) {
. . .
case 2:
    w = y/z;
    /* Fall Through */
case 3:
    w += z;
    break;
. . .
}

```

```

.L5:                                # Case 2
    movq    %rsi, %rax
    cqto
    idivq   %rcx                    # y/z
    jmp     .L6                    # goto merge
.L9:                                # Case 3
    movl    $1, %eax               # w = 1
.L6:                                # merge:
    addq    %rcx, %rax             # w += z
    ret

```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Code Blocks (x == 5, x == 6, default)

```
switch(x) {
    . . .
    case 5:  // .L7
    case 6:  // .L7
        w -= z;
        break;
    default: // .L8
        w = 2;
}
```

```
.L7:                # Case 5,6
    movl    $1, %eax    # w = 1
    subq    %rdx, %rax  # w -= z
    ret
.L8:                # Default:
    movl    $2, %eax    # 2
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Summarizing

■ C Control

- if-then-else
- do-while
- while, for
- switch

■ Assembler Control

- Conditional jump
- Conditional move
- Indirect jump (via jump tables)
- Compiler generates code sequence to implement more complex control

■ Standard Techniques

- Loops converted to do-while or jump-to-middle form
- Large switch statements use jump tables
- Sparse switch statements may use decision trees (if-elseif-elseif-else)

Summary

■ Today

- Control: Condition codes
- Conditional branches & conditional moves
- Loops
- Switch statements