

CMC-7100 CHAIRMAN UNIT
CMD-7200 DELEGATE UNIT

- Highly sensitive and unidirectional 457 mm (18") long gooseneck condenser microphone.
- The microphone is fitted with a diffused ring LED housing.
- Conference units have LCD display which shows ON/OFF status, Voting options and Voting results.
- Delegate Unit has a TALK switch. When put ON, the LED bar in the knob of TALK switch lights up.
- Delegate unit has three voting option buttons.
- Chairman unit has an additional switch for the PRIORITY function.
- Chairman unit has five buttons for various functions in a voting application.
- RJ45 connecting ports available for using CAT-5E/6 shielded cable connections.



EU-70 EXTENSION UNIT

new product

- Permits easy expansion by allowing connection of upto 90 conference units.
- Compact table top unit with facility of rigid mounting through fixing clamps.
- RJ45 connecting ports available for using CAT-5E/6 shielded cable connections.
- RED Led indicator for power and system operation.
- AC mains operation.

SPECIFICATIONS	CMA-7400
FREQUENCY RESPONSE	100-15,000Hz
S/N RATIO	> 96dB
AUDIO OUTPUT	+18dB Balanced
POWER REQUIREMENT	AC: 220-240V, 50/60Hz
DIMENSIONS	W485 × H105× D330 mm
WEIGHT	4.70 kg
ACCESSORIES	F/XLR to 6.5 mm Mono Jack Cable, 15m RJ45 CAT 5E Shielded Black Cable, Audio Visual RJ45 CAT-5E Patch Cable, Software Dongle, Licence, Key Dongle, USB to RJ45 convertor.

SPECIFICATIONS	CMC-7100	CMD-7200
MICROPHONE SENSITIVITY	7mV/Pa	7mV/Pa
FREQUENCY RESPONSE	100-15,000Hz	100-15,000Hz
IMPEDANCE	1000Ω	1000Ω
CONNECTION	RJ45 Port	RJ45 Port
MICROPHONE TYPE	Unidirectional Condenser	Unidirectional Condenser
DIMENSIONS	W145 × H55 × D175mm	W145 X H55 X D175mm
WEIGHT	550g	550g
ACCESSORIES	Foam Windshield, 2m RJ45 CAT-5E Shielded Black Cable, Gooseneck Mic	

SPECIFICATIONS	EU-70
POWER REQUIREMENT	AC: 220-240V, 50/60Hz
POWER INDICATOR	RED LED
CONNECTION	RJ45 PORT
DIMENSIONS	W253 × H63 × D226 MM
WEIGHT	2.00kg



