CMD-5200 DELEGATE UNIT



CMC-5100 CHAIRMAN UNIT



Each unit is provided with a 470 mm (18.5") long gooseneck condenser microphone which is highly sensitive and unidirectional. The microphone is provided with a diffused LED housing to provide positive visual identification of the unit in operation. The built-in speaker in each unit provides clear and crisp sound reinforcement. The output level of the speaker can be adjusted through a recessed volume control in the unit. Each unit has a headphone output, TALK switch and a TALK LED. The MIC LEVEL LED in the delegate unit flickers to indicate microphone input signal level.

Apart from delegate unit functions, the chairman unit has a TALK switch with LED. It also has a PRIORITY switch with LED. When PRIORITY switch is pressed, a chime tone is generated to seek attention and mute the active delegate microphones.

SPECIFICATIONS	CMA-5400
LINE OUTPUT 1	17.5V DC/3A Max.; -34dBV (20mV)
LINE OUTPUT 2	17.5V DC/3A Max.; -34dBV (20mV)
POWER OUTPUT	50W RMS at 2% THD, 90W Max.
INPUTS	3×Mic 0.65mV/4.7kΩ
	1×Aux 100mV/470kΩ
FREQUENCY RESPONSE	60-14,000Hz (± 3dB)
SIGNAL TO NOISE RATIO	> 60dB
TONE CONTROLS	Bass: -10dB at 100Hz
	Treble: -10dB at 10kHz
PREAMP OUTPUT	200mV/600Ω
LINE OUTPUT	1V/1kΩ
SEND OUTPUT	200mV/600Ω
RETURN INPUT	200mV/10kΩ
SPEAKER OUTPUT	4Ω, 8Ω, 16Ω, 70V & 100V
POWER REQUIREMENT	AC: 220-240V, 50/60Hz
	DC: 24V (2×12V Car Battery)
POWER CONSUMPTION	250VA
PROTECTIONS	AC Fuse 1×3A, DC Fuse 3×10A
DIMENSIONS	W483 × H110× D325 mm
WEIGHT	10.50kg
ACCESSORIES	1× Connection Cable CC-46
	1× Extension Cable CC-47
	1× Fuse 3A, 2 × Fuse 10A

SPECIFICATIONS	CMC-5100	CMD-5200
MICROPHONE	7.5mV/Pa	7.5mV/Pa
CURRENT CONSUMPTION	< 50mA Max.	< 50mA Max.
MIC AUTO SWITCH-OFF TIME	—	75 seconds approx.
INPUT	Line	Line
OUTPUT	Line, Headphone	Line, Headphone
SPEAKER	Max Input 300mW	Max Input 300mW
CONTROLS	Priority Switch,	Talk Switch,
	Talk Switch,	Speaker Volume Control,
	Speaker Volume Control,	Headphone Volume Control
	Headphone Volume Control	—
DIMENSIONS	W118 × H70 × D160 mm	W118 × H70 × D160 mm
WEIGHT	1.05 kg (w/o cable)	1.05 kg (w/o cable)
ACCESSORIES	Foam Windshield,	Foam Windshield,
	2.5m Interconnecting Cable	2.5m Interconnecting Cable

SYSTEM CONFIGURATION		
CENTRAL MIXER AMPLIFIER	CMA-5400	1 Unit
CHAIRMAN UNIT	CMC-5100	1 Unit
DELEGATE UNIT	CMD-5200	N Units (N ≤ 50)



