PA Mixer Amplifiers



SSB-80®M

80 WATTS ■ AC & 12V DC Operation

- 5 Mic & 2 Aux Inputs.
- Preamplifier Output for connecting to a Booster Amplifier and for recording the programme.
- Cut type Bass & Treble controls.
- Instant transfer to DC power (Car Battery) if AC power fails.



SSB-60®EM

65 WATTS ■ AC & 12V DC Operation

- 4 Mic & 1 Aux Inputs.
- Preamplifier Output for connecting to a Booster Amplifier and for recording the programme.
- Cut type Bass & Treble Controls.
- Instant transfer to DC power (Car Battery) if AC power fails.



SSB-45®EM

45 WATTS ■ AC & 12V DC Operation

- 3 Mic & 1 Aux Inputs.
- Preamplifier Output for connecting to a Booster Amplifier and for recording the programme.
- Cut type Bass & Treble Controls.
- Instant transfer to DC power (Car Battery) if AC power fails.

All these models are compact, portable and ideal for most general purpose applications. These are ideal for use in small sized houses of worship and other similar applications. Since these also operate on 12V Car Battery, they are convenient for areas without continuous mains power supply

SPECIFICATIONS	SSB-80®M	SSB-60®EM	SSB-45®EM
POWER OUTPUT	110W Max., 80W RMS at 10% THD	90W Max., 65W RMS at 10% THD	64W Max., 45W RMS at 10% THD
	75W RMS at 5% THD, 60W RMS at 2% THD	60W RMS at 5% THD, 50W RMS at 2% THD	40W RMS at 5% THD, 30W RMS at 2% THD
OUTPUT REGULATION	≤ 2 dB, no load to full load at 1kHz	≤ 2 dB, no load to full load at 1kHz	≤ 2 dB, no load to full load at kHz
INPUT CHANNELS	5×Mic 0.65mV/4.7kΩ, 2×Aux 100mV/470kΩ	4×Mic 0.65mV/4.7kΩ, 1×Aux 100mV/470 kΩ	3 × Mic 0.65mV/4.7kΩ, 1 × Aux 100mV/470 kΩ
FREQUENCY RESPONSE	65-15,000Hz ±3dB	50-15,000Hz ±3dB	100-15,000Hz ±3dB
SIGNAL TO NOISE RATIO	60dB	60dB	60dB
TONE CONTROLS	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz
OUTPUTS	Preamp 200mV/600Ω	Preamp 200mV/600Ω	Preamp 200mV/600Ω
SPEAKER OUTPUTS	4Ω, 8Ω, 16Ω, 70V & 100V	4Ω, 8Ω, 16Ω & 100V	4Ω, 8Ω, 16Ω & 100V
POWER SUPPLY	AC: 220-240V 50/60Hz	AC: 220-240V 50/60Hz	AC: 220-240V 50/60Hz
	DC: 12V (12V Car Battery)	DC: 12V (12V Car Battery)	DC: 12V (12V Car Battery)
POWER CONSUMPTION	AC: 180VA DC: 3A	AC: 160VA DC: 3A	AC: 110VA DC: 2A
DIMENSIONS	W355 × H133 × D285 mm	W350 × H120 × D265 mm	W280 × H120 × D270 mm
WEIGHT	7.83kg	7.00kg	4.80kg