

SSA-100®M

100 WATTS ■ AC & 24V DC Operation

- 5 Mic & 2 Aux Inputs.
- Preamplifier and Line Output for connecting to a Booster Amplifier and for recording the programme.
- Cut type Bass & Treble controls.
- Instant transfer to DC power (Car Battery) if AC power fails.



SSB-120®

120 WATTS ■ AC & 12V DC Operation

- 5 Mic & 2 Aux Inputs.
- Line Ouput for connecting to a Booster Amplifier and Preamplifier Output for recording the programme.
- Cut type Bass & Treble controls.
- Instant transfer to DC power (Car Battery) if AC power fails.



SSB-85FX

80 WATTS ■ AC & 12V DC Operation

- 4 Mic & 1 Aux Inputs.
- Built-in digital echo effect on Mic-4.
- Mic-3 is alternate to Aux through switch.
- Mic-1 & Mic-2 having LO-CUT facility.
- Preamplifier Output for connecting to a Booster Amplifier and for recording the programme.
- Cut type Bass & Treble controls.
- Instant transfer to DC power (Car Battery) if AC power fails.

SPECIFICATIONS	SSA-100®M	SSB-120®	SSB-85FX
POWER OUTPUT	130W Max., 100W RMS at 10% THD	160W Max., 120W RMS at 10% THD	110W Max., 80W RMS at 10% THD
	90W RMS at 5% THD, 80W RMS at 2% THD	105W RMS at 5% THD, 95W RMS at 2% THD	75W RMS at 5% THD, 60W RMS at 2% THD
OUTPUT REGULATION	≤ 2 dB, no load to full load at 1kHz	—	≤ 2 dB, no load to full load at 1kHz
INPUT CHANNELS	5×Mic 0.65mV/4.7kΩ, 1×Aux 50mV/470kΩ	5×Mic 0.65mV/4.7kΩ, 2×Aux 100mV/470 kΩ	4×Mic 0.65mV/4.7kΩ, 1×Aux 100mV/470kΩ
	1 × Aux 150mV/470kΩ	—	—
FREQUENCY RESPONSE	50-15,000Hz ±3dB	50-15,000Hz ±3dB	65-15,000Hz ±3dB
SIGNAL TO NOISE RATIO	60dB	60dB	60dB
TONE CONTROLS	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz	Bass: -10dB at 100Hz, Treble: -10dB at 10kHz
OUTPUTS	Preamp 200mV/600Ω, Line 1V/1kΩ	Preamp 200mV/600Ω, Line 1V/1kΩ	Preamp 200mV/600Ω
SPEAKER OUTPUTS	4Ω, 8Ω, 16Ω, 70V & 100V	4Ω, 8Ω, 16Ω, 70V & 100V	4Ω, 8Ω, 16Ω, 70V & 100V
POWER SUPPLY	AC: 220-240V 50/60Hz	AC: 220-240V 50/60Hz	AC: 220-240V 50/60Hz
	DC: 24V (2×12V Car Battery)	DC: 12V (12V Car Battery)	DC: 12V (12V Car Battery)
POWER CONSUMPTION	AC: 220VA DC: 3A	AC: 250VA DC: 5.5A	AC: 180VA DC: 3A
DIMENSIONS	W420 × H135 × D290 mm	W420 × H135 × D295 mm	W355 × H133 × D285 mm
WEIGHT	10.50kg	11.30kg	8.53kg