CCS-2300
AC Operation



CCS-2300, a two-way counter communication system, exclusively designed for easy and effective conversation across counters with transparent security barriers. It consists of an attendant unit, a customer unit and a power supply unit, which are easy to install and simple to connect through dedicated cables as supplied with the system.

- Unique design, pleasing aesthetics & rugged construction.
- Two-way, hands-free communication.
- Easy, hassle-free installation.
- Compact & elegant table top attendant unit with 508 mm (20") long gooseneck microphone for strain-free usage.
- A 3.5 mmjack socket is provided for connecting a headband microphone like Ahuja HBM-50. This is useable by the attendant as an alternate to the fixed gooseneck microphone.
- Separate controls for adjusting the speech levels during Talk & Listen modes of operation.
- Special Auto-Mute ON/OFF option provided through a toggle switch. In Auto-Mute ON condition, the customer's microphone is partially muted if it is not used for 30 sec. approx. This facility prevents the attendant from being disturbed by unwanted outside noise.
- The customer's unit has an efficient speaker and a sensitive condenser cartridge, mounted in a beautifully designed housing.
- Attendant's microphone has voice priority over the customer's microphone.
- Power Supply CCS-2300P is BIS approved.









SPECIFICATIONS	CCS-2300
OUTPUT	2W (Max.) in each amplifier
MICROPHONE ELEMENT	Electret Condenser in both the units.
AUTO MUTE 'ON'	Enables after 30 seconds (approx.)
POWER REQUIREMENT	AC: 220-240V, 50/60Hz
PROTECTIONS	AC Fuse 1 × 0.5A
DIMENSIONS	
Attendant Unit	W116 × H65 × D170 mm (w/o gooseneck)
Customer Unit	Ø98 × D52 mm
Power Supply Unit	W85 × H58 × D150 mm
WEIGHT	
Attendant Unit	1.30kg
Customer Unit	480g
Power Supply Unit	930g
ACCESSORIES	1 No. of fuse 0.5A, 2 Nos. of M4 moulded screws, 2 Nos. of self adhesive DUAL LOCK tape, 4.5mtrs. of interconnecting cable for Customer unit