Audio Interface



AI-202

2×2 USB Audio Interface

- Studio quality(16Bit/48kHz) Digital Recording.
- Features two inputs (Mic/Line & Instrument Level) and two outputs.
- Extreme low-Latency digital streaming.
- Switchable Phantom power.
- Supports Windows/Android & Mac iOS.
- Compatible with popular DAW softwares.
- USB 2.0 Bus-powered.
- Compact durable Aluminium body.



AI-22

2×2 USB Audio Interface

- Studio Quality(16Bit/48kHz) Digital Recording.
- Features two inputs (Mic/Line & Instrument Level) and two outputs.
- Extreme low-Latency digital streaming.
- Switchable Phantom power.
- Supports Windows/Android & Mac iOS.
- Compatible with popular DAW softwares.
- USB 2.0 Bus-powered.
- Compact durable Aluminium body.

SPECIFICATIONS	AI-202	AI-22
MICROPHONE INPUT / LINE INPUT		
TYPE	Combo XLR Female X2/ 2 x 6.3 mm TRS, Balanced	Combo XLR Female 6.3 mm TRS balanced
INPUT IMPEDANCE (Balanced)	2.2kΩ/ 18kΩ	2.2kΩ / 18kΩ
THD+N (1kHz @ +0dBu Output)	<0.5%	<0.5%
S/N RATIO (1kHz @ +0dBu Output)	>55dB	>55dB
INPUT LEVEL (0dBu Gain, 1kHz)	3mV ±1mV / 45mV ± 2mV	3mV ±1mV / 35mV ±2mV
PHANTOM POWER	+48 VDC at both XLR Female only	+48 VDC at XLR Female only
INSTRUMENT INPUT		
TYPE	2 x 6.3 mm TRS, Balanced	1 x 6.3 mm Female, Unbalanced
INPUT IMPEDANCE	1MΩ	1MΩ
INPUT LEVEL (0dBu Gain, 1kHz)	3.50mV ± 1mV	285mV ±10mV
FREQUENCY RESPONSE	20-20,000Hz	20-20,000Hz
PAD ON	-18dB	—
OUTPUT L & R		
TYPE	2 x 6.3 mm Female, Unbalanced	2 x 6.3 mm Female, Unbalanced
Maximum Output ±20mV	550mV	775mV
HEADPHONE OUTPUT		
TYPE	6.3 mm Active Stereo	6.3 mm Active Stereo
MAXIMUM OUTPUT ±20mV	300mV/ch. @ 8Ω Load	300mV/ch. @ 8Ω Load
DIGITAL AUDIO		
BIT DEPTH	16 bit	16 bit
INTERNAL SAMPLE FREQUENCY SELECTIONS	44.1, 48 kHz	44.1, 48 kHz
POWER	USB Bus Powered	USB Bus Powered
DIMENSIONS	W175 × H58 × D123 mm	W175 × H58 × D123 mm
WEIGHT	615g	550g