

14 CHANNEL

AMX-1412 AC & 24V DC Operation

With built-in Digital Effects

- Each Channel has separate 6.3 mm (1/4") balanced phone jack for balanced & unbalanced Mic and Line input signals.
- AUX Send & AUX Return are provided for sending the pre-fader output of channels for monitoring or for adding a Special Effects Unit.
- Mono output is available from Left & Right output jacks when the switch is in 'Mono' position.
- Each channel has GAIN, BASS, MID, TREBLE, ECHO, PAN and slide LEVEL controls with CLIP LED indicator.
- Echo section provided with Delay, Repeat & Level controls.
- Stereo RCA IN/OUT for record and playback.
- Headphone output with volume control is provided.



9 CHANNEL

AMX-912DP AC & 24V DC Operation

With built-in MP3 Player & Digital Effects

- Each Channel has separate 6.3 mm (1/4") balanced phone jack for balanced & unbalanced Mic and Line input signals.
- Built-in MP3 Player, with Bluetooth facility, is selectable through Channel 9/USB Switch and controllable through an independent USB input volume control. Channel 9 can be used for Mic & Line inputs or USB Playback function.
- Mono output is available from Left & Right output jacks when the switch is in 'Mono' position.
- Each channel has GAIN, BASS, TREBLE, ECHO, PAN and slide LEVEL controls with CLIP LED indicator.
- Echo section provided with Delay, Repeat & Level controls.
- Stereo RCA IN/OUT for record and playback.
- Headphone output with volume control is provided.



9 CHANNEL

AMX-912 AC & 24V DC Operation

With built-in Digital Effects

- Each Channel has separate 6.3 mm (1/4") balanced phone jack for balanced & unbalanced Mic and Line input signals.
- Mono output is available from Left & Right output jacks when the switch is in 'Mono' position.
- Each channel has GAIN, BASS, TREBLE, ECHO, PAN and slide LEVEL controls with CLIP LED indicator.
- Echo section provided with Delay, Repeat & Level controls.
- Stereo RCA IN/OUT for record and playback.
- Headphone output with volume control is provided.

SPECIFICATIONS	AMX-1412	AMX-912DP	AMX-912
MIC INPUT (Impedance/Gain)	2kΩ Balanced/62dB,1kΩ Unbalanced/62dB	2kΩ Balanced/62dB,1kΩ Unbalanced/62dB	2kΩ Balanced/62dB, 1kΩ Unbalanced/62dB
LINE INPUT (Impedance/Gain)	20kΩ Balanced/42dB,10kΩ Unbalanced/42dB	20kΩ Balanced/42dB,10kΩ Unbalanced/42dB	20kΩ Balanced/42dB,10kΩ Unbalanced/42dB
DISTORTION	< 0.08%	< 0.08%	< 0.08%
FREQUENCY RESPONSE	30Hz - 20kHz (+0, -1dB)	30Hz - 20kHz (+0, -1dB)	30Hz - 20kHz (+0, -1dB)
TONE CONTROLS	Bass : ±12dB at 100Hz, Mid : ±12dB at 2kHz,	Bass : ±12dB at 100Hz,	Bass : ±12dB at 100Hz,
	Treble : ± 12dB at 10kHz	Treble : ± 12dB at 10kHz	Treble : ± 12dB at 10kHz
OUTPUT LINE OUTPUT LO	-10dBu/+2dBu (200mV/1V)	-10dBu/+2dBu (200mV/1V)	-10dBu/+2dBu (200mV/1V)
LINE OUTPUT HI	0dBu/+17dBu (775mV/5.5V)	0dBu/+17dBu (775mV/5.5V)	0dBu/+17dBu (775mV/5.5V)
DELAY RANGE SETTINGS	Variable from 20 to 600ms	Variable from 30 to 400ms	Variable from 30 to 400ms
DIGITAL PLAYER	—	With USB, SD,MMC Card & Bluetooth	—
SIGNAL TO NOISE RATIO	>70dB (0dBm, 0.775V)	>70dB (0dBm, 0.775V)	>70dB (0dBm, 0.775V)
POWER SUPPLY	AC: 220-240V 50/60Hz,	AC: 220-240V 50/60Hz,	AC: 220-240V 50/60Hz,
	DC: 24V (2×12V Car Battery)	DC: 24V (2×12V Car Battery)	DC: 24V (2×12V Car Battery)
DIMENSIONS	W633 × H93 × D420 mm	W483 × H93 × D366 mm	W483 × H93 × D366 mm
WEIGHT	9.40kg	6.90kg	6.90kg



