PMX-1632FX AC Operation

With Digital Effects, 48V Phantom Supply on 4 Channels



16 CHANNEL

- Rugged, stable, high quality analog mixers with user-friendly construction & aesthetically designed side panels.
- 12 MIC/LINE Balanced Mono input channels and 2 STEREO Balanced input channels.
- MIC/LINE Balanced Mono inputs with enhanced headroom.
- All MIC inputs are through 3 pin F/XLR connectors and all LINE & STEREO inputs are through 6.3 mm (1/4") stereo phone jack sockets.
- Four MIC inputs (MIC-1 to MIC-4) are available with 48V phantom supply which can be switched ON/OFF through a common switch.
- STEREO Balanced input in two selectable sensitivities of -10dBu & +4dBu.
- Separate EFFECT channel is provided for operating the built-in digital effect processor through a delay selector switch, delay, repeat and level controls.
- Each MIC/LINE channel has a GAIN control, 3 band active Equalizer controls, a Pre-fader AUX1 control, a Post-fader AUX2 /EFX control & a PAN control.
- Each STEREO channel has a GAIN control, 2 band active Equalizer controls, AUX1 Pre fader control, AUX2/EFX Post fader control and a BALANCE control.
- Channel ON/OFF switch provided on each individual channel. Peak LED for signal clipping indication.
- High precision 60 mm slide fader on each channel.
- Balanced Left & Right Line outputs through M/XLR connectors as well as 6.3 mm (1/4") stereo phone jack sockets.
- Easy and accurate monitoring of Left & Right output levels through individual 12 segment LED array.
- Two AUX SEND outputs with level controls: one each for monitoring and effects processing applications.
- Two stereo AUX RETURN balanced inputs with level controls.
- Headphone output with Level Control for output monitoring.
- Stereo RCA IN/OUT for record and playback.
- Operates on 240V 50Hz AC mains.

SPECIFICATIONS	PMX-1632FX
MIC INPUT	
Impedance/Gain	: 2kΩ Balanced/65dB
LINE INPUT	
Impedance/Gain	: 20kΩ Balanced/45dB
STEREO INPUT (L/Mono & R)	
Impedance/Gain (-10dBu Input)	: 10kΩ Balanced/14dB
Impedance/Gain (+4dBu Input)	: 10kΩ Balanced/0dB
THD	: <0.08%
FREQUENCY RESPONSE	: 25Hz - 20kHz (+0, -1dB)
EQUALIZATION	
Bass/Mid/Treble	: ±12dB at 100Hz/2kHz/10kHz
CLIP LED INDICATION	: 4 dB prior to true clip
LINE OUTPUT	
Nominal/Max Level	: 4dBu/21dBu (1.22V/9V)
IMPEDANCE	: 600Ω
DELAY SYSTEM	: Digital Signal Processing
DELAY RANGE SETTINGS	: 1: 60-300ms, 2: 300-500ms, 3: 500-650ms
HEADPHONE OUTPUT	: 200mV at 8Ω, THD <1%
MAXIMUM GAIN	
Mic Input to Line Outputs	: 78dB
Line Input to Line Outputs	: 58dB
Stereo Input to Line Outputs	: 28dB (-10dBu Input)
	14dB (+4dBu Input)
AUX Send (Pre)	: 1.4V/100Ω Unbalanced
AUX Send (Post)	: 2.7V/100Ω Unbalanced
AUX Return (L&R)	: 150mV/10kΩ Balanced
Record Output (L&R)	: 250mV/600Ω
Playback Input (L&R)	: 250mV/1kΩ (variable through GAIN control)
SIGNAL TO NOISE RATIO	: >70dB
POWER SUPPLY	: AC: 220-240V, 50/60Hz
DIMENSIONS	: W609 × H110 × D435 mm
WEIGHT	: 9.80kg

