FMX-212PRO AC Operation

With Built-in MP3 Recorder, 24 Digital Effects, 48V Phantom Supply on all Channels



12 CHANNEL

- Reliable and versatile professional Audio Mixer in a compact and aesthetically superior construction.
- 10 MIC and 10 LINE Balanced Mono inputs with enhanced headroom. One STEREO Balanced input.
- Built-in digital MP3 player with recording & BT functions.
- Digital multi EFFECTS processor with 24 built-in effects.
- LCD display for viewing the EFFECTS/USB settings.
- All MIC inputs are through 3 pin F/XLR connectors.
- All LINE & STEREO inputs are through 6.3 mm (1/4") stereo phone jack sockets.
- All MIC inputs are available with 48V phantom supply, with ON/OFF switch for every two MIC inputs.
- Each input channel has a GAIN control, 3 band active EQ controls, AUX, FX and PAN control.
- The STEREO channel has a GAIN control, 3 band active EQ control, AUX, FX and PAN control.
- Peak LED for signal clipping indication. PFL switch for each channel.
- Balanced Left & Right MAIN Mix outputs through M/XLR connectors as well as 6.3 mm (1/4") stereo phone jack sockets.
- Monitor L&R outputs through 6.3 mm (1/4") phone jack sockets and individual fader control.
- Easy and accurate monitoring of Left & Right output levels through individual 12 segment LED array.
- Headphone output with Phones Control for output monitoring.
- Operates on 240V 50Hz AC mains.

SPECIFICATIONS	FMX-212PRO
MIC INPUT	
Impedance/Gain	: 2kΩ Balanced/65dB
LINE INPUT	
Impedance/Gain	: 20kΩ Balanced/45dB
STEREO INPUT (L/Mono & R)	
Impedance/Gain	: 10kΩ Balanced/20dB
THD	: <0.08%
FREQUENCY RESPONSE	
L/R Line Output	: 25Hz - 20kHz (+0, -1dB)
EQUALIZATION	
TREABLE/MID/BASS	: ±12dB at 12kHz/2.5kHz/80Hz
CLIP LED INDICATION	: 4 dB prior to true clip
LINE OUTPUT	
Nominal/Max Level	: 4dBu/21dBu (1.22V/9V)
Impedance	: 600Ω
DIGITAL EFFECTS	: 24 Effects Digital Processor
DIGITAL PLAYER	: MP3 Player/Recorder with USB Reader, Bluetooth
HEADPHONE OUTPUT	: 200mV at 8Ω, THD <1%
MAXIMUM GAIN	
Mic Input to Line Outputs	: 90dB
Line Input to Line Outputs	: 70dB
Stereo Input to Line Outputs	: 20dB
AUX Send (Pre) Unbalanced	: 5V
MONITOR OUTPUTS (L&R)	: 1.6V
SIGNAL TO NOISE RATIO	: >80dB
POWER SUPPLY	: AC: 220-240V, 50/60Hz
DIMENSIONS	: W522 × H135 × D385mm
WEIGHT	: 5.45kg