Unidirectional Dynamic
Multi Purpose Applications





AUD-99XLR®

For general PA applications, a robust and reliable microphone. Ideal for addressing an audience.

- Frequency Response : 50-15,000Hz
- Sensitivity : 2.5mV/Pa
- Impedance : 600Ω

Supplied with quick detachable microphone holder with 3-pin professional XLR connector & 6m twin core shielded low noise cable.





Unidirectional Dynamic
PA Applications





AUD-98XLR®

High output Neodymium cartridge. Excellent intelligibility & wide frequency response. Attractive appearance.

- Frequency Response : 50-15,000Hz
- Sensitivity : 2.5mV/Pa
- Impedance : 600Ω

Supplied with quick detachable microphone holder with 3-pin professional XLR connector & 6m twin core shielded low noise cable.





Unidirectional Dynamic
PA Applications





AUD-97XLR®

Attractive appearance. Neodymium cartridge. High intelligibility & wide frequency response.

- Frequency Response : 50-15,000Hz
- Sensitivity : 2.5mV/Pa
- Impedance : 600Ω

Supplied with quick detachable microphone holder with 3-pin professional XLR connector & 6m twin core shielded low noise cable.





PROFESSIONAL ECONOMY SERIES
Unidirectional Dynamic
Music & Vocal



ADM-511

Intelligible, crisp and bright sound suitable for all type of PA applications.

- Frequency Response : 50-15,000Hz
- Sensitivity : 2.0mV/Pa
- Impedance : 600Ω

Supplied with quick detachable microphone holder with 3-pin professional XLR connector & 6m twin core shielded low noise cable.

