## AWM-700®UL

### PA UHF Wireless Microphone



- Attractive and versatile high performance single channel UHF wireless microphone available in different frequencies.
- Receiver has built-in 6.3 mm (1/4") jack for unbalanced audio output and XLR connector for balanced audio output.
- Volume control knob & Fequency display on the front panel of the receiver.
- One bodypack transmitter, operating on 2 x 1.5V AA pencil cells.
- Bodypack transmitter has a two position slide switch for ON/OFF and one volume control.
- Receiver operates on 12V DC through an AC adaptor supplied alongwith the transmitter.
- Ideal for: PA Applications... Stage & Auditoriums... Stadia... Seminar Halls... Places of Worship... Recreation Centres...

| SPECIFICATIONS | TRANSMITTER |
|---|---|
| RF OUTPUT POWER | 15mW (Max.) |
| MODULATION MODE | FM |
| MICROPHONE ELEMENT | Condenser, Omnidirectional |
| DYNAMIC RANGE | 80dB |
| FREQUENCY RESPONSE | 80-15,000Hz |
| CURRENT CONSUMPTION | ≤ 130mA |
| POWER REQUIREMENT | 3V (2 × 1.5V AA Pencil Cells) |
| CONTROLS | ON/OFF Switch, Volume Control, |
| INDICATIONS | Red LED for indicating transmitter ON, |
| | Frequency Display |
| DIMENSIONS | W67 × H32 × D95 mm |
| WEIGHT | 60g (w/o battery) |

| SPECIFICATIONS | RECEIVER |
|---|---|
| AUDIO OUTPUT | Bal. 0dBu, Unbal. -10dBu |
| SIGNAL TO NOISE RATIO | >90dB |
| DISTORTION | ≤1% |
| FREQUENCY RESPONSE | 50-15,000Hz |
| DYNAMIC RANGE | >90dB |
| POWER REQUIREMENT | 240V AC 50Hz from AC Adaptor |
| | (supplied along with) |
| CONTROLS | ON/OFF Switch, Volume Control |
| INDICATIONS | LEDs for RF & Audio Signal, |
| | Channel Frequency Display |
| DIMENSIONS | W210 × H42 × D147 mm |
| WEIGHT | 372g |

## ABW-400®UH

### PA UHF Wireless Microphone



- Attractive and versatile high performance single channel UHF wireless microphone available in different frequencies.
- Bodypack receiver has built-in 6.3 mm (1/4") jack plug which provides unbalanced audio output.
- Volume control knob with RF & POWER LED on the front side of the receiver.
- One handheld dynamic transmitter, operating on 2 x 1.5V AA pencil cells.
- Receiver has a three position slide switch for ON/STANDBY/OFF position and operates on 2 x 1.5V AA pencil cells.
- Ideal for: PA Applications... Stage & Auditoriums... Stadia... Seminar Halls... Places of Worship... Recreation Centres...

| SPECIFICATIONS | TRANSMITTER |
|---|---|
| RF OUTPUT POWER | 10mW (Max.) |
| FREQUENCY STABILITY | ±0.005% |
| MODULATION MODE | FM |
| MICROPHONE ELEMENT | Dynamic, Cardioid |
| FREQUENCY RESPONSE | 50-15,000Hz |
| POWER REQUIREMENT | 3V (2 × 1.5V AA Pencil Cells) |
| CURRENT CONSUMPTION | ≤ 150mA |
| CONTROLS | Microphone ON/OFF switch |
| INDICATION | LED for microphone ON |
| DIMENSIONS | Ø55 (L 250) mm |
| WEIGHT | 220g (w/o battery) |

| SPECIFICATIONS | RECEIVER |
|---|---|
| AUDIO OUTPUT | Unbal. -10dBu |
| SIGNAL TO NOISE RATIO | >90dB |
| DISTORTION | ≤ 1% |
| FREQUENCY RESPONSE | 50-15,000Hz |
| POWER REQUIREMENT | 3V (2 × 1.5V AA Pencil Cells) |
| CURRENT CONSUMPTION | ≤ 150mA |
| CONTROLS | ON/OFF/SB Switch, Volume Control |
| INDICATIONS | LEDs for Power & RF Signal |
| DIMENSIONS | W62 × H128 × D26 mm |
| WEIGHT | 65g (w/o battery) |



