Wireless Desktop Microphone

AWM-630VG
PA VHF Wireless Desktop Microphone



- Stylish & rugged high band VHF wireless desktop microphone & receiver available in different frequencies.
- Condenser unidirectional transmitter has a sleek gooseneck with ring LED indicator.
- Transmitter has a push-type ON/OFF switch.
- Highly sensitive table-top receiver with a telescopic antenna & noise squelch circuitry.
- Transmitter also has a male XLR connector & connecting cable so that wired mode can also be used, if required.
- Transmitter operates with 2 × 1.5V UM-3 pencil cells.
- Receiver operates on 9V DC through an AC adaptor, supplied along with.

SPECIFICATIONS	TRANSMITTER
RF OUTPUT POWER	10mW (Max.)
MODULATION MODE	FM
MICROPHONE ELEMENT	Condenser, Cardioid
FREQUENCY RESPONSE	100-12,000Hz
POWER REQUIREMENT	2×1.5V Pencil Cells
CURRENT CONSUMPTION	<40mA
CONTROLS	ON/OFF Switch
INDICATION	Red Ring LED in the gooseneck
DIMENSIONS	W145 × H50 × D155 mm
WEIGHT	560g (w/o battery)

SPECIFICATIONS	RECEIVER
FREQUENCY STABILITY	± 0.005%
AUDIO OUTPUT	0-50mV adjustable
SIGNAL TO NOISE RATIO	>90dB
DISTORTION	<0.5%
ANTENNA TYPE	Telescopic
POWER REQUIREMENT	220V-240V AC 50Hz for AC adaptor (supplied alongwith)
CONTROLS	Power Switch, Output Volume Control
INDICATION	Red LED for Power ON, Green & Red LEDs for Signal
DIMENSIONS	W152 × H40 × D110 mm
WEIGHT	200g

Paging Microphones



ACM-96CH

ACM-96/ACM-96CH
with MULTI Tone Chime

- Robust and heavy duty Single Zone Desktop Paging Microphone.
- Sturdy, aluminium die-cast top.
- High reliability switches with integrated LED indicators.
- Flexible 300 mm (12") gooseneck and a high quality unidirectional dynamic cartridge.
- Supplied with 6m twin core shielded low noise cable terminated with 6.3 mm (1/4") phone plug.
- ACM-96CH is also provided with a multi tone electronic chime, and operates on 2 × 1.5V (UM-3) pencil cells.
- Desired chime sound level can be set through preset at the bottom side of ACM-96CH.

SPECIFICATIONS	
FREQUENCY RESPONSE	50-10,000Hz
SENSITIVITY	2.0mV/Pa
IMPEDANCE	600Ω