ALIVE 510

300 WATTS

Bi AMP | 2 WAY | CLASS D | BT | 1×10" | DSP PROCESSOR | TWS SING ALONG

new product



ALIVE 510 is Class D Bi-Amplifier Active Loudspeaker System designed for use in a wide variety of Professional and PA Programmes. Feature packed ALIVE 510 is an ideal equipment for applications such as in Professional Music and Vocal Performances, Touring PA, Mini-Theatres, Pubs and Bars, Religious Gatherings, Stage Monitors etc.

- Attractive Plastic moulded cabinet. Product designed for use in a wide variety of PA and Musical Instrument applications.
- Built-in DSP processor with presets; Music, DJ/Club, Live and Speech.
- Balanced XLR combo connector for MIC & LINE inputs.
- Balanced Line Output through XLR connector for easy connection of multiple ALIVE speakers.
- Active Bass/Mid/Treble controls for proper shaping of Low/Mid/High frequency levels.
- Built-in limiter which is tuned optimally for speaker protection.
- LIMIT indication in DSP for monitoring the output as well as caution against overdrive.
- Protection provided for output short and overdrive conditions.
- Built-in MP3 player with BT facility.

SPECIFICATIONS	ALIVE 510
POWER OUTPUT (Bi-AMP)	LF: 280W RMS at 1% THD Class D, HF: 20W RMS at 1% THD Class D
OUTPUT REGULATION	Better than 0.5dB
INPUT CHANNELS	INPUT-1: LINE Input 775mV through XLR combo or RCA, INPUT-2: MIC/Line switchable, MIC-15mV, Line775mV
	MP3 player with built-in BT facility
FREQUENCY RESPONSE	50-20,000Hz ±3dB
DSP PROCESSOR	Built-in Preset Options: Speech, Music, Club/DJ, Live
SIGNAL TO NOISE RATIO	60dB
TONE CONTROLS	Bass: ±12dB, Mid ±12dB, Treble ±12dB
OUTPUT	Line Output - 775mV (through M/XLR)
PROTECTIONS	AC: Fuse 1 x 3.15A (T 3.15AL)
POWER SUPPLY	AC: 220-240V 50/60Hz
DIMENSIONS	W330 x H575 x D310 mm
WEIGHT	13.45 kg