# PA Driver Units



## AU-40®
40W/16Ω



## AU-60®
60W/16Ω




## AU-40®XT
40W/100V




## AU-50®XT
50W/100V

- Weatherproof and rugged construction.
- High SPL, crisp penetrating sound.
- Voice coils precision-wound on an aluminium bobbin for efficient heat dissipation.
- Models AU-40®XT and AU-50®XT have a built-in 100V transformer with easily selectable power taps/impedance by changing the position of the rotary switch at the rear.
- Degree of protection IP66 provided, when mounted on a reflex horn, against foreign particles such as dust and jets of water thus making them ideal for outdoor use. Meets EN 60529.



Power Tap Selection




Power Tap Selection

| SPECIFICATIONS | AU-40® | AU-60® | AU 40®XT | AU 50®XT |
|---|---|---|---|---|
| INPUT POWER | 40W RMS/60W Max. | 60W RMS/90W Max. | 40W RMS/60W Max. | 50W RMS/70W Max. |
| IMPEDANCE/POWER TAPS | 16Ω | 16Ω | On 100V Line | On 100V Line |
| | — | — | 250Ω/40W, 330Ω/30W | 200Ω/50W, 250Ω/40W |
| | — | — | 500Ω/20W, 1kΩ/10W | 500Ω/20W, 1kΩ/10W |
| | — | — | 2kΩ/5W | 2kΩ/5W |
| FREQUENCY RESPONSE | 160-7,000Hz | 160-7,000Hz | 160-7,000Hz | 160-7,000Hz |
| SPL at 1kHz | 112.5dB/1W/1m | 113.5dB/1W/1m | 112.5dB/1W/1m | 113dB/1W/1m |
| | 128.5dB/40W/1m | 132dB/60W/1m | 128.5dB/40W/1m | 130dB/50W/1m |
| TEMPERATURE RANGE | -30° to + 70°C | -30° to + 70°C | -30° to + 70°C | -30° to + 70°C |
| THROAT COUPLING | 1-3/8" - 18TPI, Throat Couple No.1 | | | |
| DIMENSIONS | Ø116 x H98 mm | Ø126 x H100 mm | Ø150 x H137 mm | Ø150 x H143 mm |
| WEIGHT | 1.65kg | 1.95kg | 2.20kg | 2.45kg |
| MATERIAL | Die-cast Aluminium Acoustic Head (Flange) | | | |

# PA Horn Speakers

## EHC-10 10W/8Ω / EHC-10XT 10W/100V





EHC-10XT
Power Tap Selection

- Compact, sturdy and light weight weather proof horn speakers for a variety of mobile PA and installed PA applications.
- Available in low impedance 8Ω version as EHC-10 and high impedance 100V version as EHC-10XT.
- Features high acoustical efficiency together with intelligible and effective penetrating sound.
- Constructed with tough UV protected ABS plastic components.
- Provided with strong metal bracket for rigid mounting. Stand mounting bolts are in stainless steel.
- Fitted with 0.6m (2') 2-core sheathed speaker cable, secured through a water-tight, tug-proof cable gland.
- They meet European Union regulations and comply with low voltage directive standard EN 60065. Degree of protection IP66 is provided against foreign particles such as dust and jets of water, thus making them ideal for outdoor use.

| SPECIFICATIONS | EHC-10 | EHC-10XT |
|---|---|---|
| INPUT POWER | 10W RMS/15W Max. | 10W RMS/15W Max. |
| IMPEDANCE / POWER TAPS | 8Ω | 10/7.5/5/2.5/1.25W |
| FREQUENCY RESPONSE | 350-7,000Hz | 350-7,000Hz |
| SPL at 1kHz | 102dB/1W/1m, 112dB/10W/1m | 102dB/1W/1m, 112dB/10W/1m |
| DIMENSIONS | 180 × 130 (L195) mm | 180 × 130 (L215) mm |
| WEIGHT | 930g | 1.17kg |
| MATERIAL | ABS (UV Protected) | ABS (UV Protected) |