

2×15" | 2 WAY | 4Ω | 18mm PLYWOOD

SPX-810
700 WATTS

Professional 700 Watts 2-Way PA Loudspeaker in attractive painted enclosure made of 18 mm Plywood. Loaded with two highly efficient 38.1 cm (15") low frequency speakers and a reliable high frequency titanium compression horn driver. Acoustically treated bass reflex cabinet is capable of producing excellent low frequency response together with impressive mid and high frequency response. Strong steel grille ensures speaker protection and durability. Heavy duty metal handles allow easy transportation. Ideal for use in a variety of indoor and outdoor sound reinforcement applications like Auditoria, DJs, Live Performances etc.



2×15" | 2 WAY | 4Ω

SPX-1300
1100 WATTS

Outstanding professional 2-Way PA Loudspeaker with 1100 Watts continuous power handling capacity. Two high power 38.1 cm (15") LF loudspeakers and a high frequency titanium compression horn driver give very well defined, prominent lows and brilliant highs. Acoustically treated bass reflex trapezoidal carpet covered cabinet with a strong steel grille ensures protection and durability. Heavy duty metal handles allow ease of mobility and transportation. Ideal for use with high powered amplifiers for large gatherings.

SPECIFICATIONS	SPX-810	SPX-1300
POWER RATING	700W RMS/1400W Programme	1100W RMS/2200W Programme
CONFIGURATION	Two Way	Two Way
FREQUENCY RESPONSE	40-20,000Hz	35-20,000Hz
LOW FREQUENCY SPEAKER	2 × 381 mm (15"), Ø76.2mm (3") Voice coil	2 × 381 mm (15"), Ø101.6 mm (4") Voice coil
HIGH FREQUENCY UNIT	Dynamic Horn 177.8 mm (7") × 406.4 mm (16")	Dynamic Horn 177.8 mm (7") × 406.4 mm (16")
SPL at (1W/1m)	103dB	103dB
MAX. RATED SPL	131dB	133dB
NOMINAL IMPEDANCE	4Ω	4Ω
CROSSOVER FREQUENCY	2kHz	2kHz
PORT	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets	Speakon + Terminal Strip
DIMENSIONS	W528 × H1188 × D496mm	W550 × H1265 × D483 mm
WEIGHT	58.90kg	67.80kg



