




IMPRESS 75T
75 WATTS

2 WAY | 8Ω | 100V | CE

- High performance 2-Way PA Wall Speaker in modern & attractive plastic housing.
- Superb tonal quality provides high fidelity with uniform coverage.
- Comprises of a Water Resistant PP coated cone Woofer, a Titanium Dome Tweeter and a 2-way Crossover Network.
- Power taps of 30W, 15W & 7.5W are available on 100V line alongwith low impedance 8Ω tap.
- Easy power tap selection through a rotary switch knob.
- Unique mounting system provides 90° horizontal and 45° vertical rotation of the wall speaker.
- Ideal for various indoor and outdoor (under eaves) applications in Airports, Banks, Schools, Hotels, Restaurants, Lounges, Hospitals, Showrooms etc.




Power Tap Selection

IMPRESS 100T
100 WATTS

2 WAY | 8Ω | 100V | CE

- High performance 2-Way PA Wall Speaker in modern & attractive plastic housing.
- Superb tonal quality provides high fidelity with uniform coverage.
- Comprises of a Water Resistant PP coated cone Woofer, a Titanium Dome Tweeter and a 2-way Crossover Network.
- Power taps of 60W, 30W & 15W are available on 100V line alongwith low impedance 8Ω tap.
- Easy power tap selection through a rotary switch knob.
- Unique mounting system provides 90° horizontal and 45° vertical rotation of the wall speaker.
- Ideal for various indoor and outdoor (under eaves) applications in Airports, Banks, Schools, Hotels, Restaurants, Lounges, Hospitals, Showrooms etc.



Power Tap Selection

SPECIFICATIONS	IMPRESS 75T	IMPRESS 100T
POWER HANDLING	75W RMS / 115W Max.	100W RMS / 150W Max.
NOMINAL IMPEDANCE	8Ω	8Ω
TRANSFORMER POWER TAPS	30/15/7.5W	60/30/15W
FREQUENCY RESPONSE	60-20,000Hz	50-20,000Hz
SPL at 1kHz (1W/1m)	90dB	90dB
MAX SPL	110dB	112dB
COVERAGE ANGLE (HxV)	90° × 90°	90° × 90°
LF SPEAKER	133 mm (5.25")	203 mm (8.0")
HF TWEETER	20 mm (0.75")	25 mm (1.0")
CONNECTORS	Removable locking 4-pin connector (Euroblock)	Removable locking 4-pin connector (Euroblock)
	for connection to additional speakers or to the binding post	for connection to additional speakers or to the binding post
DIMENSIONS	W180 × H255 × D163mm	W250 × H390 × D236mm
WEIGHT	3.23kg	6.15kg

