2-Way Outdoor Speaker






OSX-666T
60 WATTS

2 WAY | IP66 EN 60529 | 100V | 8Ω

- Reliable IP-66 rated, weather resistant plastic cabinet wall speaker with outstanding sound clarity.
- Comprises of a Polypropylene Cone Woofer, a Titanium Silk Dome Tweeter and a Crossover Network.
- Operates on 100V line, or on direct 8Ω impedance,selectable through a slotted rotary switch knob at the rear which is accessible after removing the terminal cover.
- Front grill is made of perforated aluminium sheet which provides rust-free service in various weather conditions.
- 'U' type metal bracket for firm mounting and optimum positioning of the wall speaker.
- Bidirectional key holes in the mounting bracket are available for fixing the speaker horizontally or vertically.
- Use of Cable Gland, supplied along with, is essential for ensuring the IP rating of this speaker.
- Suitable for various indoor and outdoor applications.




Power Tap Selection

OSX-999T
90 WATTS

2 WAY | IP66 EN 60529 | 100V | 8Ω

- Reliable IP-66 rated, weather resistant plastic cabinet wall speaker with outstanding sound clarity.
- Comprises of a Polypropylene Cone Woofer, a Titanium Silk Dome Tweeter and a Crossover Network.
- Operates on 100V line, or on direct 8Ω impedance,selectable through a slotted rotary switch knob at the rear which is accessible after removing the terminal cover.
- Front grill is made of perforated aluminium sheet which provides rust-free service in various weather conditions.
- 'U' type metal bracket for firm mounting and optimum positioning of the wall speaker.
- Bidirectional key holes in the mounting bracket are available for fixing the speaker horizontally or vertically.
- Use of Cable Gland, supplied along with, is essential for ensuring the IP rating of this speaker.
- Suitable for various indoor and outdoor applications.



Power Tap Selection

SPECIFICATIONS	OSX-666T	OSX-999T
POWER RATING	60W RMS / 90W Max.	90W RMS / 135W Max.
IMPEDANCE	8Ω	8Ω
POWER TAPS ON 100V	30/15/7.5W	60/30/15W
FREQUENCY RESPONSE	95-20,000Hz	80-20,000Hz
SPL at 1kHz (1W/1m)	87dB	87dB
SPEAKER	Woofer 165 mm (6.5"), Tweeter 25 mm (1.0")	Woofer 203 mm (8"), Tweeter 25 mm (1.0")
DIMENSIONS	W205 × H330 × D199 mm	W251×H398×D232 mm
WEIGHT	3.10kg	4.30kg



