2 WAY | 100V | 8Ω



PS-300TM
10 WATTS

- High fidelity 2-Way, 100V multi-purpose PA Wall Speaker.
- 100V, Power taps of 6W, 3W & 1.5W
- Power taps can be selected through a rotary switch.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Movable mounting bracket supplied, can be mounted in vertical or horizontal positions.




PS-400TM
16 WATTS

- High fidelity 2-Way, 100V multi-purpose PA Wall Speaker.
- 100V Power taps of 16W, 8W & 4W.
- Power taps can be selected through a rotary switch.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Weather Resistant Speaker.
- Movable mounting bracket supplied, can be mounted in vertical or horizontal positions.




PS-500TM
32 WATTS


- High fidelity 2-Way, 100V multi-purpose PA Wall Speaker.
- 100V, Power taps of 32W, 16W, 8W.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Power Taps can be selected through an easily accessible rotary switch.
- Weather Resistant Speaker.
- Movable mounting bracket supplied, can be mounted in vertical or horizontal positions.



Power Tap Selection PS-300TM



Power Tap Selection PS-400TM



Power Tap Selection PS-500TM

COMMON FEATURES

- High Fidelity sound for music.
- Speaker consists of woofer & dome tweeter.
- Elegant plastic cabinet in White colour and also available in Black colour cabinet.
- Ideal for background music in offices, banks, restaurants, showrooms etc.

SPECIFICATIONS	PS-300TM	PS-400TM	PS-500TM
POWER RATING	10W RMS / 15W Max.	16W RMS / 24W Max.	32W RMS / 48W Max.
RATED VOLTAGE	100V	100V	100V
POWER TAPS ON 100V	6/3/1.5W	16/8/4W	32/16/8W
LOW IMPEDANCE	8Ω	8Ω	8Ω
FREQUENCY RESPONSE	150-20,000Hz	85-20,000Hz	80-20,000Hz
SPL at 1kHz (1W/1m)	86dB	86dB	87dB
SPEAKER	Woofer 75 mm (3"),	Woofer 93 mm (3.6"),	Woofer 130 mm (5.25"),
	Tweeter 31 mm (1.22") dome	Tweeter 47 mm (1.85") dome	Tweeter 47 mm (1.85") dome
DIMENSIONS	W105 × H161 × D119mm	W133 × H209 × D130 mm	W162 × H256 × D165 mm
WEIGHT	1.04kg	1.60kg	2.49kg

