

1×15" | 2 WAY | 8Ω

SRX-220®
200 WATTS

Professional 2-Way Loudspeaker with high efficiency, long throw & clean undistorted sound for both speech & music. It consists of one 38.1 cm (15") Full Range Dual Cone Speaker and a Piezo Horn Tweeter. The system is housed in an acoustically treated Bass Reflex Trapezoidal enclosure made of 18 mm board, and carpet covered. Stand mount adaptor is provided at the bottom.



2×12" | 2 WAY | 8Ω

SRX-250®DXM
200 WATTS

An aesthetically superior Loudspeaker that combines two 30.48 cm (12") Full Range Dual Cone speakers and a Piezo Horn Tweeter. It delivers the fidelity of sound and the column effect for sound coverage demanded in sound reinforcement and PA applications. The system is housed in a Rugged Trapezoidal Bass Reflex Enclosure made of 18 mm board, and Carpet covered. Fully protected by front grille. Ergonomically designed handles for easy portability. Stand mount adaptor is provided at the bottom.



2×12" | 2 WAY | 8Ω

SRX-260
200 WATTS

Professional 2-Way Loudspeaker System with two 30.48 cm (12") Full Range Dual Cone Speakers and a Piezo Horn Tweeter. It delivers clear and undistorted sound. It provides column effect for sound coverage demanded in sound reinforcement and PA applications. The system is housed in a Rugged Trapezoidal Bass Reflex painted enclosure made of 18 mm board and strong front grille. Ergonomically designed handles for easy portability. Stand mount adaptor is provided at the bottom.

SPECIFICATIONS	SRX-220	SRX-250®DXM	SRX-260
POWER RATING	200W RMS/400W Programme	200W RMS/400W Programme	200W RMS/400W Programme
CONFIGURATION	Two Way	Two Way	Two Way
FREQUENCY RESPONSE	50-20,000Hz	55-20,000Hz	55-20,000Hz
LOW FREQUENCY SPEAKER	1 × 381 mm (15"),	2 × 304.8 mm (12"),	2 × 304.8 mm (12"),
	Ø50.8 mm (2.0") Voice Coil	Ø38.1 mm (1.5") Voice Coil	Ø38.1 mm (1.5") Voice Coil
HIGH FREQUENCY UNIT	1 × Piezo Horn Tweeter	1 × Piezo Horn Tweeter	1 × Piezo Horn Tweeter
	76.2 mm (3") × 152.4 mm (6")	76.2 mm (3") × 152.4 mm (6")	76.2 mm (3") × 152.4 mm (6")
SPL at (1W/1m)	98dB	100dB	100dB
MAX. RATED SPL	121dB	123dB	123dB
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
PORT	Free Flow Flared	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	1/4" Phone Jack + Terminal Strip	1/4" Phone Jack + Terminal strip	1/4" Phone Jack + Terminal strip
DIMENSIONS	W490 × H680 × D415mm	W410 × H860 × D370 mm	W410 × H860 × D370 mm
WEIGHT	26.00kg	25.00kg	25.00kg