

2×12" | 2 WAY | 8Ω

SRX-440
400 WATTS

High power, high efficency professional Loudspeaker with well-balanced wide-spectrum sound. Consists of two 30.48 cm (12") Dual Cone Speakers and a Pizeo Horn Tweeter fitted in a rugged bass reflex carpet covered enclosure. The cabinet has been fitted with heavy-duty handles to allow ease of transportation and a strong steel grille for speaker protection. A stand adapter is provided at the bottom for pole mounting. Ideal for DJs, variety music programmes and general PA applications.



2×15" | 2 WAY | 8Ω

SRX-500®
400 WATTS

Professional 2-Way Loudspeaker with long throw and unmatched intelligibility of sound. It consists of two 38.1cm (15") full range dual cone speakers and a High frequency compression driver. The speaker system is housed in an acoustically treated Bass Reflex Trapezoidal carpet covered enclosure. Fitted with heavy-duty handles and a strong steel grille. Ideal for both indoor and outdoor sound reinforcement applications. Specially designed for Auditoriums and DJs.



2×15" | 2 WAY | 8Ω

SRX-510
400 WATTS

Professional 2-Way Loudspeaker with long throw and unmatched intelligibility of sound. It consists of two 38.1cm (15") full range dual cone speakers and a High frequency compression driver. The speaker system is housed in an acoustically treated Bass Reflex Trapezoidal painted enclosure. Fitted with heavy-duty handles and a strong steel grille. Ideal for both indoor and outdoor sound reinforcement applications. Specially designed for Auditoriums and DJs.

SPECIFICATIONS	SRX-440	SRX-500®	SRX-510
POWER RATING	400W RMS/800W Programme	400W RMS/800W Programme	400W RMS/800W Programme
CONFIGURATION	Two Way	Two Way	Two Way
FREQUENCY RESPONSE	50-20,000Hz	50-20,000Hz	50-20,000Hz
LOW FREQUENCY SPEAKER	2 × 304.8 mm (12"),	2 × 381 mm (15"),	2 × 381 mm (15"),
	Ø50.8 mm (2.0") Voice Coil	Ø50.8 mm (2.0") Voice Coil	Ø50.8 (2.0") Voice Coil
HIGH FREQUENCY UNIT	1 × Piezo Horn Tweeter	1 × Dynamic Horn,	1 × Dynamic Horn,
	76.2 mm (3") × 152.4 mm (6")	101.6 mm (4")×254 mm (10")	101.6 mm (4") ×254 mm (10")
SPL at (1W/1m)	100dB	101dB	101dB
MAX. RATED SPL	126dB	127dB	127dB
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
CROSSOVER FREQUENCY	—	6kHz	6kHz
PORT	Free Flow Flared	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	1/4" Phone Jack + Terminal strip	Speakon + Terminal Strip	Speakon + Terminal Strip
DIMENSIONS	W416 × H930 × D430 mm	W510 × H1135 × D505 mm	W505 × H1125 × D503 mm
WEIGHT	33.50kg	49.50kg	52.00kg



