

2×12" | 2 WAY | 8Ω

SPX-450
400 WATTS

A high efficiency 400 Watts professional 2-Way PA Loudspeaker has superb low frequency response, long throw and excellent sound intelligibility. Two 30.48 cm (12") high performance LF loudspeakers and a high frequency compression horn driver housed in an acoustically treated bass reflex trapezoidal Carpet covered enclosure. Strong steel grille for speaker protection. Heavy duty metal handles provide ease of mobility and transportation. Ideal for Auditoria… Religious Gatherings… Live Concerts… DJs… etc.



1×15" | 2 WAY | 8Ω | 18mm PLYWOOD

SPX-550
400 WATTS

Elegant and efficient 400 Watts professional 2-Way PA Loudspeaker with superior low frequency response and excellent sound intelligibility. One 38.1cm (15") high performance LF loudspeaker and a high frequency compression horn driver housed in an acoustically treated bass reflex trapezoidal painted enclosure made of 18 mm Plywood. A Stand Adapter is provided at the bottom for stand mounting. Strong steel grille for speaker protection. Heavy duty metal handles provide ease of mobility and transportation. Ideal for Auditoria… Religious Gatherings… Live Concerts… DJs… etc.

SPECIFICATIONS	SPX-450	SPX-550
POWER RATING	400W RMS/800W Programme	400W RMS/800W Programme
CONFIGURATION	Two Way	Two Way
FREQUENCY RESPONSE	45-20,000Hz	45-18,000Hz
SPEAKER	2 × 304.8 mm (12") LF Speaker	1 × 381 mm (15"), Ø76.2 mm (3") Voice Coil
HIGH FREQUENCY UNIT	Dynamic Horn 101.6 mm (4") × 254 mm (10")	Dynamic Horn 222 mm (8.75") × 280 mm (11")
SPL at (1W/1m)	100dB	98dB
MAX. RATED SPL	124dB	124dB
NOMINAL IMPEDANCE	8Ω	8Ω
CROSSOVER FREQUENCY	4kHz	2kHz
PORT	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	Speakon + Terminal Strip	2 Nos. of Speakon Socket
DIMENSIONS	W465 × H995 × D405 mm	W460 × H730 × D413mm
WEIGHT	38.80kg	30.00 kg