


## CS-5044T

Flush mounting ceiling speaker with an attractive, ultra-modern ABS plastic grille. Stylish good looks make this ideally suitable for fashionable showrooms, restaurants and offices.

- 12.7 cm (5") Full Range Speaker with power taps of 4/2/1W.
- 4 Watts continuous power handling capacity.
- Easy mounting with spring loaded wing clamps.
- 100V operation with easy selection of power taps through a terminal block.
- Ideal for Offices... Restaurants... Hotels... Hospitals... Shopping Malls... Gymnasiums...







## CS-6066T

Flush mounting ceiling speaker with an elegant, ultra-modern ABS plastic grille. Attractive looks make this ideally suitable for fashionable showrooms, restaurants and offices.

- 15.24 cm (6") Full Range Speaker with power taps of 6/3/1.5W.
- 6 Watts continuous power handling capacity.
- Easy mounting with spring loaded wing clamps.
- 100V operation with easy selection of power taps through a terminal block.
- Ideal for Offices... Restaurants... Hotels... Hospitals... Shopping Malls... Gymnasiums...







## BS-6462T

Metal box speaker for sound system installations in Railway Coaches, Industrial Establishments etc,. Powder coated sturdy metal enclosure. Vandal-proof.

- 15.24 cm (6") × 10.16 cm (4") Full Range Speaker, 6W/100V.
- Can be wall mounted also. Key holes provided on rear.




| SPECIFICATIONS | CS-5044T | CS-6066T | BS-6462T |
|---|---|---|---|
| INPUT POWER | 4W RMS | 6W RMS | 6W RMS |
| POWER TAPS ON 100V | 4/2/1W | 6/3/1.5W | 6/3/1.5W |
| IMPEDANCE | 2.5k/5k/10kΩ | 1.6k/3.3k/6.6kΩ | 1.6k/3.3k/6.6kΩ |
| FREQUENCY RESPONSE | 80-15,000Hz | 60-15,000Hz | 150-10,000Hz |
| SPL at 1kHz (1W/1m) | 92dB | 92dB | 91dB |
| DIMENSIONS | Ø157 × H75 mm | Ø195 × H79 mm | W172 × H263 × D78 mm |
| WEIGHT | 660g | 820g | 1.40kg |





