
# Wall Speakers



## WS-661TM/WS-664TM

High quality ABS wall mounting box speakers with modern design and better aesthetics. Suitable for indoors; speech & background music. For Schools, Offices, BPOs, Hospitals, Banks, Restaurants, Showrooms and Hotels.

- 15.24 cm (6") Full Range Speaker, 6W/100V.
- Key holes for easy wall mounting.
- Power tap selection on 100V through female receptacle (push fit) in WS-661TM.
- WS-664TM has an additional rotary switch for multiple power tap selection.







## WS-6255TM

Attractive design and high power ABS wall mounting box speaker in grey colour for indoor public address and background music in locations of high ambient noise. Ideal for Schools, Hospitals, Canteens, Colleges, Railway Platforms and Hostels.

- 16.51 cm (6.5") Full Range Speaker provides clear and clean sound for both speech and music; 25W/100V.
- Key holes for easy wall mounting.
- Power tap selection on 100V through terminal strip.







## BS-6082T/BS-6083T

Stylish & rugged metal box speaker for a variety of speech & background music applications such as Railway Coaches, Industrial Establishments, Schools, Warehouses, Public Buildings etc. Powder coated metal enclosure.

- Vandal-proof metal cabinet in ivory colour.
- 15.24 cm (6") Full Range Speaker, 8W/100V.
- Key holes for easy wall mounting.
- BS-6082T is wall mount version.
- BS-6083T is for both wall & ceiling mounting.
- Easy power tap selection through terminal strip.




| SPECIFICATIONS | WS-661TM/WS-664TM | WS-6255TM | BS-6082T/BS-6083T |
|---|---|---|---|
| POWER RATING | 6W RMS/9W Max. | 25W RMS/37.5W Max. | 8W RMS/12W Max. |
| POWER TAPS ON 100V | 6/3/1.5W | 25/15/10/5W | 8/4/2W |
| IMPEDANCE | 1.6k/3.3k/6.6kΩ | 400/670 /1k/2kΩ | 1.25k/2.5k/5kΩ |
| FREQUENCY RESPONSE | 60-15,000Hz | 120-15,000Hz | 60-15,000Hz |
| SPL at 1kHz (1W/1m) | 92dB | 94dB | 92dB |
| DIMENSIONS | W258 × H258 × D128 mm | W258 × H258 × D128 mm | W230 × H230 × D75 mm/ |
| | — | — | W230 × H250 × D75 mm |
| WEIGHT | 1.18kg/1.25kg | 1.69kg | 1.80kg |