PA Sound Projector



SP-5251T

Compact & elegant controlled directivity sound projector in aesthetically beautiful white plastic cabinet. Water resistant speaker used in SP-5251T is suitable for outdoor applications also.

- 11.43 cm (4.5") Full Range Speaker, 25W/100V.
- Easy power tap selection through a rotary switch.
- 'U' type powder coated mounting bracket
- Ideal for Factories··· Hospitals··· Hotels··· Schools··· Railway Platforms···

PA Dual Sound Projector



SP-6305TD

Compact & weather resistant bi-directional projection speaker in aesthetically pleasing white plastic cabinet. Creates uniform ambience of sound in a wider area from a single sound source.

- IP44 degree of dust and water protection.
- 2 × 16.51 cm (6.5") Full Range water resistant speakers facing in opposite direction, 30W/100V.
- 'U' type mounting bracket for easy & trouble free installation.
- Ideal for Railway Platforms··· Factories··· Parking Lots··· School Corridors··· Theme Parks···

SPECIFICATIONS	SP-5251T	SP-6305TD
INPUT POWER	25W RMS	30W RMS
POWER TAPS ON 100V	25/20/15/10/5W	30/20/10/5W
IMPEDANCE	400/500/670/1k/2kΩ	330/500/1k/2kΩ
FREQUENCY RESPONSE	120-15,000Hz	120-15,000Hz
SPL at 1kHz (1W/1m)	93dB	94dB
DIMENSIONS	Ø183 × H215 mm	Ø175 × H256 mm
WEIGHT	2.10kg	2.60kg

Speaker Volume Controllers

AT-06/AT-20/AT-40

Speaker Volume Control



- Attractive, aesthetically pleasing white plastic housing.
- Simple to install against walls, partitions and panels, even after the wiring is complete.
- Compatible with all Ahuja wall and ceiling speakers with 100V line matching transformer.
- Reliable, high wattage rotary switch (in AT-40 and AT-20) has 11 selectable positions: Max, 9 attenuated positions (in 3 dB steps) & OFF.
- AT-06 has a reliable rotary switch with 5 selectable positions: Max, 3 attenuated positions (in 3dB steps) & OFF.
- Suitable for connection to speaker or speakers with RMS power rating up to 40 Watts (for AT-40), 20 Watts (for AT-20) and 6 Watts (for AT-06).
- Ideal for hotels, office cabins, showrooms, greenrooms, etc.

SPECIFICATIONS	AT-06	AT-20	AT-40
RATED POWER	6W RMS	20W RMS	40W RMS
INPUT VOLTAGE	100V	100V	100V
OUTPUT POSITIONS	Max, 3 attenuation positions in 3dB	Max, 9 attenuation positions in 3dB	Max, 9 attenuation positions in 3dB
	steps (-3dB to -9dB) and OFF	steps (-3dB to -27dB) and OFF	steps (-3dB to -9dB) and OFF
DIMENSIONS	W87 × H87 × D78 mm	W87 × H87 × D78 mm	W87 × H87 × D78 mm
WEIGHT	150g	250g	250g