

4×12" | 1 WAY | 4Ω

SQX-850
800 WATTS

Sturdy & rugged carpet covered bass reflex cabinet built around 4 nos high quality 30.48 cm (12") dual cone speakers. Features high efficiency, high sound pressure level, & unmatched bass. Tuned for optimum performance, and having a high power handling capacity of 800 Watts RMS, this is an ideal cabinet speaker for large gatherings and for use with high power amplifiers.



1×12" | 2 WAY | 8Ω

SAX-200DX
200 WATTS

Professional 2-Way Loudspeaker consists of one high efficiency 30.48 cm (12") LF speaker and a 2.54 cm (1") HF Compression Driver. The system is housed in a Rugged Bass Reflex Trapezoidal Enclosure made of 18 mm board, and Carpet covered. A Stand Adapter at the bottom for stand mounting is also provided. The trapezoidal enclosure construction assures optimum low frequency performance and smoothness with minimum interference from standing waves and box resonance. The speaker produces high sound pressure levels with accuracy in any environment and thus is ideal for all PA and music performances.



1×15" | 3 WAY | 8Ω

SAX-300DX
300 WATTS

Professional 3-Way Loudspeaker consisting of one high efficiency, high SPL 38.1 cm (15") LF speaker, a 2.54 cm (1") HF Compression Driver and two Piezo Tweeters, for excellent high frequency response. The system is housed in a Rugged Bass Reflex Trapezoidal Enclosure made of 18 mm board, and Carpet covered. A Stand Adapter is provided at the bottom for stand mounting. The trapezoidal cabinet design assures optimum low frequency performance. An On/Off switch for the piezo speakers is provided to limit extended HF if desired. The speaker is ideal for PA as well as music performances.

SPECIFICATIONS	SQX-850	SAX-200DX	SAX-300DX
POWER RATING	800W RMS/1600W Programme	200W RMS/400W Programme	300W RMS/600W Programme
CONFIGURATION	One Way	Two Way	Three Way
FREQUENCY RESPONSE	50-16,000Hz	45-20,000Hz	40-20,000Hz
LOW FREQUENCY SPEAKER	4 × 304.8 mm (12") Full Range Speaker	1 × 304.8 mm (12"),	1 × 381 mm (15"),
	—	Ø50.8 mm (2") Voice Coil	Ø76.2 mm (3") Edge Wound Voice coil
HIGH FREQUENCY UNIT	—	Dynamic Horn, 101.6 mm (4") ×	Dynamic Horn, 101.6 mm (4") ×
	—	254 mm (10")	254 mm (10") + 2 Piezo Tweeters
SPL at (1W/1m)	103dB	97dB	100dB
MAX. RATED SPL	132dB	119dB	125dB
NOMINAL IMPEDANCE	4Ω	8Ω	8Ω
CROSSOVER FREQUENCY	—	4kHz	4kHz
PORT	Free Flow Flared	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	Speakon + Terminal Strip	1/4" Phone Jack + Terminal Strip	1/4" Phone Jack + Terminal Strip
DIMENSIONS	W755 × H810 × D525 mm	W510 × H655 × D405 mm	W550 × H755 × D425 mm
WEIGHT	55.10kg	25.50kg	33.00kg



