

2×15" | 2 WAY | 4Ω | 18mm PLYWOOD

SPX-1310
1100 WATTS

Superb high power professional 2-Way PA Loudspeaker in attractive painted enclosure made of 18 mm Plywood. Packed with two high power 38.1 cm (15") LF loudspeakers and a high frequency titanium compression horn driver give very well defined, prominent lows and brilliant highs. Acoustically treated bass reflex trapezoidal cabinet with a strong steel grille ensures protection and durability. Heavy duty metal handles allow ease of mobility and transportation. Ideal for use with high powered amplifiers for a variety of indoor and outdoor applications like Auditoria, DJs, Live Performances etc.



2×15" | 2 WAY | 4Ω | 18mm PLYWOOD

SPX-1610
1400 WATTS

Ultra high power professional 2-Way PA Loudspeaker in attractive painted enclosure made of 18 mm Plywood. Fitted with two high power 38.1 cm (15") LF loudspeakers and a powerful titanium compression horn driver give very well defined, prominent lows and brilliant highs. Acoustically treated bass reflex trapezoidal cabinet with a strong steel grille ensures protection and durability. Special trapezoidal profile of the cabinet for better stackability. Heavy duty metal handles allow ease of mobility and transportation. Ideal for use with high powered amplifiers for a variety of indoor and outdoor applications like Auditoria, DJs, Live Performances etc.

SPECIFICATIONS	SPX-1310	SPX-1610
POWER RATING	1100W RMS/2200W Programme	1400W RMS/2800W Programme
CONFIGURATION	Two Way	Two Way
FREQUENCY RESPONSE	35-20,000Hz	45-20,000Hz
LOW FREQUENCY SPEAKER	2 × 381 mm (15"), , Ø101.6 mm (4") Voice coil	2 × 381 mm (15") LF Speaker
HIGH FREQUENCY UNIT	Dynamic Horn 177.8 mm (7") × 406.4 mm (16")	Dynamic Horn 230 mm (9") × 354 mm (13.9")
SPL at (1W/1m)	103dB	103dB
MAX. RATED SPL	133dB	134dB
NOMINAL IMPEDANCE	4Ω	4Ω
CROSSOVER FREQUENCY	2kHz	2kHz
PORT	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets	2 Nos. of Speakon Sockets
DIMENSIONS	W542 × H1253 × D475 mm	W485 × H1260 × D510 mm
WEIGHT	63.45kg	62.30kg