SMS-450P

400 WATTS

1×15" | 2 WAY



Rear Panel



Professional 2-Way Active Stage Monitor Loudspeaker has built-in Bi-Amplifier for LF and HF driver separately. An optimally angled enclosure for effective floor monitoring in various indoor & outdoor applications. The system is housed in an acoustically treated Bass Reflex enclosure made of 18 mm board in durable paint finish. Adaptor is provided at the bottom for stand mount applications. Heavy duty metal handles allow ease of mobility and transportation.

- 1 x Balanced Mic/Line Input selectable through a push switch.
- 1 x Line Input can be used for connecting balanced MONO signal through jack or unbalanced STEREO signal source through dual RCA.
- Balanced output to link another SMS-450P or for recording on a computer, record player.
- Switchable balanced output either as a Loop through output of Input-1 or a mix output of Input-1 and 2.
- 2-Way Speaker System: 38.1cm (15") LF Woofer, Ø76.2cm (3.0") Voice Coil and Dynamic Horn 177.8 mm (7") × 406.4 mm (16").

SPECIFICATIONS	SMS-450P
POWER OUTPUT (Bi-AMP)	LF: 350W RMS at 1% THD Class H, HF: 50W RMS at 1% THD Class AB
OUTPUT REGULATION	Better than 0.5dB
INPUT CHANNELS	INPUT-1: MIC 20mV/3kΩ balanced, LINE: 775mV/10kΩ balanced,
	INPUT-2: LINE (Jack) 250mV/20kΩ balanced, RCA: 250mV (L&R)/10kΩ
FREQUENCY RESPONSE	50-20,000Hz ±3DB
CROSSOVER FREQUENCY	2.5kHz , Filter Slope 24dB per octave
SIGNAL TO NOISE RATIO	60dB
TONE CONTROLS	Bass: ±5dB at 100Hz, Treble: ±5dB at 10kHz
OUTPUT	(a) Loop through (INPUT-1): 20mV or 775mV, (b) Mixed Output (1+2): 775mV/1kΩ
PROTECTIONS	AC: Fuse 1 × 5A (T 5A L) DC: Fuse 2 × 8A (T 8A L)
POWER SUPPLY	AC: 220-240V 50/60Hz
AC POWER CONSUMPTION	500VA
DIMENSIONS	W700 × H400 × D525mm
WEIGHT	35.50kg