



1×18" 8Ω 18mm PLYWOOD SUB WOOFER

SWX-1010
1000 WATTS

SWX-1010 is a compact and powerful super power SUBWOOFER with exceptional distortion-free low frequency response. It is fitted with a 46 cm (18") LF driver having 12.7 cm (5") inside/outside voice coil wound on a polyimide fibre glass former. The speaker has an aluminium demodulating ring for better heat dissipation and a specially treated cone for water splash resistance. The cabinet is rugged and specially braced to withstand intense vibrations. The enclosure is made of 18 mm Plywood and fitted with four heavy duty handles, a recessed terminal plate and four indexed feet for ease of stacking. The strong metal grille protects the speaker from unavoidable strokes.

1×18" 8Ω 18mm PLYWOOD SUB WOOFER

SWX-1510
1500 WATTS

Compact and rugged 1500W professional subwoofer driven by an efficient 46 cm (18") LF driver to provide excellent bass response and high power handling capacity. Fitted in a strong and durable thick wooden enclosure which is well braced internally and attractively paint finished externally. The enclosure design suits all types of installed and touring applications. Strong extra-thick grille is designed to give required protection to the speaker and professional appearance to the product. The enclosure is made of 18mm Plywood and fitted with four heavy duty handles for easy handling. Four indexed feet on top surface provide easy and secure stacking of multiple cabinets. Two speakon connectors on the rear terminal plate are provided for quick & convenient connections.

SPECIFICATIONS	SWX-1010	SWX-1510
POWER RATING	1000W RMS/2000W Programme	1500W RMS/3000W Programme
CONFIGURATION	One Way	One Way
FREQUENCY RESPONSE	36-200Hz	40-250Hz
LOW FREQUENCY SPEAKER	1 × 460 mm (18") with	1 × 460 mm (18") with Ø 127 mm (5") I/O Copper Voice Coil
	Ø127 mm (5") Inside/Outside Wound Voice Coil	—
SPL at (1W/1m)	99dB	98dB
MAX. RATED SPL	129dB	129dB
NOMINAL IMPEDANCE	8Ω	8Ω
PORT	Free Flow Flared	Free Flow Flared
INPUT CONNECTORS	Terminal Strip + Speakon	2 Nos. of Speakon Sockets
DIMENSIONS	W538 × H710 × D700 mm	W605 × H785 × D605 mm
WEIGHT	55.35kg	59.60kg