SWT-1310

1300 WATTS







Rugged & reliable 1300W professional subwoofer driven by an efficient 46 cm (18") LF driver to provide superb bass response with high power handling capacity. Fitted in a strong and durable thick wooden enclosure which is well braced internally and attractively paint finished externally. The enclosure design suits all types of installed and touring applications. Strong extra-thick grille is designed to give required protection to the speaker and professional appearance to the product. The enclosure is made of 18mm Plywood and fitted with heavy duty handles for easy handling. A stand adapter has been provided at the top of the cabinet for pole mounting a full range speaker. Four indexed feet on top surface provide easy and secure stacking of multiple cabinets. Two speakon connectors on the rear terminal plate are provided for quick & convenient connections.

SPECIFICATIONS	SWT-1310
POWER RATING	1300W RMS/2600W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	36-250Hz
LOW FREQUENCY SPEAKER	1 × 460 mm (18") with Ø 114.3 mm (4.5") I/O Copper Voice Coil
SPL at (1W/1m)	97dB
MAX. RATED SPL	128dB
NOMINAL IMPEDANCE	8Ω
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W605 × H820 × D620 mm
WEIGHT	55.25kg



